

Post Construction Safe Work Practices Certification

I, _____ (name), an employee of _____ (contractor or organization), certify that we followed safe work practices on _____ (address of property). Items 1A-1D were adhered to, in compliance with Federal, state and local regulations, except in cases where the work was exempt from safe work practice requirements as described in Item 2.

Check Number 1 or 2

_____ 1. The following safe work practices were applied as appropriate.

A. The prohibited work methods listed below were not used.

- Open flame burning or torching.
- Machine sanding or grinding without a high-efficiency particulate air (HEPA) local exhaust control.
- Abrasive blasting or sandblasting without HEPA local exhaust control.
- Heat guns operating above 1,100 degrees Fahrenheit, or those that that operate high enough to char the paint.
- Dry sanding or dry scraping. (For exceptions to this rule see 24CFR 35.140 (e).)
- Paint stripping in a poorly ventilated space using a volatile stripper that is a hazardous substance in accordance with regulations of the Consumer Product Safety Commission at 16 CFR 1500.3, and/or a hazardous chemical in accordance with the Occupational Safety and Health Administration at 29 CFR 1010.1200 or 1926.59, as applicable to the work.

B. Protection of occupants and preparation of the worksite as described below.

- Occupant Protection
 - Occupants were not permitted to enter the worksite during hazard reduction activities until final clearance was achieved.
 - Occupants were temporarily relocated before and during hazard reduction activities if necessary.
 - Dwelling unit and worksite were secured against unauthorized entry, and occupants' belongings were protected from contamination by dust-lead hazards and debris during hazard reduction activities.
 - Occupants' belongings in a containment area were relocated to a secure area outside the containment area or covered with appropriate materials.
- Worksite Preparation
 - Worksite was prepared to prevent release of leaded dust and contained lead-based paint chips and other debris from hazard reduction activities within the worksite.
 - A warning sign was posted at each entry to rooms where hazard reduction activities were conducted when occupants were present.

C. Specialized cleaning after hazard reduction activities including:

- Used HEPA vacuum cleaners; or other method of equivalent efficacy; and
- Lead-specific detergents or equivalents.

D. Clearance of unit achieved before reoccupancy was permitted.

_____ 2. Safe work practices and clearance were not required when activities do not disturb painted surfaces below the *de minimis* thresholds defined below.

- The maintenance or rehab hazard reduction activities did not disturb painted surfaces that totaled more than:
 - 20 square feet on exterior surfaces;
 - 2 square feet in any one interior room or space; or
 - 10 percent of the total surface area on an interior or exterior type of component with a small surface area (such as windowsills, baseboards, and trim).

Contractor Signature

Date

City of _____ Representative

Date