

# Wood Raised Panel Doors




- Finish Ready Sanded
- CAD Files Available



3061 Verona Ave Buford, Ga 30518 (800) 992-6426 • (770) 932-0640


Please call for more information or visit www.gahwd.com

## Wood Raised Panel Cope and Stick




🄜 Georgia Hardwoods Inc 🛛 800-992-6426 🗆 www.gahwd.com □ Fax: 678-546-6105

#### Wood Raised Panel Cope and Stick




Georgia Hardwoods Inc $\ \square$ 800-992-6426 $\ \square$ www.gahwd.com $\ \square$  Fax: 678-546-6105




🎿 Georgia Hardwoods Inc 🛛 800-992-6426 🗆 www.gahwd.com 🗆 Fax: 678-546-6105

#### Wood Raised Panel Cope and Stick


#### Multi Panel / End Panel / Wainscot Layout Designs




R21 Min Size: 14<sup>3</sup>/<sub>4</sub>x8\*



R42-L Min Size: 14<sup>3</sup>/<sub>4</sub> x 14<sup>3</sup>/<sub>4</sub>\*






R42-R


D21

Min Size: 12x6\*


R32 D32 Min Size: 14<sup>3</sup>/<sub>4</sub> x 14<sup>3</sup>/<sub>4</sub>\* Min Size: 14<sup>3</sup>/<sub>4</sub> x 14<sup>3</sup>/<sub>4</sub>\*




R42 Min Size: 14<sup>3</sup>/<sub>4</sub> x 14<sup>3</sup>/<sub>4</sub>\*



D42 Min Size: 12x12\*




D42-R Min Size: 14<sup>3</sup>/<sub>4</sub> x 14<sup>3</sup>/<sub>4</sub>\*




R22 Min Size: 8x14<sup>3</sup>/<sub>4</sub>\*

D22 Min Size: 8x12\*

Multiple arch panel options are specified by the design. The panel layout in these 3 examples are R22. The design (CRP) changes to specify the panel orientation. A design of CRP on a R22 layout will only have the top panel as the CRP design. The lower panel will be SRP design. More information is available on the Wainscot page, pg.35.







2CRP

Large endpanels or wainscot is on Pg 39.


D42-L Min Size: 14<sup>3</sup>⁄<sub>4</sub> x 14<sup>3</sup>⁄<sub>4</sub>\*






Georgia Hardwoods Inc 🗆 800-992-6426 🗆 www.gahwd.com 🗆 Fax: 678-546-6105


### Wood Raised Panel Cope and Stick




G63 Min Size: 10x12\*



G93B Min Size: 12x12\*




G74L Min Size: 12x16\*




G84

Min Size: 10x16\*



G93C Min Size: 12x12\*




G74R Min Size: 12x16\*

OG42


Min Size: 12x16\*




Min Size: 10x20\*




G114 Min Size: 16x16\*




DG13 Diagonal Grids are priced per opening just as glass lite doors. Specify if opening is centered or if mullion is centered. Minimum grid square is 2x2"




Min Size: 12x24\*



G93 Min Size: 12x12\*



G135 Min Size: 16x24\*



DG7


OG72


Min Size: 12x16\*




D7


#### GLASS MULLION DOORS









#### Wood Panel Profiles




#### Cope/Stick Stile Profiles





## Wood Outside Edge Profiles





## Wood Outside Edge Profiles



















Georgia Hardwoods Inc 🗆 800-992-6426 🗆 www.gahwd.com 🗆 Fax: 678-546-6105














M211-175

M211-237


53

Georgia Hardwoods Inc 🗆 800-992-6426 🗆 www.gahwd.com 🗆 Fax: 678-546-6105


# Mitered Profiles with Applied Rope



3/8" Half round rope moulding available in Alder, Cherry, Hard Maple, Mahogany, Poplar and Red Oak.




# Mitered Profiles -1" Thick




M423-225


M423-325

Minimum Size Based on Rail Width					
	PP*-050	PP*-075	PP*-112	PP*-150	PP*-175
M***-325	7-3/4″	8-1/4″	9″	9-3/4″	10-1/4″
M***-300	7-1/4″	7-3/4″	8-1/4″	9-1/4″	9-3/4″
M***-287	7″	7-1/2″	8-1/4″	9″	9-1/2″
M***-256	6-3/8″	6-7/8″	7-5/8″	8-3/8″	8-7/8″
M***-237	6″	6-1/2″	7-1/4″	8″	8-1/2″
M***-225	5-3/4″	6-1/4″	7″	7-3/4″	8-1/4″
M***-200	5-1/4″	5-3/4″	6-1/2″	7-1/4″	7-3/4″
M***-175	4-3/4″	5-1/4″	6″	6-3/4″	7-1/4″
M***-162	4-1/2″	5″	5-3/4″	6-1/2″	7″
M***-150	4-1/4″	4-3/4″	5-1/2″	6-1/4″	6-3/4″
M***-137	3-3/4″	4-1/4″	5″	5-3/4″	6-1/4″



Reorgia Hardwoods Inc □ 800-992-6426 □ www.gahwd.com □ Fax: 678-546-6105





Georgia Hardwoods offers 4 styles of drawerfronts. Slab and Panel Profile fronts are interchangeable with both Cope and Stick and Mitered style doors.

Slab Drawerfronts

Slab drawerfronts are the most cost effective solution over 5 piece assembled fronts. Available with the same matching edge profiles as the 5 piece doors. 1"Thick slabs

are limited to certain profiles. See pages 13-14 for more details.

Cope and Stick Drawerfronts

Cope and Stick drawerfronts are available with either a standard rail on all 4 sides or a narrow top and bottom rail with standard side rails. Height constraints may require a

narrow version of the rail to be used on the top and bottom to allow for a raised panel. Shown is a drawerfront with 2-3/8" side rails and 1-3/8" top and bottom rails. This front style is ordered and priced just like a standard door with a minimum of 1 sq. ft. Refer to rail profile pages for rail sizes. Minimum panel reveal is 1-3/4"

Mitered Drawerfronts

Mitered drawerfronts are specifically used with mitered doors. Specify the smaller mitered rail version to accommodate raised panel profiles if required. These drawer-

fronts are priced as a 5 piece door with a minimum of 1 sq. ft. Minimum height is determined by the rail width. Refer to pages 15-23 for miter rail sizes. Minimum panel reveal is 1-3/4".

#### Panel Profile Drawerfronts


Panel Profile drawerfronts are a more decorative slab alternative to 5 piece fronts. Made from 3/4" or 1" thick solid stock, slabs


are machined with a panel profile (PP number) to match the door profiles. Panel profile drawerfronts can be machined with any panel profile available and include an eased edge. 1"Thick panel profile fronts can also include a matching outside edge, which is an option that is not available on 3/4" thick fronts.



















Georgia Hardwoods Inc 🗆 800-992-6426 🗆 www.gahwd.com 🗆 Fax: 678-546-6105




#### Wood Cabinet Doors




Mini: PP-LAT-M 1/2" cell opening 7/16" x 5/32" lattice strips Full Sheet: 24"x47" Available in Alder, Cherry, Hickory, Maple, Red Oak only

#### Lattice Inserts



Large: PP-LAT-L 1" cell opening 3/8" x 5/16" lattice strips Full Sheet: 24"x36" Available in Cherry, Hickory, Maple, Red Oak only



Square: PP-LAT-S 1" cell opening 3/8" x 5/16" lattice strips Full Sheet: 24"x36" Available in Cherry, Hickory, Maple, Red Oak only

Lattice sheets come in 3 styles, Mini, Large and Square. Each sheet is made of solid wood and is sanded ready to finish. Optional lattice inserts are available both installed and purchased separately. Specify insert as panel profile. Lattice doors require 1-2 day additional lead time.

#### Louvered Doors

Air through louvered doors are available in any specie. The louvered inserts are made with 5/8" side rails with 3/16" x 1-1/16" mortised slats. Each louvered panel is custom built per door. Each insert protrudes from the back of the door approximately 3/16" on 3/4" thick doors and 1/8" for 1" thick doors. Panel profile PP-LOUV.


Louvered doors require 2-3 day additional lead time.

#### Wire Grille

Wire grille inserts can be ordered as a panel insert into glass light doors. Each wire grille is available in stocked 20" x 48" sheets or custom cut sizes.

Stocked wire grilles require 2-3 day additional lead time, custom wire grilles require 5-7 day lead time. Grilles are available in Antique Brass, Oil Rubbed Bronze and Satin Steel in 9 different stocked styles.

Refer to our website for more details about wire mesh grilles.



# Wood Raised Panel


#### **OPTIONS**

#### Hinge Boring \$1.50 per Hole for Standard, \$2.50 for Specified.

Door hinge boring is offered for concealed hinges. The cup is drilled 1/2" deep with a diameter of 35mm. We offer the drilling for screw on or knock in pattern for Hettich® or Blum® hinges. Refer to the chart to the right for dimensions.

> \*Not all edge profiles allow hinge boring. Please refer to the Outside Edge profile pages D9-10 for more information.

The holes are bored 3" from the end of the door. Special 32mm on center alignment is available for an additional fee. Please specify locations and number of hinges in the notes field of the order form.



#### **Standard Hinge Placement**

Door Sizes 12" and Under

12-1/16" to 45"

45-1/16" to 65"

65-1/16" to 96"


*# of Hinges* 2 Hinges

- 2 Hinges 3 Hinges 4 Hinges
- Location 2-1/4" from end
- 3" from end 3" from end 1 centered
- 3" from end spaced equally

# 11 ‡ 11,8 Hettich<sup>®</sup> ø 35 11,8 11 **Blum**<sup>®</sup> 11,8 Screw on

#### Standard Cup Drilling Distance

All standard hinge boring is 4-1/2mm from the edge for Hettich pattern and 4-1/2mm or 2-1/2mm from the edge for Blum pattern. Custom distance is available for an additional fee. Please refer to your hinge specifications for the proper measurement. If using hinges supplied by Georgia Hardwoods, please specify on your order.




"C" = distance from edge of door to edge of cup hole

#### **Boring Side**

You must specify the side of the door to be bored. The correct side can be determined by looking at the face of the door. Note the side to bore on the order form.

T-Top **B-Bottom** L-Left **R-Right** N-None



Door is bored for "Left". Door opens to the left.

### Wood Raised Panel

#### OPTIONS

#### \$3.00 per finger pull

#### **Finger Pulls**

Standard finger pulls are 5" long with a radius cut of 5/16" x 7/16" deep and is located in the center of the rail of the door or 1-1/2" from the corner. Finger pulls on slab drawerfronts are always in the center of the long side. Additional charge to have finger pulls on multiple sides.

Side rail finger pulls are also available for hardwood doors. These pulls are a 3/8" x 6-3/8" long x 1/8" deep and are machined 3/32" from the back edge of the door. This will allow the door to have an edge profile with the finger pull. Pulls are machined in the middle of the rail on center on any side of the door. Additional charge for finger pulls on multiple sides.

Default finger pull placements are either on center of the frame rail or stile or 1-1/2" from the corner. To determine the proper location, specify the side using T(top), B (bottom), L(left) or R(right). Then specify the location of the pull. L(left), C(center) or R(right) for the top and bottom rail, T(top), C(center) or B(bottom) for the sides. The side is determined by looking at the face of the door. The drawing to the right is for a left side, bottom placement pull.

Placements
------------


	Left	Center	Right
T (top)	TL	TC	TR
B (bottom)	BL	BC	BR
	Тор	Center	Bottom
L (left)	Top LT	Center LC	Bottom LB


On Slab Drawer Fronts, the pull placement is always centered.


Full side finger pulls are available for doors for an additional charge. Each pull is machined 1-1/2" from the corners. This option is available for both pulls FP10 and FP20. Additional charge for finger pulls on multiple sides.


Notes:

Finger pulls are not available on outside edge profile OE8. Minimum length side, width or height for finger pulls is 8". Additional charge for specified length or special placement finger pulls.










D38

## Wainscot


Wainscots are available in lengths up to 144" and widths up to 42". Larger sizes can be custom quoted and a oversize surcharge will apply. There are no standard rail sizes for wainscots. It is common to have a 6" bottom rail and 3" vertical stiles.



### Valances


Valances:

Built with OE16 outside edge. Only available with "S" rail profiles 1, 2, 3, 4 and 8. Priced as 2, 3 or 4 panel door plus design fee. Maximum individual panel width is 34".



Solid Slab Valances

Sold by the square foot. All drawn as 6"x45" scale. 35.00 Design fee.




# Wood Door Distressing

Simulated distressing options are available for all wood products manufactured or distributed by Georgia Hardwoods. These enhancements provide a "broken in" appearance to the cabinetry and adds instant character to new construction. Distressing options are available either before or after the finish is applied and include dents, scratches, worm holes and edge wear. A glaze finish option will enhance

the look of any distressed prefinished door. Distressing is available in Light and Heavy patterns. Light distressing is 2-4 marks per sq. ft. and heavy distressing is 4-8 marks per sq. ft. Price based per square foot. Not all door panels will accept distressing.

	Light	Heavy
Patterns:	\$1.00 / SqFt	\$1.25 / SqFt
Worn Edge	DIS-EDGE-L	DIS-EDGE-H
Wear Marks	DIS-CORN-L	DIS-CORN-H
Rub Through	DIS-RUB-L	DIS-RUB-H
Rasp Marks	DIS-RASP-L	DIS-RASP-H
Worm Holes	DIS-WORM-L	DIS-WORM-H
Nail	DIS-NAIL-L	DIS-NAIL-H
Screw Impression	DIS-SCR-L	DIS-SCR-H





# Prefinishing

#### Prefinished doors

Georgia Hardwoods has 22 standard colors and 4 glazes. Below are the colors and species used to match the color. These colors are only available on the specified species.

#### Maple

Apricot Barley Candlelight Chocolate Pear Crimson Cumberland Espresso Russet Sandalwood Scandia Wheat

#### Cherry

Autumn Moca Medium Red Cherry North Hampton Port Orange Summer Flame Lauren Mahog

#### Paint/Glaze

Antique white paint Beige paint Bright white paint Shutter white paint Black paint

Van Dyke Glaze Black Glaze Coco Glaze White Glaze

#### **Color Matching**

Occasionally customers will order one of our standard cherry wood colors on a less expensive specie such as maple or poplar. Please note that due to the different characteristics of cherry, the stain will not look the same on other specie. Colors ordered on a different specie will be considered a custom match and are subject to a matching fee.

Any colors other than our standards are considered custom matches. Customers must supply us with a sample to match. All custom color matches require that the customer approve our match before any finishing begins. Please allow for a longer lead time on custom colors due to the matching and approval process. There is a one- time \$75.00 charge for custom colors. There will be no additional charges if you order the same color again for future jobs or add on orders.

#### Stain techniques

Wiping is are sprayed on and wiped off. Pigment is absorbed in the end grain of the panels and rails causing it to be darker than the rest of the door.

Toners are sprayed on after a wiping stain has been applied and are not wiped off. Some colors cannot be achieved with wipe stain alone and require toning. As more toner is used, the wood grain becomes less visible.

Spray NGR dye stains are sprayed on with no wiping. NGR stains do not penetrate into the pores and end grain which will give a more uniform look, but this process will also cause the light to reflect differently than wipe stains which will make the color appear to change at different angles. NGR stains cannot be applied to doors with deep profiles (shaker style doors, applied molding doors or mitered doors with deep profiles) without leaving a light halo effect in the crevasse. The darker the color the more noticeable the halo. We do not recommend using NGR colors on these styles of doors.



# Prefinishing

#### Glazing

Glazing can be added to accentuate doors with detailed profiles. They are applied and wiped off by hand. Slight variation from door to door is not uncommon and is part of the beauty of a glazed finish. Our standard point glazing is only applied to the profiles and not the face of the panels and rails which does not alter the overall stain or paint color on the door. Because this type of glazing does not alter the appearance of the base color, we generally glaze the doors and trim only but not flat sheets goods such as plywood or veneers used for skinning cabinets.

Some customers prefer flood glazing where the whole part it sprayed with glaze and then wiped off. This process will alter the stain or paint color. This type of glazing is offered by request only to achieve uniformity all sheet goods will need to be flood glazed as well. There is an extra charge for flood glazing. Glaze is not applied to the backs of the doors.

#### What we finish with

Georgia Hardwoods is a stocking distributor of Valspar<sup>®</sup> finishes. We can supply you with whatever stain, sealers or topcoats you may need to match your cabinets to our finished doors. We suggest you test the stain on a sample first before staining the entire job. We use several different techniques to apply the finish depending on the specie and color to be achieved. It is always a good idea to talk to us about how we applied your particular color before finishing your cabinets.

Because of the low price, Poplar is an economical substitute for painted Maple. However; the porous grain does not fill as well as maple which will leave the endgrain more visible. If this is not acceptable we suggest ordering a harder species. Paint grade maple is very close in price to poplar and gives a superior finish for painted doors.

The characteristics of painted solid wood doors deserve some special notes. Textures of natural grain patterns are often not visible in a stained finish but will remain visible with painted finishes and should be accepted as inherent characteristics when selecting painted solid wood doors. With solid wood products, normal movement is typical due to changes in climate conditions. Over time this will cause hairline cracks in panel joints and in the stile and rail cope joints. This is a normal characteristic of painted finishes on solid wood and will not be considered a reason for product replacement. Also, we suggest ordering MDF center panels rather than solid wood panels for painted doors to reduce the affects of wood movement on painted finishes.

# **Prefinish Agreement**

#### PAINTED FINISH AGREEMENT

Thank you for choosing one of our painted door colors. Because of its unique characteristic, this finish may be different than other door finishes you are accustomed to. Your satisfaction is important to us and we want you to fully understand the characteristics that make a painted finish distinctive.

It is important to realize that the beauty of wood cabinetry comes from the natural qualities of the wood itself such as the grain. Because of this Georgia Hardwoods utilizes only select hardwoods. The textures of those natural grain patterns are often not visible in a stained finish but will remain visible with painted finishes and should be accepted as inherent characteristics when selecting painted solid wood doors.

With solid wood products, normal movement is typical due to changes in climate conditions. This will cause hairline cracks in panel joints and in the stile and rail cope joints. This is a normal characteristic of painted finishes on solid wood and will not be considered a reason for product replacement. We mention these characteristics because Georgia Hardwoods cannot be responsible for these conditions and variations.

Accordingly, we ask that the following agreement be signed for painted finishes on solid wood doors.

I have read the above and find the characteristic variations of painted solid wood doors desirable. As such, I agree not to hold Georgia Hardwoods responsible in the event that these characteristics are later found by me to be less desirable than I had expected.

Purchase order # \_\_\_\_\_

**Customer Signature** 

Customer Name (please Print)

Available for download: www.gahwd.com/t-docs.aspx

# Shipping

#### Shipping

Orders that meet the minimum amount are delivered at no charge on our trucks within our regular delivery area. Contact your sales representative for details. Orders outside of our delivery range are shipped LTL or UPS. There is a \$.15 per square foot handling/ packaging charge on all orders.

LTL orders shipped in the southeastern states that total \$2,000 or more are shipped without freight charges but with a \$35.00 packaging material/crate charge.

LTL orders less than \$2,000 are charged a percentage which includes the packaging material/crate charge. Shipping charges for orders totaling less than \$2,000 are calculated by the percentages below:

- 0-\$900 are charged 15% (\$135 or less)
- \$900-\$1,200 are charged 12% (\$108 \$144)
- \$1,200-\$2,000 are charged 10% (\$120-\$200)

If multiple orders are shipped together to the same location, the total of all the orders can be combined to reach the \$2,000 minimum for free shipping.

Individual quotes or orders that fall below the \$2,000 minimum will be confirmed with the shipping charges added on each order based on the above percentages with the understanding that at the time of shipment we will consolidate all orders that are ready to ship and if the total orders exceed the \$2,000 minimum, the shipping charges will be adjusted according to the rates listed above. Free freight only applies to door or drawer box orders not lumber or plywood.

#### Damage claims

- Be sure to inspect all packaging at the time of delivery. If there is no visible damage to the packaging note "Subject to inspection for internal damage" on the freight bill.
- If the packaging looks to be damaged even slightly, note it in detail on the freight bill. If the packaging looks to be compromised, it would be prudent, if at all possible, to open the crate and inspect the doors before the driver leaves. Note any visible damage on the freight bill.
- Notify Georgia Hardwoods immediately of any damage. Damaged products will be replaced as quickly as possible at no charge.
- Georgia Hardwoods will handle filing the damage claims. Please notify us as soon as possible. Claims must be filed with the carriers within 10 days. The carrier may require inspection of the damaged order. Please keep the doors in the original packaging until an onsite inspection is complete. The carrier may choose to pick-up the doors for inspection at their terminal or our facility.
- We do not guarantee the condition of any UPS shipments.

Wood is a material formed by nature, not man, and must be handled as such. Climate, light, rainfall and minerals in the soil all create diverse grain and color patterns that make every tree unique. The infinite variety in color, grain, and texture are what give wood its natural character and are not considered defects. We guarantee our doors to be free from defect in material and workmanship for one year from the ship date. Our warranty covers only the replacement of defective products manufactured by Georgia Hardwoods. Georgia Hardwoods will not be liable for costs related to travel expenses, installation, finishing or labor to remove and install new products. This warranty does not apply to damages resulting from improper handling, alterations made to our doors, or inappropriate storage, and does not cover any product used or installed in connection with our products. Our liability is limited to the net invoice price of defective doors only. No other warranties are implied or expressed.

Natural wood will expand and contract with changes in the climate. This natural phenomenon can have a negative effect on wood doors that are left unfinished. Our doors are constructed to allow for proper wood movement, however we strongly advise that the doors be stored in an area that has controlled humidity and be sealed and top coated on all sides within seven days. Sealing and top coating wood doors will slow down the moisture absorption from humid conditions and greatly reduces the chances of warping and cracking problems that are seen in doors that are left unfinished. Georgia Hardwoods will not be liable for problems with doors that have been left unfinished for more than one week after delivery. All warranties are voided for any doors, raw or finished, that have been stored or installed in an area without controlled humidity. Georgia Hardwoods will not warranty issues that could have been prevented, such as improper surface preparation before finishing. Our doors are sanded to180 grit and are ready to accept most finishes; however some specialized finishes may require additional preparation. Application of finish materials implies that the doors are accepted as suitable for the finish you have selected. If in doubt, test the finish on one of the doors before finishing the entire job. Most customers finish our doors right out of the box , however it is recommended that you lightly sponge sand your doors with the same grit you sanded your cabinets to remove any burnish marks or scratches that may occurred from handling during packaging or shipping. If unfinished doors are replaced at no charge, Georgia Hardwoods will not be liable for finishing costs.

#### REASONABLE TREATMENT REQUIREMENTS:

- Doors are not to be stored in freshly plastered or damp work sites.
- Doors are to be sealed with equal coats of finish on both sides, and all edges within one week from delivery in order to minimize moisture absorption.
- Doors are not to be exposed to excessive moisture, heat, cold, drastic swings in humidity, dryness, sunlight, abrasive cleaners or solvents. Wood doors should never be left on a construction site that is open to the elements.
- Wood doors should be kept in a humidity controlled environment through all seasons. Due to normal wood movement, stile and rail joints may open slightly during a regular heating and cooling cycle. This is normal and is not subject to no charge replacement.
- If needed, clean doors with a damp cloth followed by a dry towel. Do not use a wet sponge. Avoid excessive moisture and do not leave moisture standing on doors. Do not let water run into the rail and stile grooves.
- High heat can cause RTF doors to delaminate. Take precautions to avoid exposure to high temperatures. Delaminations due to high heat are not warranted

We will guarantee for one year against warpage, cracking, twisting or swelling for doors that have been given reasonable treatment and are within our minimum or maximum sizes.

- Raised panel doors less than 24" wide and 40" high are warranted against warpage of more than 3/16". Twists are measured after placing the face of the door on a true flat surface.
- Doors more than 24" wide and/or 40" high are not warranted.
- Glass doors are not warranted for warpage.
- Slab Drawer fronts less than 8" high and 24" wide are warranted against warpage of more than 1/8"
- Slab drawer fronts more than 8" high and 24" wide are not warranted
- There is NO warranty on slab doors.
- Any requested variation from our normal construction specs voids warranty.
- A visible glue joint on finished door rails and /or panels, or hairline cracks in the rail cope joint due to normal wood movement is not a defect.
- Doors must be inspected at the time of delivery. Any concerns or problems must be reported to Georgia Hardwoods immediately. Warranty claims must be inspected by a Georgia Hardwoods employee before applying finishes or altering the doors in any way.
- Outside dimension tolerances are +/- 1/16".

#### Mitered Doors:

Our mitered doors are made with a strong mortise and tenon joint using PUR glue. We have a tolerance of up to .010 on the inside corner of the joint to allow for the natural expansion and contraction of the wood. Mitered doors are not warranted for joint separations caused by extremes in high or low humidity. Due to the complexity of contoured mitered rails, the mitered faces are sanded before assembly to avoid cross sanding at the miter joints.

#### Pre-finished doors:

Our colors are formulated for solid wood doors. There may be a variance in color or appearance when applied to plywood, veneers and accessories such as corbels and range hoods. This is not a defect. With flat recessed panel doors we recommend a solid recessed (reversed raised) panel to assure the best possible match of color and grain. The colors on our samples are matched on specific species. We can use these stain colors on other species but the color or appearance is not guaranteed to match. Customers can purchase our stains and topcoats for their own application. Different application techniques will produce different results therefore we do not guarantee the final color match when applied by the customer. Feel free to contact us for directions on how we apply any of our colors. To assure consistency of color, we recommend that you order all components together for an entire job (doors, trim, veneers, and plywood). If new doors are ordered to be added to a previously completed prefinished job we recommend you send a sample from the original order for color consistency.

#### Painted Doors

Painted finishes tend to reveal more visible flaws than stained finishes. Hairline cracks due to expansion and contraction at joints become more noticeable and are a normal characteristic of painted doors. For this reason, hairline cracks in the finish at the joints will not be considered a reason for replacement. In order to achieve the best possible finish, we highly recommend using a hardwood like maple rather than a soft wood like poplar. Soft woods tend to produce inconsistent finishes due to varying absorption rates. Furthermore, an MDF panel is recommended because there are no glue lines and the face is very flat and smooth making it an ideal paintable surface. If you need further assistance explaining the pros and cons of painted finishes on wood doors to your client, there is a disclaimer available for download at our web site or you can simply call your sales representative and one can be faxed to you.

#### Replacement Policy

Upon receipt of your door order, we ask that you thoroughly inspect the doors for any defects in materials or craftsmanship and for damages that may have occurred in the shipping process. If you discover a defect please contact your sales representative within 5 days so we may make arrangements to inspect the doors.

In some cases it may be necessary to have the doors shipped back to us for inspection. If we require the doors be returned, we will ask that you re-package the defective doors and we will arrange the return shipment at no cost to you. In order to minimize any inconvenience to you, Georgia Hardwoods will replace any defective product as quickly as possible.

#### Ordering

There are three methods available to place an order. The first method for placing an order is by telephone. Although this may be the quickest way to place an order, often times it is the most inaccurate method. Phone orders will be read back at the time of the order so it is very important that you listen carefully as this is your confirmation. The other two methods are fax and email orders. These are the preferred methods because they tend to be very accurate and are easier to make corrections. To get started placing your order by fax or email you will first need to download an order form from our website. Order forms can also be faxed to you by contacting a sales representative. Once you have completed the order form, fax or email it back to Georgia Hardwoods. Once your order has been entered, an acknowledgement will be faxed to you, usually within one hour, for your review. If you do not receive an acknowledgement within one hour please call your sales representative to make sure your order was received. You will need to look over the acknowledgement very closely to ensure accuracy. If you agree with the acknowledgement, please initial in the appropriate box and fax it back confirming your approval. Any changes must be made within 24 hours from the time your order was confirmed. If we do not receive your confirmation within 24 hours of placing your order, we will assume you are in agreement and we will proceed with the order as we confirmed. Orders received before 2:00 pm (EST) will be put into production the following morning. Orders received after 2:00 pm (EST) will be processed the next business day.

#### THINGS TO REMEMBER WHEN WRITING UP YOUR ORDERS:

- 1. Please write your order on one of our order forms.
- 2. Please order using our style names & numbers. We will not accept orders placed using a competitor's style name or number. We will gladly assist you with our style numbers and send you a current catalogue.
- 3. Order in increments of 1/16".
- 4. Please check for minimum or maximum sizes.
- 5. If you plan to bore for concealed hinges or if you want us to bore the doors for you, specify Blum<sup>®</sup> or Hettich<sup>®</sup> pattern, with or without dowels. Also please be sure that the outside edge is compatible with your hole pattern.
- 6. Doors 40"+ high will be divided into two panels with a center rail unless specified otherwise. We will not guarantee that a single panel door over 40" tall for warpage. We also reserve the right to charge extra for single panel doors over 40" tall.
- 7. We do not add to the door sizes ordered to account for overlay options. Customers must give the finished sizes required.

For new customers, a customer number will be assigned to you after we receive your basic information. It may take a few days to set up your customer number. A customer number is required to track your orders, look up previous orders and to apply payments. If time will allow, we prefer to have this number assigned before confirming the first order. If not, the first order can be written up under a house account but you will need to provide us with the sales order number for any future reference. All orders written up for customers without a customer number will require a 50% deposit. All first time orders will require a 50% deposit unless credit terms have already been approved. A customer number does not imply that credit terms have been approved. The account will be COD unless our credit department approves terms. Contact your sales representative for a credit application or for a COD set up form or visit www.gahwd.com to download a copy.



Contact information: Georgia Hardwoods Inc. 3061 Verona Ave. Buford, Ga. 30518 800-992-6426 770-932-7643 door sales fax 678-546-6105 doorshop office fax

Email: doorshop@gahwd.com Website: www.gahwd.com

#### Production scheduling and confirmations

Order confirmations are normally faxed but can be emailed if requested. There are three dates on our confirmations. Order Date, Due Date and Pre-Finish Due: The Order Date is the date the quote or order was entered. The day the order is placed is not counted as a production day. The Due Date is the date the doors (unfinished) are scheduled to complete in the shop. The Pre-Finish Due date is the date that pre-finished orders are scheduled to complete.

We do our best to produce your order by these dates but completion dates are not guaranteed and may vary due to unforeseen events or order volume. The scheduled due dates are the estimated dates the orders are to complete and not necessarily the dates they will ship out or arrive at your shop. Depending on how the doors are to be shipped please allow another 1-2 days for packaging and cure times for pre-finished doors. Be sure to allow enough time for delivery when scheduling time in your shop or installation.

We will accommodate rush orders when we can. Depending on the type of door requested or the workload in the shop at the time of the request, we may not be able to rush your order. We believe that all customers orders are equally important and therefore a rush order will not be taken if it will cause a delay of production for other existing orders. If we are able to accept a rush order there will be a 30% up charge for any order shipped in less time than our regular lead time. There will be a 50% up charge for rushes in 3 days or less. Lead times for complex styles (non-standard rails, multiple panels, radiuses, etc...) will not be confirmed until all details are supplied. Rush confirmation dates are manufacturing times only. You need to specify if you need expedited shipping as well.

#### **Order Confirmations**

In order to produce orders on schedule, most orders will go into production in less than 24 hours after confirmations are signed. Any changes made after that time will be subject to extra charges. If we are not able to rework the parts to accommodate changes you will be responsible for the cost of the original parts plus the price of the new changes.

Due to material, shipping and energy costs, list prices can change without notice. If you need a current list price sheet please contact your sales representative. Quotes are honored for 30 days. Georgia Hardwoods reserves the right to pass along surcharges from suppliers resulting from energy or fuel related increases.



D49

L	horn	Non Non			Custon	ner/A								W	OOD I	DOOI	R
Mar Mar		good G	eorgia											QUO	TE ON		
~	يا ليحر	H	ardwo	ods In									0	rder:			 
) C	) ( 770) 9			e • Buford, G 992-6420			Fax:						Ι	Date:			
,	,		546-61			Е							Sales	Rep:			
AL	LOW	1-2 DAYS	FOR DE	CLIVERY	\$300			FOR DE			VAN		LUM	UPS	CPU	LTL	
Map		ors (Matched			5			hed on Cherr		olors	Paint	t Col	ors		lazes		
	Apri Barl			ussett andlewood		Autumn Mocha English Oak — English Oak — English Oak — English Oak					Ant White Cocoa Shutter White White						
	_Choo Crin	colate Pean		/heat candia			Red Cl hampto	nerry on Cherry				Beige Van Dyke Brown Black Black					
		berland		andlelight and maple only		Port C	Drange ner Flai	-					ight W				
										_Clear Only					#:		
Hın	-	-				5mm+				□35mm No		el	Fin	-	: □FP-1	0 🗌 FP-2	20
		-						-				W	ood S		erfronts		
	Pan	el Profile	: PP				Pa	nel Profil	e: PP						C1		
S	Edg tile/Ra	ge Profile ail Profile	:OE :									_			e profiles as Slab: PP		
	Qty	Width	Height	Not			Qty	Width	Height	Notes		_	Qty	Width	Height	Notes	s
1						1						1	~ ~				
2						2						2					
3						3						3					
4						4						4					
5						5						5					
6						6						6					
7						7						7					
8						8 9						8					
9						10						9					
11						10						10					
12						12						12					
13						13						13					
14						14						14					
15						15						15					
16						16						16					
17						17						17					
18						18						18					
19						19						19					
20						20						,	[[] Total	Drawer I	Fronts		_
21 22						21 22											
22						22							Faxed Date/	Ву: Гіте:			_
<i>23</i>						23							Initial	if Corre	ct:		

Total Doors \_\_\_\_\_

Total Doors \_\_\_\_\_

CONFIRMATIONS NOT RETURNED WITHIN 24 HOURS WILL BE CONSIDERED CORRECT.

# Georgia Hardwoods Inc

Vala	nce
Order	Form

Use this form to specify dimensions for both wood and mdf custom raised panel valances. Valances have a design fee plus the square foot charge for a standard door. Panels are evenly divided based on the style chosen. Only outside edge OE16 is available. Panel designs with applied moulding are limited to profiles that fit to curved parts. Valances not following the variations in this order form or on the technical catalog are considered non-catalog and will be charged a design fee and/or a customization fee.

Valance leadtimes are the same as that of wood doors and mdf doors.

CUSTOMER (contact name, a	address and phon	e)							DATI	EIN		
									DATE	EREQUEST	ED	
NAME OF JOB						PO #			APPRO	VAL		
SPECIE					RTF					Part of I	arger Order	
□ Wood Specie				Vinyl Co	olor					□ Ship wit	h Doors/Boxes	
SHAPE VAL-2P X \$325.00 VAL-3P X \$350.00 VAL-4P X \$400.00 SLAB X \$35.00 Custom X \$400.00	WOOD RAIL S-1 S-2 S-3 S-4 S-8	MDF RP	PANEL PP	: (Frame Only)	OUTSIDE EDGE		GH	De thin bendal	ble profiles.	FINISH Raw Prefit F Will add 3-5 a days to due d	dditional working	
<i>l</i> easurements			<b>I</b>		1	Solid Slab \	/alanc	es				
A (Width) B (Height)	C (Drop)	D (Foot)	E (Key T	op) F (Key	Bot)		-	A (Width)		B (Height)	OE (Edge)	
c	V	A E F AL-2P		B		VA	ged NL-E1 NL-F1					
Ev	en Width S	L-3P pec Width Center F	2anel			VA	NL-S1 NL-S2					
							NL-F2 NL-G1					
Ew		L-4P Dec Width Center P	anels			VA	AL-S3				E15, OE17 OR O	

Copyright 2011 Georgia Hardwoods Inc. All rights reserved.

P.O. Box 938 Buford, GA 30515 • Phone: 770-932-0640 • 800-992-6426 • Fax: 678-546-6105 • Fax: 770-932-0651