



JSL-300-AC / JSL-300-B

FAUCET GROUP

LAVATORY SENSOR FAUCET AC or BATTERY POWER





	APPROVED FOR MANUFACTURING	
MODEL NO.:		_QTY:
JOB NAME:		
TAG/ITEM:		
CUSTOMER:		
SIGNATURE:		



TECHNICAL DATA CONSTRUCTION:

Deck mount - non-mixing Senor range - 6" - 30" - Preset/Adjustable Automatic time-out -

Preset/adjustable to 0, 15, 30 or 60 sec.

Shut-off delay - Preset - Adjustable 1 to to 8 sec.

In-line filter with clean-out trap

Slow closing, piston operated solenoid

Control circuit- Solid state, AC or Battery (field switchable)

Solenoid valve - VSI silicone elastomer piston seal

6V DC, normally closed .4W (idle), 5W (in use)

Operating pressure - 5psi to 125 psi

Control module- wall mountable

Control/power cable - armored, vandal resistant

AC Mode - Power Adapter (UL/CSA)

Standard plug-in: Input AC 120V 60Hz or 220V

Output DC 12V. 0.8A/Class 2

Power cable: Armored, vandal resistant

Battery Mode - (UL/CSA)

Batteries - uses (4) AA Alkaline batteries Battery Life - 400,000 on/off cycles, up to 4yrs

FLOW RATE

0.5 GPM Laminar Flow Control - vandal resistant

FINISH

Chrome plated

OPTIONS

Multi-unit adapter - serves up to (8) faucets Input AC 120V, Output DC 12V, 3A

JUST MFG. COMPANY CONTINUES TO MAKE QUALITY AND FUNCTIONALITY A MARK OF THE JUST PRODUCT LINE. TO DO SO REQUIRES THAT WE RESERVE THE RIGHT TO CHANGE PRODUCT INFORMATION WITHOUT NOTICE. DIMENSIONS MAY VARY AND ARE SUBJET TO CHANGE WITHOUT NOTICE. NO RESPONSIBILITY IS ASSUMED FOR USE OF SUPERCEDED OR VOIDED DATA. FOR THE MOST CURRENT AND ACCURATE INFORMATION REGARDING THE COMPLETE LINE OF JUST SINKS, FAUCETS AND DRAINS, CLICK ON THE **SPEC LINE DRAWINGS** LINK ON OUR WEB SITE AT **www.justmfg.com**

JUST MANUFACTURING COMPANY9233 KING STREET . FRANKLIN PARK . ILLINOIS . 60131-2111PH: 847-678-5150. FAX: 847-678-6817. E-MAIL: custserv@justmfg.com . www.justmfg.com