REO INTERIOR WALL


AIW10376



ADA

Reo can be fully recessed, revealing only the faceplate. With a 1.0" wall projection, Reo easily satisfies ADA standards. Five optional color gels add a splash of color, serving as a guide or visual path. The ability to complement any style comes standard.

JOB NAME TYPE



Dimensions

W	Н	D	MC	
13.0 in	39.8 in	1.0 in	19.5 in	
330 mm	1011 mm	25 mm	495 mm	

Weight

Hanging weight: 25.0 lb (11.4 kg).

Features

- Integral Class II power supply included, eliminating the need for remote mounting, simplifying installation.
- Formed metal construction provides durable protection for internal components and is recyclable.
- Embossed stainless steel-linear and crosshatch face plate option adds a unique, metal accent and texture to a space.
- Standard thermoset polyester powder coat paint provides durable protection in a palette of color options. Custom colors available upon request.
- Fixture adds a splash of color to a space with theatrical color gels. Standard colors are available with other colors available upon request. Contact factory to customize a color gel that coordinates with your application.
- Compliant with Americans with Disabilities Act (ADA) requirements.

Technical Notes

Electrical

- Fluorescent versions have integral electronic ballasts utilizing the latest energy-saving technology, providing prolonged lamp life and maintaining consistent color.
- Advent uses strict quality guidelines in LED selection to ensure the white LED's we use meet or exceed ANSI Binning Standards (ANSI C78.733).
- Thermally protected ballast limits operating temperature.
- Class "A" sound rated ballast for use in low ambient noise applications.
- Meets NEC 410.73 double-ended, fluorescent lamp ballast disconnect requirements.
- ETL listed to UL standards (US and Canada) for use in damp locations. Not recommended for exterior applications.

Lamping/lamp

- L70 life= 50,000+ hours.
- Fluorescent lamps are 3500K unless specified.
- · Lamps included, with the exception of T8, T5 and incandescent.

Mounting

· Requires recessed mounting.

Additional Documents

Color Chart (http://www.specAdvent.com/pdfs/advent_color_chart.pdf)

MODEL NUMBER	LIGHT SOURCE	FINISH	VOLTAGE	LAMP OPTIONS	OPTIONS	COLOR ACCENTS

Not all options are available in all configurations, consult factory for details.

Light Source		Photometry
L35.8W	White 35.8W 3.2W/6" LED Light Engine Delivered Lumens: 1,467	40IN REC WS LED LOW
L71.7W	White 71.7W 6.4W/6" LED Light Engine Delivered Lumens: 2,933	40IN REC WS LED HIGH
2F21 📡 1	2F21WT5/Mini Bipin	
2F21DM \(\setminus \) 1	2F21WT5/Mini Bipin Dimming	
2F25 📡 1	2F25WT8/Med Bipin	
2F39 📡 1	2F39WT5HO/Mini Bipin	
2F39DM 📡 1	2F39WT5HO/Mini Bipin Dimming	

120-277V Universal Voltage					
120V	120 Volt				
277V	277 Volt				
amp Options					
3000K	0K 3000K Cct				
DML ²	0-10V Dimming				
3500K	3500K Cct				
4000K	4000K Cct				
EMR	Emergency Ballast Remote				

Options	
ES1	Embossed Stainless Steel-linear Pattern
ES2	Embossed Stainless Steel-cross Hatch Pattern
WF1	Cherry Laminate
WF2	Maple Laminate
Color Accent	s
CG00	White Color Gel
CG01	Red Color Gel
CG02	Orange Color Gel
CG03	Green Color Gel
CG04	Blue Color Gel

Painted Finishes

PT01	SuperWhite	PT07	Light Taupe	PT13	Warm Gray	PT19	Blue	PT29	Red Brass	PT42	Sky Blue	PT48	Brass
PT02	White	PT08	Medium Taupe	PT14	Light Gray	PT20	Dark Green	PT31	Medium Bronze	PT43	Teal	PT49	Bronze
PT03	Morning Light	PT09	Medium Gray	PT15	Sage	PT21	Pearl White	PT32	Dark Bronze	PT44	Green		
PT04	Warm White	PT10	Dark Gray	PT16	Spruce	PT22	Platinum	PT33	Dark Blue	PT45	Purple		
PT05	Putty	PT11	Black	PT17	Red	PT27	Deep Copper	PT40	Yellow	PT46	Aluminum		
PT06	Warm Beige	PT12	Dark Chocolate	PT18	Deep Red	PT28	Dark Stainless	PT41	Orange	PT47	Deep Red Brass		

Metal and Plated Finishes

BAL	Brushed Aluminum	

T5 & T8 Fluorescent Linear Lamp(s) Not Included
DML with LED lamping only.