
# PAVO INTERIOR PENDANT SIP11735



Minimalist form meets functional lighting with the Pavo 3 fixture pendant. The sleek 2.5 inch diameter acrylic lens encloses two T5 lamps and an integral ballast. Power cord suspension adds to the Pavo's minimalist flair by eliminating unnecessary aircraft cables or stems. The Pavo works great in high ceiling applications such as churches, stairwells, and atriums. A splash of color or metal finish can be added to the fixture with the optional tube cover accessory.

JOB NAME TYPE



#### **Dimensions**

	-
V	
16.2	
411	

#### Weight

Hanging weight: 50.0 lb (22.7 kg).

# **Features**

- · Fixture Head Heights Are Individualy Adjustable
- Extruded aluminum construction provides durable protection for internal components and is recyclable.
- Opal acrylic diffuser lens enhances a space with filtered illumination.
- External fasteners are not visible, providing a clean fixture design.
- Fixture design allows relamping without the use of tools, simplifying maintenance.
- Standard thermoset polyester powder coat paint provides durable protection in a palette of color options. Custom colors available upon request.
- · Electronic ballast increases energy savings and performance.
- Integral ballast simplifies installation by eliminating the need to locate, mount and wire a remote ballast.
- Canopy painted to match decorative accents (AC1 or AC2) when selected.

### **Technical Notes**

# **Electrical**

- · 48" white power cord standard.
- Class "A" sound rated ballast for use in low ambient noise applications.
- Meets NEC 410.73 double-ended, fluorescent lamp ballast disconnect requirements.
- ETL listed to UL standards (US and Canada) for use in damp locations. Not recommended for exterior applications.

#### Mounting

Oversized White Round Canopy Standard.

#### **Additional Documents**



MODEL NUMBER	LIGHT SOURCE and LENGTH	VOLTAGE	LAMP OPTIONS	OPTIONS	ACCENT	ACCENT FINSH

Not all options are available in all configurations, consult factory for details.

Light Source		Photometr	Voltage	
4 Foot Nominal Fixture			120V	120 Volt
(3) 2F14 <sup>1</sup>	<b>№</b> 2	(3 HEAD) 2F14T5/Mini Bipin	277V	277 Volt
(3) 2F14DM	<b>∑</b> 2	(3 HEAD) 2F14T5/Mini Bipin Dimming	Lamp Option	ns
5 Foot Nominal Fixture			BPC	Black Power Core
(3) 2F21 <sup>3</sup>	<b>№</b> 2	(3 HEAD) 2F21T5/Mini Bipin	DM	Dimming
(3) 2F21DM	<b>№</b> 2	(3 HEAD) 2F21T5/Mini Bipin Dimming	F	Fusing
6 Foot Nominal Fixture				
(3) 2F28 <sup>4</sup>	<b>№</b> 2	(3 HEAD) 2F28T5/Mini Bipin		
(3) 2F28DM	<b>∑</b> 2	(3 HEAD) 2F28T5/Mini Bipin Dimming		

/oltage		Options	Options					
120V	120 Volt	DL	Down Light LED MR16 (12V,					
277V	277 Volt		GU5.3Base)					
_amp Options	<b>S</b>	CAS	16" Canopy & 48" Stem					
BPC	Black Power Cord	Accent						
DM	Dimming	AC1	Decorative Accent Top					
F	Fusing	AC2	Decorative Accent Top And Bottom					

# Painted Finishes

PT01	SuperWhite	PT07	Light Taupe	PT13	Warm Gray	PT19	Blue	PT29	Red Brass	PT42	Sky Blue	PT48	Brass
PT02	White	PT08	Medium Taupe	PT14	Light Gray	PT20	Dark Green	PT31	Medium Bronze	PT43	Teal	PT49	Bronze
PT03	Morning Light	PT09	Medium Gray	PT15	Sage	PT21	Pearl White	PT32	Dark Bronze	PT44	Green		
PT04	Warm White	PT10	Dark Gray	PT16	Spruce	PT22	Platinum	PT33	Dark Blue	PT45	Purple		
PT05	Putty	PT11	Black	PT17	Red	PT27	Deep Copper	PT40	Yellow	PT46	Aluminum		
PT06	Warm Beige	PT12	Dark Chocolate	PT18	Deep Red	PT28	Dark Stainless	PT41	Orange	PT47	Deep Red Brass		

#### Metal and Plated Finishes

BAL Brushed Aluminum

# Kit Details



Down Light LED MR16 (12V, GU5.3Base)

<sup>1</sup> H= 46.5in (118.1cm) OAH= 98.5in (250.2cm)
2 T5 & T8 Fluorescent Linear Lamp(s) Not Included
3 H= 58.5in (148.6cm) OAH= 110.5in (280.7cm)
4 H= 70.0in (177.8cm) OAH= 122.0in (309.9cm)