

A photograph of a truck's cargo area. In the foreground, a yellow ratchet strap is attached to a metal anchor. Behind it, several rusty metal chains are visible, some connected to a black metal structure. The background shows the interior of a truck cab and a window. The overall scene is industrial and focuses on trucking equipment.

# Tiedown Handbook for Truck Movements

SDDCTEA PAMPHLET 55-20  
FOURTH EDITION

TRANSPORTATION AND TRAVEL

**TIEDOWN HANDBOOK**

**FOR**

**TRUCK MOVEMENTS**

FOURTH EDITION

**July 2008**

Terry Jenkins

Graphic designs: Terry L. Jenkins  
Pamphlet consultant: Robert E. Kerr

---

MILITARY SURFACE DEPLOYMENT AND DISTRIBUTION COMMAND  
TRANSPORTATION ENGINEERING AGENCY  
Building 1990, 709 Ward Drive  
Scott AFB, IL 62225  
[www.tea.army.mil](http://www.tea.army.mil)

Director  
Military Surface Deployment and Distribution Command  
Transportation Engineering Agency  
ATTN: SDTE - DPE  
Building 1990, 709 Ward Drive  
Scott AFB, IL 62225

Telephone: DSN 770-5263, 618-220-5263, or 1-800-722-0727

E-mail: [john.d.newman@us.army.mil](mailto:john.d.newman@us.army.mil)

The publications in this series are:

TEA PAM 55-19, *Tiedown Handbook for Rail Movement*  
TEA PAM 55-20, *Tiedown Handbook for Truck Movements*  
TEA PAM 55-21, *Lifting and Tiedown of U.S. Military Helicopters*  
TEA PAM 55-22, *Lifting Handbook for Marine Movements/Lashing Handbook  
for Marine Movements*  
TEA PAM 55-23, *Containerization of Military Vehicles*  
TEA PAM 55-24, *Vehicle Preparation Handbook for Fixed Wing Air Move-  
ments*

TB-55-46-1, *Standard Characteristics for Transportability of Military Equip-  
ment* is available in compact disc and contains all of the 55-pamphlet series. It  
also includes the Ports for National Defense, TEA 70-1, 700-2, and 700-5.

---

Local Reproduction Authorized  
Not Copyrighted

First edition published September 1992, with a Pink Desert Camouflage Cover  
First edition, second printing, published November 1993, with a Yellow Cover  
Second edition, first printing, September 1996, with a Pale Green Cover  
Third edition published July 2001, with an M1000/M1 Photo Cover  
Fourth edition published July 2008, with an M872/HYEX Photo Cover

## Preface

This is the fourth edition of the publication. It contains some changes and improvements over the previous editions. Between printings, the most current information can always be found online at [http://www.tea.army.mil/pubs/nr/dep/fgpamphlets/PAM\\_55-20.pdf](http://www.tea.army.mil/pubs/nr/dep/fgpamphlets/PAM_55-20.pdf). This publication will aid the Soldier in ensuring safe highway transport of equipment.

This publication provides users with the proper methods for securing wheeled and tracked vehicles on flatbed semitrailers, and general cargo on cargo trucks and semitrailers. It comprises basic information from Transportability Guidance Technical Manuals and experience gained through participating in many military exercises. When used in this publication, “cargo vehicle” includes both single-unit trucks that carry cargo and cargo-carrying semitrailers of tractor- semitrailer combinations. “Payload vehicle” refers to a vehicle that the cargo vehicle is carrying.

This publication covers minimum standards. Also, it only covers the types of military equipment commonly carried on cargo vehicles. Although this publication gives adequate tiedown patterns, responsibility for the safe transport of the load rests with the truck driver. The driver may apply additional tiedown chains or cables provided they are attached to authorized tiedown provisions on the payload vehicle.

Remember, all equipment loaded onto cargo vehicles must be firmly and properly secured to counteract longitudinal (fore and aft), lateral (side to side), and vertical (up and down) forces. All hazardous material must be in compliance with the Code of Federal Regulations (CFR) Title 49, and all military oversize, overweight, or special movements must be in accordance with DOD Reg 4500.9-R, Part III, Mobility. To avoid having an oversize load, you may have to ship some items in their reduced configuration.

SDDCTEA welcomes comments and recommendations for improving this publication. Readers may send their suggestions by letter, on DA Form 2028, or on a marked copy of a page(s) of the publication to Director, Military Surface Deployment and Distribution Command Transportation Engineering Agency, ATTN: SDTE-DPE, Building 1990, 709 Ward Drive, Scott AFB, IL 62225. You may also email [john.d.newman@us.army.mil](mailto:john.d.newman@us.army.mil) to submit suggestions.

Questions can be answered by contacting us using the information from page ii. Please feel free to make copies of this publication at your own discretion.

# Notes

**TIEDOWN HANDBOOK FOR TRUCK MOVEMENTS****CONTENTS**

<i>Section</i>	<i>Page</i>
I. GENERAL CARGO AND LOADING PRINCIPLES .....	1
II. MILITARY CARGO VEHICLES .....	9
A. General .....	9
B. M172A1 Lowbed Semitrailer .....	16
C. M870 and M870A1 Semitrailers .....	16
D. M872-Series (and M871) Flatbed Semitrailers .....	36
E. M747 Semitrailer .....	45
F. M1000 Semitrailer .....	58
G. Trucks with Shelters .....	71
H. Palletized Load System (PLS) .....	72
III. GENERAL FLATBED SEMITRAILER LOADS .....	81
A. Tiedown with Chains .....	81
B. Tiedown with Wire Rope .....	89
C. Tiedown with Web Strap .....	100
D. Tiedown with Steel banding .....	104
IV. PAYLOAD VEHICLE TIEDOWN TIPS .....	107
A. Preparing Payload Vehicles Prior to Loading .....	107

## CONTENTS - cont

<i>Section</i>	<i>Page</i>
B. Loading Payload Vehicles .....	107
C. Securing Vehicles .....	109
D. Toolkit .....	111
V. FORSCOM CARGO FORMS .....	114
A. General .....	114
B. FORSCOM Form 285-R .....	114
C. DD Form 1750 .....	118
ACRONYMS .....	121

# LIST OF ILLUSTRATIONS

<i>Figure</i>	<i>Page</i>
1 Common cargo loading “Do’s” and “Don’ts” .....	3
2 Five-ton truck on semitrailer illustrating chains and cables in crossed and same-side patterns .....	11
3 Interference with a same-side pattern .....	12
4 Two chains using the same side tiedown fitting .....	13
5 Crossed chains for inadequate chain length with same side pattern .....	14
6 Tiedowns with no lateral angle .....	15
7 Detail of chain tiedown configuration using a loadbinder .....	17
8 M172A1 semitrailer .....	18
9 M113 or similar vehicle on the M172A1 .....	19
10 6K variable reach rough terrain forklift (VRRFL) on the M172A1 .....	20
11 M870 semitrailer .....	21
12 M870A1 semitrailer .....	22
13 Tiedown configuration of the M1097 HMMWV or similar vehicle on the M870 .....	24
14 Detail on attaching chains to the M870 outrigger supports .....	25
15 Tiedown configuration of the M1028 CUCV or similar vehicle on the M870A1 .....	36



## LIST OF ILLUSTRATIONS - cont

<i>Figure</i>		<i>Page</i>
16	Tiedown configuration of the M9 ACE on the M870 .....	26
17	Tiedown configuration of grader on the M870 .....	27
18	Tiedown configuration of grader on the M870A1 .....	28
19	Tiedown configuration of scoop loader on the M870 .....	29
20	Tiedown configuration of 6K VRRTFL on the M870 .....	30
21	Tiedown configuration of 6K VRRTFL on the M870A1 .....	31
22	Top and side view tiedown configuration of the M2 Bradley fighting vehicle and similar vehicles on the M870 .....	32
23	Rear tiedown configuration of the M2 Bradley fighting vehicle and similar vehicles on the M870 .....	33
24	Top and side view tiedown configuration of the M2 Bradley fighting vehicle and similar vehicles on the M870A1 .....	34
25	Rear view of the M2 Bradley fighting vehicle and similar vehicles on the M870A1 .....	35
26	3D views of the M872A1, M872A2, and M872A3 semitrailers .....	37
27	Operation of the M872 retractable twist lock .....	38

## LIST OF ILLUSTRATIONS - cont

<i>Figure</i>		<i>Page</i>
28	Operation of the M872A3 retractable twist lock .....	39
29	M872 removable container locks .....	40
30	Installation of M872 side racks and removable side stakes .....	41
31	Two M113 variants secured to an M872A1 or M872A2 .....	42
32	Two M113 variants secured to an M872A3 .....	43
33	HMMWVs on M872A1 or M872A2 .....	44
34	M747 HET .....	46
35	M747 loading ramp tiedown .....	47
36	Blocks under the M747 for loads over 55 tons .....	48
37	M747 curbing positions .....	50
38	M747 curbing .....	51
39	M1 tank on the M747 .....	53
40	3D view of M1 tank on the M747 .....	54

## LIST OF ILLUSTRATIONS - cont

<i>Figure</i>		<i>Page</i>
41	M60-series tank on the M747 .....	55
42	Tiedown configuration of M2 Bradley fighting vehicle or similar vehicles on the M747 .....	56
43	M109-series howitzer on the M747 .....	57
44	M1000 HET .....	59
45	M2 Bradley fighting vehicle on the M1000 .....	60
46	M2 Bradley fighting vehicle facing forward on the M1000 (rear view) .....	61
47	M109-series howitzer on the M1000 .....	63
48	Front angled view of M1 tank on the M1000 .....	64
49	M1 tank on the M1000 .....	65
50	Rear view of M1 tank on the M1000 .....	66
51	M60-series tank on the M1000 .....	67
52	Tiedown configuration of M113 and similar vehicles on the M1000 .....	69
53	Shoring for M104 Wolverine Bridge and Wolverine loaded on M1000 .....	70
54	Securing the S-280 shelters to trucks .....	71

## LIST OF ILLUSTRATIONS - cont

<i>Figure</i>		<i>Page</i>
55	Palletized load system truck with material handling crane .....	72
56	Palletized load system trailer .....	72
57	M1077 flatrack .....	73
58	M1 flatrack .....	74
59a	M3 and M3A1 .....	75
59b	M3 and M3A1 with CG location .....	76
60	Palletized load system M1077 flatrack .....	77
61	HMMWV on a PLS flatrack .....	79
62	Payload on an M1077 A-frame flatrack .....	80
63	Types of loadbinders .....	82
64	Tying down using chain .....	85
65	Chain tiedown running through a stake pocket .....	88
66	Tying down using wire rope .....	90
67	Complete loop wire rope assembly .....	94
68	Single strand wire rope assembly .....	95
69	Detail of thimble attachment .....	96

## LIST OF ILLUSTRATIONS - cont

<i>Figure</i>	<i>Page</i>
70 Turnbuckles .....	97
71 Chain hoist and cable grippers .....	99
72 Chain hoist and cable grippers in use .....	99
73 Web strap (NSN 5340-01-204-3009) .....	101
74 Typical loads secured with web straps .....	102
75 Palletized load using web straps or steel banding .....	103
76 Illustration of steel band notch and crimp type seal joints .....	105
77 Typical load secured with steel straps and strap anchoring detail .....	106
78 When to use dunnage .....	110
79 FORSCOM Form 285-R (sample vehicle loading card) .....	115
80 DD Form 1750 (sample vehicle packing list) .....	119

## LIST OF TABLES

<i>Table</i>		<i>Page</i>
1	Military Semitrailers .....	10
2	Positions for M747 Curbing .....	49
3	Loadbinders .....	83
4	Common Chains .....	84
5	Wire Rope .....	93
6	Turnbuckles .....	98
7	Suggested Vehicle Loading Toolkit .....	112

# Notes

## SECTION I. GENERAL CARGO AND LOADING PRINCIPLES

Single-unit and tractor-semitrailer trucks both commonly transport general cargo. General cargo can be loose, palletized, or containerized. Because each cargo load is different, this pamphlet cannot show tiedown patterns for all possible loads. This section presents general principles for tying down cargo. The driver who follows these general principles and uses extra tiedowns, when in doubt, will have a properly-loaded vehicle.

Always secure a load, even if the trip is just a short distance on a military installation. A jolt, during starting or stopping, or a road vibration could topple an unsecured load. Accidents caused by unsecured loads have occurred on trips of less than 1/10 mile. Generally, the first requirement to conduct a halt to check the load during a convoy is at the 1 hour mark. All other halts are 10 minutes every 2 hours. On longer trips, check tiedowns about 2 miles from your origin, at all halts (rest stops), and whenever you suspect a problem with your load. Vibration may reveal a problem with a load that appeared to be adequately secured at the origin. If the load has a turret and gun or other rotating parts, be sure to secure those parts to prevent rotation into the path of oncoming traffic. Weather proofing exposed loads is also recommended.

Based on FM 55-30, *Army Motor Transport Units and Operations*, 27 June 1997, Figure 1 shows some common do's and don'ts for loading cargo vehicles. The payload should be as symmetrical as possible about the longitudinal centerline of the cargo vehicle. It should also be distributed as uniformly as possible over the cargo vehicle's bed.

Improperly placed cargo can make vehicles unstable and difficult to control. It can also overstress the frame. Of course, you should never overload a cargo vehicle. The vehicle data plate shows the rated cargo (payload) capacity. The names of most military cargo vehicles also tell the payload capacity. For example, a 5-ton truck can carry up to 5 tons (10,000 pounds). The rated cargo capacity is for a vehicle with a properly distributed load.



Munitions must be restrained by specific procedures, which can be obtained from the U.S. Army Defense Ammunition Center (DAC). For ordering procedure publications, start at the following web link: <https://www3.dac.army.mil/>

When your vehicle is transported by highway, the following restraint criteria are used for developing tiedown procedures:

Highway

0.7 g forward (relative to the transporter)

0.3 g aft and lateral

0.5 g vertical

When your vehicle is transported by other modes, the following restraint criteria are used for developing tiedown procedures:

Rail

4.0 g longitudinal

1.5 g lateral

2.0 g vertical

Marine

0.81 g lateral relative to ship

0.42 g longitudinal

0.00 g vertical

Air (USAF) Fixed Wing

3.0 g forward relative to aircraft

2.0 g vertical


1.5 g aft and lateral

Air (Army) Rotary Wing CH-47


4.0 g forward relative to aircraft

2.0 g aft and vertical

1.5 g lateral



Tires, axles, frame, and so forth, are designed to carry a load distributed as above.




Distribute trailer loads between the rear tires and the fifth wheel. This transfers the load to the tractor.

Figure 1. Common cargo loading "Do's" and "Don'ts."



WRONG




RIGHT

The right vehicle for the right job.



WRONG

This overloads trailer rear wheels, brakes won't brake properly, rubber scuffs away.




RIGHT

Distribute the load over the full trailer floor.



WRONG


This overloads one spring and set of tires. Brakes lock on the right side, cause skids.



RIGHT


Nothing overloaded, frame won't twist and loosen crossmember.

Figure 1. (continued)




WRONG

This will bend the frame, overload front tires, and make steering harder.




RIGHT

Place heavy part of load near rear axle for proper tire loading and to keep frame from bending.



WRONG


This kind of weight distribution bends the frame, overloads rear tires, and makes steering almost impossible.




RIGHT

Set a concentrated load just ahead of the rear axle with, if possible, the longest side on the floor.


Figure 1. (continued)

**WRONG**


This overloads tires, shortens their life, and bends the truck rear axle housing. Applying the trailer brakes may lock the wheels and cause flat spots and skidding.

**RIGHT**


Distribute the load over the full trailer floor.

**WRONG**

If you are not careful, this will happen.




*Figure 1. (continued)*



PLS

Place cargo tight against front end wall of flatrack.

PLS ONLY



↑  
5-10%

↑  
90-95%

Trailer

Distribute trailer load between the axle and the pintle

Figure 1. (continued)

A cargo vehicle with substantial side and end boards (or stakes) may not need tiedowns if the cargo:

- (a) can be loaded against the sides and forward end without voids,
- (b) the cargo is below the top of the side and end boards, and
- (c) there is no danger of the cargo tipping over or shifting dangerously.

Cargo in sacks will usually be stable if personnel stagger the layers of sacks. Most loads will need securement to prevent shifting and damage. You must secure all loads on flatbeds without sides to keep the loads from falling off. All cargo on the PLS flatrack must be tied down to prevent shifting.

Chains and loadbinders are usually the best devices for securing large items on cargo vehicles. You can use nylon or polyester straps (NSN 1670-00-725-1437 or NSN 5340-01-204-3009) to secure boxed or crated items weighing up to about 3,000 pounds. You can tie down heavier crates by using several nylon or polyester straps. Shippers can also use manila rope, wire rope, cargo nets, or steel banding to secure loads. Steel banding must be at least 5/8 and preferably 1-1/4 inches wide and must have at least two pairs of crimps in each seal and, when end-over-end lap joints are formed, must be sealed with at least two seals. When used during rail transport, steel banding must be approved by the Association of American Railroads.

These tiedown guidelines are valid for highway/cross-country transport. If the cargo vehicle will hold cargo while carried in an aircraft or on a railcar, then its cargo will need to be tied down more securely. It will have to meet the approval of the aircraft loadmaster or railroad representative, as appropriate. In general, items on vehicles riding on railcars must be fastened to the vehicle as securely as they would be fastened to a flatcar if they were riding directly on the flatcar. For guidance on securing items for rail transport, see TEA PAM 55-19, *Tiedown Handbook for Rail Movements*. Distribute the load over the full trailer floor. If a cargo vehicle is aboard a ship, its cargo will usually be adequately restrained if it was properly restrained for movement over the highway. However, the vessel's master is the final authority. In some cases, additional lateral restraint may be necessary. For guidance on securing items for marine transport, see TEA PAM 55-22, *Lifting and Lashing Handbook for Marine Movements*.

## SECTION II. MILITARY CARGO VEHICLES

### A. GENERAL

A commercial truck driver is responsible for securing exposed loads. Therefore, military personnel will rarely secure loads on commercial flatbeds. Even when military personnel load and help tie down cargo, the commercial truck driver is still responsible for ensuring that the tiedown arrangement is safe.

The driver of a military cargo vehicle is responsible for the safety of the load. The unit is responsible for loading and unloading the vehicle. Securing the cargo is a shared responsibility between the two. The truck driver will advise in securing the load and check to ensure it is safe for movement.

Table 1 summarizes common military flatbed semitrailers. The following paragraphs contain detailed information on some of these semitrailers. If several different types of cargo vehicles are available, the user must select one with an adequate load rating and cargo bed area. The lowest and lightest acceptable cargo vehicle will usually cause the fewest conflicts with highway weight and vertical clearance limits.

You should usually run chains or cables in a same-side pattern (fig 2). You should cross chains or cables when:

1. There is interference with a same-side pattern (fig 3).
2. Two chains use the same tiedown fitting on the payload vehicle. In this case, one chain may be same-side and the other may be crossed (fig 4).
3. When the same-side pattern results in a chain length that is too short for the appropriate loadbinder (fig 5).
4. Same-side may not provide adequate lateral restraint, if the tiedowns have no lateral angle. In the end view, the two tiedowns would appear nearly parallel to each other and/or vertical if they have no lateral angle. In this case, a cross pattern should be used to secure the payload vehicle (fig 6).




**TABLE 1**  
**MILITARY SEMITRAILERS**


Semitrailers	Load Rating (short tons)	Cargo Area		Deck Height (in.)
		Length x (in.)	Width (in.)	
M1000 HET <sup>1</sup>	70	406.5	120	43 <sup>3,4</sup>
M747 HET <sup>1</sup>	60	317	120	46
M870 (Army) <sup>1</sup>	40 <sup>5</sup>	216	120 <sup>6</sup>	40
M870 (USMC) <sup>1</sup>	40 <sup>5</sup>	204	120 <sup>6</sup>	48
M872 <sup>2</sup>	34	485	96	58 <sup>7</sup>
M172A1 <sup>1</sup>	25	192	115	39
M871 <sup>2</sup>	22.5	354	96	55

1. Lowbed
2. Flatbed
3. Normal travel height
4. Deck height can vary from 33 to 53 inches during loading
5. No more than half of the payload weight may be placed on the outriggers
6. Width with outriggers; normal width is 96 inches
7. M872A1 and A3 variants have a 55-inch high bed

**TOP VIEW**




5-ton truck, tiedowns crossed.




5-ton truck, tiedowns same-side.

**SIDE VIEW**




5-ton truck on semitrailer.


*Figure 2. Five-ton truck on semitrailer illustrating chains and cables in crossed and same side patterns.*




*Figure 3. Interference with a same side pattern.*



*Figure 4. Two chains using the same tiedown fitting.*



*Figure 5. Crossed chains for inadequate chain length with same side pattern.*



*Figure 6. Tie-downs with no lateral angle.*

Many military flatbeds have basic issue item (BII) chains and loadbinders. Use chains and loadbinders when they are available. Figure 7 shows a typical chain and loadbinder combination.

## **B. M172A1 LOWBED SEMITRAILER**

The M172A1 (fig 8) is a common military lowbed semitrailer with a 25-ton capacity. These trailers have portable ramps for use at the rear end. Their bed width is 115 inches. The M172A1 has 19 lashing rings (D-rings); 5 on each side, 3 on the rear, and 6 on the gooseneck. These semitrailers have open wheel wells and a usable bed length of 192 inches.

A load on an M172A1 gets adequate forward restraint if it is firmly against the gooseneck. You must use chains or cables to provide adequate vertical, lateral, and rearward restraint. Some loads cannot rest against the gooseneck. If the semitrailer is carrying an item that is not touching the gooseneck, chains must restrain it against forward motion as well. Figures 9 and 10 show adequately restrained loads on this semitrailer. Restraint patterns in figures 9 and 10 use 3/8-inch chain assemblies (NSN 4010-00-803-8858) and loadbinders (NSN 3990-01-213-1746).

## **C. M870 AND M870A1 SEMITRAILERS**

The M870 and M870A1 are adaptations of commercial construction equipment haulers. They can haul most types of military construction equipment and most tracked vehicles that weigh less than 40 tons. Blocking and bracing generally are not required. Figures 11 and 12 show the M870 and M870A1. You can load these trailers at end ramps or by uncoupling from the tractor and dropping the gooseneck to use as a front ramp. The USMC version of the M870 also has portable ramps for use at its back end. These semitrailers have a normal bed width of 96 inches. However, outriggers can extend the bed width to 120 inches. Loads wider than 96 inches must be loaded over the back end since the outriggers do not extend over the gooseneck portion. At least 1/2 of the tire or track must be placed on the 96" bed width. The remainder may be placed on the outrigger. An exception is all versions of the hydraulic excavator (HYEX) which has been approved for the M870 and M870A1.




Figure 7. Detail of chain tiedown configuration using a loadbinder.








Figure 8. M172A1 semitrailer.

**TOP VIEW**

One chain on each rear tiedown.



Position M113 with the tracks clearing the semitrailer wheel wells.

**SIDE VIEW**

*Figure 9. M113 or similar vehicle on the M172A1.*




Figure 10. 6K variable reach rough terrain forklift (VRRTFL) on the M172A1.




Figure 11. M870 semitrailer.




Figure 12. M870A1 semitrailer.



The M870 has six lashing rings (D-rings) on each side. It also has two D-rings on the rear cargo bed and four D-rings on the gooseneck. The M870A1 has five D-rings on each side. It also has two D-rings and two 17-ton shackles on the cargo bed and two D-rings and two 17-ton shackles on the gooseneck.

Figures 13 through 25 show adequately restrained loads on these semitrailers. Most vehicles will be easier to secure if they are snug against the M870 gooseneck. You can secure many vehicles by chaining the front payload vehicle *lifting eye* to D-rings on the M870 gooseneck (figs 16, 17, 22, and 24). A load on an M870 or M870A1 gets adequate forward restraint when parked firmly against the gooseneck. You must use chains or cables to provide adequate vertical, lateral, and rearward restraint. If the semitrailer is carrying two pieces of equipment, chains must restrain the item that is away from the gooseneck against forward motion as well. Many loads are too wide to restrain using the shackles on the M870A1 gooseneck. Bulldozer blades hide these shackles, for instance. Items that mask the shackles at the base of the gooseneck can be secured to D-rings on the top part of the gooseneck.


The M870 BII includes 10 chain assemblies (NSN 4010-00-443-4845) and 10 loadbinders<sup>1</sup>. The M870A1 BII includes six chain assemblies (NSN 4010-00-443-4845) and six loadbinders. You can tie down relatively light vehicles using one chain attached to a tiedown point on each corner of the vehicle (fig 13). You should use a crossed chain pattern if you secure a vehicle to the M870 outrigger support members (fig 14). Figure 15 shows how to secure a light vehicle on the M870A1.

---

<sup>1</sup> M870s are being equipped with improved loadbinders (NSN 3990-01-213-1746) as BII. However, some M870s still have type II loadbinders (NSN 3990-00-171-9774), which were the original BII loadbinder. Loadbinders are described and specified in Federal Specification GGG-B-325.


**TOP VIEW****SIDE VIEW**

*Figure 13. Tiedown configuration of the M1097 HMMWV or similar vehicle on the M870.*

**REAR VIEW**

*Figure 14. Detail on attaching chains to the M870 outrigger supports.*







1. The vehicle may be driven onto the semitrailer if a ramp is available or back onto the semitrailer if the gooseneck of the semitrailer is extended. Some restrictions apply.
2. The H-frame shoring should be installed between the tracks.
3. The vehicle should be parked, with the brake set. Allow the hydraulics to settle to the bump stops before tying the M9 down.
4. The M870 semitrailer gooseneck must be raised to the travel position by using the truck-tractor winch cable, and the semitrailer must be connected to the truck tractor.

Refer to TM 55-2350-262-14 for additional guidance on tiedown procedures to include

*Figure 16. Tiedown configuration of the M9 ACE (Armored Combat Earthmover) on the M870.*

**TOP VIEW****SIDE VIEW**

*Figure 17. Tiedown configuration of grader on the M870.*





**TOP VIEW****SIDE VIEW**

Figure 18. Tiedown configuration of grader on the M870A1.

**REAR VIEW**



**SIDE VIEW**






Figure 19. Tiedown configuration of scoop loader on the M870.

**TOP VIEW**



**SIDE VIEW**




Figure 20. Tiedown configuration of 6K VRRFTL on the M870.






Figure 21. Tiedown configuration of 6K VRRFTL on the M870A1.




*Figure 22. Top and side view tiedown configuration of the M2 Bradley fighting vehicle and similar vehicles on the M870.*


**REAR VIEW**

*Figure 23. Rear tiedown configuration of the M2 Bradley fighting vehicle and similar vehicles on the M870.*





*Figure 24. Top and side view tiedown configuration of the M2 Bradley fighting vehicle and similar vehicles on the M870A1.*

**REAR VIEW**

*Figure 25. Rear view of the M2 Bradley fighting vehicle and similar vehicles on the M870A1.*

#### **D. M872-SERIES (AND M871) FLATBED SEMITRAILERS**

The M872-series 40-foot flatbed semitrailers can carry a wide variety of cargo. All models can carry containers, bulk cargo, and general cargo. The M872A1 (fig 26), A2, and A3 also have tiedown fittings for securing two M113s or similar vehicles. The M872 does not normally carry vehicles. These semitrailers are 96 inches wide and 490 inches long. The M872 and M872A2 deck height is 58 inches. The M872A1 and M872A3 deck height is 58 inches. Units/shippers must arrange for container handling equipment (CHE), materials handling equipment (MHE), and/or loading ramps to load their cargo onto the M872-series semitrailers.

The operator's manual, TM 9-2330-359-14&P, shows how to use container locks and cargo rings on these semitrailers. Figures 27 through 30 are extracted from the operator's manual. Users should refer to the operator's manual for additional information on the M872.

Figures 27 through 29 show how to use the container locks. You can secure one 40-foot container using the in-place retractable twistlocks. You must also use removable container locks when securing two 20-foot containers or other containers shorter than 40 feet. You can use T-hooks to secure general cargo with straps. Figure 29 shows the installation of removable container locks. Figure 30 shows the M872 configured for carrying bulk cargo such as sand. You should use similar procedures when securing cargo to an M871 semitrailer.

Figures 31 through 33 show vehicles loaded on an M872A1 or M872A2. The illustrated tiedown arrangements are based on using 1/2-inch chain assemblies (NSN 4010-00-803-8858) and loadbinders (NSN 3990-01-213-1746). You could also use these tiedown patterns if you use stronger chains.




Figure 26. 3D views of the M872A1, M872A2, and M872A3 semitrailers.

1. Push twist lock up and turn handle (1) 90° clockwise.

2. Push twist lock up until bayonet collar (2) is clear of siderail (3).

3. While holding twist lock up, turn bayonet collar (2) 90° clockwise. Release twist lock to seat bayonet collar on siderail (3).

4. Load and secure container on semitrailer.

5. Turn handle (1) 90° counterclockwise into locked position. Move locking tab (4) down to secure.




Figure 27. Operation of the M872 retractable twist lock.

1. Release handle (6) from latch (7).
2. Push handle (6) up until bayonet collar (5) is above siderail (3) surface and turn 90° counter-clockwise.
3. Load and secure container(s) on semi-trailer.

**NOTE: Hold bayonet collar while turning handle.**

4. Turn handle (6) 90° clockwise into locked position with bayonet (8) perpendicular to bayonet collar (5).
5. Secure handle (6) in latch (7).





Figure 28. Operation of the M872A3 retractable twist lock.



1. Insert container lock (9) in siderail (3) and turn counterclockwise until lockpin (13) is aligned with slot (12) in siderail.
2. Push lockpin (13) down to engage in siderail (3).
3. Load and position container(s) on semitrailer.
4. Insert F-pin (11) through hole (10) in container lock (9) and turn until container is secured.





Figure 29. M872 removable container locks.

## STEPS

1. Position cover plates (4) on siderails (2) and rear sill.
2. Install side racks (1) in rectangular holes (3) in siderails (2) and rear sill position shown.
3. Install side racks (5) in siderails (2) and lock in position with retainer clips (6).



## **COVER PLATE ARRANGEMENT**

## NOTES:

1. Step 1 applies only if hauling granular bulk cargo or ammunition.
2. Side racks are three different sizes. Ensure that they are installed in proper position.







Figure 30. Installation of M872 side racks and removable side stakes.





**NOTE:** All chains are attached to the center D-rings (not to stake pockets).


*Figure 31. Two M113 variants secured to an M872A1 or M872A2.*




**NOTE:** All chains are attached to the cargo tiedown rings (not to the outside stake pockets).

*Figure 32. Two M113 variants secured to an M872A3.*

**TOP VIEW**



**SIDE VIEW**



*Figure 33. HMMWVs on M872A1 or M872A2.*

## E. M747 SEMITRAILER

The M747 lowbed heavy equipment transporter (HET) (fig 34) has a rated load-carrying capacity of 60 tons. The overall length of the semitrailer is about 43 feet. The usable bed is 317 inches long, 44 inches above the ground, 120 inches wide, and can accept cargo with some side overhang. The M747 can carry heavy tracked vehicles, including the M1 tank.

The operator's manual, TM 9-2330-294-14, shows how to load both operable and inoperable vehicles. Users should refer to the operator's manual for additional information on the M747.

The M747 has two adjustable loading ramps at the rear of the semitrailer. Each ramp can be moved laterally to load different width vehicles. When the M747 travels, the ramps must be raised and secured in position by a chain tiedown assembly (fig 35). The ramps can be removed when loading the M747 from a permanent ramp or dock.

Two jacking pads are welded underneath the frame at the rear corners. The jacking pads are under the stenciled instructions, "BLOCK HERE." You must put blocks under the jacking pads when loading a vehicle that weighs more than 55 tons. The M747 BII includes wood blocks for this purpose (fig 36).

The M747 comes with eight removable curbs. Up to four curbs should be placed on each side of the M747. These curbs restrain cargo laterally during transport and help guide vehicles onto the M747 during loading operations. Table 2 and figures 37 and 38 show locations and proper positioning of the curbing. Six sets of holes on each side of the M747 bed are for placing the curbing. Each set of holes has four lateral positions for proper adjustment. The curb portion of the curbing assembly can be positioned either toward the center of the M747 (inboard) or toward the outer edge of the M747 (outboard). Curbing should always be in location "F" on each side of the M747 when loading or unloading vehicles. Location "A" curbing may be temporarily moved to location "F" for loading and unloading operations. Before moving the M747, stow location "F" curbs if not used in location "A."




Figure 34. M747 HET.






Figure 35. M747 loading ramp tiedown.



*Figure 36. Blocks under the M747 for loads over 55 tons.*

TABLE 2  
POSITIONS FOR M747 CURBING

Vehicle	Location		Row	Position of Curbing
	Transporting and Loading	Loading Only		
M113 family of vehicles	A, B	F	3	Outboard
M551	A, B, C	F	4	Outboard
M578	A, B, C	F	3	Inboard
M109, M992	A, B, C	F	4	Inboard
M2, M3	A, B, C	F	1	Inboard
M1, M48, M60, M88	A, B, C, D	F*	2	Inboard

\*NOTE: Move curbs from position A to F when loading or unloading vehicle.







Figure 37. M747 curbing positions.



*Figure 38. M747 curbing.*


Load and park vehicles against the M747 gooseneck to prevent forward movement. The curbing provides much lateral restraint. However, chains are still necessary to prevent aft movement. The M747 comes with six BII 3/4-inch chains (NSN 4010-00-449-6573). These chains have a breaking strength of 50,400 pounds. The M747 also has six BII loadbinders (NSN 3990-00-401-1503). Figures 39 through 43 show tiedown patterns using these chains and loadbinders.

Vehicles in good condition can be driven onto the M747. Personnel can load disabled vehicles using a winch on the M911 truck tractor and the snatch block and roller assemblies on the trailer. Firm-tracked vehicles such as bulldozers should be attached to the winch cable, even if they are driven on. TM 9-2330-294-14 contains detailed instructions on using the winch, snatch block, and roller assemblies.


When possible, load on level ground. In adverse conditions, you can load on side and lateral slopes of up to 10 percent and with a towing vehicle - M747 offset angle up to 5°. Avoid loading on a severe downgrade to prevent the payload from rolling forward on the M747.

**NOTE:** If the vehicle is not placed in contact with the M747 gooseneck, tiedowns are required on both ends of the vehicle to prevent movement.

**TOP VIEW**




**SIDE VIEW**





**NOTE:** Payload not to exceed 60 tons.


*Figure 39. M1 tank on the M747.*



*Figure 40. 3D view of M1 tank on the M747.*

**TOP VIEW****SIDE VIEW**

*Figure 41. M60-series tank on the M747.*



*Figure 42. Tiedown configuration of M2 Bradley fighting vehicle or similar vehicles on the M747.*



**TOP VIEW****SIDE VIEW**

Figure 43. M109-series howitzer on the M747.



## F. M1000 SEMITRAILER

The M1000 HET (fig 44) can carry cargo weighing up to 70 tons. The overall length of the semitrailer is about 52 feet. The bed is 403 inches long by 120 inches wide, and can accept cargo with some overhang. The hydraulic suspension system on the M1000 trailer allows adjustment in the deck height from 33 to 53 inches. For travel, the deck height should be set at 43 inches. The M1000 was designed to carry heavy tracked vehicles.

Technical manual, Operator's Unit, Direct Support, and General Support Maintenance Manual for the heavy Equipment Transporter Semitrailer, 70 TON, M1000, which is referenced as TM 9-2330-381-14, shows how to load operable and inoperable vehicles. Users should refer to the this manual for additional information on the M1000, with the following exceptions: 1) Reference TB-9-2330-381-13-1, September 2007, when loading an M1 Series Main Battle Tank (MBT) with the Tank Urban Survivability Kit (TUSK) and the Counter-Improvised Explosive Device (C-IED) Kit and 2) Reference TB 9-2330-381-14-1, August 2000, when loading an M1 Series Main Battle Tank (MBT) with the Mine Clearing Blade Attached. Also note the M1000 is not authorized to haul two Bradley Fighting Vehicles (BFVs), which overloads the rear axle and exceeds the rating on the cargo tiedowns (D-rings). In addition to technical guidance, there are a number of warnings given throughout TM 9-2330-381-14 that users should observe during loading/unloading operations to avoid injury to personnel and damage to equipment.

The M1000 comes with 12 removable curbs. Six curbs should be placed on each side of the M1000 during loading to ensure proper vehicle alignment. All curbs not pinned beneath the cargo once the trailer is loaded should be stowed before transport. Six sets of holes on each side of the M1000 bed are for placing the curbing. Each set of holes has three lateral positions for proper adjustment. The curb portion of the curbing assembly can be positioned either toward the center of the M1000 (inboard) or toward the outer edge of the M1000 (outboard).

The curbing on the M1000 provides much lateral restraint. However, Chains are still necessary for longitudinal restraint. Basic Issue Items (BII) for the M1000 include, but are not limited to:

six 1/2-inch alloy chains—

two - 7 feet long - NSN 4010-01-361-8378

two - 11 feet long - NSN 4010-01-371-5772

two - 19 feet long - NSN 4010-01-385-5974

six 1/2-inch load binders - NSN 3990-01-440-5975 (Two added for front chains)

four 5/16-inch chain assemblies/utility chains, 11 ft long (for chock tie down) - NSN 4010-01-361-7267

two 5/16-inch load binders (for chock tie down) - NSN 3990-01-360-9669

Unlike the M747, it is not possible to place loads against the M1000 gooseneck, therefore, chains must provide forward restraint.

You should use a four-chain and load binder same-side pattern when securing M2s and most other tracked vehicles weighing less than 75,000 pounds. You should position the payload vehicle so that the front chains form an angle of about 45° from the deck to the vehicle. The rear chain should be at an angle of about 30° to 45°. Figures 45 and 46 show restraint for an M2 or similar vehicle facing forward on the M1000.

## Notes






Figure 44. M1000 HET.

**TOP VIEW**


M2 facing forward

**SIDE VIEW**


M2 facing forward

**TOP VIEW**


M2 facing aft

**SIDE VIEW**

M2 facing aft



*Figure 45. M2 Bradley fighting vehicle on the M1000.*



*Figure 46. M2 Bradley fighting vehicle facing forward on the M1000 (rear view).*

The M1000 can also carry most tracked vehicles facing aft. The tiedown pattern is similar to when the tracked vehicles face forward. Figure 45 shows an aft-facing M2 type vehicle. Figure 47 shows an M109.

The basic steps in loading and securing an M2 or other tracked vehicle that weighs less than 75,000 pounds are:

1. Properly position the side curbing.
2. Drive or winch the M2 to the proper position on the M1000.
3. Put the M1000 chock blocks in front of and behind the tracks.
4. Attach chains and tighten loadbinders.



Use the same basic steps in loading an M1 tank or other tracked vehicle over 75,000 pounds while using all six chains and load binders to secure the heavier load.

## **WARNING**

Do not roll by gravity. Roll by winch or drive the vehicle into position for attaching chains and chain binders. Attach and tighten the six chains with load binders to avoid injury to personnel, damage to the vehicle, and over-stretching the chains.


Figures 48 through 51 show procedures for securing heavy tracked vehicles to the M1000. For some figures, the trailer gooseneck is not shown, some inside axles are not shown on the M1000, and load binders are not shown in order to keep the drawings as legible as possible. Photographs instead show detail.

Figures 48 through 51 show procedures for securing heavy tracked vehicles to the M1000.

**TOP VIEW****SIDE VIEW**

*Figure 47. M109-series howitzer on the M1000.*







*Figure 48. Front angled view of M1 tank on the M1000.*

**TOP VIEW**


M1 facing forward

**SIDE VIEW**

M1 facing forward

**TOP VIEW**

M1 facing aft

**SIDE VIEW**

M1 facing aft




Figure 49. M1 tank on the M1000.






Figure 50. Rear view of M1 tank on the M1000.

**TOP VIEW****SIDE VIEW**

*Figure 51. M60-series tank on the M1000.*

Vehicles in good condition can be driven onto the M1000. Personnel can load disabled vehicles using a winch on the M1070 tractor. When loading steel-tracked vehicles such as bulldozers, place 2- x 10-inch lumber under the tracks to prevent metal to metal contact. Place and reposition the lumber as the vehicle is being driven or winched onto the M1000 so steel grousers do not contact the deck. The M1000 deck can be tilted to allow gravity to roll payload vehicles into their final position.


Figure 52 shows the M1000 carrying two M113s, which requires additional chains and loadbinders. The M1000 BII chains and loadbinders should go on the rear fittings of both M113s. To secure the front of each M113, use two 3/8-inch chain assemblies (NSN 4010-00-443-4845 or NSN 4010-00-803-8858) and two loadbinders (NSN 3990-01-213-1746).

Figure 53 shows the shoring required for the M104 Wolverine Bridge and Wolverine loaded on the M1000.

**TOP VIEW**


Secure the forward M113 to the M1000 D-rings.

Secure the rear M113 to the M1000 D-rings with 1/2 inch chains.





Secure the forward M113 to the M1000 lift/tiedown points with 3/8 inch chains and two loadbinders (see note).

Secure the rear M113 to the M1000 center tiedown points with 3/8 chains and two loadbinders (see note).

**SIDE VIEW**

**NOTE:** 3/8-inch chains (NSN 4010-00-443-4845 or 4010-00-803-8858)  
loadbinders (NSN 3990-01-213-1746).

*Figure 52. Tiedown configuration of M113 and similar vehicles on the M1000.*



**NOTES:**

1. Bridge can be placed on M1000 with a package mode launch.
2. See operator's manual (TB 5-5420-232-10-1) for details on securing Tow Light Assembly, Safety-warning Light, and M1000 ramps to bridge.
3. See operator's manual for details on using bridge package launch strap and chain for properly securing upper treadways.

*Figure 53 . Shoring for M104 Wolverine Bridge and Wolverine loaded on M1000*

## G. TRUCKS WITH SHELTERS

TB 43-0124 shows how to load S-280 and S-250 shelters on M35, M809, and M939 series trucks. Figure 54 shows the tiedown pattern for the S-280 shelter on these trucks. S-250 shelters are rarely unloaded from HMMWV and CUCV shelter carriers. The procedure is similar for the FMTV.





Figure 54. Securing the S-280 shelters to trucks.




## H. PALLETIZED LOAD SYSTEM (PLS)

There are two configurations of the PLS: the basic configuration truck, M1075, and the M1074, which incorporates a materials handling crane (MHC), figure 55. Either tows the M1076 trailer, figure 56.



*Figure 55. Palletized load system truck with materials handling crane.*



*Figure 56. Palletized load system trailer.*

Currently, there are three flatracks that are compatible with the PLS: the M1077, M1, and M3 (Container Roll-in/Out Platform (CROP)) flatracks. The demountable 16.5 ton payload cargo bed, called a flatrack is loaded on and off the truck and trailer using the truck's load handling system.

The M1077 flatrack (fig 57) is typically referred to as the A-frame flatrack. The M1077 is equipped with ISO corner fittings and can transport a 20 foot (6.10 m) ISO container.

External Dimensions:

Length 240 inches, 6096 mm

Width 96 inches, 2438 mm

Height 68.4 inches, 1737 mm

Internal Dimensions (cargo maximums):

Length 230.4 inches, 5852 mm


Width 90.5 inches, 2299 mm

Height 72.3 inches, 1836 mm

Tare weight: 3,190 pounds, 1447 kg

Gross weight: 36,250 pounds, 16 443 kg

CG of the M1077 is 106" CURB (front edge of the flatrack).



*Figure 57. M1077 flatrack*

The M1 flatrack (fig 58) is transportable throughout the intermodal system as an ISO container or on the PLS truck without the use of additional equipment.

External Dimensions:

Length 240 inches, 6096 mm

Width 96 inches, 2438 mm

Height 82 inches, 2083 mm

Internal Dimensions (cargo maximums):

Length 228 inches, 5791 mm


Width 96 inches, 2438 mm

Height 70 inches, 2083 mm

Tare weight: 7,300 pounds, 3311 kg

Gross weight: 36,250 pounds, 16 443 kg

CG of the M1 is 116" CURB (front edge of the flatrack).



*Figure 58. M1 flatrack*

The M3 (fig 59a) is a cargo carrying platform capable of being transported on the PLS truck and trailer and inside any ISO 1CC dry cargo container.

External Dimensions:

Length 233.27 inches, 5925 mm  
 Width 91.0 inches, 2311 mm  
 Height 10.11 inches, 257 mm (ground to deck)  
 17.84 inches, 453 mm (to top of A-frame<sup>1</sup>)  
 62.9 inches, 1598 mm (to top of A-frame<sup>2</sup>)  
 71.5 inches, 1816 mm (to top of A-frame<sup>3</sup>)

Internal Dimensions (cargo maximums):

Deck Length 217 inches, 5512 mm  
 Width 89 inches, 2261 mm  
 Height 74 inches, 1880 mm

Tare weight maximum: 3,800 pounds, 1724 kg

Gross weight: 9,625 pounds, 4,349 kg

1. Ground to top of A-frame assembly
2. Ground to top of A-frame assembly when in raised position, not to top of marker springs.
3. Ground to top of A-frame assembly when in raised position, to top of marker springs.

The M3A1 (fig 59a) is also a cargo carrying platform capable of being transported on the PLS truck and trailer and inside any ISO 1CC dry cargo container.

External Dimensions:

Length 233.36 inches, 5927 mm  
 Width 91.5 inches, 2324 mm  
 Height 9.97 inches, 253 mm (ground to deck)  
 17.22 inches, 437 mm (to top of A-frame<sup>1</sup>)  
 62.9 inches, 1598 mm (to top of A-frame<sup>2</sup>)  
 71.5 inches, 1816 mm (to top of A-frame<sup>3</sup>)

Internal Dimensions (cargo maximums):

Deck Length 217 inches, 5512 mm  
 Width 89 inches, 2261 mm  
 Height 74 inches, 1880 mm

Tare weight maximum: 4,000 pounds, 1814 kg

Gross weight: 36,250 pounds, 16,443 kg

36,250 pounds, 16,443 kg





Figure 59 a. M3 and M3A1

The M3 and M3A1 CG location is located 111 inches centered from the front edge of the flatrack as shown in Figure 59b.



*Figure 59 b. M3 and M3A1 with CG location*

The operator's manuals, TM 9-2320-364-10 (M1074/M1075 Truck), TM 9-3990-206-14&P (M1077 and M1 Flatrack), and TM 9-3990-260-14&P (M3 and M3A1 Flatrack) show how to prepare the flatracks to transport cargo and load them on the trucks. Users should refer to the operator's manuals for additional information on the PLS.


Flatracks are made by different manufacturers and have different configurations. The data plate on the flatrack gives specific information about its weight, cargo capacity, and tiedown fittings. Features which are common on all flatracks are:

1. The front end is the end with the load handling mechanism bail bar.
2. Cargo tiedown rings are spaced around the edge of the flatrack. The large rings have a capacity of 25,000 pounds. The smaller rings have a capacity of 10,000 pounds, figure 60.
3. All cargo rings will accept hooks, chains, and loadbinders having a 3/4-inch hook opening. All will accept metal banding up to 2 inches wide.

Front ISO twist lock fitting




Rear fitting



ISO stacking guide

Hold drum

ISO corner fitting



10,000 pound tiedown



25,000 pound tiedown

Figure 60. Palletized load system M1077 flatrack.

The M1077 flatrack has twist lock fittings (fig 60) so that a standard 20-foot ISO container can be locked in place without the use of chains. The containers will cause the truck to exceed the height for normal highway transport, requiring special permits and routing. The containers loaded on the M1076 trailer are within height limits for highway transport in the U.S.


The M1 flatrack is NATO intermodal, has a wood deck, and is the exact size of a 20-foot ISO container. Its end walls fold down on to the deck, and it has a maximum payload of 29,000 pounds.

The M3 and M3A1 are NATO interoperable and were designed as a primary means to ship strategic configured loads of ammunition from the depot to the user. These flatracks fit inside an ISO container and have a maximum payload capability of 32,250 pounds.

For adequate safety during highway operations with the tires inflated at highway tire pressures, the following guidance should be followed when loading PLS flatracks. For operations with payloads of 12,000 pounds or less at speeds up to 55mph, the payload CG should be centered longitudinally and laterally on the flatrack and have a maximum height above the flatrack deck of 48" for the M1077, M3, and M3A1 or 39" for the M1. For operations with payloads of 12,000 pounds or less that exceed these CG heights, speeds should be restricted to a maximum of 50 mph. Light wheeled vehicles, such as the HMMWV (fig 61) and 4K forklifts, are approved for transport on the PLS as long as the specific vehicle's weight and CG are in accordance with the guidance for payloads of 12,000 pounds or less. When transporting light wheeled vehicles, reference the tiedown procedure in MTMC TEA PAM 55-19 *Tiedown Handbook for Rail Movements*. For operations with gross rated payloads, the payload CG should be as far forward on the flatrack as possible, be centered laterally on the flatrack, and have a maximum height above the flatrack deck of 13" for speeds up to 55 mph or 25" for speeds up to 50 mph.

**WARNING: Extremely hazardous handling behavior can occur if payloads near the gross load rating are loaded such that their CG falls rearward of the longitudinal center of the flatrack.**


The M1077 and M1077A1 flatracks were designed to transport a load uniformly distributed on the deck for its full payload capability. The M1 has a deck strength of 272 pounds per square inch (psi), and the M3 and M3A1 have deck strengths of 80 psi.



*Figure 61. HMMWV on a PLS flatrack*



Web straps (NSN 5340-01-204-3009) are provided with each flatrack. These are used to secure boxes, pallets, and odd shaped cargo. Cargo of this type is loaded as far forward and as low as possible on the flatrack. All items, no matter how small, should be secured in place. Unsecured cargo will shift during loading of the flatrack onto the truck. Figure 62 shows appropriate restraint of a load of mixed cargo with web straps. The restraint must unitize the load and prevent movement in all directions.



*Figure 62. 16-1/2 ton payload on an M1077 A-frame flatrack.*

## SECTION III. GENERAL FLATBED SEMITRAILER LOADS

### A. TIEDOWN WITH CHAINS


Sometimes you may have to secure loads that are not listed in this book on flatbed semitrailers. Tiedown operations are simpler if you use chains and loadbinders instead of wire ropes and clamps. You should refer to the figures in section III as a general guide. Modify those procedures if necessary, to secure to the cargo or cargo vehicle.

Figure 63 shows the different types of loadbinders. Tables 3 and 4 show stock numbers for some loadbinders and chains. Loadbinders are described and specified in Federal Specification GGG-B-325. The ratchet loadbinder can achieve significantly greater tiedown forces than the other types of loadbinders. Of the loadbinders shown, the ratchet and type IV are the safest. Other types of loadbinders may spring back with great force upon release. If you must use them, be very careful when releasing them. Stay clear of the swing-path of the loadbinder handle.


If you cannot position your load snugly against a gooseneck, use chains to provide enough forward restraint. Figure 64 provides general guidance on how many chains to use. In most cases, one additional pair of chains running from the aft tiedown provision of the payload vehicle to the semitrailer will be enough. If available, you should attach the chains to D-rings on the semitrailer. On semitrailers without D-rings, you can usually attach the chain to stake pockets (fig 65).




Type I



Type II



Type IV



Ratchet

**NOTE:** Federal Specification GGG-B-325 defines types of loadbinders

*Figure 63. Types of loadbinders.*


**TABLE 3  
LOADBINDERS**

NSN	Breaking Strength (lb) (approx)	Size (in)	Type
3990-00-274-6746	16,000	1/4	Type I
3990-00-596-7044	16,200	3/8	Type I
3990-01-095-8769	19,000	3/8	Type I
3990-00-596-7051	15,000	1/2	Type IV
3990-01-213-1746	26,000	3/8-1/2	Type IV
3990-00-401-1503	72,000	3/4	Ratchet
3990-01-440-5975	50,000	1/2	Ratchet


**TABLE 4  
COMMON CHAINS**

NSN	Working Load Limit (lb)	(Grade) Breaking Strength (lb) (Approx)	Size	Used on:
4010-01-518-5269	4,700	(Grade 70) 18,800	5/16" x 20'	
4010-00-443-4845	6,600	(Grade 70) 26,400	3/8" x 14-1/2'	M870
4010-00-803-8858	4,125	16,500	1/2" x 10'	M172A1 M872A1 M872A2 M872A3
4010-00-047-3902		(Grade 43) 20,700	7/16" x 16'	
4010-01-361-8378		(Grade 80) 50,000	1/2" x 7'	M1000
4010-01-371-5772		(Grade 80) 50,000	1/2" x 11'	M1000
4010-01-385-5974		(Grade 80) 50,000	1/2" x 19'	M1000
4010-01-361-7266			3/4" x 10.5'	M747
4010-00-449-6573			3/4" x 12'	

**3/8-Inch Chain**  
(NSN 4010-00-443-4845)



Maximum payload vehicle weight = 12,000 lbs




Maximum payload vehicle weight = 17,000 lbs


**NOTE:** Additional chains are required on the rear of the vehicle, because forces seen when braking are higher than when accelerating.

*Figure 64. Tying down using chain.*

**7/16-Inch Chain**  
(NSN 4010-00-047-3902)



Maximum payload vehicle weight = 19,000 lbs




Maximum payload vehicle weight = 27,000 lbs


**NOTE:** Additional chains are required on the rear of the vehicle, because forces seen when braking are higher than when accelerating.

*Figure 64. (continued).*

**3/4-Inch Chain**  
(NSN 4010-00-449-6573).



Maximum payload vehicle weight = 48,000 lbs



Maximum payload vehicle weight = 67,000 lbs

**NOTE:** Additional chains are required on the rear of the vehicle, because

forces seen when braking are higher than when accelerating.  
*Figure 64. (continued).*






Figure 65. Chain tiedown running through a stake pocket.

## B. TIEDOWN WITH WIRE ROPE

Chains are easier to work with than wire rope. However, if chains are not available, you can use wire rope. Figure 66 provides general guidance on acceptable wire rope tiedown patterns. The tiedown patterns are based on using the wire rope shown in Table 5.


Apply wire rope through the tiedown provisions of the payload vehicle and through the stake pockets on the flatbed truck in a complete loop as shown in figure 67. Application and diameter of wire rope will depend on the gross weight of the payload vehicle. Be sure that the payload vehicle weight includes any payload vehicle cargo load. Apply a thimble under the stake pocket as shown in figure 69 to prevent chafing of wire rope. Ensure the thimble is at the best angle to protect the wire rope and prevent it from pulling out of the thimble during highway movement. The thimble may have to be spread at the open end to be used properly. Secure the thimble to the wire rope with a cable clamp one or two sizes larger than the wire rope being used.

Use clamps to maintain tension in the wire rope. Apply the clamps, also referred to as clips, with the saddle against the tension-bearing side of the wire rope, about six times the diameter of the wire rope apart. The size of the clamp must match the wire rope being used. A complete loop always has at least four clamps, not counting the clamps holding thimbles in place. Use high-strength cable clamps and torque them to the values in Table 5. If the available clamps cannot be torqued to these values, torque them to just below their breaking value, and apply six (instead of four) clamps on each wire rope loop.


Turnbuckles can be used to properly tension wire rope. Turnbuckles can also be used with chains if loadbinders are not available. Turnbuckles with jaws and/or eyes (fig 70) should be used. Hook end turnbuckles are not recommended because they are weaker than jaw or eye turnbuckles of the same size. Table 6 shows what size turnbuckle to use with various chain and wire rope.

Instead of a turnbuckle, a chain hoist with two cable grippers can be used to tension the wire rope attached to the payload vehicles (figs 71 and 72). Be sure that at least 24 inches of wire rope are available on either side of the intersection point to allow proper application of cable clamps. Also, be sure proper tension of wire rope exists. Tension wire rope to allow no more than 1-inch deflection when supporting the weight of a 200-pound person.

**3/8-Inch Wire Rope**  
(NSN 4010-00-272-8849)



Maximum payload vehicle weight = 19,000 lbs




Maximum payload vehicle weight = 27,000 lbs


**NOTE:** Additional wire ropes are required on the rear of the vehicle because forces seen when braking are higher than when accelerating.

*Figure 66. Tying down using wire rope*

**1/2-Inch Wire Rope**  
(NSN 4010-00-272-8848).



Maximum payload vehicle weight = 35,000 lbs




Maximum payload vehicle weight = 50,000 lbs


**NOTE:** Additional wire ropes are required on the rear of the vehicle because forces seen when braking are higher than when accelerating.

*Figure 66. (continued).*

**5/8-Inch Wire Rope**  
(NSN 4010-00-763-9361)



Maximum payload vehicle weight = 50,000 lbs



Maximum payload vehicle weight = 75,000 lbs

**NOTE:** Additional wire ropes are required on the rear of the vehicle because forces seen when braking are higher than when accelerating.

*Figure 66. (continued).*

**TABLE 5**  
**WIRE ROPE**

Size (in.)	Stock Number	Nominal Strength (lb)	Required Clamp Torque (ft-lb)
1/4	4010-00-269-9324	5,880	25
3/8	4010-00-272-8849	13,120	45
1/2	4010-00-272-8848	23,000	65
5/8	4010-00-763-9361	35,800	130

**NOTES:**

1. Improved plow steel (IWRC IPS) 6 x 19 Independent wire rope core.
2. Breaking strength as listed in supply documentation.
3. If a torque wrench is not available, adequate torque can be attained by: For 3/8-inch clamps, use 12-inch-long wrench and apply a force of about 50 pounds. For 1/2-inch clamps, use a 15-inch-long wrench and apply a force of about 60 pounds. For 5/8-inch clamps, use an 24-inch-long wrench and apply a force of about 70 pounds.
4. Wire rope is rated in nominal strength; actual strength may vary. When wire rope is assembled in a complete loop using wire rope clamps, the strength should be calculated as 80% of twice the value of the nominal strength. With an end loop, the strength should be calculated as 80% of the nominal strength of the wire rope.




Figure 67. Complete loop wire rope assembly.




Figure 68. Single strand wire rope assembly.






Figure 69. Detail of thimble attachment in figure 60.




Figure 70. Turnbuckles.

**TABLE 6**  
**TURNBUCKLES**

Wire Rope Size (in.)	Grade 70 Chain Size (in.)	Grade 80 Chain Size (in.)	Jaw End or Eye End Turnbuckle Size (in.)
1/4	1/4	7/32	3/8
3/8	5/16	9/32	5/8
7/16	3/8	5/16	3/4
1/2	3/8	3/8	7/8
5/8	1/2	1/2	1
--	1/2	5/8	1-1/4




Figure 71. Chain hoist and cable grippers.




Figure 72. Chain hoist and cable grippers in use.

### C. TIEDOWN WITH WEB STRAP

Web straps are easy to use to secure boxes and pallets for transport. The web straps, easily obtained from the Army inventory (NSN 1670-00-725-1437 and NSN 5340-01-204-3009, fig 73), are rated at 5,000 pounds.

Before each use, straps should be inspected for burns, tears, punctures, cuts, caustic damage, oil or grease contamination, and fraying or broken stitches. Also, their metal parts should be inspected for improper operation, corrosion, cracks, or distortion. If any of these conditions exist, the tiedown should be replaced. They should not be used for any mode of transport if they have been damaged. No strength testing of straps will be made.

When tiedown straps are attached to cargo and to vehicle tiedown fittings, each strap must be tensioned to form at least 1-1/2 turns on the takeup spool of the tensioning ratchet. The 1-1/2 turns must take place after webbing-to-webbing contact. To prevent movement of the cargo, each tiedown must be tightened until about equal tension is applied throughout the tiedown arrangement. After tensioning is completed, the takeup spool locking latch must be checked to ensure that it is fully seated at both ends of the spool in the matching locking notches. The scuff sleeve may have to be removed to allow tightening of tiedowns. Secure the loose ends of straps by suitable means.

When using web straps to secure loads on pallets, you may need to place padding between the load and the hooks to prevent the hooks from damaging the load. Figure 74 shows typical loads secured to the cargo bed of the vehicle with web straps. Steel banding is used to secure the items together. Figure 75 shows how to use web straps or steel banding to secure a load to a pallet.






Figure 73. Web strap (NSN 5340-01-204-3009).



**NOTE:** The tail gate is removed to allow a clear view of the load.

*Figure 74. Typical loads secured with web straps.*



*Figure 75. Palletized load using web straps or steel banding.*




#### **D. TIEDOWN WITH STEEL BANDING**

Steel banding is an effective way to secure a load for transport, if you have the equipment to tighten the straps and crimp the bands. This type of banding can be used for all modes of transport. Rail transport is the only mode that has specific requirements for steel bands and crimping the bands. If the band requirements meet rail transport they will not have to be changed during transport. Figure 76 shows the different types of crimps approved for rail transport and appropriate for highway transport. The railroad banding requirements generally reflect proper band application as developed by the band manufacturing industry. When used during rail transport, steel banding must be approved by the Association of American Railroads and labeled as required. The banding suppliers should be aware of these requirements. Figure 77 shows a typical load secured to a cargo bed of a vehicle. Blocking is typically used to prevent the load from moving longitudinally and laterally. Steel banding is also good for binding together several items with identical dimensions without blocking.

Blocking can be nailed directly to wood deck semitrailers or it must be against the end and side walls of the cargo vehicle to prevent it from shifting during transport.

**CRIMP TYPE TIE JOINT**



2 SEALS - 4 pairs of crimps



1 SEAL - 4 pairs of crimps



1 SEAL - 3 pairs of crimps



2 SEALS - 6 pairs of crimps


**NOTCH TYPE TIE JOINT**



1 SEAL - 2 pairs of notches



2 SEALS - 4 pairs of notches



Approved Seal-Less Crimp

Figure 76. Illustration of steel band notch and crimp type seal joints.




Figure 77. Typical load secured with steel straps and strap anchoring detail.

## SECTION IV. PAYLOAD VEHICLE TIEDOWN TIPS

### A. PREPARING PAYLOAD VEHICLES PRIOR TO LOADING

1. Be sure that all shackles are on the vehicle. **Do not use bumperettes, axles, towing pintles, or towing hooks as points of attachment for chains.**
2. Be sure fuel tanks of payload vehicles are no more than three-fourths full.
3. Remove or band canvas and bows to prevent wind damage.
4. Protect windshields of payload vehicles if needed.
5. Reduce payload vehicles to their lowest height configuration consistent with the operational requirements and unit standing operating procedures.
6. Secure any materials or equipment loaded in the beds of cargo vehicles by banding, chains, or cargo straps.
7. Remove all sensitive or pilferable items that cannot be secured.


### B. LOADING PAYLOAD VEHICLES

1. Make sure tractor and semitrailer parking brakes are on to assure maximum vehicle stability during drive-on operation.
2. If vehicle is on a grade, block the downhill side of wheels.

3. Put blocks under the M747 rear frame if loading payloads of more than 55 tons (fig 31).
4. Position a guide in a prominent location to assure constant visual contact with payload vehicle driver.
5. Position a ground guide off the rear corner of semitrailer to maintain visual contact with guide in the prominent forward location.
6. Warn personnel to stay clear of the semitrailer during loading operations. Ensure personnel are in no danger during loading.
7. When loading the M747 or M1000, put curbing in the proper positions.
8. When loading any firm-tracked vehicle such as a crane or bulldozer onto an M747 or M1000, attach towing vehicle winch cables to towing lugs of payload vehicle as a safety precaution. Operate towing vehicle winches to try to keep cable under even tension at all times to prevent payload from tipping or rolling backwards and to assist payload during breakover at top of ramp. Rig cables for payload weight. When loading a crane, turn crane counterbalance to forward end.
9. Shut payload vehicle down, turn off all switches, close doors and hatches, and swing in mirrors. Make sure all items are secure on payload to prevent them from falling off during transport.
10. Observe other special procedures when loading and securing heavy tracked vehicles on M747 or M1000 semitrailers (see previous sections on these semitrailers).

### C. SECURING PAYLOAD VEHICLES

1. Make sure wood bumpers are on the M747 gooseneck for all single vehicle loads. Use wood dunnage on M870 and M172A1 goosenecks when a portion of the payload vehicle will contact the gooseneck (fig78). Avoid metal-to-metal contact.
2. Make sure curbing is properly located against payload tracks on M747 and M1000 semitrailers. After payload is on the M747, move curbs from position F to position A (or store them if not needed in position A).
3. Tighten chains using the loadbinders.
4. Secure excess chain to the tension-bearing part of the chain.
5. On chain devices, secure open-faced hooks to the chain link with wire.
6. Lock chain tightening devices with wire. Tighten jamnuts on turnbuckles with a wrench.
7. Set brakes on payload vehicles and put their transmissions in neutral.
8. Make sure gun turrets or other rotating parts are properly secured.
9. Make sure the retractable clearance lights are in the retracted position for regular loads or are extended for all loads wider than the semitrailer bed.
10. Make sure ramps are raised and properly secured.
11. Make sure all basic issue items are properly stowed on the semitrailer.
12. Check the tractor and the semitrailer brakes and all lights to make sure they are operating.



Dunnage required to prevent metal-to-metal contact.




Figure 78. When to use dunnage.

13. Check all tiedowns at the first opportunity after departure. If possible, plan a check within the first 2 miles of your trip. Recheck all tiedowns at halts and at any time you suspect a problem.

#### **D. TOOLKIT**

Loading and tiedown operations will be easier if the proper tools are readily available. Table 7 contains a list of recommended tools. Tables 3, 4, and 5 show national stock numbers of common chain assemblies, loadbinders, and wire rope.



**TABLE 7**  
**SUGGESTED VEHICLE LOADING TOOLKIT**

Quantity	Item	Remarks	NSN
1 pr	Pliers	Side cutting or slip-joint (8-inch)	5120-00-239-8251 or 5120-00-223-7397
1	Wire cutter	Diagonal steel wire cutter	5110-00-516-4227
2	Claw and pinch bar	30-inch length	NA
3	Hammer	1-pound 2-pound 3-pound	5120-00-061-8543 5120-00-061-8546 5120-00-900-6111
1	Ratchet	1/2-inch square drive, reversible	5120-00-230-6385
2	Torque wrench	1/2-inch square drive, for wire rope clips	5120-00-640-6364
2	Socket	1/2-inch square drive, 3/4-inch (12-point)	5120-00-189-7984
2	Socket	1/2-inch square drive, 7/8 inch (12-point)	5120-00-189-7934
2	Socket	1/2-inch square drive, 15/16-inch (12-point)	5120-00-189-7935

**TABLE 7 (continued).**

Quantity	Item	Remarks	National Stock Number
2	Adjustable wrench	Lightweight, 11-inch long, 3-inch capacity	5120-00-293-3009
1	Screwdriver	Common, 8-inch square shank	5120-00-596-9364
2	Tape measure	Steel, 25-foot, recoil type	5210-01-139-7444
1	Wire rope cutter	Hydraulic, 3/4-inch cable capacity	5110-00-224-7058
2	Marker crayon	One black, one yellow	7510-00-285-1730
2	Puller, hoist	Chain type, ratchet-action ("come-along"), 3-ton capacity	5120-00-785-5860
2	Cable grip	5/16-inch capacity	5120-00-238-4436
2		5/8-inch capacity	5120-00-224-2661
10 pr	Gloves, work	Leather, or leather-palm	8415-00-634-4658

## SECTION V. FORSCOM CARGO FORMS

### A. GENERAL

When loading organic cargo onto a vehicle, certain forms must be completed and maintained.

This section is a general guide for the use of FORSCOM Form 285-R, Vehicle Load Card and DD Form 1750, Packing List. Refer to FORSCOM/ARNG Reg 55-1, Unit Movement Planning, for more detailed guidance.

### B. FORSCOM FORM 285-R

FORSCOM Form 285-R (fig 79) is used for developing and recording a unit's organic vehicle cargo load and is included in the unit's movement plan. It will reflect a general description and location of all items in the cargo bed to include boxed/crated items. Information on dimensions, weights, and cubes for all Army equipment is contained in the CD-ROM and worldwide web versions of TB 55-46-1. The following general guidance is provided to assist in completing this form:

1. Drivers and assistant drivers are not normally added to the weight of the vehicle. However, on HMMWVs and CUCVs, all personnel on board, including drivers and assistant drivers, must be computed as part of the payload to avoid overloading the vehicle.
2. When transporting personnel in the cargo compartment, a planning factor of 245 pounds for each soldier will be used.

Line Item Number

Reduced configuration IAW TB 55-46-1

Shipment unit number will be placed in the space above the block titled (date compiled).

INDEX		VEHICLE LOAD CARD			D0013	
X40009	31	UNIT			DATE COMPILED	
HHC 633D	SP GP	BUMPER NO				
		LHQ-10				
VEHICLE INFORMATION						
TYPE	LENGTH	WIDTH	HEIGHT	EMPTY WT	CB/CG is _____ inches from _____	
M35A2	265	96	102	13,180		
2 1/2 T						
CARGO COMPARTMENT VIEW						
Cargo Loc No	Cargo Description and Type Pack			Quantity	PC Weight	
1	TOOL CHEST			3	500	
2	DRILL PRESS			2	1000	
3	LIGHT SETS			4	70	
RED LINE						
4	DUFFLE BAGS			18	65	
5	PILLOWS (BOYED)			2	25	
LOADED VEH WEIGHT		DRIVER (Name and Order)				
16,960		SP FRANK WILLIAMS LINE/PARA				

Date of entry (pencil)

Computed based on axle loads. Not required from home station to mobilization station (MS).

Show where items are loaded in the cargo compartment. (Use cargo location numbers). DD form 1750 is required for each item packed in a box or container.

List the number of items and weight of each. All items will be reduced to the shipping configuration listed in TB 55-46-1.

Red line to separate the items loaded above the reduced load that will move to the MS on the vehicle and be transferred from the vehicle at the MS.

**NOTE:**  
List any packing and crating materials needed for items loaded on vehicle.

Total weight of items loaded above the red line, plus the empty weight of the vehicle.

Driver (qualified), identified by name or TDA/Para position (pencil).

Figure 79. FORSCOM Form 285-R (sample vehicle loading card).

3. Duffle bags (A and B) will be estimated at 70 pounds each.
4. Twenty two inches of width will be used per person transported in the cargo compartment of the vehicle.
5. Generally, vehicles will have no more than a three-fourths tank of fuel if they are to be shipped by air, rail, or sea.
6. The shipment unit number (SUN) is found on the unit's Automated Unit Equipment List (AUEL)/Deployment equipment List.
7. The date block is completed in pencil to allow for periodic updating.
8. The vehicle LIN and Index Number entered on this form should be the same as entries on the AUEL. The LIN number corresponds to the vehicle model. The index number corresponds to the vehicle/load configuration.
9. The cargo compartment view is not a picture of the vehicle being loaded, but a portrayal of the load on the vehicle.
10. The cargo location number correlates to the location of the numbered piece of cargo on the load diagram.
11. The unit should enter as much information as is needed in the Cargo Description and Type Pack blocks to describe the cargo.
12. To compute total weight, the unit multiplies the number from the Number of items column by the quantity in the Piece Weight column.

13. For Reserve Component units, items listed below the red line will be offloaded at the mobilization station and shipped by commercial transportation. For Active Component units, the loaded vehicle weight is computed by adding the empty weight of the vehicle to all the items listed on the card. The total weight must never exceed the rated capacity of the vehicle.

In the upper right-hand corner of the FORSCOM Form 285-R is the shipment unit number. This number is found on your Automated Unit Equipment List (AUEL). On the left side you could further identify your vehicle by inserting the line item number and/or index number. Complete the unit and bumper number blocks with the appropriate information. The date compiled block is filled out in pencil because changes may occur.

The vehicle information blocks are probably the most misunderstood entries on the form. For mobilization vehicle information, you must always refer to chapter 3 of TB 55-46-1. Determine if your vehicle has a load; this information is needed to research the appropriate index number. The information from this part of the FORSCOM Form 285-R should be exactly the same as entries on the AUEL. That is provided by the Unit Movement Officer to the Installation Transportation Officer. The beginning of chapter 3 in TB 55-46-1 contains information on how to use the rest of the chapter.

The cargo compartment view is not a picture of the vehicle you are loading, but a portrayal of the *load* on the vehicle. When filling this out, keep in mind that the individual unloading this vehicle may not be the individual who loaded it. How do you reflect multiple levels of equipment on a card? There is no single correct answer; use whatever you can devise to clearly identify the layers. If you look at the example in figure 71, you will see that we used a broken line to depict the second layer. As an option, you could take a photograph of the load once it is complete, and submit it with the FORSCOM Form 285-R. Remember, keep it simple and legible; that's the key.

The cargo location number is the most exact location of a piece of cargo on the load. When you get to the cargo description and type pack, enter as much information as is needed

to identify what is located there. The quantity column is the number of pieces found at that cargo location. Remember:

1. Ensure that only the piece weight is entered in this column.
2. When adding up the total weight, multiply the number from the quantity column by the quantity in the piece weight column.

This takes us to the lower left hand side of the form. The loaded vehicle weight is computed by taking the empty weight of the vehicle and adding to it everything above the red line. Everything that is below the red line will be removed at the mobilization site and shipped by commercial transportation. The most important thing you must remember about this entry is that the total weight must never exceed the rated capacity of the vehicle. In the driver block, enter the driver's name or line/paragraph.

### **C. DD FORM 1750**

DD Form 1750 (fig 80) is a packing list prepared by the unit for all consolidated cargo loaded in vehicles, containers, and on 463L pallets moving commercially or on organic transportation. Once deployment begins, copies of the packing list are distributed as follows:

- a. One inside the container.
- b. One on the outside of the container (exception - containers with sensitive items)
- c. Two copies retained by unit representatives at POE.
- d. One with the Unit Movement Plan.
- e. One provided to UMO/ITO for commercial shipments.

SAMPLE FILE IN ANNEX W, UNIT MVT PLAN		USE PENCIL			
<b>PACKING LIST</b>		PACKED BY Individual Packing the container	1. NO. BOXES One (1) unless consolidated	2a. REQUISITION NO. Vehicle No. or Commercial	
3. END ITEM		DO NOT USE MISC. TOE EQUIPMENT. e.g. NBC Defense Equipment		2b. ORDER NO. Shipment Unit Order	
		Be specific		4. DATE Form is compiled	
				5. PAGE ___ OF ___ PAGES	
BOX NO.		CONTENTS - STOCK NUMBER AND NOMENCLATURE		QUANTITIES REQUIRED	
(a)	(b)	UNIT OF ISSUE (c)	INITIAL OPERATION (d)	RUNNING SPARES (e)	TOTAL (f)
1.	Line Item Number (Form Property Book)  Stock Number  Nomenclature    BBPCT e.g., Special crating and/or internal packing materials etc, BE SPECIFIC   Total Weight-----  Description of Container Dimensions  Bumper Number of Vehicle Box is to be Placed  STATEMENT: "This box/container does/does not contain Hazardous Cargo IAW CFR 49.  (The above statement will be made by a Hazardous Material Certified person or technical specialist.)	EA	N/A	N/A	
6. THIS CERTIFIES THAT ITEMS LISTED HEREON ARE WITHIN THE SPECIFIED BOXES					
TYPED NAME AND TITLE		SIGNATURE			
Primary or Alternate UMO		Primary or Alternate UMO			

DD Form 1750, SEP 70

Figure III-52

416-795

Figure 80. DD Form 1750 (sample vehicle packing list).



Installations may request additional copies. Packing lists are not required for items that do not need identification (such as empty vehicles, nested cans, or bundled shovels). However, these items must be listed on the load diagram if loaded in a truck or container. A packing list is not required for a container already having a list of contents affixed to it, such as inventories of tools or parts found in supply bulletins. The packing list will be placed on both the inside and outside of the container. The exception is for sensitive items. Sensitive items will not be listed on a packing list on the outside of the container. However, the UMO will notify the ITO that sensitive items are being shipped by completing a DD Form 1907 (Signature and Tally Record). It will accompany the GBL to create a “chain-of-custody” IAW DoD Reg 4500.9-R, Part II.

NOTE: DA Form 5748-R, Shipment Unit Packing List and Load Diagram, is an authorized substitute for DD Form 1750 and FORSCOM Form 285-R.

The following general guidance is provided to assist in completing this form:

1. Block 1 reflects the number of box/boxes (if used as a consolidated list).
2. Block 2a is the vehicle number.
3. Block 2b is the SUN.
4. Block 3 (End item) contains the description of the contents of the container/box/pallet.
5. Blocks (d), (e), and (f) reflect the “Packs,” “Weight,” and “Total Weight,” respectively. The Total Weight column is the total for that line only. The “Total Weight” at the bottom of the form is the cumulative weight of all the contents.
6. The blocking, bracing, packing, crating, and tiedown materials (BBPCT) are entered under the contents column and the weight added to the total.
7. The description of container and bumper number entries identify the container/vehicle on which the load is carried.
8. The primary or alternate UMO must certify the load by signing block 6.

## ACRONYMS

<u>Acronym</u>	<u>Definition</u>
AUEL	Automated Unit Equipment List
BBPCT	Blocking, Bracing, Packing, Crating, and Tiedown
BII	Basic Issue Item
CG	Center of Gravity
CHE	Container Handling Equipment
CROP	Container Roll-in/Out Platform
DAC	Defense Ammunition Center
DD	Department of Defense
FM	Field Manual
FMTV	Family of Medium Tactical Vehicles
FORSCOM	Forces Command
HET	Heavy Equipment Transporter
HMMWV	High Mobility Multi-Purpose Wheeled Vehicle
HYEX	Hydraulic Excavator
ITO	Installation Transportation Officer
IAW	In Accordance With
LIN	Line Item Number

## ACRONYMS

<b><u>Acronym</u></b>	<b><u>Definition</u></b>
NSN	National Stock Number
MHC	Materials Handling Crane
MHE	Materials Handling Equipment
MS	Mobilization Station
MTMCTEA	Military Traffic Management Command Transportation Engineering Agency
PLS	Palletized Load System
SUN	Shipment Unit Number
TB	Technical Bulletin
TDA	Table of Distributions and Allowances
TM	Technical Manual
UMO	Unit Movement Officer
USMC	United States Marine Corps
VRRTFL	Variable Reach Rough Terrain ForkLift

# Notes

## Notes