Off-grid Solar Modules 80, 100, 120, 140 Watt peak





Designed in Europe Manufactured in Kenya

In 1 day the earth receives enough radiation from the sun to cover our global energy consumption for a full year. So let's use it!


Our high-performance solar modules are designed by our Dutch mother company Ubbink for optimal yield and return-on-investment.

Ubbink solar modules are manufactured in our own production facility in Naivasha, Kenya. The use of European production knowledge and carefully selected components like European Solar Cells are the foundation for a top quality solar module.

Electrical Properties at STC*					
Model	80 Watt 100 Watt 120 Watt 140 Watt				
Maximum power Pmax	80W	100W	120W	120W	
Current maximum power point Impp	4,4A	5,6A	6,7A	7,9A	
Voltage maximum power point Vmpp	18V				
Open circuit voltage Voc (STC)	21.6V				
Short circuit current Isc	5.2A	6.5A	7,6A	8,8A	
Operating temperature	-40°C to 85°C				
Maximum system voltage (V)	715V				
Power tolerance	±3%				
Diode	10A				

- *STC (Standard Test Condition):
- Irradiance 1000 W/m2,
- Module temperature 25°C Spectrum AM 1.5

Ubbink East Africa Ltd. PO Box 1158, 20117 Naivasha, Kenya Tel +254 (0) 20 2167757, www.ubbink.co.ke QS-001-4-1213



Off-grid Solar Modules 80, 100, 120, 140 Watt peak




Warranty				
Model	80 Watt	100 Watt	120 Watt	140 Watt
Product Warranty	10 years			
Output Warranty	Linear warranty (1 st year 97%, after 2 nd year 0.7% annual degradation, 80% after 25 years)			


Mechanical Properties				
Model	80 Watt	100 Watt	120 Watt	140 Watt
No. of cells	36 (4x9)			
Cell type	Polycrystalline cell			
Module dimensions (a)x (b)	667 x 881mm	667 x 1081mm	667 x 1283mm	667 x 1479mm
Distance mounting hole (c) – (d)	150-581-150	200-681-200	200-883-200	140-250-699- 250-140
Weight	8.8kg	11.0kg	12.9kg	13.8kg

Physic	al dimensions (a)	
(d) (c)	Front view Back view	(b)
(d)		

Output Terminal					
Model	80 Watt	100 Watt	120 Watt	140 Watt	
Output Terminal	Junction box IP65 with male/female connection				
Cable	2.5mm2 - 10A - 1000V				

Characteristic Curves





Ubbink East Africa Ltd. PO Box 1158, 20117 Naivasha, Kenya Tel +254 (0) 20 2167757, www.ubbink.co.ke QS-001-4-1213

