U.S. DEPARTMENT OF HOMELAND SECURITY U.S. COAST GUARD CG-33 Rev. (02-08)

BULK DRY CARGO RESIDUE REPORTING FORM

OMB Number 1625-0072 Expires:

OFFICIAL/IMO NO.

MASTER'S CERTIFICATION: VESSEL NAME:

For Cargo Loading & Unloading Operations							For Residue Discharge Operations Only				
Date	Cargo Involved ¹	Operation (check one) Load Unload	ration ck one)	ation (cone) Facility Name	Control Measures Used ² (see list of codes)		Time Spent to Implement	Estimated Residue to be Discharged ³	Discharge Start	Discharge Stop	Vessel Speed (kts)
				Facility	Vaccel	Control Measure (hrs)	Date/Time(D/T) Ship's Position (Lat/Long)		Date/Time(D/T) Ship's Position (Lat/Long)		
					<i>-асшту</i>	Vessel			D/T:	D/T:	
								<u> </u> 			
								 	Lat:	Lat:	
									Long:	Long:	
									D/T:	D/T:	
									Lat:	Lat:	
									Long:	Long:	
									D/T:	D/T:	
									Lat:	Lat:	
									Long:	Long:	
									D/T:	D/T:	
									Lat:	Lat:	
									Long:	Long:	
									D/T:	D/T:	
									Lat:	Lat:	
									Long:	Long:	
									D/T:	D/T:	
									Lat:	Lat:	
									Long:	Long:	
									D/T:	D/T:	
									Lat:	Lat:	
									Long:	Long:	

Remarks:

NOTES:

³ Estimated residue after loading and unloading operations to be discharged in accordance with 33 CFR 151.66

Cargo	Facility Control Measures		Vessel Control Measures		
Involved	<u>Code</u>	<u>Measure</u>	<u>Code</u>	<u>Measure</u>	
	Α	Enclosed conveyor	1	Enclosed conveyor	
iron ore	В	Troughed conveyor	2	Troughed conveyor	
taconite	С	Conveyor skirts	3	Conveyor skirts	
scale	D	Belt Scrapers	4	Belt Scrapers	
coal/coke	E	Water/mist for dust control	5	Water/mist for dust control	
grain	F	Conveyor capacity indicators	6	Conveyor capacity indicators	
seed	G	Deck remote controls of conveyors	7	Deck remote controls of conveyors	
wood pulp	Н	Stop conveyor while ship or belt is repositioned	8	Stop conveyor while ship or belt is repositioned	
potash	I	Delay loading/unloading during high wind	9	Delay loading/unloading during high wind	
fertilizer	J	Radio Communication between deck and loader	10	Radio Communication between deck and loader	
limestone	K	Crew training on procedures to reduce residue	11	Crew training on procedures to reduce residue	
sand/gravel	L	Limit vertical angle of conveyor boom	12	Limit vertical angle of conveyor boom	
dolomite	M	Plow feeder	13	Broom & shovel (to return to hold or shore)	
clay	N	Loading chute, incl. Telescoping or conveyors	14	Tarps to collect residue(to return to hold or shore)	
aggregates	0	Chemical surfactants	15	Cargo hold vibrator	
salt	Р	Suction pumped cargo, slurry transport,	16	Watertight gate seal	
gypsum		pneumatic or screw conveyors	17	Cargo hold lining (teflon or kevlar)	
cement	Q	Other (describe measure on "Remarks" line	18	Minimize hatch removal during poor weather	
Other		on front of form)	19	Careful cargo hold gate operation	
			20	Other (describe measure on "Remarks" line on front of form)	

Equivalence Table for estimating residue					
Cargo	Density	Equivalent Volume	Volume		
Cargo	Density (lbs/ft ³)	for 350 lbs of DCR	in m ³		
Coal	50	7 ft ³	0.2		
Limestone Taconite	150 222	2.3 ft ³ 1.6 ft ³	0.07 0.05		

Note: One 5 gallon bucket is equivalent to 0.019 m³

1 cubic ft = 0.0283 m^3

¹ **Cargo Involved:** Provide the common name of the cargo (e.g., coal, taconite, sand, limestone, grain, salt, etc.) When multiple cargo types are discharged, please create a separate entry for each type

² **Control Measures:** Enter the code(s) below for each dry cargo residue control measure(s) used during cargo handling operations, for both cargo facilities (if known), and for your vessel.