

Masterpact NT or NW Circuit breaker and automatic switch



Name of customer: _____
 Address for delivery: _____
 Requested delivery date: _____
 Customer order no.: _____

To indicate your choices, check the applicable square
 and enter the appropriate information in the rectangles.

Circuit breaker or automatic switch		Quantity
Masterpact type	NT <input type="checkbox"/> NW <input type="checkbox"/>	
Rating	A	
Sensor rating	A	
Circuit breaker	NT: N, L1 NW: N, H	
Automatic switch	HF	
Number of poles	3 or 4	
Brand	MG <input type="checkbox"/> SD <input type="checkbox"/>	
Option: neutral on right side (NW only) <input type="checkbox"/>		
Type of equipment	Fixed <input type="checkbox"/>	
	Drawout with chassis <input type="checkbox"/>	
	Drawout without chassis (moving part only) <input type="checkbox"/>	
	Chassis alone <input type="checkbox"/>	

Micrologic control unit			
A - ammeter	3.0 <input type="checkbox"/>	5.0 <input type="checkbox"/>	6.0 <input type="checkbox"/>
P - power meter		5.0 <input type="checkbox"/>	6.0 <input type="checkbox"/>
H - harmonic meter		5.0 <input type="checkbox"/>	6.0 <input type="checkbox"/>
LR - long-time rating plug	Standard 0.4 to 1 Ir <input type="checkbox"/>		
Plug:	B, C, D, E, F, G, H <input type="checkbox"/>		
AD - external power-supply module	V <input type="checkbox"/>		
BAT - battery module	<input type="checkbox"/>		
TCE - external sensor (CT) for neutral and residual ground-fault protection	<input type="checkbox"/>		
TCW - external sensor for SGR protection	<input type="checkbox"/>		
PTE - external voltage connector	<input type="checkbox"/>		

Communication			
COM module	JBus/ModBus Device <input type="checkbox"/>	Chassis <input type="checkbox"/>	

Connection			
Horizontal	Top <input type="checkbox"/>	Bottom <input type="checkbox"/>	
Vertical	Top <input type="checkbox"/>	Bottom <input type="checkbox"/>	
Front (NT only)	Top <input type="checkbox"/>	Bottom <input type="checkbox"/>	

Micrologic control unit functions:
 3.0: protection de base LI
 5.0: selective protection (long time + short time + inst.)
 6.0: selective + ground-fault protection (long time + short time + inst. + ground-fault)

Indication contacts

OF - ON/OFF indication contacts			
Standard	4 OF 6 A-240 V AC (10 A-240 V AC and low-level for NW)		
Alternate	1 OF low-level for NT	Max. 4	qty <input type="text"/>
Additional	1 block of 4 OF for NW	Max. 2	qty <input type="text"/>
EF - combined "connected/closed" contacts			
	1 EF 6 A-240 V AC for NW	Max. 8	qty <input type="text"/>
	1 EF low-level for NW	Max. 8	qty <input type="text"/>

SDE - "fault-trip" indication contact			
Standard	1 SDE 6 A-240 V AC		
Additional	1 SDE 6 A-240 V AC <input type="checkbox"/>	1 SDE low level	<input type="text"/>
Programmable contacts			
	2 M2C contacts <input type="checkbox"/>	6 M6C contacts	<input type="text"/>
Carriage switches			
	Low level <input type="checkbox"/>	6 A-240 V AC	<input type="text"/>
CE - "connected" position	Max. 3 for NW/NT		qty <input type="text"/>
CD - "disconnected" position	Max. 3 for NW - 2 for NT		qty <input type="text"/>
CT - "test" position	Max. 3 for NW - 1 for NT		qty <input type="text"/>
AC - NW actuator for 6 CE - 3 CD - 0 CT additional carriage switches			qty <input type="text"/>

Remote operation			
Remote ON/OFF			
	MCH - gear motor	V	<input type="text"/>
	XF - closing voltage release	V	<input type="text"/>
	MX - opening voltage release	V	<input type="text"/>
	PF - "ready to close" contact	Low level 6 A-240 V AC	<input type="text"/>
	BPFE - electrical closing pushbutton		<input type="text"/>
	Res - electrical reset option	V	<input type="text"/>
Remote tripping			
	MN - undervoltage release	V	<input type="text"/>
	R - delay unit (non-adjustable)		<input type="text"/>
	Res - adjustable delay unit		<input type="text"/>
	2 nd MX - shunt release	V	<input type="text"/>

Locking

VBP - ON/OFF pushbutton locking (by transparent cover + padlocks)			
<input type="checkbox"/>			
OFF position locking:			
VCPO - by padlocks			<input type="text"/>
VSPO - by keylocks	Keylock kit (without keylock)	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
		Kirk <input type="checkbox"/>	Castell <input type="text"/>
	1 keylock	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
	2 identical keylocks, 1 key	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
	2 keylocks, different keys	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
Chassis locking in "disconnected" position:			
VSPP - by keylocks	Keylock kit (without keylock)	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
		Kirk <input type="checkbox"/>	Castell <input type="text"/>
	1 keylock	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
	2 identical keylocks, 1 key	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
	2 keylocks, different keys	Profalux <input type="checkbox"/>	Ronis <input type="text"/>
	Optional connected/disconnected/test position lock		
VPEC - door interlock		On right-hand side chassis <input type="checkbox"/>	
		On left-hand side chassis <input type="checkbox"/>	
VPOC - racking interlock	<input type="checkbox"/>		
IPA - cable-type door interlock	<input type="checkbox"/>		
VDC - mismatch protection (standard)	<input type="checkbox"/>		
IBPO - racking interlock between crank and OFF pushbutton for NW (standard)	<input type="checkbox"/>		
DAE - automatic spring discharge before breaker removal for NW (standard)	<input type="checkbox"/>		

Accessories

VO - safety shutters on chassis for NT and NW (standard)	<input type="checkbox"/>		
CDM - mechanical operation counter NT, NW	<input type="checkbox"/>		
CB - auxiliary terminal shield for chassis NT, NW	<input type="checkbox"/>		
CDP - escutcheon NT, NW	<input type="checkbox"/>		
CP - transparent cover for escutcheon NT, NW	<input type="checkbox"/>		
OP - blanking plate for escutcheon NT, NW	<input type="checkbox"/>		
Brackets for mounting	NW fixed <input type="checkbox"/>	On backplates	<input type="text"/>
Test kits	Mini test kit <input type="checkbox"/>	Portable test kit	<input type="text"/>
IV - shutter position indicator for NW	<input type="checkbox"/>		
VV - shutter-locking system for NW	<input type="checkbox"/>		



Guiding

TOOLS

merlin-gerin.com

This international site allows you to access all the Merlin Gerin products in just 2 clicks via comprehensive range data-sheets, with direct links to:

- complete library: technical documents, catalogs, FAQs, brochures...
- selection guides from the e-catalog.
- product discovery sites and their Flash animations.

You will also find illustrated overviews, news to which you can subscribe, the list of country contacts...



CAD software and tools

The CAD software and tools enhance productivity and safety. They help you create your installations by simplifying product choice through easy browsing in the Guiding System offers. Last but not least, they optimise use of our products while also complying with standards and proper procedures.





Schneider Electric Industries SAS

89, boulevard Franklin Roosevelt
F - 92500 Rueil-Malmaison (France)
Tel : +33 (0)1 41 29 85 00

<http://www.schneider-electric.com>
<http://www.merlin-gerin.com>

As standards, specifications and designs change from time to time, please ask for confirmation of the information given in this publication.



Printed on recycled paper

Publication: Schneider Electric
Production: SEDOC
Printed: Centre Impression - Made in France