

## DM-932 Series Digital Multimeter



- Impact resistant rubber and ABS plastic case with a flip out desk stand
- 34 mm LCD display with large digits 61 segment bargraph and function indicators with backlight
- Auto polarity indication
- Auto ranging with range hold
- Data hold
- Min/max recording mode
- Fast blow fuse for overload protection
- Temperature
- True RMS
- Low battery indication
- Supplied with soft zip carry pouch, 2 test leads & battery (& K Type temperature bead probe)
- CAL-DM Calibration Certificate available

### Technical Specifications

Function	Range	Basic Accuracy
DC Voltage	1000V	± 0.5%
AC Voltage	1000V	± 0.8%
DC Current	10A	± 1.2%
AC Current	10A	± 1.8%
Resistance	60MΩ	± 0.8%
Capacitance	1000μF	± 3.0%
Frequency	10MHz	± 1.5%
Temperature	760°C, 1400°F	± 3%
Diode Check	Open circuit voltage 1.5V DC typical; test current 0.3mA	
Continuity	Threshold < 100Ω	
Dimensions	150 x 70 x 48mm	
Weight	255g	

Model No.	Description
DM-932	True RMS 6000 Count Multimeter
CAL-DM	Calibration Certificate
LR-61	9V PP3 Alkaline Battery

**Global Measurement and Control Limited**  
PO Box 1  
Derwent Street, Long Eaton  
Nottingham NG10 3LP

Telephone: 0115 946 7441 • Fax: 0115 946 7442  
e-mail: [enquiries@globaltld.co.uk](mailto:enquiries@globaltld.co.uk)  
website: [www.globaltld.co.uk](http://www.globaltld.co.uk)

Company Registration No. 4918028  
Registered Address: Trent Mills, Long Eaton, Nottinghamshire NG10 3LP

*A member of the Concord Holdings Group*