



Hochschule  
Zittau/Görlitz

UNIVERSITY OF APPLIED SCIENCES

Faculty of  
MECHANICAL ENGINEERING

Department of  
TECHNICAL THERMODYNAMICS

# Property Library for R134a

**FluidLAB**  
with **LibR134a**  
for **MATLAB®**

Prof. Hans-Joachim Kretzschmar

Dr. Ines Stoecker

Matthias Kunick

A. Blaeser

# Property Library for the Calculation of R134a FluidLAB for MATLAB<sup>®</sup> LibR134a

## Contents

0. Package Contents
  - 0.1 Zip file for 32-bit MATLAB<sup>®</sup>
  - 0.2 Zip file for 64-bit MATLAB<sup>®</sup>
1. Property Functions
2. Application of FluidLAB in MATLAB<sup>®</sup>
  - 2.1 Installing FluidLAB including LibR134a
  - 2.2 Licensing the LibR134a Property Library
  - 2.3 Example: Calculation of  $h = f(p,t,x)$  in an M-File
  - 2.4 Example: Calculation of  $h = f(p,t,x)$  in the Command Window
  - 2.5 Removing FluidLAB including LibR134a
3. Program Documentation
4. Property Libraries for Calculating Heat Cycles, Boilers, Turbines, and Refrigerators
5. References
6. Satisfied Customers

---

© Zittau/Goerlitz University of Applied Sciences, Germany  
Faculty of Mechanical Engineering  
Department of Technical Thermodynamics  
Professor Hans-Joachim Kretzschmar  
Dr. Ines Stoecker  
Phone: +49-3583-61-1846 or -1881  
Fax: +49-3583-61-1846  
E-mail: [hj.kretzschmar@hs-zigr.de](mailto:hj.kretzschmar@hs-zigr.de)  
Internet: [www.thermodynamics-zittau.de](http://www.thermodynamics-zittau.de)

## 0. Package Contents

### 0.1 Zip file for 32-bit MATLAB®

The following zip file is delivered for your computer running a 32-bit version of MATLAB®.

#### "CD\_FluidLAB\_LibR134a.zip"

Including the following files:

FluidLAB_LibR134a_Setup.exe	- Installation program for the FluidLAB Add-On for use in MATLAB®
LibR134a.dll	- Dynamic Link Library for R134a for use in MATLAB®
FluidLAB_LibR134a_Docu_Eng.pdf	- User's Guide

### 0.2 Zip file for 64-bit MATLAB®

The following zip file is delivered for your computer running a 64-bit version of MATLAB®.

#### "CD\_FluidLAB\_LibR134a\_x64.zip"

Including the following files and folders:

##### Files:

Setup.exe	- Self-extracting and self-installing program for FluidLAB
FluidLAB_LibR134a_64_Setup.msi	- Installation program for the FluidLAB Add-On for use in MATLAB®
LibR134a.dll	- Dynamic Link Library for R134a for use in MATLAB®
FluidLAB_LibR134a_Docu_Eng.pdf	- User's Guide

##### Folders:

vcredist_x64	- Folder containing the "Microsoft Visual C++ 2010 x64 Redistributable Pack"
WindowsInstaller3_1	- Folder containing the "Microsoft Windows Installer"

# 1. Property Functions

Functional Dependence	Function Name	Call from Fortran program	Call in DLL LibR134a as parameter	Property or Function	Unit of the result
$a = f(p, t, x)$	a_ptx_R134a	A_PTX_R134A(P, T, X)	C_A_PTX_R134A(A, P, T, X)	Thermal diffusivity	m <sup>2</sup> /s
$c_p = f(p, t, x)$	cp_ptx_R134a	CP_PTX_R134A(P, T, X)	C_CP_PTX_R134A(CP, P, T, X)	Specific isobaric heat capacity	kJ/(kg K)
$c_v = f(p, t, x)$	cv_ptx_R134a	CV_PTX_R134A(P, T, X)	C_CV_PTX_R134A(CV, P, T, X)	Specific isochoric heat capacity	kJ/(kg K)
$\eta = f(p, t, x)$	eta_ptx_R134a	ETA_PTX_R134A(P, T, X)	C_ETA_PTX_R134A(ETA, P, T, X)	Dynamic viscosity	Pa s
$h = f(p, t, x)$	h_ptx_R134a	H_PTX_R134A(P, T, X)	C_H_PTX_R134A(H, P, T, X)	Specific enthalpy	kJ/kg
$\kappa = f(p, t, x)$	kappa_ptx_R134a	KAP_PTX_R134A(P, T, X)	C_KAP_PTX_R134A(KAP, P, T, X)	Isentropic exponent	-
$\lambda = f(p, t, x)$	lambda_ptx_R134a	LAM_PTX_R134A(P, T, X)	C_LAM_PTX_R134A(LAM, P, T, X)	Thermal conductivity	W/m K
$\nu = f(p, t, x)$	ny_ptx_R134a	NY_PTX_R134A(P, T, X)	C_NY_PTX_R134A(NY, P, T, X)	Kinematic viscosity	m <sup>2</sup> /s
$p_s = f(t)$	ps_t_R134a	PS_T_R134A(T)	C_PS_T_R134A(PS, T)	Vapor pressure from temperature	Bar
$Pr = f(p, t, x)$	Pr_ptx_R134a	PR_PTX_R134A(P, T, X)	C_PR_PTX_R134A(PR, P, T, X)	<i>Prandtl</i> -Number	-
$\rho = f(p, t, x)$	rho_ptx_R134a	RHO_PTX_R134A(P, T, X)	C_RHO_PTX_R134A(RHO, P, T, X)	Density	kg/m <sup>3</sup>
$s = f(p, t, x)$	s_ptx_R134a	S_PTX_R134A(P, T, X)	C_S_PTX_R134A(S, P, T, X)	Specific entropy	kJ/(kg K)
$t = f(p, h)$	t_ph_R134a	T_PH_R134A(P, H)	C_T_PH_R134A(T, P, H)	Backward function: Temperature from pressure and enthalpy	°C
$t = f(p, s)$	t_ps_R134a	T_PS_R134A(P, S)	C_T_PS_R134A(T, P, S)	Backward function: Temperature from pressure and entropy	°C
$t_s = f(p)$	ts_p_R134a	TS_P_R134A(P)	C_TS_P_R134A(TS, P)	Saturation temperature from pressure	°C
$u = f(p, t, x)$	u_ptx_R134a	U_PTX_R134A(P, T, X)	C_U_PTX_R134A(U, P, T, X)	Specific internal energy	kJ/kg
$v = f(p, t, x)$	v_ptx_R134a	V_PTX_R134A(P, T, X)	C_V_PTX_R134A(V, P, T, X)	Specific volume	m <sup>3</sup> /kg
$w = f(p, t, x)$	w_ptx_R134a	W_PTX_R134A(P, T, X)	C_W_PTX_R134A(W, P, T, X)	Isentropic speed of sound	m/s <sup>2</sup>
$x = f(p, h)$	x_ph_R134a	X_PH_R134A(P, H)	C_X_PH_R134A(X, P, H)	Backward function: Vapor fraction from pressure and enthalpy	kg/kg
$x = f(p, s)$	x_ps_R134a	X_PS_R134A(P, S)	C_X_PS_R134A(X, P, S)	Backward function: Vapor fraction from pressure and entropy	kg/kg

**Units:**  $t$  in °C  
 $p$  in bar  
 $x$  in (kg of saturated steam)/(kg wet steam)

### Range of validity

Temperature range: from  $t(p, p_{\max})$  to 181.85 °C

Pressure range: from  $p_t = 0.000389564$  bar to 700 bar

### Reference state

$h = 200$  kJ/kg and  $s = 1$  kJ/(kg K) at  $t = 0$  °C on the saturated liquid line ( $x = 0$ )

### Details on the vapor fraction $x$

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

#### Single-phase region

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

#### Wet-steam region

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered. In this case, the backward functions result in the appropriate value between 0 and 1 for  $x$ . When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$  and in both cases the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If this is not the case the calculation for the property of the chosen function results in  $-1000$ .

Wet steam region: Temperature ranges from  $t_t = -103.30$  °C to  $t_c = 101.03$  °C

Pressure ranges from  $p_t = 0.000389564$  bar to  $p_c = 40.566$  bar

### Hint:

*If the calculation results in  $-1000$ , the values entered represent a state point beyond the range of validity of LibR134a. For further information on each function and its range of validity see Chapter 3. The same information may also be accessed via the online help pages.*

## 2 Application of FluidLAB in MATLAB®

The FluidLAB Add-In has been developed to calculate thermodynamic properties in MATLAB® more conveniently. Within MATLAB® it enables the direct call of functions relating to R134a from the LibR134a property library.

### 2.1 Installing FluidLAB

#### Installing FluidLAB including LibR134a for 32-bit MATLAB®

This section describes the installation of FluidLAB LibR134a for a 32-bit version of MATLAB®. Before you begin, it is best to close any Windows® applications, since Windows® may need to be rebooted during the installation process.

After you have downloaded and extracted the zip-file "CD\_FluidLAB\_LibR134a.zip", you will see the folder

CD\_FluidLAB\_LibR134a

in your Windows Explorer®, Norton Commander® or another similar program you are using.

Open this folder by double-clicking on it.

In this folder you will see the following files:

FluidLAB\_LibR134a\_Docu\_Eng.pdf

FluidLAB\_LibR134a\_Setup.exe

LibR134a.dll.

In order to run the installation of FluidLAB including, the LibR134a property library, double-click on the file

FluidLAB\_LibR134a\_Setup.exe.


Installation may start with a window noting that all Windows® programs should be closed. When this is the case, the installation can be continued. Click the "Next >" button.

In the following dialog box, "Destination Location", the default path offered automatically for the installation of FluidLAB is

C:\Program Files\FuildLAB\LibR134a (for English version of Windows)

C:\Programme\FuildLAB\LibR134a (for German version of Windows).

By clicking the "Browse..." button, you can change the installation directory before installation (see Figure 2.1).



**Figure 2.1:** "Destination Location"

If you wish to change directories, click the "Browse..." button and select your desired directory. The instructions in this documentation refer to the stated default directory. Leave this window by clicking the "Next >" button.

The dialog window "Start Installation" pops up. Click the "Next >" button to continue installation. The FluidLAB files are now being copied into the created directory on your hard drive. Click the "Finish >" button in the following window to complete installation.

The installation program has copied the following files for LibR134a into the directory:

C:\Program Files\FuildLAB\LibR134a	(for English version of Windows)
C:\Programme\FuildLAB\LibR134a	(for German version of Windows)):
advapi32.dll	LC.dll
Dformd.dll	msvcp60.dll
Dforrt.dll	msvcrt.dll
INSTALL.LOG	Unwise.exe
LibR134a.dll	Unwise.ini

Now, you have to overwrite the file "LibR134a.dll" in your FluidLAB directory with the file of the same name provided on your CD with FluidLAB.

To do this, open the CD in "My Computer" and click on the file "LibR134a.dll" in order to highlight it. Then click on the "Edit" menu in your Explorer and select "Copy".

Now, open your FluidLAB directory (the standard being

C:\Program Files\FuildLAB\LibR134a (for English version of Windows)

C:\Programme\FuildLAB\LibR134a (for German version of Windows))

and insert the file "LibR134a.dll" by clicking the "Edit" menu in your Explorer and then select "Paste". Answer the question whether you want to replace the file by clicking the "Yes" button. Now, you have overwritten the file "LibR134a.dll" successfully and the property functions are available in MATLAB.

## Installing FluidLAB including LibR134a for 64-bit MATLAB®

This section describes the installation of FluidLAB LibR134a.

Before you begin, it is best to close any Windows® applications, since Windows® may need to be rebooted during the installation process.

After you have downloaded and extracted the zip-file "CD\_FluidLAB\_LibR134a\_x64.zip", you will see the folder

CD\_FluidLAB\_LibR134a

in your Windows Explorer®, Norton Commander® or any other similar program you are using.

Open this folder by double-clicking on it.

In this folder you will see the following files

FluidLAB\_LibR134a\_Docu\_Eng.pdf

FluidLAB\_LibR134a\_64\_Setup.msi

LibR134a.dll

Setup.exe

and folders

/vcredist\_x64

/WindowsInstaller3\_1.

In order to run the installation of FluidLAB including, the LibR134a property library, double-click on the file

Setup.exe.

Installation of FluidLAB LibR134a starts with a window noting that the installer will guide you through the installation process. Click the "Next >" button to continue.


In the following dialog box, "Destination Location", the default path offered automatically for the installation of FluidLAB is

C:\Program Files\FuildLAB\LibR134a      (for English version of Windows)

C:\Programme\FuildLAB\LibR134a      (for German version of Windows)

By clicking the "Browse..." button, you can change the installation directory before installation (see Figure 2.2).





**Figure 2.2:** "Select Installation Folder"

Finally, click on "Next >" to continue installation; click "Next >" again in the "Confirm Installation" window which follows in order to start the installation of FluidLAB.

After FluidLAB has been installed, you will see the sentence "FluidLAB LibR134a 64 has been successfully installed." Confirm this by clicking the "Close" button.

The installation program has copied the following files for LibR134a into the directory

"C:\Program Files\FuildLAB\LibR134a" (for English version of Windows)  
 "C:\Programme\FuildLAB\LibR134a" (for German version of Windows):

capt_ico_big.ico	libifcoremd.dll
LC.dll	libiomp5md.dll
LibR134a.dll	libmmd.dll

Now, you have to overwrite the file "LibR134a.dll" in your FluidLAB directory with the file of the same name provided on your CD with FluidLAB.

To do this, open the CD in "My Computer" and click on the file "LibR134a.dll" in order to highlight it. Then click on the "Edit" menu in your Explorer and select "Copy".

Now, open your FluidLAB directory (the standard being

"C:\Program Files\FuildLAB\LibR134a" (for English version of Windows)  
 "C:\Programme\FuildLAB\LibR134a" (for German version of Windows))

and insert the file "LibR134a.dll" by clicking the "Edit" menu in your Explorer and then select "Paste". Answer the question whether you want to replace the file by clicking the "Yes" button. Now, you have overwritten the file "LibR134a.dll" successfully and the property functions are available in MATLAB.

The installation programs for both the 32-bit and the 64-bit Windows version have copied the following function files for LibR134a into the directory

"C:\Program Files\FluidLAB\LibR134a" (for English version of Windows)

"C:\Programme\FluidLAB\LibR134a" (for German version of Windows):

- Dynamic Link Library "LibR134a.dll" and other necessary system DLL files.

- MATLAB®-Interface-Program for calculable functions

a_ptx_R134a	rho_ptx_R134a
cp_ptx_R134a	s_ptx_R134a
cv_ptx_R134a	t_ph_R134a
eta_ptx_R134a	t_ps_R134a
h_ptx_R134a	ts_p_R134a
kappa_ptx_R134a	u_ptx_R134a
lambda_ptx_R134a	v_ptx_R134a
ny_ptx_R134a	w_ptx_R134a
Pr_ptx_R134a	x_ph_R134a
ps_t_R134a	x_ps_R134a

Please note that there is a difference in the file extension of the function files.

The 32-bit installation program has copied function files with the file extension

.mexw32

and the 64-bit installation program has copied function files with the file extension

.mexw64


into your LibR134a directory (the standard being

"C:\Program Files\FluidLAB\LibR134a" (for English version of Windows)

"C:\Programme\FluidLAB\LibR134a" (for German version of Windows)).


## 2.2 Licensing the LibR134a Property Library

The licensing procedure must be carried out when the prompt message appears. In this case, you will see the "License Information" window for LibR134a (see figure below).



**Figure 2.3:** "License Information" window

Here you are asked to type in the license key which you have obtained from the Zittau/Goerlitz University of Applied Sciences. If you do not have this, or have any questions, you will find contact information on the "Content" page of this User's Guide or by clicking the yellow question mark in the "License Information" window. Then the following window will appear:



**Figure 2.4:** "Help" window

If you do not enter a valid license it is still possible to use MATLAB<sup>®</sup> by clicking "Cancel". In this case, the LibR134a property library will display the result "-11111111" for every calculation.


The "License Information" window will appear every time you use FluidLAB LibR134a until you enter a license code to complete registration. If you decide not to use FluidLAB LibR134a, you can uninstall the program following the instructions given in section 2.5 of this User's Guide.

### 2.3 Example: Calculation of $h = f(p,t,x)$ in an M-File

Now we will calculate, step by step, the specific enthalpy  $h$  as a function of pressure  $p$ , temperature  $t$  and vapor fraction  $x$  using FluidLAB.

Please carry out the following instructions:


- Start Windows Explorer®, Total Commander®, My Computer or another file manager program. The following description refers to Windows Explorer®.
- Your Windows Explorer® should be set to "Details" for easier viewing. Click the "Views" button and select "Details."
- Switch into the program directory of FluidLAB, in which you will find the folder "\LibR134a"; it is generally saved under: "C:\Program Files\FluidLAB"
- Create the folder "\LibR134a\_Example" by clicking on "File" in the Explorer® menu, then "New" in the menu which appears and afterwards selecting "Folder". Name the new folder "\LibR134a\_Example."
- You will now see the following window:



**Figure 2.5:** Folders "LibR134a" and "LibR134a\_Example"

- Switch into the directory "\LibR134a" within "\FluidLAB", the standard being  
 "C:\Program Files\FluidLAB\LibR134a" (for English version of Windows)  
 "C:\Programme\FluidLAB\LibR134a" (for German version of Windows)."

- You will see the following window:



**Figure 2.6:** Contents of the folder "LibR134a"

If you have installed the 32-bit version of LibR134a you will now have to copy the following files into the directory

"C:\Program Files\FluidLAB\LibR134a\_Example" (for English version of Windows)

"C:\Programme\FluidLAB\LibR134a\_Example" (for German version of Windows)

in order to calculate the function  $h = f(p, t, x)$ .

- The following files are needed:

- "h\_ptx\_97.mexw32"
- "LibR134a.dll"
- "libifcoremdd.dll"
- "libmmd.dll"
- "libmdd.dll"
- "msvcr71d.dll"
- "dforrt.dll.dll"
- "msvcrt.dll"

- Click the file "h\_ptx\_R134a.mexw32", then click "Edit" in the upper menu bar and select "Copy".
- Switch into the directory

"C:\Program Files\FluidLAB\LibR134a\_Example" (for English version of Windows)


"C:\Programme\FluidLAB\LibR134a\_Example" (for German version of Windows),

click "Edit" and select "Paste".

- Repeat these steps in order to copy the other files listed above.

You may also select all the above-named files and then copy them as a group (press the Control button to enable multiple markings).

- You will see the following window:



**Figure 2.7:** Contents of the folder "LibR134a\_Example"

If you have installed the 64-bit version of LibR134a you will now have to copy the following files into the directory

"C:\Program Files\FluidLAB\LibR134a\_Example" (for English version of Windows)

"C:\Programme\FluidLAB\LibR134a\_Example" (for German version of Windows)

in order to calculate the function  $h = f(p,t,x)$ .

- The following six files are needed:

- "h\_ptx\_R134a.mexw64"
- "LC.dll"
- "LibR134a.dll"
- "libifcoremd.dll"
- "libiomp5.dll"
- "libmmd.dll."

- Click the file "h\_ptx\_R134a.mexw64", then click "Edit" in the upper menu bar and select "Copy."
- Switch into the directory




"C:\Program Files\FluidLAB\LibR134a\_Example" (for English version of Windows)

"C:\Programme\FluidLAB\LibR134a\_Example" (for German version of Windows),


click "Edit" and then "Paste."

- Repeat these steps in order to copy the other files listed above. You may also select all the above-named files and then copy them as a group (press the Control button to enable multiple markings).
- Now, start MATLAB (if you have not started it before).
- Click the button marked in the next figure in order to open the folder "\LibR134a\_Example" in the "Current Folder" window.



**Figure 2.8:** Selection of the working directory

- Find and select the directory "C:\Program Files\FluidLAB\LibR134a\_Example" in the pop-up menu (see the following figure).




**Figure 2.9:** Choosing the "LibR134a\_Example" folder

- Confirm your selection by clicking the "OK" button.
- First of all you need to create an M-File in MATLAB®. Within MATLAB® click "Desktop", then select "Editor". Now click on the "New Script" button in the Editor Window.
- If the "Editor" window appears as a separate window, you can embed it into MATLAB® by clicking the insertion arrow (see next figure) in order to obtain a better view.



**Figure 2.10:** Embedding the "Editor" window

- In the following figure you will see the "Editor – Untitled" window.



**Figure 2.11:** Embedded "Editor" window

- Now type the following lines in the "Editor - Untitled" window:

Text to be written:	Explanation:
<code>% h_ptx_R134a.m</code>	file name as comment
<code>%%</code>	paragraph separation
<code>p=10; % pressure in bar</code>	declaration of the variables pressure, temperature, art and composition of mixture
<code>t=25; % temperature in °C</code>	
<code>x=-1; % vapor fraction in kg/kg</code>	paragraph separation
<code>%%</code>	
<code>h=h_ptx_R134a(p,t,x)</code>	function call
<code>%%</code>	paragraph separation

- Remarks:

- The program interprets the first line, starting with "%," to be a data description in "Current Directory."
- Paragraph separations which are mandatory are marked with "%%". This also serves to separate the declaration of variables and calculation instructions.



- The words which are printed in green, start with "%" and come after the variables are comments. They are not in fact absolutely necessary, but they are very helpful for your overview and to make the process more easily understood.
- Omit the semicolons after the numerical values if you wish to see the result for  $h$  and the input parameters.

The values of the function parameters in their corresponding units stand for:

- First operand: Value for  $p = 10$   
(Range of validity:  $p = 0.00391 \text{ bar} \dots 700 \text{ bar}$ )
- Second operand: Value for  $t = 25 \text{ }^\circ\text{C}$   
(Range of validity:  $t = -103.30 \text{ }^\circ\text{C} \dots 181.85 \text{ }^\circ\text{C}$ )
- Third operand: Value for  $x = -1 \text{ kg/kg}$

Since the wet steam region is calculated automatically by the subprograms, the following fixed details on the vapor fraction  $x$  are to be considered when the value for  $x$  is entered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam), e. g., pressure  $p$  and temperature  $t$  are given,  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.

When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If this is not the case the enthalpy calculated later will result in -1000.


(Vapor pressure curve of R134a:  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3) \dots t_c = 101.03 \text{ }^\circ\text{C}$   
 $p_t = 0.00389564 \text{ bar} \dots p_c = 40.566 \text{ bar}$ )

- Save the "M-File" by clicking the "File" button and then click "Save As...".
- The menu "Save file as:" appears; In this menu, the folder name "LibR134a\_Example" must be displayed in the "Save in:" field.
- Next to "File name" you have to type "Example\_h\_ptx\_R134a.m" and afterwards click the "Save" button.

**Note.**


*The name of the example file has to be different in comparison to the name of the used function. For example, the file could not be named "h\_ptx\_R134a.m" in this case. Otherwise an error message will appear during the calculation.*

- You will now see the following window:




**Figure 2.12:** "Example\_h\_ptx\_R134a.m" M-file

- Within the "Current Folder" window, the file "Example\_h\_ptx\_R134a.m" appears.
- Right-click on this file and select "Run" in the menu which appears (see next figure).



**Figure 2.13:** Running the "Example\_h\_ptx\_R134a.m" M-file

- You will see the following window:



**Figure 2.14:** MATLAB® with calculated result


The result for  $h$  appears in the "Command Window".

⇒ The result in our sample calculation here is: " $h = 234.5572$ ". The corresponding unit is kJ/kg (see table of the property functions in Chapter 1).

To be able to calculate other values, you have to copy the associated mexw32 files as well because MATLAB® can only access functions that are located in the "Current Directory" window. The example calculated can be found in the directory C:\Program Files\FuildLAB\LibR134a\_Example," and you may use it as a basis for further calculations using FluidLAB.


## 2.4 Example: Calculation of $h = f(p,t,x)$ in the Command Window

- Start MATLAB® (if you have not started it already).
- Click the button marked in the following image in order to open the folder "\LibR134a\_Example" in the window "Current Folder."




**Figure 2.15:** Selection of the working directory

- Find and select the directory  
 "C:\Program Files\FluidLAB\LibR134a\_Example" (for English version of Windows)  
 "C:\Programme\FluidLAB\LibR134a\_Example" (for German version of Windows)  
 in the menu which appears (see the following figure).



**Figure 2.16:** Choosing the "LibR134a\_Example" folder

- Confirm your selection by clicking the "OK" button.
- You will see the following window:



**Figure 2.17:** MATLAB<sup>®</sup> with necessary files

Corresponding to the table of the property functions in Chapter 1 you have to call up the function "**h\_ptx\_R134a**" as follows for calculating  $h = f(p, t, x)$ .

Write "**h=h\_ptx\_R134a(10,25,-1)**" within the "Command Window"

The values of the function parameters in their corresponding units stand for:

- **First operand: Value for  $p = 10$  bar**  
(Range of validity:  $p = 0.00391$  bar ... 700 bar)
- **Second operand: Value for  $t = 25$  °C**  
(Range of validity:  $t = -103.30$  °C ... 181.85 °C)
- **Third operand: Value for  $x = -1$**

Since the wet steam region is calculated automatically by the subprograms, the following fixed details on the vapor fraction  $x$  are to be considered when the value for  $x$  is entered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam), e. g., pressure  $p$  and temperature  $t$  are given,  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.


When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If this is not the case the enthalpy calculated later will result in -1000.

(Vapor pressure curve of R134a:  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3) \dots t_c = 101.03 \text{ °C}$   
 $p_t = 0.00389564 \text{ bar} \dots p_c = 40.566 \text{ bar}$ )



- Confirm your entry by pressing the "ENTER" button.
- You will see the following window:



**Figure 2.18:** MATLAB<sup>®</sup> with calculated result

⇒ In the "Command Window" you will see the result "h = 234.5572". The corresponding unit is kJ/kg (see table of the property functions in Chapter 1).

To be able to calculate other values, you will have to copy the respective mexw32 or mexw64 files into the working directory as well because MATLAB<sup>®</sup> can only access functions that are located in the "Current Directory" window.

## 2.5 Removing FluidLAB including LibR134a

To remove the property library LibR134a from your hard disk drive in Windows<sup>®</sup>, click "Start" in the Windows<sup>®</sup> task bar, select "Settings" and click "Control Panel".

Now double-click on "Add or Remove Programs". In the list box of the "Add or Remove Programs" window that appears select "FluidLAB LibR134a" by clicking on it and click the "Change/Remove" button.

In the following dialog box click "Automatic" and then click the "Next >" button.

Confirm the following menu "Perform Uninstall" by clicking the "Finish" button.

Finally, close the "Add or Remove Programs" and "Control Panel" windows. Now, FluidLAB has been removed.

If there is no library other than LibR134a installed, the directory "FluidLAB" will be removed as well.

### 3. Program Documentation

#### Thermal Diffusivity $a = f(p, t, x)$

Function Name: **a\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION A\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_A\_PTX\_R134A(A,P,T,X)**  
 for call from DLL: **REAL\*8 A,P,T,X**

#### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

#### Result

**A\_PTX\_R134A, A** or **a\_ptx\_R134a** – Thermal diffusivity  $a = \frac{\lambda^* v}{c_p}$  in  $\text{m}^2 / \text{s}$

#### Range of validity

Temperature range: from - 73.15 °C to 176.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar  
 Density range: from 0.00105455  $\text{kg} / \text{m}^3$  to 1550  $\text{kg} / \text{m}^3$

#### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered.

The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve.

Saturated liquid and saturated vapor line :

Temperature range from  $t = - 73.15$  °C to  $t_c = 101.03$  °C  
 Pressure range from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

#### Results for wrong input values

Result **A\_PTX\_R134A, A = -1000** or **a\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700$  bar or  $p < 0.00389564$  bar or  
 ( $x = -1$ )  $t > 181.85$ °C or  $t < -103.3$  °C or  $\rho > 1550$   $\text{m}^3 / \text{kg}$   
 Saturation lines: at  $p = -1000$  and  $t > 101.03$  °C or  $t < 73.15$ °C  
 at  $t = -1000$  and  $p > 40.566$  bar or  $p < 0.00389564$ bar or  
 at  $p > 40.566$  bar or  $p < 0.00389564$  bar and  
 $t > 101.03$  °C or  $t < -103.3$  °C

#### References: [16], [23]

## Specific Isobaric Heat Capacity $c_p = f(p, t, x)$

Function Name: **cp\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION CP\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_CP\_PTX\_R134A(CP,P,T,X)**  
 for call from DLL: **REAL\*8 CP,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**CP\_PTX\_R134A, CP** or **cp\_ptx\_R134a** – Specific isobaric heat capacity  $c_p$  in kJ / (kg K)

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C

Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered.

The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range	from $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$ to $t_c = 101.03 \text{ °C}$
Pressure range	from $p_t = 0.00389564 \text{ bar}$ to $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **CP\_PTX\_R134A, CP = -1000**, or **cp\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ kg/m}^3$

Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]



## Specific Isochoric Heat Capacity $c_v = f(p, t, x)$

Function Name: **cv\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION CV\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C CV\_PTX\_R134A(CV,P,T,X)**  
 for call from DLL: **REAL\*8 CV,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**CV\_PTX\_R134A, CV** or **cv\_ptx\_R134a** – Specific isochoric heat capacity  $c_v$  in kJ / (kg K)

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered. The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $t_c = 101.03 \text{ °C}$   
 Pressure range from  $p_t = 0.00389564 \text{ bar}$  to  $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **CV\_PTX\_R134A, CV = -1000** or **cv\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$   
 Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

## Dynamic Viscosity $\eta = f(p, t, x)$

Function Name: **eta\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION ETA\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_ETA\_PTX\_R134A(ETA,P,T,X)**  
 for call from DLL: **REAL\*8 ETA,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**ETA\_PTX\_R134A**, **ETA** or **eta\_ptx\_R134a** – Dynamic viscosity  $\eta$  in Pa s

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered. The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1$ , or the given value for  $p$  and  $t = -1$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range	from $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$ to $t_c = 101.03 \text{ °C}$
Pressure range	from $p_t = 0.00389564 \text{ bar}$ to $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **ETA\_PTX\_R134A**, **ETA = -1000** or **eta\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

**References:** [16], [22]

## Specific Enthalpy $h = f(p, t, x)$

Function Name: **h\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION H\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_H\_PTX\_R134A(H,P,T,X)**  
 for call from DLL: **REAL\*8 H,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**H\_PTX\_R134A, H** or **h\_ptx\_R134a** - Specific enthalpy  $h$  in kJ/kg

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of wet steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.

When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$  and in both cases the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $t_c = 101.03 \text{ °C}$   
 Pressure range from  $p_t = 0.00389564 \text{ bar}$  to  $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **H\_PTX\_R134A, H = -1000** or **eta\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

## Isentropic Exponent $\kappa = f(p, t, x)$

Function Name: **kappa\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION KAP\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_KAP\_PTX\_R134A(KAP,P,T,X)**  
 for call from DLL: **REAL\*8 KAP,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**KAP\_PTX\_R134A, KAP** or **kappa\_ptx\_R134a** – Isentropic exponent  $\kappa = \frac{w^2}{p^*v}$

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered.

The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range	from $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$ to $t_c = 101.03 \text{ °C}$
Pressure range	from $p_t = 0.00389564 \text{ bar}$ to $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **KAP\_PTX\_R134A, KAP = -1000** or **kappa\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

Zittau/Goerlitz University of Applied Sciences, Department of Technical Thermodynamics, Professor H.-J. Kretschmar, Dr. I. Stoecker



## Thermal Conductivity $\lambda = f(p, t, x)$

Function Name: **lambda\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION LAM\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_LAM\_PTX\_R134A(LAM,P,T,X)**  
 for call from DLL: **REAL\*8 LAM,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**LAM\_PTX\_R134A**, **LAM** or **lambda\_ptx\_R134a** – Thermal conductivity  $\lambda$  in W / m K

### Range of validity

Temperature range: from - 73.15 °C to 176.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered.

The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t = - 103.30$  °C to  $t_c = 101.03$  °C  
 Pressure range from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

### Results for wrong input values

Result **LAM\_PTX\_R134A**, **LAM = - 1000** or **lambda\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700$  bar or  $p < 0.00389564$  bar or  
 ( $x = -1$ )  $t > 181.85$ °C or  $t < -103.3$  °C or  $\rho > 1550$  m<sup>3</sup> / kg  
 Saturation lines: at  $p = -1000$  and  $t > 101.03$  °C or  $t < 73.15$ °C  
 at  $t = -1000$  and  $p > 40.566$  bar or  $p < 0.00389564$  bar or  
 at  $p > 40.566$  bar or  $p < 0.00389564$  bar and  
 $t > 101.03$  °C or  $t < -103.30$  °C

**References:** [16], [23]

## Kinematic Viscosity $\nu = f(p, t, x)$

Function Name: **ny\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION NY\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_NY\_PTX\_R134A(NY,P,T,X)**  
 for call from DLL: **REAL\*8 NY,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**NY\_PTX\_R134A**, **NY** or **ny\_ptx\_R134a** – Kinematic viscosity  $\nu = \eta * v$  in  $\text{m}^2 / \text{s}$

### Range of validity

Temperature range: from - 73.15 °C to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar  
 Density range: from 0.00105455  $\text{m}^3 / \text{kg}$  to 1550  $\text{m}^3 / \text{kg}$

### Details on the vapor fraction $x$ and on the calculation of saturated liquid and saturated steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered.

The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t = - 103.30$  °C to  $t_c = 101.03$  °C  
 Pressure range from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

### Results for wrong input values

Result **NY\_PTX\_R134A**, **NY= -1000** or **ny\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700$  bar or  $p < 0.00389564$  bar or  
 ( $x = -1$ )  $t > 181.85$ °C or  $t < -103.3$  °C or  $\rho > 1550$   $\text{m}^3 / \text{kg}$   
 Saturation lines: at  $p = -1000$  and  $t > 101.03$  °C or  $t < 73.15$ °C  
 at  $t = -1000$  and  $p > 40.566$  bar or  $p < 0.00389564$  bar or  
 at  $p > 40.566$  bar or  $p < 0.00389564$  bar and  
 $t > 101.03$  °C or  $t < -103.30$  °C

**References:** [16], [22]



**Prandtl-Number  $Pr = f(p, t, x)$** 

Function Name: **Pr\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION PR\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_PR\_PTX\_R134A(PR,P,T,X)**  
 for call from DLL: **REAL\*8 PR,P,T,X**

**Input Values:**

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

**Result**

**PR\_PTX\_R134A, PR** or **Pr\_ptx\_R134a** – Prandtl-Number  $Pr = \frac{\eta^* c_p}{\lambda}$

**Range of validity**

Temperature range: from - 73.15 °C to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar  
 Density range: from 0.00105455 m<sup>3</sup> / kg to 1550 m<sup>3</sup> / kg

**Details on the vapor fraction  $x$  and on the calculation of saturated liquid and saturated steam**

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered. The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t = - 103.30$  °C to  $t_c = 101.03$  °C  
 Pressure range from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

**Results for wrong input values**

Result **PR\_PTX\_R134A, PR = -1000** or **Pr\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700$  bar or  $p < 0.00389564$  bar or  
 ( $x = -1$ )  $t > 181.85$ °C or  $t < -103.3$  °C or  $\rho > 1550$  m<sup>3</sup> / kg  
 Saturation lines: at  $p = -1000$  and  $t > 101.03$  °C or  $t < -73.15$ °C  
 at  $t = -1000$  and  $p > 40.566$  bar or  $p < 0.00389564$  bar or  
 at  $p > 40.566$  bar or  $p < 0.00389564$  bar and  
 $t > 101.03$  °C or  $t < -103.30$  °C

**References:** [16], [22], [23]

## Vapor Pressure $p_s = f(t)$

Function Name: **ps\_t\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION PS\_T\_R134A(T)**  
 for call from Fortran: **REAL\*8 T**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_PS\_T\_R134A(PS,T)**  
 for call from DLL: **REAL\*8 PS,T**

### Input Values:

T - Temperature  $t$  in °C

### Result

**PS\_T\_R134A, PS** or **ps\_t\_R134a** – Vapor pressure  $p_s$  in bar

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 101.03 °C

### Results for wrong input values

Result **PS\_T\_R134A, PS = -1000** or **ps\_t\_R134a = -1000** for input values:

$t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

**Density  $\rho = f(p, t, x)$** 

Function Name: **rho\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION RHO\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_RHO\_PTX\_R134A(RHO,P,T,X)**  
 for call from DLL: **REAL\*8 RHO,P,T,X**

**Input Values:**

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

**Result**

**RHO\_PTX\_R134A, RHO** or **rho\_ptx\_R134a** – Density  $\rho$  in kg / m<sup>3</sup>

**Range of validity**

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

**Details on the vapor fraction  $x$  and on the calculation of wet steam**

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.

When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$  and in both cases the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $t_c = 101.03 \text{ °C}$   
 Pressure range from  $p_t = 0.00389564 \text{ bar}$  to  $p_c = 40.566 \text{ bar}$

**Results for wrong input values**

Result **RHO\_PTX\_R134a, RHO= -1000** or **rho\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$   
 Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < -73.15 \text{ °C}$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

**References:** [16]

## Specific Entropy $s = f(p, t, x)$

Function Name: **s\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION S\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_S\_PTX\_R134A(S,P,T,X)**  
 for call from DLL: **REAL\*8 S,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**S\_PTX\_R134A, S** or **s\_ptx\_R134a** - Specific entropy  $s$  in kJ/kg K

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of wet steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.

When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$  and in both cases the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve.

If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range	from $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$ to $t_c = 101.03 \text{ °C}$
Pressure range	from $p_t = 0.00389564 \text{ bar}$ to $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **S\_PTX\_R134A, S = -1000** or **s\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < -73.15 \text{ °C}$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$   
 Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < -73.15 \text{ °C}$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

## Backward Function: Temperature $t = f(p,h)$

Function Name: **t\_ph\_R134a**

Subroutine with function value: **REAL\*8 FUNCTION T\_PH\_R134A(P,H)**  
 for call from Fortran: **REAL\*8 P,H**

Subroutine with parameter: **INTEGER\*4 FUNCTION C\_T\_PH\_R134A(T,P,H)**  
 for call from DLL: **REAL\*8 T,P,H**

### Input Values:

**P** - Pressure  $p$  in bar  
**H** - Specific enthalpy  $h$  in kJ/kg

### Result

**T\_PH\_R134A, T** or **t\_ph\_R134a** - Temperature  $t$  in °C

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C  
 Pressure range: from 0.00389564 bar to 700 bar

### Details on the calculation of wet steam

The wet steam region is calculated automatically. This means that from the given values of  $p$  and  $h$  the function will determine whether the state point to be calculated is located within the single-phase region (liquid or steam) or the wet steam region. Afterwards the calculation of  $t$  in the appropriate region will be carried out.

Wet steam region: Pressure ranges from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

### Results for wrong input values

Result **T\_PH\_R134A, T = -1000** or **t\_ph\_R134a = -1000** for input values:

Single phase region:  $p > 700$  bar or  $p < 0.00389564$  bar or  
 ( $x = -1$ )  $t > 181.85^\circ\text{C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p > 70.54$  bar or  $p < 0.00389564$  bar or  
 $t > 101.03^\circ\text{C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

## Backward Function: Temperature $t = f(p,s)$

Function Name: **t\_ps\_R134a**

Subroutine with function value: **REAL\*8 FUNCTION T\_PS\_R134A(P,S)**  
 for call from Fortran: **REAL\*8 P,S**

Subroutine with parameter: **INTEGER\*4 FUNCTION C\_T\_PS\_R134A(T,P,S)**  
 for call from DLL: **REAL\*8 T,P,S**

### Input Values:

- P** - Pressure  $p$  in bar
- S** - Specific entropy  $s$  in kJ/(kg K)

### Result

**T\_PS\_R134A, T** or **t\_ps\_R134a** - Temperature  $t$  in °C

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C

Pressure range: from 0.00389564 bar to 700 bar

### Details on the calculation of wet steam

The wet steam region is calculated automatically. This means that from the given values of  $p$  and  $s$  the function will determine whether the state point to be calculated is located within the single-phase region (liquid or steam) or the wet steam region. Afterwards the calculation of  $t$  in the appropriate region will be carried out.

Wet steam region: Pressure ranges from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

### Results for wrong input values

Result **T\_PS\_R134A, T = -1000** or **t\_ps\_R134a = -1000** for input values:

Single phase region:  $p > 700$  bar or  $p < 0.00389564$  bar or  
 ( $x = -1$ )  $t > 181.85^\circ\text{C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p > 70.54$  bar or  $p < 0.00389564$  bar or  
 $t > 101.03$  °C or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

**References:** [16]

<b>Saturation Temperature <math>t_s = f(p)</math></b>
---

Function Name: **ts\_p\_R134a**

Subroutine with function value: **REAL\*8 FUNCTION TS\_P\_R134A(P)**  
 for call from Fortran: **REAL\*8 P**

Subroutine with parameter: **INTEGER\*4 FUNCTION C\_TS\_P\_R134A(TS,P)**  
 for call from DLL: **REAL\*8 TS,P**

**Input Values:**

**P** - Pressure  $p$  in bar

**Result**

**TS\_P\_R134A, TS** or **ts\_p\_R134a** – Saturation temperature  $t_s$  in °C

**Range of validity**

Pressure range: from 0.00389564 bar to 40.566 bar

**Results for wrong input values**

Result **TS\_P\_R134A, TS = -1000** or **ts\_p\_R134a = -1000** for input values:  
 $p < 0.00389564$  bar or  $p > 40.566$  bar

**References:** [16]

## Specific Internal Energy $u = f(p, t, x)$

Function Name: **u\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION U\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_U\_PTX\_R134A(U,P,T,X)**  
 for call from DLL: **REAL\*8 U,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**U\_PTX\_R134A, U** or **u\_ptx\_R134a** - Specific internal energy  $u$  in kJ/kg

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C

Pressure range: from 0.00389564 bar to 700 bar

### Details on the vapor fraction $x$ and on the calculation of wet steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.

When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$  and in both cases the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in -1000.

Saturated liquid and saturated vapor line :

Temperature range from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $t_c = 101.03 \text{ °C}$   
 Pressure range from  $p_t = 0.00389564 \text{ bar}$  to  $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **U\_PTX\_R134A, U = -1000** or **u\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < -73.15 \text{ °C}$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]



## Specific Volume $v = f(p, t, x)$

Function Name: **v\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION V\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_V\_PTX\_R134A(V,P,T,X)**  
 for call from DLL: **REAL\*8 V,P,T,X**

### Input Values:

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

### Result

**V\_PTX\_R134A, V** or **v\_ptx\_R134a** – Specific volume  $v$  in  $\text{m}^3 / \text{kg}$

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $181.85 \text{ }^\circ\text{C}$   
 Pressure range: from  $0.00389564 \text{ bar}$  to  $700 \text{ bar}$

### Details on the vapor fraction $x$ and on the calculation of wet steam

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located in the wet steam region, a value for  $x$  between 0 and 1 ( $x = 0$  for saturated liquid,  $x = 1$  for saturated steam) must be entered.

When calculating wet steam either the given value for  $t$  and  $p = -1000$  or the given value for  $p$  and  $t = -1000$  and in both cases the value for  $x$  between 0 and 1 must be entered.

If  $p$  and  $t$  and  $x$  are entered as given values, the program considers  $p$  and  $t$  to be appropriate to represent the vapor pressure curve. If it is not the case the calculation for the quantity of the chosen function to be calculated results in  $-1000$ .

Saturated liquid and saturated vapor line :

Temperature range from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $t_c = 101.03 \text{ }^\circ\text{C}$   
 Pressure range from  $p_t = 0.00389564 \text{ bar}$  to  $p_c = 40.566 \text{ bar}$

### Results for wrong input values

Result **V\_PTX\_R134A, V = -1000** or **v\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85^\circ\text{C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$   
 Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ }^\circ\text{C}$  or  $t < -73.15^\circ\text{C}$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ }^\circ\text{C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

### References: [16]

**Isentropic Speed of Sound  $w = f(p, t, x)$** 

Function Name: **w\_ptx\_R134a**  
 Subroutine with function value: **REAL\*8 FUNCTION W\_PTX\_R134A(P,T,X)**  
 for call from Fortran: **REAL\*8 P,T,X**  
 Subroutine with parameter: **INTEGER\*4 FUNCTION C\_W\_PTX\_R134A(W,P,T,X)**  
 for call from DLL: **REAL\*8 W,P,T,X**

**Input Values:**

**P** - Pressure  $p$  in bar  
**T** - Temperature  $t$  in °C  
**X** - Vapor fraction  $x$  (kg of saturated steam)/(kg wet steam)

**Result**

**W\_PTX\_R134A, W** or **w\_ptx\_R134a** - Speed of sound  $w$  in m/s

**Range of validity**

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C

Pressure range: from 0.00389564 bar to 700 bar

**Details on the vapor fraction  $x$  and on the calculation of saturated liquid and saturated steam**

The wet steam region is calculated automatically by the subprograms. For this purpose the following fixed details on the vapor fraction  $x$  are to be considered:

If the state point to be calculated is located in the single-phase region (liquid or superheated steam)  $x = -1$  must be entered as a pro-forma value.

If the state point to be calculated is located on the saturated liquid line,  $x = 0$  must be entered. When calculating saturated steam (saturated vapor line)  $x = 1$  must be entered.

The calculation for  $x$ -values between 0 and 1 is not possible.

When calculating saturated liquid or saturated steam, it is adequate to enter either the given value for  $t$  and  $p = -1000$ , or the given value for  $p$  and  $t = -1000$ , plus the value for  $x$  ( $x = 0$  or  $x = 1$ ). If  $p$  and  $t$  and  $x$  are entered as given values, the program will consider  $p$  and  $t$  to be appropriate to represent the vapor pressure curve.

Saturated liquid and saturated vapor line :

Temperature range from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to  $t_c = 101.03 \text{ °C}$   
 Pressure range from  $p_t = 0.00389564 \text{ bar}$  to  $p_c = 40.566 \text{ bar}$

**Results for wrong input values**

Result **W\_PTX\_R134A, W = -1000** or **w\_ptx\_R134a = -1000** for input values:

Single phase region:  $p > 700 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 ( $x = -1$ )  $t > 181.85 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  or  $\rho > 1550 \text{ m}^3 / \text{kg}$

Saturation lines: at  $p = -1000$  and  $t > 101.03 \text{ °C}$  or  $t < -73.15 \text{ °C}$   
 at  $t = -1000$  and  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  or  
 at  $p > 40.566 \text{ bar}$  or  $p < 0.00389564 \text{ bar}$  and  
 $t > 101.03 \text{ °C}$  or  $t < t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$

**References:** [16]

## Backward Function: Vapor Fraction $x = f(p, h)$

Function Name: **x\_ph\_R134a**

Subroutine with function value:  
for call from Fortran: **REAL\*8 FUNCTION X\_PH\_R134A(P,H)**  
REAL\*8 P,H

Subroutine with parameter:  
for call from DLL: **INTEGER\*4 FUNCTION C\_X\_PH\_R134A(T,P,H)**  
REAL\*8 X,P,H

### Input Values:

**P** - Pressure  $p$  in bar  
**H** - Specific enthalpy  $h$  in kJ/kg

### Result

**X\_PH\_R134A, X** or **x\_ph\_R134a** - Vapor fraction  $x$  in (kg saturated steam/kg wet steam)

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 181.85 °C

Pressure range: from 0.00389564 bar to 700 bar

### Details on the calculation of wet steam

The wet steam region is calculated automatically. This means that from the given values of  $v$  and  $u$  the function will determine whether the state point to be calculated is located within the single-phase region (liquid or steam) or the wet steam region. When calculating wet steam the value for  $x$  between 0 and 1 is calculated (0 for saturated liquid, 1 for saturated steam). If the state point to be calculated is located in the single-phase region the result  $x = -1$  will be returned.

Wet steam region: Pressure ranges from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

### Results for wrong input values

Result **X\_PH\_R134A, X = -1** or **x\_ph\_R134a = -1** for input values:

In case the state point is located in the single phase region

$$p < 40.566 \text{ bar or } p > 0.00389564 \text{ bar}$$

### References: [16]

## Backward Function: Vapor Fraction $x = f(p,s)$

Function Name: **x\_ps\_R134a**

Subroutine with function value:  
for call from Fortran: **REAL\*8 FUNCTION X\_PS\_R134A(P,S)**  
REAL\*8 P,S

Subroutine with parameter:  
for call from DLL: **INTEGER\*4 FUNCTION C\_X\_PS\_R134A(X,P,S)**  
REAL\*8 X,P,S

### Input Values:

- P** - Pressure  $p$  in bar
- S** - Specific entropy  $s$  in kJ/(kg K)

### Result

**X\_PS\_R134A, X** or **x\_ps\_R134a** - Vapor fraction  $x$  in (kg saturated steam/kg wet steam)

### Range of validity

Temperature range: from  $t(p, \rho_{\max} = 1550 \text{ kg/m}^3)$  to 101.03 °C

Pressure range: from 0.00389564 bar to 700 bar

### Details on the calculation of wet steam

The wet steam region is calculated automatically. This means that from the given values of  $p$  and  $s$  the function will determine whether the state point to be calculated is located within the single-phase region (liquid or steam) or the wet steam region. When calculating wet steam the value for  $x$  between 0 and 1 is calculated (0 for saturated liquid, 1 for saturated steam). If the state point to be calculated is located in the single-phase region the result  $x = -1$  will be returned.

Wet steam region: Pressure ranges from  $p_t = 0.00389564$  bar to  $p_c = 40.566$  bar

### Results for wrong input values

Result **X\_PS\_R134A, X = -1** or **x\_ps\_R134a = -1** for input values:

In case the state point is located in the single phase region

$$p < 40.566 \text{ bar or } p > 0.00389564 \text{ bar}$$

**References:** [16]



## 4. Property Libraries for Calculating Heat Cycles, Boilers, Turbines, and Refrigerators

### Water and Steam

#### Library LibIF97

- Industrial Formulation IAPWS-IF97 (Revision 2007)
- Supplementary Standards
  - IAPWS-IF97-S01
  - IAPWS-IF97-S03rev
  - IAPWS-IF97-S04
  - IAPWS-IF97-S05
- IAPWS Revised Advisory Note No. 3 on Thermodynamic Derivatives (2008)

### Humid Combustion Gas Mixtures

#### Library LibHuGas

- Model: Ideal mixture of the real fluids:
- CO<sub>2</sub> - Span and Wagner    O<sub>2</sub> - Schmidt and Wagner  
 H<sub>2</sub>O - IAPWS-95          Ar - Tegeler et al.  
 N<sub>2</sub> - Span et al.
- and of the ideal gases:
- SO<sub>2</sub>, CO, Ne (Scientific Formulation of Bucker et al.)
- Consideration of:
- Dissociation from VDI 4670 and Poynting effect

### Humid Air

#### Library LibHuAir

- Model: Ideal mixture of the real fluids:
- Dry Air from Lemmon et al.
  - Steam, water and ice from IAPWS-IF97 and IAPWS-06
- Consideration of:
- Condensation and freezing of steam
  - Dissociation from the VDI 4670
  - Poynting effect from ASHRAE RP-1485

### Carbon Dioxide including Dry Ice

#### Library LibCO2

Formulation of Span and Wagner (1994)

### Ideal Gas Mixtures

#### Library LibIdGasMix

- Model: Ideal mixture of the ideal gases:
- |                 |                  |                 |            |
|-----------------|------------------|-----------------|------------|
| Ar              | NO               | He              | Propylene  |
| Ne              | H <sub>2</sub> O | F <sub>2</sub>  | Propane    |
| N <sub>2</sub>  | SO <sub>2</sub>  | NH <sub>3</sub> | Iso-Butane |
| O <sub>2</sub>  | H <sub>2</sub>   | Methane         | n-Butane   |
| CO              | H <sub>2</sub> S | Ethane          | Benzene    |
| CO <sub>2</sub> | OH               | Ethylene        | Methanol   |
| Air             |                  |                 |            |

Consideration of:

- Dissociation from the VDI Guideline 4670

### Dry Air including Liquid Air

#### Library LibRealAir

Formulation of Lemmon et al. (2000)

### Seawater

#### Library LibSeaWa

IAPWS Formulation 2008 of Feistel and IAPWS-IF97

### Nitrogen

#### Library LibN2

Formulation of Span et al. (2000)

### Ice

#### Library LibICE

Ice from IAPWS-06, Melting and sublimation pressures from IAPWS-08, Water from IAPWS-IF97, Steam from IAPWS-95 and -IF97

#### Library LibIDGAS

Model: Ideal gas mixture from VDI Guideline 4670

Consideration of:

- Dissociation from the VDI Guideline 4670

### Hydrogen

#### Library LibH2

Formulation of Leachman et al. (2007)

### Refrigerants

#### Ammonia

#### Library LibNH3

Formulation of Tillner-Roth (1995)

#### R134a

#### Library LibR134a

Formulation of Tillner-Roth and Baehr (1994)

#### Iso-Butane

#### Library LibButane\_Iso

Formulation of Bucker et al. (2003)

#### n-Butane

#### Library LibButane\_n

Formulation of Bucker et al. (2003)

### Mixtures for Absorption Processes

#### Ammonia/Water Mixtures

#### Library LibAmWa

IAPWS Guideline 2001 of Tillner-Roth and Friend (1998)

Helmholtz energy equation for the mixing term (also useable for calculating Kalina Cycle)

#### Water/Lithium Bromide Mixtures

#### Library LibWaLi

Formulation of Kim and Infante Ferreira (2004)

Gibbs energy equation for the mixing term

### Liquid Coolants

#### Liquid Secondary Refrigerants

#### Library LibSecRef

Liquid solutions of water with

- |   |                     |
|---|---------------------|
| C <sub>2</sub> H <sub>6</sub> O <sub>2</sub>  | Ethylene glycol     |
| C <sub>3</sub> H <sub>8</sub> O <sub>2</sub>  | Propylene glycol    |
| C <sub>2</sub> H <sub>5</sub> OH              | Ethyl alcohol       |
| CH <sub>3</sub> OH                            | Methyl alcohol      |
| C <sub>3</sub> H <sub>8</sub> O <sub>3</sub>  | Glycerol            |
| K <sub>2</sub> CO <sub>3</sub>                | Potassium carbonate |
| CaCl <sub>2</sub>                             | Calcium chloride    |
| MgCl <sub>2</sub>                             | Magnesium chloride  |
| NaCl  | Sodium chloride     |
| C <sub>2</sub> H <sub>3</sub> KO <sub>2</sub> | Potassium acetate   |

Formulation of the International Institute of Refrigeration (1997)

### Siloxanes as ORC Working Fluids

Octamethylcyclotetrasiloxane  $C_8H_{24}O_4Si_4$  **Library LibD4**

Decamethylcyclopentasiloxane  $C_{10}H_{30}O_5Si_5$  **Library LibD5**

Tetradecamethylhexasiloxane  $C_{14}H_{42}O_6Si_6$  **Library LibMD4M**

Hexamethyldisiloxane  $C_6H_{18}OSi_2$  **Library LibMM**

Formulation of Colonna et al. (2006)

Dodecamethylcyclohexasiloxane  $C_{12}H_{36}O_6Si_6$  **Library LibD6**

Decamethyltetrasiloxane  $C_{10}H_{30}O_3Si_4$  **Library LibMD2M**

Dodecamethylpentasiloxane  $C_{12}H_{36}O_4Si_5$  **Library LibMD3M**

Octamethyltrisiloxane  $C_8H_{24}O_2Si_3$  **Library LibMDM**

Formulation of Colonna et al. (2008)

### Propane

**Library LibPropane**

Formulation of Lemmon et al. (2007)

### Methanol

**Library LibCH3OH**

Formulation of de Reuck and Craven (1993)

### Ethanol

**Library LibC2H5OH**

Formulation of Schroeder et al. (2012)

### Helium

**Library LibHe**

Formulation of Arp et al. (1998)

### Hydrocarbons

Decane  $C_{10}H_{22}$  **Library LibC10H22**

Isopentane  $C_5H_{12}$  **Library LibC5H12\_ISO**

Neopentane  $C_5H_{12}$  **Library LibC5H12\_NEO**

Isohexane  $C_6H_{14}$  **Library LibC5H14**

Toluene  $C_7H_8$  **Library LibC7H8**

Formulation of Lemmon and Span (2006)

### Further Fluids

Carbon monoxide **CO** **Library LibCO**

Carbonyl sulfide **COS** **Library LibCOS**

Hydrogen sulfide **H<sub>2</sub>S** **Library LibH2S**

Dinitrogen monoxide **N<sub>2</sub>O** **Library LibN2O**

Sulfur dioxide **SO<sub>2</sub>** **Library LibSO2**

Acetone **C<sub>3</sub>H<sub>6</sub>O** **Library LibC3H6O**

Formulation of Lemmon and Span (2006)

### For more information please contact:

Zittau/Goerlitz University of Applied Sciences  
Department of Technical Thermodynamics  
Professor Hans-Joachim Kretzschmar  
Dr. Ines Stoecker

Theodor-Koerner-Allee 16  
02763 Zittau, Germany

Internet: [www.thermodynamics-zittau.de](http://www.thermodynamics-zittau.de)

E-mail: [hj.kretzschmar@hs-zigr.de](mailto:hj.kretzschmar@hs-zigr.de)

Phone: +49-3583-61-1846

Fax.: +49-3583-61-1846

### The following thermodynamic and transport properties can be calculated<sup>a</sup>:

#### Thermodynamic Properties

- Vapor pressure  $p_s$
- Saturation temperature  $T_s$
- Density  $\rho$
- Specific volume  $v$
- Enthalpy  $h$
- Internal energy  $u$
- Entropy  $s$
- Exergy  $e$
- Isobaric heat capacity  $c_p$
- Isochoric heat capacity  $c_v$
- Isentropic exponent  $\kappa$
- Speed of sound  $w$
- Surface tension  $\sigma$

#### Transport Properties

- Dynamic viscosity  $\eta$
- Kinematic viscosity  $\nu$
- Thermal conductivity  $\lambda$
- Prandtl-number  $Pr$

#### Backward Functions

- $T, v, s(p, h)$
- $T, v, h(p, s)$
- $p, T, v(h, s)$
- $p, T(v, h)$
- $p, T(v, u)$

#### Thermodynamic Derivatives

- Partial derivatives can be calculated.


<sup>a</sup> Not all of these property functions are available in all property libraries.






# Property Software for Calculating Heat Cycles, Boilers, Turbines, and Refrigerators


## Add-In FluidEXL<sup>Graphics</sup> for Excel<sup>®</sup>



Choosing a property library and a function




Displaying the calculated values in diagrams



Menu for the input of given property values


## Add-In FluidMAT for Mathcad<sup>®</sup>

The property libraries can be used in Mathcad<sup>®</sup>.




## Add-In FluidLAB for MATLAB<sup>®</sup>

Using the Add-In FluidLAB the property functions can be called in MATLAB<sup>®</sup>.




## Add-On FluidVIEW for LabVIEW<sup>®</sup>

The property functions can be calculated in LabVIEW<sup>®</sup>.



## Add-In FluidDYM for DYMOLA<sup>®</sup> (Modelica) and SimulationX<sup>®</sup>



The property functions can be called in DYMOLA<sup>®</sup> and SimulationX<sup>®</sup>.



## Add-In FluidEES for Engineering Equation Solver®

## App International Steam Tables for iPhone, iPad, iPod touch, Android smart phones and tablets

## Online Property Calculator at [www.thermodynamics-zittau.de](http://www.thermodynamics-zittau.de)



**Zittau's Fluid Property Calculator**

Fluid:

Function:

Unit System:

Enter given values: [Range of validity](#)

Pressure p:  bar

Temperature t:  °C

Vapor fraction x:  kg/kg

**Calculate / Recalculate**

**Result:**

Specific enthalpy h = 3097.38 kJ/kg

For further information on property libraries available for EXCEL®, MATLAB®, Mathcad®, Engineering Equation Solver®, DYMOLA® (Modelica), SimulationX®, and LabView® click [here](#)

An App for calculating steam properties on iPhone, iPad, and iPod touch can be found [here](#) PDF with the [description](#)

© Zittau/Goerlitz University of Applied Sciences  
 Faculty of Mechanical Engineering  
 Department of Technical Thermodynamics  
 Prof. Hans-Joachim Kretzschmar  
 Dr. Ines Stoecker  
 Programmer Joachim Posselt

Tel.: +49-3583-61-1846 or -1881  
 Fax: +49-3583-61-1846  
 E-mail: [info@thermodynamics-zittau.de](mailto:info@thermodynamics-zittau.de)  
[www.thermodynamics-zittau.de](http://www.thermodynamics-zittau.de)  
[www.thermodynamic-property-libraries.com](http://www.thermodynamic-property-libraries.com)  
[www.international-steam-tables.com](http://www.international-steam-tables.com)  
[www.thermodynamic-formelsammlung.de](http://www.thermodynamic-formelsammlung.de)

## Property Software for Pocket Calculators

### FluidCasio



fx 9750 G II    CFX 9850 fx-GG20    CFX 9860 G Graph 85    ALGEBRA FX 2.0

### FluidHP



HP 48    HP 49

### FluidTI



TI 83    TI Voyage 200    TI 92

## For more information please contact:

Zittau/Goerlitz University of Applied Sciences  
 Department of Technical Thermodynamics  
 Professor Hans-Joachim Kretzschmar  
 Dr. Ines Stoecker  
 Theodor-Koerner-Allee 16  
 02763 Zittau, Germany

E-mail: [hj.kretzschmar@hs-zigr.de](mailto:hj.kretzschmar@hs-zigr.de)  
 Internet: [www.thermodynamics-zittau.de](http://www.thermodynamics-zittau.de)  
 Phone: +49-3583-61-1846  
 Fax.: +49-3583-61-1846

The following thermodynamic and transport properties<sup>a</sup> can be calculated in Excel®, MATLAB®, Mathcad®, Engineering Equation Solver® EES, DYMOLA® (Modelica), SimulationX®, and LabVIEW®:

### Thermodynamic Properties

- Vapor pressure  $p_s$
- Saturation temperature  $T_s$
- Density  $\rho$
- Specific volume  $v$
- Enthalpy  $h$
- Internal energy  $u$
- Entropy  $s$
- Exergy  $e$
- Isobaric heat capacity  $c_p$
- Isochoric heat capacity  $c_v$
- Isentropic exponent  $\kappa$
- Speed of sound  $w$
- Surface tension  $\sigma$

### Transport Properties

- Dynamic viscosity  $\eta$
- Kinematic viscosity  $\nu$
- Thermal conductivity  $\lambda$
- Prandtl-number  $Pr$

### Backward Functions

- $T, v, s(p, h)$
- $T, v, h(p, s)$
- $p, T, v(h, s)$
- $p, T(v, h)$
- $p, T(v, u)$

### Thermodynamic Derivatives

- Partial derivatives can be calculated.

<sup>a</sup> Not all of these property functions are available in all property libraries.



## 5. References

- [1] Release on the IAPWS Industrial Formulation 1997 for the Thermodynamic Properties of Water and Steam IAPWS-IF97.  
IAPWS Sekretariat, Dooley, B, EPRI, Palo Alto CA (1997)
- [2] Wagner, W.; Kruse, A.:  
Zustandsgrößen von Wasser und Wasserdampf.  
Springer-Verlag, Berlin (1998)
- [3] Wagner, W.; Cooper, J.R.; Dittmann, A.; Kijima, J.; Kretzschmar, H.-J.; Kruse, A.; Mareš, R.; Oguchi, K.; Sato, H.; Stöcker, I.; Šifner, O.; Takaishi, Y.; Tanishita, I.; Trübenbach, J.; Willkommen, Th.:  
The IAPWS Industrial Formulation 1997 for the Thermodynamic Properties of Water and Steam.  
ASME Journal of Eng. for Gas Turbines and Power 122 (2000) Nr. 1, S. 150-182
- [4] Kretzschmar, H.-J.; Stöcker, I.; Klinger, J.; Dittmann, A.:  
Calculation of Thermodynamic Derivatives for Water and Steam Using the New Industrial Formulation IAPWS-IF97.  
in: Steam, Water and Hydrothermal Systems: Physics and Chemistry Meeting the Needs of Industry, Proceedings of the 13th International Conference on the Properties of Water and Steam, Eds. P.G. Hill et al., NRC Press, Ottawa, 2000
- [5] Kretzschmar, H.-J.:  
Mollier h,s-Diagramm.  
Springer-Verlag, Berlin (1998)
- [6] Revised Release on the IAPS Formulation 1985 for the Thermal Conductivity of Ordinary Water Substance.  
IAPWS Sekretariat, Dooley, B., EPRI, Palo Alto CA, (1997)
- [7] Revised Release on the IAPS Formulation 1985 for the Viscosity of Ordinary Water Substance.  
IAPWS Sekretariat, Dooley, B., EPRI, Palo Alto CA, (1997)
- [8] IAPWS Release on Surface Tension of Ordinary Water Substance 1994.  
IAPWS Sekretariat, Dooley, B., EPRI, Palo Alto CA, (1994)
- [9] Kretzschmar, H.-J.; Stöcker, I.; Willkommen, Th.; Trübenbach, J.; Dittmann, A.:  
Supplementary Equations  $v(p, T)$  for the Critical Region to the New Industrial Formulation IAPWS-IF97 for Water and Steam.  
in: Steam, Water and Hydrothermal Systems: Physics and Chemistry Meeting the Needs of Industry, Proceedings of the 13th International Conference on the Properties of Water and Steam, Eds. P.G. Hill et al., NRC Press, Ottawa, 2000
- [10] Kretzschmar, H.-J.; Cooper, J.R.; Dittmann, A.; Friend, D.G.; Gallagher, J.; Knobloch, K.; Mareš, R.; Miyagawa, K.; Stöcker, I.; Trübenbach, J.; Willkommen, Th.:  
Supplementary Backward Equations for Pressure as a Function of Enthalpy and Entropy  $p(h, s)$  to the Industrial Formulation IAPWS-IF97 for Water and Steam.  
ASME Journal of Engineering for Gas Turbines and Power - in preparation
- [11] Release on the IAPWS Formulation 1995 for the Thermodynamic Properties of Ordinary Water Substance for General and Scientific Use.  
IAPWS Sekretariat, Dooley, B., EPRI, Palo Alto CA, (1995)

- [12] Grigull, U.:  
Properties of Water and Steam in SI Units.  
Springer-Verlag, Berlin (1989)
- [13] Kretzschmar, H.-J.:  
Zur Aufbereitung und Darbietung thermophysikalischer Stoffdaten für die  
Energietechnik.  
Habilitation, TU Dresden, Fakultät Maschinenwesen (1990)
- [14] VDI Richtlinie 4670  
Thermodynamische Stoffwerte von feuchter Luft und Verbrennungsgasen.  
VDI-Handbuch Energietechnik (2000)
- [15] Lemmon, E. W.; Jacobsen, R. T.; Penoncello, S. G.; Friend, D. G.:  
Thermodynamic Properties of Air and Mixtures of Nitrogen, Argon and Oxygen from  
60 to 2000 K at Pressures to 2000 MPa.  
Journal of Physical Chemical Reference Data 29 (2000) Nr. 3, S. 331-385
- [16] Baehr, H.D.; Tillner- Roth, R.:  
Thermodynamische Eigenschaften umweltverträglicher Kältemittel,  
Zustandsgleichungen und Tafeln für Ammoniak, R22, R134a, R152a und R 123.  
Springer-Verlag, Berlin Heidelberg (1995)
- [17] Fenghour, A.; Wakeham, W. A.; Vesovic, V.; Watson, J. T. R.; Millat, J.; Vogel, E.:  
The Viskosity of Ammonia.  
J. Phys. Chem. Ref. Data, 24, (1995) Nr. 5, S. 1649-1667
- [18] Tufeu, R.; Ivanov, D. Y.; Garrabos, Y.; Le Neindre, B.:  
Thermal Conductivity of Ammonia in a Large Temperature and Pressure Range  
Including the Critical Region.  
Ber. Bunsenges. Phys. Chem. 88 (1984) S. 422-427
- [19] Span, R.; Wagner W.:  
A New Equation of State for Carbon Dioxide Covering the Fluid Region from the Triple-  
Point Temperature to 1100 K at Pressures up to 800 MPa.  
J. Phys. Chem. Ref. Data, 25, (1996) Nr. 6, S. 1506-1596
- [20] Vesovic, V.; Wakeham, W. A.; Olchowy, G. A.; Sengers, J. V.; Watson, J. T. R.;  
Millat, J.:  
The Transport Properties of Carbon Dioxide.  
J. Phys. Chem. Ref. Data, 19, (1990) Nr. 3, S. 763-808
- [21] Bläser, A.:  
Diplomarbeit: Berechnung der thermodynamischen Stoffeigenschaften von Ammoniak  
in energietechnischen Prozessmodellierungen  
Hochschule Zittau/Görlitz, 2003
- [22] Laesecke, A.:  
Unpublished 1998 correlation R134aFitSelDV
- [23] Perkins, R.A., Laesecke, A., Howley, J., Ramires, M.L.V., Gurova, A.N., Cusco, L.:  
Experimental thermal conductivity values for the IUPAC round-robin sample of 1,1,1,2-  
tetrafluoroethane (R134a)", NISTIR, 2000.

## 6. Satisfied Customers

Date: 10/2011

The following companies and institutions use the property libraries

- FluidEXL *Graphics* for Excel®
- FluidLAB for MATLAB®
- FluidMAT for Mathcad®
- FluidEES for Engineering Equation Solver® EES
- FluidDYM for Dymola® (Modelica)
- FluidVIEW for LabVIEW®:

### 2011

Lopez, Munguia, Spain	10/2011
University of KwaZulu-Natal, Westville, South Africa	10/2011
Voith, Heidenheim	09/2011
SpgBe Montreal, Canada	09/2011
SPG TECH, Montreuil Cedex, France	09/2011
Voith, Heidenheim-Mergelstetten	09/2011
MTU Aero Engines, Munich	08/2011
MIBRAG, Zeitz	08/2011
RWE, Essen	07/2011
Fels, Elingerode	07/2011
Weihenstephan University of Applied Sciences	07/2011, 09/2011, 10/2011
Forschungszentrum Juelich	07/2011
RWTH Aachen University	07/2011, 08/2011
Voith, Zschopau	07/2011
INNEO Solutions, Ellwangen	06/2011
Caliqua, Basel, Switzerland	06/2011
Technical University of Freiberg	06/2011
Fichtner IT Consulting, Stuttgart	05/2011, 06/2011, 08/2011
Salzgitter Flachstahl, Salzgitter	05/2011
Helbling Beratung & Bauplanung, Zurich, Switzerland	05/2011
INEOS, Cologne	04/2011
Enseleit Consulting Engineers, Siebigerode	04/2011

Witt Consulting Engineers, Stade	03/2011
Helbling, Zurich, Switzerland	03/2011
MAN Diesel, Copenhagen, Denmark	03/2011
AGO, Kulmbach	03/2011
University of Duisburg	03/2011, 06/2011
CCP, Marburg	03/2011
BASF, Ludwigshafen	02/2011
ALSTOM Power, Baden, Switzerland	02/2011
Universität der Bundeswehr, Munich	02/2011
Calorifer, Elgg, Switzerland	01/2011
STRABAG, Vienna, Austria	01/2011
TUEV Sued, Munich	01/2011
ILK Dresden	01/2011
Technical University of Dresden	01/2011, 05/2011, 06/2011, 08/2011

## 2010

Umweltinstitut Neumarkt	12/2010
YIT Austria, Vienna, Austria	12/2010
MCI Innsbruck, Austria	12/2010
University of Stuttgart	12/2010
HS Cooler, Wittenburg	12/2010
Visteon, Novi Jicin, Czech Republic	12/2010
CompuWave, Brunntal	12/2010
Stadtwerke Leipzig	12/2010
MCI Innsbruck, Austria	12/2010
EVONIK Energy Services, Zwingenberg	12/2010
Caliqua, Basel, Switzerland	11/2010
Shanghai New Energy Resources Science & Technology, China	11/2010
Energieversorgung Halle	11/2010
Hochschule für Technik Stuttgart, University of Applied Sciences	11/2010
Steinmueller, Berlin	11/2010
Amberg-Weiden University of Applied Sciences	11/2010
AREVA NP, Erlangen	10/2010
MAN Diesel, Augsburg	10/2010
KRONES, Neutraubling	10/2010

Vaillant, Remscheid	10/2010
PC Ware, Leipzig	10/2010
Schubert Consulting Engineers, Weißenberg	10/2010
Fraunhofer Institut UMSICHT, Oberhausen	10/2010
Behringer Consulting Engineers, Tagmersheim	09/2010
Saacke, Bremen	09/2010
WEBASTO, Neubrandenburg	09/2010
Concordia University, Montreal, Canada	09/2010
Compañía Eléctrica de Sochagota, Bogota, Colombia	08/2010
Hannover University of Applied Sciences	08/2010
ERGION, Mannheim	07/2010
Fichtner IT Consulting, Stuttgart	07/2010
TF Design, Matieland, South Africa	07/2010
MCE, Berlin	07/2010, 12/2010
IPM, Zittau/Goerlitz University of Applied Sciences	06/2010
TUEV Sued, Dresden	06/2010
RWE IT, Essen	06/2010
Glen Dimplex, Kulmbach	05/2010, 07/2010 10/2010
Hot Rock, Karlsruhe	05/2010
Darmstadt University of Applied Sciences	05/2010
Voith, Heidenheim	04/2010
CombTec, Zittau	04/2010
University of Glasgow, Great Britain	04/2010
Universitaet der Bundeswehr, Munich	04/2010
Technical University of Hamburg-Harburg	04/2010
Vattenfall Europe, Berlin	04/2010
HUBER Consulting Engineers, Berching	04/2010
VER, Dresden	04/2010
CCP, Marburg	03/2010
Offenburg University of Applied Sciences	03/2010
Technical University of Berlin	03/2010
NIST Boulder CO, USA	03/2010
Technical University of Dresden	02/2010
Siemens Energy, Nuremberg	02/2010

Augsburg University of Applied Sciences	02/2010
ALSTOM Power, Baden, Switzerland	02/2010, 05/2010
MIT Massachusetts Institute of Technology Cambridge MA, USA	02/2010
Wieland Werke, Ulm	01/2010
Siemens Energy, Goerlitz	01/2010, 12/2010
Technical University of Freiberg	01/2010
ILK, Dresden	01/2010, 12/2010
Fischer-Uhrig Consulting Engineers, Berlin	01/2010

## 2009

ALSTOM Power, Baden, Schweiz	01/2009, 03/2009, 05/2009
Nordostschweizerische Kraftwerke AG, Doettingen, Switzerland	02/2009
RWE, Neurath	02/2009
Brandenburg University of Technology, Cottbus	02/2009
Hamburg University of Applied Sciences	02/2009
Kehrein, Moers	03/2009
EPP Software, Marburg	03/2009
Bernd Munstermann, Telgte	03/2009
Suedzucker, Zeitz	03/2009
CPP, Marburg	03/2009
Gelsenkirchen University of Applied Sciences	04/2009
Regensburg University of Applied Sciences	05/2009
Gatley & Associates, Atlanta, USA	05/2009
BOSCH, Stuttgart	06/2009, 07/2009
Dr. Nickolay, Consulting Engineers, Gommersheim	06/2009
Ferrostal Power, Saarlouis	06/2009
BHR Bilfinger, Essen	06/2009
Intraserv, Wiesbaden	06/2009
Lausitz University of Applied Sciences, Senftenberg	06/2009
Nuernberg University of Applied Sciences	06/2009
Technical University of Berlin	06/2009
Fraunhofer Institut UMSICHT, Oberhausen	07/2009
Bischoff, Aurich	07/2009
Fichtner IT Consulting, Stuttgart	07/2009
Techsoft, Linz, Austria	08/2009

DLR, Stuttgart	08/2009
Wienstrom, Vienna, Austria	08/2009
RWTH Aachen University	09/2009
Vattenfall, Hamburg	10/2009
AIC, Chemnitz	10/2009
Midiplan, Bietigheim-Bissingen	11/2009
Institute of Air Handling and Refrigeration ILK, Dresden	11/2009
FZD, Rossendorf	11/2009
Techgroup, Ratingen	11/2009
Robert Sack, Heidelberg	11/2009
EC, Heidelberg	11/2009
MCI, Innsbruck, Austria	12/2009
Saacke, Bremen	12/2009
ENERKO, Aldenhoven	12/2009
<b>2008</b>	
Pink, Langenwang	01/2008
Fischer-Uhrig, Berlin	01/2008
University of Karlsruhe	01/2008
MAAG, Kuesnacht, Switzerland	02/2008
M&M Turbine Technology, Bielefeld	02/2008
Lentjes, Ratingen	03/2008
Siemens Power Generation, Goerlitz	04/2008
Evonik, Zwingenberg (general EBSILON program license)	04/2008
WEBASTO, Neubrandenburg	04/2008
CFC Solutions, Munich	04/2008
RWE IT, Essen	04/2008
Rerum Cognitio, Zwickau	04/2008, 05/2008
ARUP, Berlin	05/2008
Research Center, Karlsruhe	07/2008
AWECO, Neukirch	07/2008
Technical University of Dresden, Professorship of Building Services	07/2008
Technical University of Cottbus, Chair in Power Plant Engineering	07/2008, 10/2008
Ingersoll-Rand, Unicov, Czech Republic	08/2008
Technip Benelux BV, Zoetermeer, Netherlands	08/2008

Fennovoima Oy, Helsinki, Finland	08/2008
Fichtner Consulting & IT, Stuttgart	09/2008
PEU, Espenhain	09/2008
Poyry, Dresden	09/2008
WINGAS, Kassel	09/2008
TUEV Sued, Dresden	10/2008
Technical University of Dresden, Professorship of Thermic Energy Machines and Plants	10/2008, 11/2008
AWTEC, Zurich, Switzerland	11/2008
Siemens Power Generation, Erlangen	12/2008

## 2007

Audi, Ingolstadt	02/2007
ANO Abfallbehandlung Nord, Bremen	02/2007
TUEV NORD SysTec, Hamburg	02/2007
VER, Dresden	02/2007
Technical University of Dresden, Chair in Jet Propulsion Systems	02/2007
Redacom, Nidau, Switzerland	02/2007
Universität der Bundeswehr, Munich	02/2007
Maxxtec, Sinsheim	03/2007
University of Rostock, Chair in Technical Thermodynamics	03/2007
AGO, Kulmbach	03/2007
University of Stuttgart, Chair in Aviation Propulsions	03/2007
Siemens Power Generation, Duisburg	03/2007
ENTHAL Haustechnik, Rees	05/2007
AWECO, Neukirch	05/2007
ALSTOM, Rugby, Great Britain	06/2007
SAAS, Possendorf	06/2007
Grenzebach BSH, Bad Hersfeld	06/2007
Reichel Engineering, Haan	06/2007
Technical University of Cottbus, Chair in Power Plant Engineering	06/2007
Voith Paper Air Systems, Bayreuth	06/2007
Egger Holzwerkstoffe, Wismar	06/2007
Tissue Europe Technologie, Mannheim	06/2007
Dometic, Siegen	07/2007
RWTH Aachen University, Institute for Electrophysics	09/2007



National Energy Technology Laboratory, Pittsburg, USA	10/2007
Energieversorgung Halle	10/2007
AL-KO, Jettingen	10/2007
Grenzebach BSH, Bad Hersfeld	10/2007
Wiesbaden University of Applied Sciences, Department of Engineering Sciences	10/2007
Endress+Hauser Messtechnik, Hannover	11/2007
Munich University of Applied Sciences, Department of Mechanical Engineering	11/2007
Rerum Cognitio, Zwickau	12/2007
Siemens Power Generation, Erlangen	11/2007
University of Rostock, Chair in Technical Thermodynamics	11/2007, 12/2007

## 2006

STORA ENSO Sachsen, Eilenburg	01/2006
Technical University of Munich, Chair in Energy Systems	01/2006
NUTEC Engineering, Bisikon, Switzerland	01/2006, 04/2006
Conwel eco, Bochoy, Czech Republic	01/2006
Offenburg University of Applied Sciences	01/2006
KOCH Transporttechnik, Wadgassen	01/2006
BEG Bremerhavener Entsorgungsgesellschaft	02/2006
Deggendorf University of Applied Sciences, Department of Mechanical Engineering and Mechatronics	02/2006
University of Stuttgart, Department of Thermal Fluid Flow Engines	02/2006
Technical University of Munich, Chair in Apparatus and Plant Engineering	02/2006
Energietechnik Leipzig (company license),	02/2006
Siemens Power Generation, Erlangen	02/2006, 03/2006
RWE Power, Essen	03/2006
WAETAS, Pobershau	04/2006
Siemens Power Generation, Goerlitz	04/2006
Technical University of Braunschweig, Department of Thermodynamics	04/2006
EnviCon & Plant Engineering, Nuremberg	04/2006
Brassel Engineering, Dresden	05/2006
University of Halle-Merseburg, Department of USET Merseburg incorporated society	05/2006

Technical University of Dresden, Professorship of Thermic Energy Machines and Plants	05/2006
Fichtner Consulting & IT Stuttgart (company licenses and distribution)	05/2006
Suedzucker, Ochsenfurt	06/2006
M&M Turbine Technology, Bielefeld	06/2006
Feistel Engineering, Volkach	07/2006
ThyssenKrupp Marine Systems, Kiel	07/2006
Caliqua, Basel, Switzerland (company license)	09/2006
Atlas-Stord, Rodovre, Denmark	09/2006
Konstanz University of Applied Sciences, Course of Studies Construction and Development	10/2006
Siemens Power Generation, Duisburg	10/2006
Hannover University of Applied Sciences, Department of Mechanical Engineering	10/2006
Siemens Power Generation, Berlin	11/2006
Zikesch Armaturentechnik, Essen	11/2006
Wismar University of Applied Sciences, Seafaring Department	11/2006
BASF, Schwarzheide	12/2006
Enertech Energie und Technik, Radebeul	12/2006

## 2005

TUEV Nord, Hannover	01/2005
J.H.K Plant Engineering and Service, Bremerhaven	01/2005
Electrowatt-EKONO, Zurich, Switzerland	01/2005
FCIT, Stuttgart	01/2005
Energietechnik Leipzig (company license)	02/2005, 04/2005, 07/2005
eta Energieberatung, Pfaffenhofen	02/2005
FZR Forschungszentrum, Rossendorf/Dresden	04/2005
University of Saarbruecken	04/2005
Technical University of Dresden Professorship of Thermic Energy Machines and Plants	04/2005
Grenzebach BSH, Bad Hersfeld	04/2005
TUEV Nord, Hamburg	04/2005
Technical University of Dresden, Waste Management	05/2005
Siemens Power Generation, Goerlitz	05/2005

Duesseldorf University of Applied Sciences, Department of Mechanical Engineering and Process Engineering	05/2005
Redacom, Nidau, Switzerland	06/2005
Dumas Verfahrenstechnik, Hofheim	06/2005
Alensys Engineering, Erkner	07/2005
Stadtwerke Leipzig	07/2005
SaarEnergie, Saarbruecken	07/2005
ALSTOM ITC, Rugby, Great Britain	08/2005
Technical University of Cottbus, Chair in Power Plant Engineering	08/2005
Vattenfall Europe, Berlin (group license)	08/2005
Technical University of Berlin	10/2005
Basel University of Applied Sciences, Department of Mechanical Engineering, Switzerland	10/2005
Midiplan, Bietigheim-Bissingen	11/2005
Technical University of Freiberg, Chair in Hydrogeology	11/2005
STORA ENSO Sachsen, Eilenburg	12/2005
Energieversorgung Halle (company license)	12/2005
KEMA IEV, Dresden	12/2005
<b>2004</b>	
Vattenfall Europe (group license)	01/2004
TUEV Nord, Hamburg	01/2004
University of Stuttgart, Institute of Thermodynamics and Heat Engineering	02/2004
MAN B&W Diesel A/S, Copenhagen, Denmark	02/2004
Siemens AG Power Generation, Erlangen	02/2004
Ulm University of Applied Sciences	03/2004
Visteon, Kerpen	03/2004, 10/2004
Technical University of Dresden, Professorship of Thermic Energy Machines and Plants	04/2004
Rerum Cognitio, Zwickau	04/2004
University of Saarbruecken	04/2004
Grenzebach BSH, Bad Hersfeld	04/2004
SOFBID Zwingenberg (general EBSILON program license)	04/2004
EnBW Energy Solutions, Stuttgart	05/2004
HEW-Kraftwerk, Tiefstack	06/2004
h s energieanlagen, Freising	07/2004
FCIT, Stuttgart	08/2004

Physikalisch Technische Bundesanstalt (PTB), Braunschweig	08/2004
Mainova Frankfurt	08/2004
Rietschle Energieplaner, Winterthur, Switzerland	08/2004
MAN Turbo Machines, Oberhausen	09/2004
TUEV Sued, Dresden	10/2004
STEAG Kraftwerk, Herne	10/2004, 12/2004
University of Weimar	10/2004
energeticals (e-concept), Munich	11/2004
SorTech, Halle	11/2004
Enertech EUT, Radebeul (company license)	11/2004
Munich University of Applied Sciences	12/2004
STORA ENSO Sachsen, Eilenburg	12/2004
Technical University of Cottbus, Chair in Power Plant Engineering	12/2004
Freudenberg Service, Weinheim	12/2004

## 2003

Paper Factory, Utzenstorf, Switzerland	01/2003
MAB Plant Engineering, Vienna, Austria	01/2003
Wulff Energy Systems, Husum	01/2003
Technip Benelux BV, Zoetermeer, Netherlands	01/2003
ALSTOM Power, Baden, Switzerland	01/2003, 07/2003
VER, Dresden	02/2003
Rietschle Energieplaner, Winterthur, Switzerland	02/2003
DLR, Leupholdhausen	04/2003
Emden University of Applied Sciences, Department of Technology	05/2003
Petterssson+Ahrends, Ober-Moerlen	05/2003
SOFBID ,Zwingenberg (general EBSILON program license)	05/2003
Ingenieurbuero Ostendorf, Gummersbach	05/2003
TUEV Nord, Hamburg	06/2003
Muenstermann GmbH, Telgte-Westbevern	06/2003
University of Cali, Colombia	07/2003
Atlas-Stord, Rodovre, Denmark	08/2003
ENERKO, Aldenhoven	08/2003
STEAG RKB, Leuna	08/2003
eta Energieberatung, Pfaffenhofen	08/2003
exergie, Dresden	09/2003

AWTEC, Zurich, Switzerland	09/2003
Energie, Timelkam, Austria	09/2003
Electrowatt-EKONO, Zurich, Switzerland	09/2003
LG, Annaberg-Buchholz	10/2003
FZR Forschungszentrum, Rossendorf/Dresden	10/2003
EnviCon & Plant Engineering, Nuremberg	11/2003
Visteon, Kerpen	11/2003
VEO Vulkan Energiewirtschaft Oderbruecke, Eisenhuettenstadt	11/2003
Stadtwerke Hannover	11/2003
SaarEnergie, Saarbruecken	11/2003
Fraunhofer-Gesellschaft, Munich	12/2003
Erfurt University of Applied Sciences, Department of Supply Engineering	12/2003
SorTech, Freiburg	12/2003
Mainova, Frankfurt	12/2003
Energieversorgung Halle	12/2003
<b>2002</b>	
Hamilton Medical AG, Rhaezuens, Switzerland	01/2002
Bochum University of Applied Sciences, Department of Thermo- and Fluid Dynamics	01/2002
SAAS, Possendorf/Dresden	02/2002
Siemens, Karlsruhe (general license for the WinIS information system)	02/2002
FZR Forschungszentrum, Rossendorf/Dresden	03/2002
CompAir, Simmern	03/2002
GKS Gemeinschaftskraftwerk, Schweinfurt	04/2002
ALSTOM Power Baden, Switzerland (group licenses)	05/2002
InfraServ, Gendorf	05/2002
SoftSolutions, Muehlhausen (company license)	05/2002
DREWAG, Dresden (company license)	05/2002
SOFBID, Zwingenberg (general EBSILON program license)	06/2002
Kleemann Engineering, Dresden	06/2002
Caliqua, Basel, Switzerland (company license)	07/2002
PCK Raffinerie, Schwedt (group license)	07/2002
Fischer-Uhrig Engineering, Berlin	08/2002

Fichtner Consulting & IT, Stuttgart (company licenses and distribution)	08/2002
Stadtwerke Duisburg	08/2002
Stadtwerke Hannover	09/2002
Siemens Power Generation, Goerlitz	10/2002
Energieversorgung Halle (company license)	10/2002
Bayer, Leverkusen	11/2002
Dillinger Huette, Dillingen	11/2002
G.U.N.T. Geraetebau, Barsbuettel (general license and training test benches)	12/2002
VEAG, Berlin (group license)	12/2002

**2001**

ALSTOM Power, Baden, Switzerland	01/2001, 06/2001, 12/2001
KW2 B. V., Amersfoot, Netherlands	01/2001, 11/2001
Eco Design, Saitamaken, Japan	01/2001
M&M Turbine Technology, Bielefeld	01/2001, 09/2001
MVV Energie, Mannheim	02/2001
Technical University of Dresden, Department of Power Machinery and Plants	02/2001
PREUSSAG NOELL, Wuerzburg	03/2001
Fichtner Consulting & IT Stuttgart (company licenses and distribution)	04/2001
Muenstermann GmbH, Telgte-Westbevern	05/2001
SaarEnergie, Saarbruecken	05/2001
Siemens, Karlsruhe (general license for the WinIS information system)	08/2001
Neusiedler AG, Ulmerfeld, Austria	09/2001
h s energieranlagen, Freising	09/2001
Electrowatt-EKONO, Zurich, Switzerland	09/2001
IPM Zittau/Goerlitz University of Applied Sciences (general license)	10/2001
eta Energieberatung, Pfaffenhofen	11/2001
ALSTOM Power Baden, Switzerland	12/2001
VEAG, Berlin (group license)	12/2001

**2000**

SOFBID, Zwingenberg (general EBSILON program license)	01/2000
AG KKK - PGW Turbo, Leipzig	01/2000

PREUSSAG NOELL, Wuerzburg	01/2000
M&M Turbine Technology, Bielefeld	01/2000
IBR Engineering Reis, Nittendorf-Undorf	02/2000
GK, Hannover	03/2000
KRUPP-UHDE, Dortmund (company license)	03/2000
UMAG W. UDE, Husum	03/2000
VEAG, Berlin (group license)	03/2000
Thinius Engineering, Erkrath	04/2000
SaarEnergie, Saarbruecken	05/2000, 08/2000
DVO Data Processing Service, Oberhausen	05/2000
RWTH Aachen University	06/2000
VAUP Process Automation, Landau	08/2000
Knuerr-Lommatec, Lommatzsch	09/2000
AVACON, Helmstedt	10/2000
Compania Electrica, Bogota, Colombia	10/2000
G.U.N.T. Geraetebau, Barsbuettel (general license for training test benches)	11/2000
Steinhaus Informationssysteme, Datteln (general license for process data software)	12/2000
<b>1999</b>	
Bayernwerk, Munich	01/1999
DREWAG, Dresden (company license)	02/1999
KEMA IEV, Dresden	03/1999
Regensburg University of Applied Sciences	04/1999
Fichtner Consulting & IT, Stuttgart (company licenses and distribution)	07/1999
Technical University of Cottbus, Chair in Power Plant Engineering	07/1999
Technical University of Graz, Department of Thermal Engineering, Austria	11/1999
Ostendorf Engineering, Gummersbach	12/1999
<b>1998</b>	
Technical University of Cottbus, Chair in Power Plant Engineering	05/1998
Fichtner Consulting & IT (CADIS information systems) Stuttgart (general KPRO program license)	05/1998
M&M Turbine Technology Bielefeld	06/1998
B+H Software Engineering Stuttgart	08/1998
Alfa Engineering, Switzerland	09/1998

VEAG Berlin (group license)	09/1998
NUTEC Engineering, Bisikon, Switzerland	10/1998
SCA Hygiene Products, Munich	10/1998
RWE Energie, Neurath	10/1998
Wilhelmshaven University of Applied Sciences	10/1998
BASF, Ludwigshafen (group license)	11/1998
Energieversorgung, Offenbach	11/1998

**1997**

Gerb, Dresden	06/1997
Siemens Power Generation, Goerlitz	07/1997