DENNISON STATIONERY PRODUCTS COMPANY -- CARTER'S RUBBER CEMENT -- 8040-00-262-9040

Product ID:CARTER'S RUBBER CEMENT MSDS Date:07/19/1988 FSC:8040 NIIN:00-262-9040 MSDS Number: BHDFB === Responsible Party === Company Name: DENNISON STATIONERY PRODUCTS COMPANY Address:300 HOWARD STREET City: FRAMINGHAM State:MA ZIP:01701 Country:US Emergency Phone Num: 508-879-0511 X4636 CAGE:HO918 === Contractor Identification === Company Name: DENNISON STATIONARY PRODUCTS CO Address:300 HOWARD STREET Box:City:FARMINGTON State:MA ZIP:01701 Country:US Phone: 508-879-0511 CAGE:H0918 Ingred Name:SOLVENT NAPTHA CAS:67472-89-8 Fraction by Wt: 88.6% Other REC Limits:400 PPM Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: OVEREXPOSURE CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION PRODUCING HEADACHES, DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS. Effects of Overexposure: HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS. Medical Cond Aggravated by Exposure:SKIN DISEASE, CHRONIC RESPIRATORY DISEASE First Aid:EYES: FLUSH WITH WATER, CALL PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. RESTOREBREATHING. CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. LAUNDER CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTI ON. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION. Flash Point Method:TCC

Flash Point: < 10F/-24C Lower Limits:7.0 Upper Limits:1.1 Extinguishing Media:CO2, FOAM, DRY CHEMICAL, WATER FOG OR SPRAY Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING INCLUDING NIOSH SELF-CONTAINED BREATHING APPARATUSCOOL EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: IN CASE OF LARGE FIRES, ALSO COOL SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER. DO NOT MIX WITH STRONG OXIDANTS. Spill Release Procedures: AVOID OPEN FLAMES OR SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. ADD ABSORBANT (SAWDUST, SANDETC.) TO SPILL AREA. TO AVOID SPILLING, DEEP CAP TIGHTLY CLOSED WHEN NOT USING. Handling and Storage Precautions: AVOID OPEN FLAMES, SPARK SOURCES, SPLASH SPILLING, EXCESSIVE HEAT. KEEP CONTAINERS CLOSED WHEN NOT USING. Other Precautions: CAREFULLY READ ALL DIRECTIONS AND CAUTIONS ON PRODUCT CONTAINER. ====== Exposure Controls/Personal Protection ========== Ventilation:LOCAL EXHAUST IF NEEDED TO CONTROL VAPOR. MECHANICAL (GEN) VENTILATION EXPLOSION PROOF EQUIPMENT. Protective Gloves: PVA OR NITRILE RUBBER Eve Protection: SAFETY GLASSES/GOGGLES Work Hygienic Practices: WASH HANDS BEFORE EATING, DO NOT SMOKE OR USE NEAR OPEN FLAME. Supplemental Safety and Health NK Boiling Pt:B.P. Text:151 - 225F Vapor Pres:250 @ 100F Vapor Density:3.3 Spec Gravity:.72 Evaporation Rate & Reference: 5.8 (BUTYL ACETATE = 1) Solubility in Water:NEGLIGIBLE Appearance and Odor: BUFF COLOR LIQUID WITH HYDROCARBON ODOR. Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS LIKE CHLORINE Stability Condition to Avoid: HEAT, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products: CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION. Waste Disposal Methods: EVAPORATE AND PEEL RESIDUE FROM SURFACE. TREAT AS HYDROCARBON. Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.