ADVE NT SPECIFICATION SHEET


REO INTERIOR WALL

JOB NAME



Reo can be mounted to any wall surface and comply with ADA requirements while providing supplemental side illumination. Five optional color gels add a splash of color, serving as a guide or visual path. The ability to complement any style comes standard.

ADA



Dimensions

W	Н	D	MC	
13.0 in	52.0 in	3.7 in	26.0 in	
330 mm	1321 mm	94 mm	660 mm	

Weight

Hanging weight: 25.0 lb (11.4 kg).

Features

- Integral Class II power supply included, eliminating the need for remote mounting, simplifying installation.
- Formed metal construction provides durable protection for internal components and is recyclable.
- Embossed stainless steel-linear and crosshatch face plate option adds a unique, metal accent and texture to a space.
- Durable wood laminate faceplate option adds a warm, natural texture to a space.
- Fixture adds a splash of color to a space with theatrical color gels. Standard colors are available with other colors available upon request. Contact factory to customize a color gel that coordinates with your application.
- Standard thermoset polyester powder coat paint provides durable protection in a palette of color options. Custom colors available upon request.
- Compliant with Americans with Disabilities Act (ADA) requirements.

Technical Notes

Electrical

- Fluorescent versions have integral electronic ballasts utilizing the latest energy-saving technology, providing prolonged lamp life and maintaining consistent color.
- Advent uses strict quality guidelines in LED selection to ensure the white LED's we use meet or exceed ANSI Binning Standards (ANSI C78.733).
- Thermally protected ballast limits operating temperature.
- Class "A" sound rated ballast for use in low ambient noise applications.
- Meets NEC 410.73 double-ended, fluorescent lamp ballast disconnect requirements.
- ETL listed to UL standards (US and Canada) for use in damp locations. Not recommended for exterior applications.

Lamping/lamp

- L70 life= 50,000+ hours.
- Fluorescent lamps are 3500K unless specified.

- Lamps included, with the exception of T8, T5 and incandescent.
- Mounting
- Mounts to standard 4" octagonal junction box.
- Additional mounting structure and hardware required (by others).

Additional Documents

Color Chart (http://www.specAdvent.com/pdfs/advent_color_chart.pdf)

ADVENT SPECIFICATION SHEET

Blue Color Gel

CG04

MODEL NUMBER	LIGHT SOURCE	FINISH	VOLTAGE	LAMP OPTIONS	OPTIONS	COLOR ACCENTS

Not all options are available in all configurations, consult factory for details.

Light Source			Photometry	Voltage		Options		
L50.2W		White 50.2W 3.2W/6" LED Light Engine	52IN REC	120-277V	Universal Voltage	ES1	Embossed Stainless Steel-linear	
		Delivered Lumens: 2,053	WS LED LOW	120V	120 Volt		Pattern	
L100.4W		White 100.4W 6.4W/6" LED Light Engine	52IN REC WS LED HIGH	277V 277 Volt		ES2	Embossed Stainless Steel-cross Hatch Pattern	
		Delivered Lumens: 4,106		Lamp Options		WF1	Cherry Laminate	
2F28	N ¹	2F28WT5/Mini Bipin	ITL59302	DML ²	0-10V Dimming	WF2	Maple Laminate	
	· · ·	•		3000K	3000K Cct	Color Accents		
2F28DM	<u> </u>	2F28WT5/Mini Bipin Dimming	ITL59302	3500K	3500K Cct		White Color Gel	
2F32	<u></u> № 1	2F32WT8/Med Bipin		4000K	4000K Cct	CG00		
2F54	$\tilde{\mathbf{N}}^1$	2F54WT5HO/Mini Bipin	ITL59302			CG01	Red Color Gel	
		•		EMI	Emergency Ballast Integral	CG02	Orange Color Gel	
2F54DM	 	2F54WT5HO/Mini Bipin Dimmming	ITL59302	EMR	Emergency Ballast Remote	CG03	Green Color Gel	

1 T5 & T8 Fluorescent Linear Lamp(s) Not Included 2 DML with LED light engine only.

Painted Finishes

PT01	SuperWhite	PT07	Light Taupe	PT13	Warm Gray	PT19	Blue	PT29	Red Brass	PT42	Sky Blue	PT48	Brass
PT02	White	PT08	Medium Taupe	PT14	Light Gray	PT20	Dark Green	PT31	Medium Bronze	PT43	Teal	PT49	Bronze
PT03	Morning Light	PT09	Medium Gray	PT15	Sage	PT21	Pearl White	PT32	Dark Bronze	PT44	Green		
PT04	Warm White	PT10	Dark Gray	PT16	Spruce	PT22	Platinum	PT33	Dark Blue	PT45	Purple		
PT05	Putty	PT11	Black	PT17	Red	PT27	Deep Copper	PT40	Yellow	PT46	Aluminum		
PT06	Warm Beige	PT12	Dark Chocolate	PT18	Deep Red	PT28	Dark Stainless	PT41	Orange	PT47	Deep Red Brass		

Metal and Plated Finishes

BAL Brushed Aluminum

Kit Details