Town of Harrisburg BACKFLOW PREVENTER TEST AND MAINTENANCE REPORT

CUSTOMER:ADDRESS OF PROPERTY: MAILING ADDRESS: METER MODEL & NUMBER:SERVICE NUMBER: TYPE OF SERVICE: DOM. [] IRRIG. [] F.L. [] COMBINATION (DOM. & F.L.) [] TYPE OF ASSEMBLY: RP [] DC [] PVB [] SIZE OF ASSEMBLY: MANUFACTURER: MODEL: SERIAL NO LOCATION OF ASSEMBLY: [] or Isolation (at branch): [] Line Pressure: PSI _(#10r #2 Test cock)				
CHECK VALVE #1	RELIEF VALVE	CHECK VALVE #2	PRESSURE VACUUM BREAKER	
SEAT[SPRING[STEM/GUIDE[RETAINER[LOCK NUTS[OTHER[OPENED AT PSID DID NOT OPEN [] BUFFERPSI []CLEANED ONLY REPLACED: RUBBER KIT [] RV ASSEMBLY[] OR DISC [] O-RINGS [] SEAT [] SPRING [] GUIDE [] DIAPHRAGM [] OTHER []	[] LEAKED [] CLOSED TIGHT DIFF. PRESSURE ACROSS CHECK VALVEPSID [] CLEANED ONLY REPLACED: RUBBER KIT [] CV ASSEMBLY [] OR DISC [] OR DISC [] OR DISC [] SEAT [] SFRING [] STEM/GUIDE [] RETAINER [] LOCK NUTS [] OTHER []	AIR INLET OPENED ATPSID DIDN'T OPEN [] CHECK VALVE: LEAKED [] HELD ATPSID []CLEANED ONLY REPLACED: RUBBER KIT [] CV ASSEMBLY [] DISC, AIR [] DISC, CV [] SPRING, AIR [] SPRING, CV [] RETAINER [] GUIDE [] O-RING [] OTHER []	
[] CLOSED TIGHT DIFF. PRESSURE ACROSS CHECK VALVE PSID	OPENED AT PSID BUFFERPSI	[] CLOSED TIGHT DIFF. PRESSURE ACROSS CHECK VALVE PSID	AIR INLETPSID CHECK VALVE PSID	
SHUT - OFF #1 SHUT-OFF#2 Leaked () Held Tight () Leaked () Held Tight () Assembly PASSED () OR FAILED () NOTE: ALL REPAIRS MUST BE COMPLETED WITHIN (10) DAYS. REMARKS:				

KIT: DIFF. [] DUPL. []	ELEC []	MANUFACTURER:		
MODEL: SERIAL NO.:				
I HEREBY CERTIFY THAT THIS DATA IS ACCURATE AND REFLECTS THE PROPER OPERATION AND MAINTENANCE				
OF THE ASSEMBLY. Mail to: Town of Harrisburg				
		P.O. Box 100		
TIME OF TEST:	DATE	: Harrisburg NC 28075		
		ATTN. Silas Bolen		
TESTER (Print Name):		CERT.NO. :		
	Phone:	(704) 455-4669 Fax: (704) 455-4681		