



# Single-Family Dwelling Erosion Control Affidavit



Bryce A. Stuart Municipal Building  
Suite 328  
100 E. First Street  
Winston-Salem, NC 27101  
P.O. Box 2511  
Winston-Salem, NC 27102-2511

Phone: 311 or (336) 747-7453  
Fax: (336) 727-2792

**This affidavit must be submitted at the time of the building permit application.**

Permit # \_\_\_\_\_ Date: \_\_\_\_\_

Job Site Address: \_\_\_\_\_

Subdivision: \_\_\_\_\_ Pin # \_\_\_\_\_ Block: \_\_\_\_\_ Lot: \_\_\_\_\_

General Contractor: \_\_\_\_\_

Address: \_\_\_\_\_

City/State/Zip: \_\_\_\_\_ Office Phone: \_\_\_\_\_

Mobile Phone: \_\_\_\_\_ Fax Number: \_\_\_\_\_ Email: \_\_\_\_\_

My signature hereto signifies I am the owner/financially responsible party for job site compliance with the Erosion and Sediment Control Ordinance as outlined in Article V of the Unified Development Ordinances (UDO). I hereby acknowledge that Best Management Practices must be used to control soil erosion on my job site to include but not be limited to the following:

1. Installation and regular maintenance of silt fencing using the preferred method of trenching installation on all low/down slope sides of my job site. Silt fence is to have an upslope return at each end no less than 5 feet; and
2. Installation and regular maintenance of a stone construction entrance. Stone construction entrance shall consist of a 2 inch to 3 inch coarse aggregate stone. Construction entrance shall be a minimum 6 inches in thickness, 12 foot wide and extend to the structure or a minimum of 50 feet in length; and
3. Removal of mud and sediment from the street or adjacent property(ies) immediately following such an occurrence; and
4. Conduct no land disturbing activity within 15 feet of the banks of streams, lakes, wetlands or other water course or water body; and
5. Provide temporary vegetation and/or mulch on any exposed areas to provide an effective barrier from erosion; and
6. Install any other measures as deemed necessary by the Erosion Control Inspections Program.
7. Beginning January 1, 2013, all sediment (silt) fence installation will be required to meet the minimum standards as specified in the NC Erosion and Sediment Control Planning and Design Manual Section 6.62 (link: [http://portal.ncdenr.org/c/document\\_library/get\\_file?uuid=aa69789b-4c3f-42ea-97fc-2f66a2ddd04f&groupId=38334](http://portal.ncdenr.org/c/document_library/get_file?uuid=aa69789b-4c3f-42ea-97fc-2f66a2ddd04f&groupId=38334)).

I understand that if the disturbed are for any reason becomes greater than 20,000 square feet, a formal Erosion Control Plan will be required to be submitted with proper fee for review, approval and permitting. I further acknowledge the City Inspection's staff may refuse to make building inspections and the Department of Stormwater/Erosion and Sedimentation Control may issue Notices of Violation, Stop Work Orders and/or Civil Penalties for failure to comply with Erosion Control Requirements.

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Print Name

\_\_\_\_\_  
Title

\_\_\_\_\_  
Date Signed