Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence number	011-7S1778 F
	Date of issue	08.10.212

Company holding the licence	Solarfocus GmbH	**Country**		Austria
Brand (optional)		**Website**		www.solarfocus.at
Street, number	Werkstrasse 1	**E-mail**		g.gleiss@solarfocus.at
Postal Code	A - 4451	**Tel.**	43	(0) 7252 / 50002-462
City	St.Ulrich/Steyr	**Fax**	+43	(0)7252 / 50 002-53

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	Yes

Collector name	Aperture area (Aa) [m²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (AG) [m²]	Power output per collector unit G = 1000 W/m² Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
CPC S1k	2,17	2.125	1.155	68	2,45	1.538	1.450	1.256	1.039	797

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0,70	-
	a_{1a}	3,88	W/(m²K)
	a_{2a}	0,0135	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	183	°C
Effective thermal capacity	c_{eff} = C/Aa	4,99	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	1000	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	max	θ_T / θ_L	50°	10°	20°	30°	40°	60°	70°
			$K_\theta(\theta_T)$	0,98	1,01	1,05	1,06	1,04	0,86	0,68
	0,1	0,2	$K_\theta(\theta_L)$	0,86	1,00	0.99	0,97	0,93	0,77	0,61
G_{DIF}/G_{TOT}: min&max - while measuring					***Optional values***					

Testing Laboratory	**ASi C - Austria Solar Innovation Center**
Website	www.asic.at
Test report id. number	P-201109001-PC; 2.04.00360.1.0-1 (AIT)
Date of test report	02.12.2011; 17.11.2006
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :

Note 1	**Fluid**	Water	**Flow rate**	0,056	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²; Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

VERSION 3.6, 2012.01.20

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence number	011-7S1778 F
	Issued	08.10.212

Annual collector output kWh

Collector name	Location and collector temperature (Tm)														
	Athens			Davos			Stockholm			Würzburg					
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
CPC S1k	2.435	1.649	1.003	1.931	1.255	722	1.336	830	469	1.451	889	494			

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO • Alboinstraße 56 • 12103 Berlin
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de.

Datasheet version:
VERSION 3.6, 2012.01.20
Calculation program version:
3.07, October 2011 (SP)