Technologies - No.55 Bench/Pedestal Grinder (List additional hazards, risks and controls particular to your school using the blank template no.69)

| Hazards | Is the hazard present? Y/N | What is the risk? | Risk rating H=High | | Is this control | Action/to do list/outstanding controls *Risk rating applies to outstanding | Person responsible | Signature and date |
|---------------------------|-------------------------------------|---|-----------------------|---|-----------------|---|-----------------------|-----------------------|
| | | | M = Medium L = Low | (When all controls are in place risk will be reduced). | in place? | controls outlined in this column | | completed |
| Contact with moving parts | | Laceration of fingers due to contact with moving parts | Н | Notice setting out the dangers arising from the use of grinding wheels and the precautions to be observed in relation to them is prominently displayed close to the grinder | | | | |
| | | | Н | Work rests fitted with a gap <3mm between the edge of the work rest and the wheel | | | | |
| | | | Н | Guard enclosing the grinding wheels and spindles, with an appropriate gap at the front to allow access to the work piece | | | | |
| | | | Н | The stop control is more prominent than the start control to facilitate ease and speed of access when it is necessary to turn off the machine | | | | |
| | | | Н | Machine is fitted with an emergency stop control (usually red domed mushroom type head on yellow housing) in an appropriate location, which is easily accessible in an emergency | | | | |
| | | | Н | The flap type emergency stop control (flap-stop is a normal start and stop contact, which is equipped with a yellow flap and red mushroom-type push buttons, covering both the start and stop contacts) is not acceptable where there is a need for an emergency stop | | | | |
| Disintegration of wheel | | Laceration of fingers, flying objects / debris from | M | Maximum speed of the spindle clearly marked on the machine | | | | |
| | | disintegrating grinding wheel | M | Maximum operating speed of a wheel should never be exceeded | | | | |
| | | | Н | Only persons trained in the fitting of grinding wheels are permitted to do so | | | | |

Technologies - No.55 Bench/Pedestal Grinder cont'd. (List additional hazards, risks and controls particular to your school using the blank template no.69)

| Hazards | Is the hazard present? Y/N | What is the risk? | Risk rating H=High M=Medium L=Low | Controls (When all controls are in place risk will be reduced). | Is this control in place? | Action/to do list/outstanding controls *Risk rating applies to outstanding controls outlined in this column | Person responsible | Signature and date completed |
|---|-------------------------------------|--|--|---|------------------------------------|--|-----------------------|------------------------------------|
| Contact by persons other than the operator with moving machinery | | Entanglement, pinching, amputtation of body parts | Н | Safe operational areas should be marked out clearly around machines | | | | |
| Direct contact with moving parts | | Cutters, blades abrasive wheels and sanding discs, contact with which can cause injuries | Н | Before use a visual check should be carried out to ensure where applicable all guards and covers are fitted, in good order and there are no visible faults | | | | |
| | | | н | Tools are used in compliance with manufacturers instructions | | | | |
| | | | Н | Dangling jewellery prohibited | | | | |
| | | | Н | Long hair is tied back | | | | |
| | | | M | Operators manual is available where required | | | | |
| Ejection of flying debris when grinding | | Eye injury | M | Eye screen is constructed, fastened to the fixed flange guard and appropriately adjusted so that the operator shall see the working part of the wheel only through the screen | | | | |
| | | | M | Suitable eye or face protection worn | | | | |
| Sparks from grinder | | Source of ignition leading to fire | Н | Ensure correct precautions are taken when using grinder including good housekeeping to prevent accumulation of any combustible material nearby | | | | |

Technologies - No.55 Bench/Pedestal Grinder cont'd. (List additional hazards, risks and controls particular to your school using the blank template no.69)

| Is this Action/to do list/outstanding controls Person Signature control responsible and date in *Risk rating applies to outstanding controls outlined in this column complete | control in | Controls (When all controls are in place risk will be reduced). | Risk rating H=High M=Medium L=Low | What is the risk? | Is the hazard present? Y/N | Hazards |
|---|---------------|---|--|--|-------------------------------------|---|
| | | Visual check carried out prior to use | Н | Electric shock/fire/ burns | | Electric shock, electrocution, burns, death |
| of | - | Machines are serviced by a competent person and service records kept as part of the maintenance schedule | Н | | | |
| ok | | Defective electrical equipment shall be clearly identified, labelled as out of use. Ensure all faults are recorded in log book. Ensure any previous faults have recieved attention. Report defects to person in control of workplace to ensure all items are repaired or replaced | н | | | |
| the ent rrect | | The operation of the RCD is checked by pressing the test button regularly and the RCD is tested periodically by a competent person to ensure that it operates at correct leakage current (leakage current not exceeding 30 mA in a time of not more than 0.3 seconds) | н | | | |
| | | Ensure cables are free from damage, do not have any non-standard joints or show any signs of overheating | Н | | | |
| | | Ensure cable and plug are in good condition | н | | | |
| | | Ensure equipment is disconnected or isolated when not in use | Н | | | |
| | | Machine securely fixed to the floor or bench and appropriate clamps in place to ensure that work pieces are secured, where applicable | н | Movement of machine or unsecured work piece leading to injury during use | | Unsecured machine / unsecured work piece |
| | | | | injury during use | | , |

Technologies - No.55 Bench/Pedestal Grinder cont'd. (List additional hazards, risks and controls particular to your school using the blank template no.69)

| Hazards | Is the hazard present? Y/N | What is the risk? | Risk rating H=High M=Medium L=Low | Controls (When all controls are in place risk will be reduced). | Is this control in place? | Action/to do list/outstanding controls *Risk rating applies to outstanding controls outlined in this column | Person responsible | Signature and date completed |
|------------------------------------|-------------------------------------|---|--|---|------------------------------------|--|-----------------------|------------------------------------|
| Unsupervised use of machines | | Unsupervised use leading to injury | Н | Pupils are prohibited from using certain machinery | | | | |
| | | to injury | Н | Pupils are instructed by teacher before using any machine | | | | |
| | | | Н | Pupils are supervised by teacher when using any machine | | | | |
| | | | Н | Machinery to be used by teachers only should be clearly identified | | | | |
| Noise | | Hearing damage | Н | Noise measurements carried out where necessary by a competent person | | | | |
| | | | Н | Warning signs are in place beside fixed noisy equipment and are visible | | | | |
| | | | Н | Hearing protection is worn where necessary | | | | |
| Inadequate signage | | Inadequate information and warnings leading to unsafe use of machine and injury | M | Warning signs are prominently located and maintained in good condition | | | | |
| Ingestion of contaminated material | | Poisoning or ill health | М | Food and drink are prohibited in working area | | | | |
| Contact with hazardous materials | | Exposure to hazardous materials | M | Personal hygiene is promoted (washing of hands, use of barrier creams etc.) | | | | |
| | | | | | | | | |

| If there is one or more High Risk (H) actions needed, then the risk of injury could be high and immediate action should be taken. Medium Risk (M) actions should be dealt with as soon as possible. Low Risk (L) actions should be dealt with as soon as practicable. | | | | | | | | | | |
|--|--|--|--|--|--|--|---|---|--|-----------------------|
| Risk Assessment carried out by: | | | | | | | / | 1 | | © All Rights Reserved |
| | | | | | | | | | | |