

IDAHO SCHOOLS POLE VAULT COMPLIANCE FACILITY CHECK LIST

1. Pole Vault Landing Area

- Width: 19'8" minimum beyond the back of standard bases
Reference Rule 7-5-7
- Length: 16'5" minimum from back of the box to the back of the pit
Reference Rule 7-5-7
- Uniform top pad must cover all selections
Reference Rule 7-5-7
- Maximum of 3" only is allowed between back of box and the pit
Reference Rule 7-5-8
- Minimum of 2" of padding must cover hard and unyielding surfaces around the pit including between the box and the pit
Reference Rule 7-5-14
- The front edge of the box cannot extend above the grade of the runway surface
Reference Rule 7-5-12
- All parts of Standard bases must be covered by protector pads
Reference Rule 7-5-9
- The width between the crossbar pegs should not be less than 13'8" or exceed 14'8"
Reference Rule 7-5-10

2. Vaulting Poles:

- All poles must have a maximum handhold band and a manufacturers weight label with 3/4" weight label numbers
Reference Rule 7-5-3
- Vaulters weight cannot exceed the test weight of the pole. Their weight should be at or less than the test weight of the pole
Reference Rule 7-5-3

3. Certified Coaches:

Our pole vault coaching staff has successfully completed the IHSAA pole vault safety course; or a similar recognized certification course. Please list the names and certification of you high school pole vault coaching staff.

1. _____	_____
(Print Name)	(Certification)
2. _____	_____
3. _____	_____
4. _____	_____

____XXX- We Do Not Have the Pole Vault

School: _____

School Administrator Signature _____ Date: _____

****This form must be completed and kept on file at the school prior to your schools first date of competition.**