

ShanghaiExceedingEnterprisesCo.,Ltd
 Address:No1608XinghuaRoadFengbangTownJiadingDistrictShanghai
 Tel:+86-021-59134085, +86-021-591331456--48, +86-021-59139113
 Fax:+86-021-59132333
<http://www.wdf-belt.com.cn/>

TUSILO/PU FORM



Suction and delivery hose suitable for powdery and granular dry food products.

DESCRIPTION

Tube	polyurethane, translucent. Meets FDA 21 CFR 177.2600
Reinforcement	synthetic plies, steel wire helices
Cover	smooth, green, abrasion resistant, ageing and ozone resistant, cloth finish
Sterilization	according to 3A Sanitary Standard Class III
Marking	TUDERTECHNICA TUSILO/PU FORM



TECHNICAL CHARACTERISTICS

Temperature range	-30°C / +100°C
Vacuum	0,8 bar
Norm	ISO 1307 for dimensional tolerances 3A Sanitary Standard Class III

Code	ID [mm]	OD [mm]	Working pressure [bar]	Burst pressure [bar]	Weight [kg/m]	Bending radius [mm]
	51	-	5	15	2,06	260
	63,5	-	5	15	2,54	340
	76	-	5	15	2,98	440
	80	-	5	15	3,12	490
	102	-	5	15	4,56	600

Other diameters, wall thickness, cover colours and pressure only on specific request.