	_								
		SMITH ®	ay r. smi	TH.	ര		LOCATION		
			PLUMBING & DRAINAGE P	RODUCTS		I			
	1		959 Alness Street, North York, C						
l _	H	CUSTOMER DRIVEN	TEL: (416) 736-9610 FAX:	(416) 736-	3789				
MBER S9340-CAN		SPECIAL PURPOSE ISOLATED FLOOR DRAIN							
S93	Ψ	UPPER BODY							
N D N	ND DA			_	_			UPPER BODY REGULARLY FURNISHED:	
DRAWING NUMBER S9340	SUPERSEDED OR VOID DATA			13 S	Area Q IN			Duco Cast Iron Body and Flashing Collar with Cast Iron Tractor Grate.	
	EDED			(84) 3	SQ CM			OPTIONAL MATERIALS:	
SIZE	Nickel B Galvani:							Nickel Bronze Top -NB Galvanized Body -G	
			<del> </del>	——— 8 1/2 (2	5) DIA ——— 215) DIA———		<ul><li>Seepage Openings</li></ul>	Polished Bronze Top -PB	
۱	FOR USE OF		<u>,  </u>	8 (205	5) DIA ———		— Collar Can Be Used as Flashing	VARIATIONS:	
NONE	/ FOR		1 5/8 (41)			c	lamp When Requi		
SCALE:	WE CAN ASSUME NO RESPONSIBILITY		2(51)	_			1		
S	SNO		4 4 5 6 4 6 4						
	RES		4,6,0.4.4,0.4	- 7			Specify Height When		
3-5-08	ME NO	5/1	25) MIN	4			-C2 Required	I	
	ASSU		30) MAX	ν - V - 0 Δ					
DATE:	CAN	9. % Finished 6. % Floor Clamp -C2							
l	WE		d d v v v v v d d v	0 4	;	When Specifie	d)		
D BY:			4 9 b 9 α α 9 b b	Φ Δ.			•		
C C			Isolation			- Neoprene Ga	ısket		
APPF	Isolation Panel Neoprene Gasket								
	NOTICE		4 (100) (100)			Sec	epage Holes		
BY:	THOUT		1 1/4 Structural Slab	0.4					
	E WIT		(32)						
снескер <b>сг</b>	HANG			<b>_</b>	A				
0	9 (230) DIA ———————————————————————————————————								
	ANCE	A (Pipe Size) = 02(50), 03(75), 04(100)							
д В Ж.	OLER/								
DRAWN BY: RN	ERS T	△Collar can be used as flashing device when required					Fig. 9340Y-CAN NO-HUB OUTLET		
	CTUR								
<b> </b> –	NUFA								
A (Pipe Size) = 02(50), 03(75), 04(100)  A (Pipe Size) = 02(50), 03(75), 04(100)  ΔCollar can be used as flashing device when required  Fig. 9340Y-CAN No-  LOWER BODY  REGULARLY FURNSIHED: All Duco Cast Iron Lower Body and Flashing Collar, Adjustment Nipple and Upper Body, neoprene Isolation Gasket.									
14	E SUB	REGULARLY FURNSIHED: VARIATIONS:							
All Duco Cast Iron Lower Body and Flashing Collar, Adjustment Nipple									
and Upper Body, neoprene Isolation Gasket.									
18	DIME								
			1			WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	
FIGURE NUMBER						LOOND2	CUDIC FEET	9340-CAN	
FIGL		REV. DATE	DESCRIPTION	BY	CKD. BY			1 30-10 OAI1	