Acceptance Indemnity Insurance Company

WOODSTOVE INSPECTION REPORT

Report must be completed and signed by <u>licensed contractor</u> or member of <u>local fire department</u> when woodstove is **not** factory installed or commercially installed by appliance distributor or licensed expert.

PHOTOGRAPHS MUST BE SUBMITTED SHOWING INSIDE AND OUTSIDE VENTING. (If installed by Manufacturer, do not complete.)

NAMED INSURED:	POLICY NUMBER:
STOVE INFORMATION	
DATE INSTALLED: INSTALLED BY:	PURCHASE COST: \$
MAKE/NAME:	IS WOODSTOVE EQUIPPED WITH A HEAT RECLAIMING DEVICE? YES NO
TYPE: RADIANT JACKETED WHAT TYPE OF FUEL IS USED?	USE: PRIMARY HEAT AUXILIARY HEAT COOKING OTHER (Specify)
HOW OFTEN ARE CHIMNEY AND STOVEPIPES CLEANED?	DATE LAST CLEANED: BY WHOM:
INSTALLATION INFORMATION (If woodstove is primary source of heat or double vented, risk is unacceptable.)	
LOCATION OF STOVE IN HOME:	IS THERE A SMOKE DETECTOR IN THIS ROOM: YES NO
FLOOR PROTECTION: ASBESTOS MILLBOARD COVERED WITH METAL OTHER (Specify)	METAL STONE/BRICK
WALL PROTECTION: ASBESTOS MILLBOARD COVERED WITH METAL OTHER (Specify)	METAL ASBESTOS MILLBOARD IF NONE, IS THIS ACCEPTABLE WITH MANUFACTURER? YES NO
CHIMNEY TYPE: FACTORY CHIMNEY MASONRY OTHER (Describe)	HOW MUCH AIR SPACE BETWEEN WALL PROTECTION AND COMBUSTIBLE WALL? INCHES.
CLEARANCES	
1 INCHES SIDE OF UNIT NEAREST TO WALL	
2 INCHES REAR OR UNIT TO WALL	
3 INCHES TOP OF STOVE PIPE TO CEILING	3
4 INCHES BOTTOM OF UNIT TO FLOOR	
5 INCHES FRONT OF UNIT TO FRONT EDGE OF FLOOR PROTECT	TION
6 INCHES SIZE OF PIPE USED	
7 INCHES SIZE OF THIMBAL OR ROOF JOIST SHIELD	
DO THESE DISTANCES COMPLY WITH THE MANUFACTURER'S STANDARDS?	YES NO 2
REMARKS	(a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c
Contractor/Fire Department Signature:	Date: