

Material Safety Data SheetNo. **231**

Page 1 of 3



Product Name:

Printed:

01/15/2008


Last Update:

01/15/2008

ArtLube- 100**I. Basic Information:**

Supplier: ArtMolds
 Address: 18 Bank Street
 City, ST Zip: Summit, NJ 07901
 Emergency Phone: 908-273-5401

1	Health
3	Flammability
1	Reactivity
G	Pers. Protection



Transportation Emergency Phone: Chem-trec 1-800-424-9300

Chemical State: Liquid Gas Solid Chemical Type: Pure Mixture

II. Ingredients:

CAS No.	Chemical Name	% Range EHS	NTP IARC SUB Z 313	SARA	OSHA PEL	ACGIH TLV	Other Limits
67641	Non-Hazardous Release Blend	4-8			NE	NE	NE
	Acetone	3-6			1000ppm		750 ppm
64742956	Solvent naphtha (petroleum),	3-6		X	NE	500ppm 350 ppm	NE
1330207	light aromatic Xylene (mixed isomers)	4-8		X	100 ppm	100 ppm	150 ppm
108883	Toluene	75-80		X	100 ppm	50 ppm	150 ppm

III. Hazardous Identification:Hazard Category: ACUTE CHRONIC **FIRE****Hazardous Identification Information:**

Warning!

Beige to translucent colored liquid with an aromatic odor.

Contains Xylene and Toluene.

This material is flammable and may be ignited by heat, sparks, flame, welding arcs and other high temperature sources.

V. First Aid Measures:

Route(s) of Entry: Inhalation, Ingestion, Skin and Eye contact.

Health Hazards (Acute and Chronic):

Acute (Short-Term)

Eye and skin contact can cause mild to moderate irritation.
respiratory tract.

Inhalation can cause irritation to the nose, throat and upper

Chronic (Delayed)

Prolonged or repeated skin contact can defat the skin, cause irritation and lead to the development of dermatitis.
high concentrations of vapors can cause dizziness, headache and incoordination.

Inhalation of

Signs and Symptoms:

Contact may cause mild to moderate skin and eye irritation.
headaches and incoordination.

Inhalation of high concentrations of vapors can cause dizziness,

Medical Conditions Generally Aggravated by Exposure:

Persons with asthma-like conditions may experience additional breathing difficulties due to respiratory tract irritation.

Emergency and First Aid Procedures:

SKIN CONTACT: Wash affected area with warm soapy water and apply barrier cream.



Material Safety Data Sheet

No. 231

Page 1 of 3

Printed:

01/15/2008

Last Update:

01/15/2008

Product Name:

ArtLube – 100

EYE CONTACT: Flush eyes with water for at least 15 minutes and contact a physician.

INGESTION: Do NOT induce vomiting and contact a physician. Do NOT give anything by mouth to an unconscious person.

INHALATION: Remove person to fresh air.
physician.

If person is not breathing give mouth-to-mouth resuscitation and contact a

Other Health Warnings

Toluene reports indicate nervous system depression and impaired lung function with excessive exposure. may cause liver, kidney and brain damage. Ingestion can cause nausea, vomiting and gastrointestinal upset.

Deliberate misuse

V. Fire Fighting Measures:

Flash Point: 45°F

Lower Explosive Limit:

Upper Explosive Limit:

1.2

7.6

Fire Extinguishing Media:

Foam, water spray, carbon dioxide or dry chemical extinguishers.

Special Fire Fighting Procedures:

Firefighters should wear a self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion:

None known

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Remove all sources of ignition. Cover liquid with an absorbent material (sawdust, vermiculite or wet sand). After the material is absorbed scoop up and place in containers for disposal. If the original container is damaged, transfer material to a closed metal, glass or plastic container. People performing clean-up should have full protective equipment.

VII. Handling and Storage:

Precautions to be Taken:

Keep away from heat, sparks, flames and other high temperature sources.
area.

Keep container tightly closed in a well ventilated

Other Precautions:

Transfer operations must be electrically grounded to dissipate static buildup.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Recommended to meet TLV limits.
Mechanical ventilation or exhaust system may be required.

Personal Protective Equipment:

RESPIRATORY PROTECTION: If air concentrations exceed established limits, use a supplied air respirator.

PROTECTIVE GLOVES: Impervious rubber gloves.

EYE PROTECTION: Wear safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Protect all exposed skin from liquid contact.

IX. Physical and Chemical Properties:

Boiling Point:	*	Melting Point:	NA	Evaporation Rate:	<1
Vapor Pressure (mm Hg.):		26@77°F	Vapor Density (AIR = 1):		>3.2
Solubility In Water:		Negligible			



Material Safety Data Sheet

No. 231

Page 1 of 3

Printed:

01/15/2008

Last Update:

01/15/2008

Product Name:

ArtLube – 100

Appearance and Odor: Beige to translucent; aromatic odor

Other Information: *BOILING POINT 120-180°F

VOLATILITY @75°F: Moderate

PERCENT VOLATILE BY VOLUME(%): 96%

SPECIFIC GRAVITY: 0.85

X. Stability and Reactivity:

Stability: Stable

Incompatibility (Materials to Avoid):

Acids and strong oxidizing agents.

Decomposition/By Products:

Hydrogen chloride, small amounts of phosgene and chlorine.

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

None Available

XII. Ecological Information:

None Available

XIII. Disposal Considerations:

Waste must be disposed of in accordance with federal, state and local environmental regulations.

XIV. Transport Information:

Contains Toluene. RQ - 1000 lbs (as Toluene)

DOT Shipping Name: Flammable Liquid N.O.S. (Contains Toluene)

Class 3

PG II

UN 1993

NFPA 30 - Flammable Liquid Class IB

XV. Regulatory Information:

TSCA Inventory Status: This product, or its components, are listed on, or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

SARA 313 INFORMATION: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

CHEMICAL NAME	CAS NUMBER	CONCENTRATION
Toluene	108-88-3	75-80%
Xylene	1330-20-7	4-8%
Acetone	67-64-1	3-6%

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:
An immediate health hazard ; A delayed health hazard ; A fire hazard

XVI. Other Information:

In this document the following abbreviations are used:
NA: Not Applicable. NE: Not Established