



Order form
Purchaser

Version 1.3

Date Feb 1st 2015

HMT140 WiFi Data Logger

			1	2	3	4	5	6	7	8	9	10	11	12	13	14		
Vaisala Data Logger Package			HMT140															
Channel Measurement Type	<i>Vaisala Humicap Humidity and Temp Probe (HMP110)</i>	<i>RH/T</i>	1													N	N	Price
	<i>Dual RTD Temperature Inputs w/5M Probes</i>	<i>-200C to 90C</i>	3															
	<i>Voltage Inputs</i>	<i>0-5 VDC</i>	4															
	<i>Voltage inputs</i>	<i>0-10 VDC</i>	5															
	<i>Current Inputs</i>	<i>0-20 mA</i>	6															
	<i>Boolean Inputs</i>		7															
	<i>RTD Temperature Input w/5M Probe & Boolean Input</i>	<i>-200C to 90C</i>	8															
Display	None	Display not installed	0															
	<i>Display</i>		1															
Calibration Ranges*	No Calibration Range	Boolean Inputs		N														
	Standard	See Table*		A														
	<i>Extended Range RTD -196 to +90 Deg C</i>	<i>Additional 2 week delivery</i>		C														
	<i>Vaisala HMP110</i>	<i>Two Additional Temp Points</i>		D														
	<i>Vaisala HMP110</i>	<i>Four Additional Temp Points</i>		E														
Calibration Type	No Calibration Type	Boolean	0															
	NIST Traceable only	All Input types except Boolean	1															
	<i>ISO 17025 Accredited - NIST Traceable</i>	<i>RTD</i>	2															
RTD Probe Thermal Dampener Blocks	None			N														
	<i>1 Thermal Dampener Block</i>			A														
	<i>2 Thermal Dampener Blocks</i>			B														
Humicap Probe Cable Length	None		0															
	Fixed Probe		1															
	<i>3 Meter</i>		2															
	<i>5 Meter</i>		3															
	<i>10 Meter</i>		4															
Humicap Sensor Protection	No Humicap Sensor			N														
	Plastic grid			A														
	Plastic grid with PTFE filter			B														
	Stainless steel sintered filter			C														
Installation Kit for Humicap Probe	None		0															
	<i>Duct installation kit</i>		1															
	<i>Probe mounting flange</i>		2															
Boolean Switch Kit with Door Contact	None			N														
	<i>1 Kit - 7.6 Meters</i>			A														
	<i>2 Kits - 7.6 Meters</i>			B														
Quick Guide	None		0															
	<i>Multilingual</i>		1															
External Power Supply (Optional)	supply and connector			N														
	<i>NA</i>	<i>North America</i>		A														
	<i>UK</i>	<i>United Kingdom</i>		B														
	<i>EUR</i>	<i>Europe</i>		C														
	<i>AUS</i>	<i>Australia</i>		D														
	<i>JA</i>	<i>Japan</i>		E														
	<i>ZH</i>	<i>China</i>		F														
Calibration Interval	Recommended	12 Months		N														
	Customer Specified	3 - 120 Months		X														
Reserved																N		
Reserved																N		

HMT140 1 1 A 1 N 4 C 2 N 1 A N N N

Calibration Ranges *	Sensor Type (HMT140 model)	Range
No Calibration Range	Used with Boolean Inputs (148)	None
Standard	HMP110 Vaisala Humicap (141)	10%, 30%, 85% RH 23 Deg C
	0 - 5 Voltage (144)	0.1 - 2.5 and 5 V
	0 - 10 Voltage (145)	0.1 - 5 and 10 V
	0 - 20mA (146)	4 - 12 and 20 mA
	Standard RTD (143/8)	-90, -45, 0, 45, 90 Deg C
RTD -196 to +90 Deg C	Extended range RTD (143/8)	-196, -90, -45, 0, 45, 90 Deg C
Vaisala Humicap Additional Temp points	HMP110 Vaisala Humicap (141)	10%, 30%, 85% RH 23 Deg C plus 2 or 4 more specified between -25, +70