Product Specification Sheet

Catalog Number: UB18-2C-BLK

Catalog Number: UB18-2C-BLK	
Construction Detail	Product Illustration
Ripcord 18 AWG Component Outer Jacket Water Block Tape	
Physical Construction	Description
Component 1: 18 AWG 7/26 bare copper conductor PVC Insulation: .016-inch nominal thickness Nylon Insulation: .005-inch nominal thickness	In-wall rated power limited tray cable for audio, instrumentation and control applications in accordance with NEC article 725. Suitable for wet locations, sunlight resistant, and direct burial applications. Color Code Black, Red
	Electrical Specifications
	18 AWG: DCR: 6.04 Ω per 1000 feet Capacitance: 25 pF per foot Voltage: 300 Volts RMS Temperature: -30°C to 105°C
Final assembly:	Regulatory Specifications
2 of component 1 cabled together 100% water blocking tape binder Nylon ripcord under the jacket. PVC jacket: .040-inch nominal thickness Final construction: .278-inch nominal OD Product Print Legend: ISOTEC, INC. 18 AWG (UL) CL3/PLTC OR FPL "SUN RES" "DIR BUR" SUITABLE FOR DIR BUR SUITABLE FOR WET LOCATIONS 105C Sequential footmarks are applied in conjunction with the print legend.	(UL) rated CL3, PLTC or FPL Product is not rated for Canada Sunlight resistant and Suitable for Direct Burial Suitable for wet locations EU RoHS 2002/95/EC Compliant since 06/15/2005
Specification Control	Product Information
Revision Date: 02/14/2003 Liberty Wire & Cable specifications are subject to change without notice. Contact an account representative for current product specifications. Liberty Wire & Cable continuously strives to ensure product specifications are accurate and complete. All physical specifications are nominal.	Jacket Colors: Black Packaging: 2500 foot reels

FOR IMMEDIATE SERVICE FAX YOUR ORDER

719-260-0075



Form Revision Date: 04/15/2004

CALL TO PLACE YOUR ORDER TODAY

MOST ORDERS SHIPPED WITHIN 48 HOURS