

AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT				1. CONTRACT ID CODE	PAGE 1 OF 3 PAGES
2. AMENDMENT/MODIFICATION NO. AMENDMENT NO. 0001		3. EFFECTIVE DATE 09/11/14	4. REQUISITION/PURCHASE REQ. NO.	5. PROJECT NO. (If applicable) 14-0084	
6. ISSUED BY CODE		CODE mks	7. ADMINISTERED BY (If other than Item 6) CODE See Item 6		
6. ISSUED BY Officer in Charge of Construction MCI-East 1005 Michael Road Camp Lejeune, NC 28547-2521					
8. NAME AND ADDRESS OF CONTRACTOR (No., street, county, State and ZIP Code)				(X)	9A. AMENDMENT OF SOLICITATION NO. N40085-14-R-0084
				X	9B. DATED (SEE ITEM 11) 09/10/14
					10A. MODIFICATION OF CONTRACT/ORDER NO.
					10B. DATED (SEE ITEM 11)
CODE	FACILITY CODE				

11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS

The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offers is extended, is not extended.
 Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods:
 (a) By completing items 8 and 15, and returning _____ copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted;
 or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment your desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.

12. ACCOUNTING AND APPROPRIATION DATA (If required)

**13. THIS ITEM ONLY APPLIES TO MODIFICATION OF CONTRACTS/ORDERS.
IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.**

CHECK ONE	A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.
	B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(b).
	C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:
	D. OTHER (Specify type of modification and authority)

E. IMPORTANT: Contractor is not, is required to sign this document and return _____ copies to the issuing office.

14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.)

14-0084 Interior and Exterior Repairs, Bldg AS-840

(CONTINUED)

Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.

15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)	
15B. CONTRACTOR/OFFEROR		16B. UNITED STATES OF AMERICA	
15C. DATE SIGNED		16C. DATE SIGNED	
(Signature of person authorized to sign)		(Signature of Contracting Officer)	

Amendment No. 1

Project No. 14-0084 Interior and Exterior Repairs, Bldg AS-840

1. The following is a revision to the floor finishes called out on drawings and Finish Schedule Sheet A-7:

a. Except for Mech Room 117, Hangar 115, Battery Room 109, Women's Head 119 and Men's Head 108, all rooms in the one-story admin building are to receive resinous epoxy flooring with turned up base. Use the following specification for resinous epoxy flooring:

Epoxy resinous troweled mortar includes concrete epoxy primers, solid color quartz aggregate epoxy resin mortar, quartz broadcast finish topping, and associated epoxy sealer. Built up layers of quartz broadcast systems will not be accepted. Epoxy mortar base must be utilized with a final topping of quartz broadcast.

System characteristics:

1. Color and pattern to be selected by architect from color samples submittal
2. Wearing surface: Textured
3. Integral base: Cove 1" radius, 6" height
4. Overall system thickness: 3/16"

System components: manufacturers standard components that are compatible with each other, and as follows:

1. Primer formulation description: 2 component 100% solids epoxy
2. Formulation description body coat:
 - A. Resin: Epoxy
 - B. Formulation description: 3 component 100% solids
 - C. Application method: Metal trowel
 - D. Coats: One
 - E. Thickness: 3/16 "
 - F. Aggregates: Solid/ single color pigmented quartz blended
3. Under coat:
 - A. Resin: Epoxy
 - B. Formulation description: 2 component 100% solids
 - C. Type: Clear
 - D. Finish: Matte
 - E. Number of coats: One
 - F. Application method: Squeegee
4. Broadcast quartz:
 - A. Aggregates: pigmented colored tweed or solid quartz
 - B. Number of coats: One
 - C. Application method: Broadcast to refusal

5. Sealer finish coat:

A. Resin: Epoxy

Additional sealer finish coat standard texture = one coat, medium texture = two topcoats

B. Formulation description: 2 component 100% solids epoxy

C. Type: Clear

D. Finish: Gloss

E. Number of coats: One (texture dependent)

F. Application method: Squeegee

b. The Men's Head 108 and Women's Head 119 are to receive porcelain ceramic tile flooring. Use the following specification for the porcelain tile:

Provide ceramic tile that complies with ANSI A137.1 for types, compositions and other characteristics indicated. Submit manufacturer's Data Sheets on each product to be used, including preparation instructions and recommendations and installation methods. Submit manufacturers standard color charts for selection.

Unglazed porcelain floor tile

1. Product: Unglazed porcelain floor tile
2. Size and Shape: 12" x 12" nominal
3. Coefficient of Friction equal to or exceeding 0.6 wet
4. Moisture absorption less than 0.5%
5. Tile thickness: 5/16"
6. Colors: To be selected by architect from manufacturer's standard range.

Install tile and grout in accordance with applicable requirements of ANSI A108.1 through A108.13, Manufacturer's instructions, and TCA Handbook recommendations.

Tile installer to use stain resistant grout additive equal to "Grout Boost".

c. Contractor to dispose of :

2. Contractor is to provide 4 port-a-johns for the buildings tenants to use while the AS840 head is out of commission due to renovation.

3. Because the planes normally housed in the hangar will have to be relocated while work is taking place, Contractors are requested to consider doing as much hangar work as possible (lights, sprinkler system, hangar door replacement) simultaneously to minimize the length of time the planes need to be housed elsewhere.