1	
2	
3	
4	
5	
6	
7	
8	FIRST AMENDED
9	SITE CERTIFICATE
10	
11	FOR THE
12	
13	NORTHWEST NATURAL
14	SOUTH MIST PIPELINE EXTENSION
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26 27	Incluse DV
27	Issued by
28	
29 20	OREGON ENERGY FACILITY SITING COUNCIL
30	625 MARION STREET NE Salem OR 97301-3737
31	SALEM OR 9/301-3/3/
32 33	503.378.4040
33 34	503.378.4040 503.373.7806 FAX
34 35	<i>JUJ.J J. OUU FAA</i>
36	
30 37	AUGUST 28, 2003
38	10000120,2005

Image: Second state of the second s

II.	SITE CERTIFICATION	1
III.	FACILITY DESCRIPTION	2
	A. Facility	2
	B. Location of the Facility	4
IV.	SITE CERTIFICATE CONDITIONS	7
	A. Mandatory Conditions from OAR Chapter 345 Division 27	7
	B. Site Specific Conditions under OAR 345-027-0023	9
	C. Monitoring Conditions under OAR 345-027-0028	9
	D. Conditions under OAR 345-027-0020(10)	10
	E. Conditions related to EFSC Standards	11
	Organization Expertise	11
	Structural Standard	11
	Soil Protection	12
	Land Use	13
	Protected Area	18
	Retirement and Financial Assurance	18
	Fish and Wildlife Habitat	20
	Threatened and Endangered Species	28
	Historic, Cultural and Archeological Resources	28
	Public Services	30
	Waste Minimization	30
	F. Conditions related to Public Health and Safety	31
	G. Permitting Requirements of Agencies other than EFSC	32
	SEVERABILITY, CONSTRUCTION, GOVERNING LAW AND FORUM	32

1

1			
2		First Amended	
3		SITE CERTIFICATE	
4		FOR THE	
5		NORTHWEST NATURAL	
6		SOUTH MIST PIPELINE EXTENSION	
7			
8			
9	I.	INTRODUCTION	
10	This S	ite Certificate for the South Mist Pipeline Extension ("SMPE") is issued and executed in	
11		nner provided by ORS chapter 469, by and between the State of Oregon ("State"), acting	
12		I through its Energy Facility Siting Council ("Council"), and Northwest Natural Gas	
13	Comp	any ("NWN" or "certificate holder").	
14	T1 C		
15 16		ndings of fact, reasoning and conclusions of law underlying the terms and conditions of te Certificate are set forth in: (1) the Council's Final Order in the Matter of the Application	
16 17		the Certificate for the South Mist Pipeline Extension, which the Council granted on March	
18		03, and which by this reference is incorporated herein; and (2) the Council's Order	
19		ving Amendment #1, which the Council issued on August 28, 2003.	
20	11		
21	In interpreting this Site Certificate, any ambiguity shall be clarified by reference to, and in the		
22	following priority: (1) this Site certificate; (2) the Order Approving Amendment 1; and (3) the		
23	record of the proceedings that led to the Final Order in the Matter of the Application for Site		
24	Certifi	cate,.	
25	T1	ment and in this Site Contificate shall have the same meaning set forth in ODS 4(0,200 and	
26 27	The terms used in this Site Certificate shall have the same meaning set forth in ORS 469.300 and		
27 28	Oregon Administrative Rules (OAR) 345-001-0010, except where otherwise stated or where the context clearly indicates otherwise.		
28 29	contex		
30	II.	SITE CERTIFICATION	
31	1.	To the extent authorized by State law and subject to the conditions set forth herein, the	
32		State approves and authorizes the certificate holder to construct, operate and retire a 24-	
33		inch diameter natural gas transmission pipeline, approximately 62 miles in length, within	
34		a corridor described in Section C of this Site Certificate, between the Bacona Station in	
35		Washington County and the Molalla Gate Station near Molalla Oregon. ORS 469.401(1).	
36	•		
37	2.	This Site Certificate shall be effective (1) until it is terminated pursuant to OAR	
38		345-027-0110 or the rules in effect on the date that termination is sought, or (2) until the Site Certificate is rangeed surgeont to OPS 460 440 and OAB 245 020 0100 or the	
39 40		Site Certificate is revoked pursuant to ORS 469.440 and OAR 345-029-0100 or the statutes and rules in affect on the data that revocation is ordered. ORS 469.401(1)	
40 41		statutes and rules in effect on the date that revocation is ordered. ORS 469.401(1).	
42	3.	This Site Certificate does not address, and is not binding with respect to, matters that	
43	2.	were not addressed in the Council's Final Order of March 13, 2003 or the Order	
44		Approving Amendment #1. These matters include, but are not limited to: building code	

1 compliance; wage, hour and other labor regulations; local government fees and charges; 2 other design or operational issues that do not relate to siting the SMPE; and permits 3 issued under statutes and rules for which the decision on compliance has been delegated 4 by the federal government to a state agency other than the Council. ORS 469.401(4) and 5 469.503(3). 6 7 4. Both the State and the certificate holder shall abide by local ordinances and state law and 8 the rules of the Council in effect on the date this Site Certificate is executed. In addition, 9 upon a clear showing of a significant threat to the public health, safety or the environment 10 that requires application of later-adopted laws or rules, the Council may require compliance with such later-adopted laws or rules. ORS 469.401(2). 11 12 13 5 For a permit, license or other approval addressed in and governed by this Site Certificate, 14 the certificate holder shall comply with applicable state and federal laws adopted in the future to the extent that such compliance is required under the respective state agency 15 16 statutes and rules. ORS 469.401(2). 17 18 Subject to the conditions herein, this Site Certificate binds the State and all counties, 6. 19 cities and political subdivisions in this state as to the approval of the site and the 20 construction, operation and retirement of the Summit Project as to matters that are 21 addressed in and governed by this Site Certificate. ORS 469.401(3). 22 23 7. Each affected state agency, county, city and political subdivision in the State with 24 authority to issue a permit, license or other approval addressed in or governed by this Site 25 Certificate shall, upon submission of the proper application and payment of the proper fees, but without hearings or other proceedings, issue such permit, license or other 26 27 approval subject only to conditions set forth in this Site Certificate. ORS 469.401(3). 28 29 8. After issuance of this Site Certificate, each state agency or local government agency that 30 issues a permit, license or other approval for the SMPE shall continue to exercise 31 enforcement authority over such permit, license or other approval. ORS 469.401(3). 32 33 9. After issuance of this Site Certificate, the Council shall have continuing authority over 34 the site and may inspect, or direct the Office to inspect, or request another state agency or 35 local government to inspect, the site at any time in order to assure that the SMPE is constructed and operated consistently with the terms and conditions of this Site 36 37 Certificate. ORS 469.430. 38 39 III. **FACILITY DESCRIPTION** 40 41 A. FACILITY The SMPE is a 24-inch diameter natural gas pipeline, approximately 62 miles long. Its northern 42 43 terminus is the Bacona Blowdown Station, which is located in forest land north of Dairy Creek 44 just south of the Washington and Columbia County border. It extends generally south and east

through rural lands in Washington, Marion and Clackamas Counties. Its most southerly point is
 the Williams Pipeline Gate Station located northwest of Molalla.

3

4 NWN proposed the pipeline to effectively utilize gas storage capacity at the Mist Underground 5 Natural Gas storage facility. An underground natural gas storage facility provides NWN with a 6 means of balancing relatively constant pipeline gas supplies with widely fluctuating demand. 7 Gas usage is generally lowest during summer months and peaks during the winter. The 8 underground natural gas storage operation consists of a natural gas production field, retrofitted to 9 inject gas back into the ground and withdraw it on a cyclical basis. Gas is injected into storage 10 during off-peak periods and is withdrawn during periods of peak demand. 11 12 Underground reservoir storage requires suitable underground geological conditions in a specific 13 geographic area, and can only be sited where those conditions exist naturally. Mist is one such 14 area because it was, at one time, a producing gas field. The gas stored at Mist is purchased from 15 the interstate natural gas transmission system. NWN proposes this pipeline in order to connect

- 16 the Mist storage facility with the interstate system.
- 17

18 A second purpose of this pipeline is to accommodate the growth in demand for natural gas in the

19 western Portland suburbs. The NWN distribution system currently includes major feeder lines

20 serving Hillsboro, Sherwood and Newberg. NWN proposed the SMPE in order to connect with

21 these feeder lines and increase the available supply to these suburbs during peak periods.

22

23 NWN already operates one 16-inch pipeline that connects the Mist storage facility with the

24 distribution system serving the Portland area. NWN operates this pipeline under a Site

25 Certificate issued by the Council in 1989. The 16-inch pipeline is called the South Mist Feeder.

26 It travels south from Mist, crosses the Tualatin Mountains and enters Washington County in

27 forested land north of the Dairy Creek Valley, travels south through Dairy Creek Valley and east

along Mountaindale and West Union Roads until it reaches West Union.

29

30 In 1999 the Council amended the South Mist Feeder site certificate, authorizing a 24-inch

31 pipeline parallel to the 16-inch line and located within the same corridor. NWN constructed this

32 24-inch pipeline in 1999. It starts at the Mist storage facility and runs for approximately 30

33 miles, tying in to the 16-inch line at a point called the Bacona Blowdown Station, located in

34 forest land just south of the Washington and Columbia County border. NWN proposes to begin

35 the SMPE at the Bacona Blowdown Station and follow the existing corridor for the 16-inch line

36 until just north of Mountaindale Road. From that point, the SMPE site is all new corridor.

37

38 In most locations, the proposed pipeline will be buried at a depth of 5 feet on average. This

39 depth may vary based on local requirements. The pipeline must be designed and constructed in

40 accordance with federal safety regulations of the US Department of Transportation at 49 CFR

192. The maximum allowable operating pressure (MAOP) as established by the hydrostatic
 pressure test, will be 720 psig. The Oregon Public Utility Commission administers the 49 CFR

42 pressure test, will be 720 psig. The Oregon Public Offitty Commission administers the 49 CF
 43 192 regulations under a delegation from the federal government. The pipeline would be

43 192 regulations under a delegation from the rederal government. The pipeline would be44 underground its entire length, with the exception of certain above ground valves and inspection

44 underground its entire length, with the exception of certain above 45 points that are required by the federal code.

2 Although NWN requested a 200-foot wide corridor, the approved site is limited by condition. 3 During the construction period, there will be a construction easement, generally 80 feet wide (the 4 "Construction Easement"). The full width of the Construction Easement will be used only 5 during construction. It will be restored after construction and returned to its previous use. NWN 6 also will require a permanent easement directly over the pipeline for maintenance and safety (the 7 "Maintenance Easement"). The Maintenance Easement will be restored to its pre-construction 8 condition and use except that large trees or other vegetation with potentially damaging root 9 structures will not be allowed to grow in close proximity to the pipeline. The term "easement" is 10 given a specific meaning in this site certificate and is defined for the purposes of this site certificate in General Land Use Conditions. 11 12 13 In general, the Maintenance Easement will be 40 feet wide. Where the pipeline is along public 14 right-of-way, the Council adopts conditions limiting the width of the easement on private land in 15 the EFU zone. In areas where the new pipeline will be placed next to the 16-inch pipeline, the 16 easement will remain 40 feet. In certain locations NWN may need to deviate from the nominal widths of these easements. The site certificate includes conditions under the Council's Land Use 17 18 Standard OAR 345-022-0030 and Mandatory Conditions under OAR 345-027-0020 that address 19 deviations from the nominal width of the Maintenance and Construction easements. 20 21 NWN included 44 aerial photographic panels with the ASC, submitted as Appendix K-2 (and 22 supplemented in July 2001). These panels are the clearest representation of the proposed corridor location, and we refer to them throughout this site certificate. Among other things, the 23 24 panels show the expected location of temporary lay-down areas that will be required in

- connection with the construction of the proposed facility. Portions of these proposed lay-down
- areas are outside of the 200-foot pipeline corridor. On June 5, 2003 NWN requested approval for additional lavdown areas and temporary access roads outside the 200-foot corridor. The
- for additional laydown areas and temporary access roads outside the 200-foot corridor. The
 Council approved of these additional laydown areas and access roads in its August 28, 2003
- 28 Council approved of these additional laydown areas and access roads in its August 28, 2005 29 Order Approving Amendment #1. The approval granted by EFSC includes approval for the
- 30 construction-related use of the temporary lay-down areas and access roads. To ensure that this
- 31 use complies with applicable siting standards, this site certificate contains conditions relating to
- 32 the temporary use of these areas. NWN has also indicated that certain other areas will be used
- 33 for pipeline construction staging in connection with construction of the proposed facility. This
- 34 site certificate authorizes only the use of those areas shown on the 44 aerial photographs in $\frac{1}{25}$ Arnendix K 2 as supplemented, and those described in Exhibits 2 and shown on Exhibits 4 and 5
- Appendix K-2 as supplemented, and those described in Exhibit 3 and shown on Exhibits 4 and 5 of NWN's June 5, 2003 request for amendment #1. In the event that the use of other areas is
- 37 necessary in connection with the construction of the proposed facility, NWN will (to the extent
- 38 such uses are within the Council's jurisdiction) address the use of those areas through additional
- 39 amendment to the site certificate. [amendment 1]
- 40
- The SMPE does not include any "related or supporting facilities", as that term is defined at OAR
 345-001-0010.
- 4344 B. LOCATION OF THE FACILITY
- 45

1 The following route description is for the approved corridor and the alternate corridor segments.

2 The corridor and corridor segments have also been overlain onto 44 aerial photos, which provide

3 more accurate visual representations of them. Figure K-2 of the ASC shows this in reduced size

4 and is the clearest depiction of the pipeline location in the Application. For purposes of this 5 description, road names are used to identify the location of the Preferred Corridor and Alternate

6 Corridor Segments, but the location in or along the right of way for those roads is governed

7 solely by conditions of the site certificate. The following description does not attempt to deal

8 with the specific location of the pipeline within the corridor.

9

10 The approved corridor for the SMPE has its northern terminus in Washington County at the

Bacona Blowdown Station, which is the terminus of the 24-inch loop that NWN added to the 11 12 South Mist Feeder pipeline in 1999 under amendment 2 to its existing site certificate. It

13 continues through the Dairy Creek Valley, paralleling in close proximity to the existing 16-inch

14 South Mist Feeder. The Preferred Corridor deviates from the existing easement for the 16-inch

15 pipeline just north of Mountaindale Road. At this point, the Council authorizes Preferred and

16 Alternate corridor segments. Both options include a bore under Dairy Creek near its intersection

with Mountaindale road. From this intersection, the route proceeds south along Mountaindale 17

18 Road and Dersham Road to the north side of State Highway 26, where it turns to the east and

runs parallel to the highway right-of-way. The route continues east approximately one-half mile 19

20 to the highway overpass and then turns south, crossing under the highway overpass and the

- 21 railroad right-of-way.
- 22

23 At this point, a Preferred Corridor and an Alternate Corridor Segment have been identified. The 24 Preferred Corridor aligns with Milne Road and continues south to Zion Church Road, turns east, 25 and then proceeds to Davis Road. The Alternate Corridor Segment, known as the Milne/Gordon

Road Alternate, proceeds east along the south side of the Highway 26 right-of-way, turns south 26

27 along Gordon Road, proceeds south to Zion Church Road, and then turns west and proceeds to

28 Davis Road. The Preferred Corridor and the Milne/Gordon Road Alternate intersect at Davis

29 Road and Zion Church Road where both turn south along Davis Road.

30

31 The Preferred Corridor then proceeds south to Wren Road, where it turns east and then south

32 along Leisy Road. It continues south to the intersection with Hornecker Road and Padgett Road,

33

where it continues south along the Padgett Road public right-of-way for approximately one-half 34 mile and then traverses private land to the west. At this point, NWN again identified Preferred

and Alternate options. Both options generally parallel Dairy Creek and lead to an underground

35 bore south across State Highway 8. The corridor continues cross-country in a general 36

- 37 southeasterly direction and then turns southerly just west of Highway 219, which it parallels until 38 the first crossing of the Tualatin River.
- 39

40 The Preferred Corridor intersects Highway 219 just south of the Tualatin River and continues to 41 just south of Burkhalter Road, where it traverses cross-country in a generally easterly direction

42 along property boundaries and then intersects Burkhalter Road near Rood Bridge Road.

43

44 The corridor continues east past Rood Bridge Road and traverses cross-country in a southeasterly direction to the second crossing of the Tualatin River. Just south of the Tualatin River, the 45

corridor intersects River Road and continues southerly and southeasterly along River Road
 where it transitions to Highway 210. In the vicinity of Tuefel Hill Road, the corridor traverses

3 cross-country until it intersects Pleasant Valley Road and then proceeds southbound. Just south

- 4 of the Tualatin River National Wildlife Refuge, the corridor traverses cross-country to the south,
- 5 crossing the Tualatin River and continuing south to Scholls-Sherwood Road.
- 6

7 At this point, the Council has approved a Preferred corridor and one Alternate corridor segment.

8 The Preferred corridor aligns eastbound along Scholls-Sherwood Road and transitions onto

9 Elwert Road southbound. It diverges from Elwert Road at Chicken Creek, where the corridor

10 traverses southwest cross-country to Krueger Road. The alternate to the Preferred Corridor, the

11 Edy/Elwert Road Alternate, continues further south along Elwert Road, and across Edy Road, for

12 approximately one-half mile and then proceeds cross-country to the west, turning south and east

13 along property lines to Haide Road, until it intersects the Preferred Corridor. (A second alternate

14 Corridor Segment, the Eastview Road Alternate, was proposed in the application but shall not be

15 used, in accordance with a condition to the Site Certificate.)

16

17 At this point, the Preferred Corridor turns east and crosses Highway 99W and continues east

18 along Brookman Road. The corridor follows Brookman Road to a point near the

19 Washington/Clackamas County line, traverses cross-country to the south and intersects with

20 Ladd Hill Road. It continues south and east following Ladd Hill, Pleasant Hill, McConnell, and

- 21 Tooze Roads, and then turns south onto Baker Road.
- 22

23 At this point, Council approved a Preferred Corridor, which continues along Baker Road, and an

24 Alternate Corridor Segment, the Baker Road Alternate, which would provide a more direct

25 lineup for the directional drilling under the Willamette River. The Preferred Corridor and the

26 Baker Road Alternate join at the proposed laydown area, where the Preferred Corridor continues

27 south cross-country, passing under the Willamette River and emerging in close proximity to

28 Butteville Road approximately one-half mile west of Graham Road. The Preferred Corridor

29 continues cross-country to the south, crosses the Marion/Clackamas County line, continues to

- 30 Arndt Road, and turns east.
- 31

32 At this point the Preferred Corridor proceeds eastbound, crosses under I-5, transitions from

- 33 Marion to Clackamas County, and continues east to the Hubbard cutoff, where it turns south.
- 34 The corridor continues south a short distance and traverses to the east on private property to
- 35 Airport Road. Before the Preferred Corridor's intersecting with Airport Road, NW Natural has
- 36 identified another Alternate Corridor Segment, the Aurora Airport Alternate, through the Aurora

37 Airport. The Aurora Airport Alternate and the Preferred Corridor join at the intersection with

- 38 Airport Road.
- 39

40 The Preferred Corridor then turns south onto Airport Road, proceeds a short distance to the

41 south, turns east and traverses private property, crosses under the Pudding River, and emerges in

42 the vicinity of Anderson Road. It follows Anderson Road for a short distance, turns south about

43 600 feet before Barlow Road, and crosses Highway 99E. The corridor intersects Barlow Road,

44 turns south, and follows Barlow road south until a point just before Zimmerman Road.

45

1 At this point, the Preferred Corridor runs parallel to roads, but follows property lines. It

2 traverses easterly cross-country just north of Zimmerman Road and proceeds east to Oglesby

3 Road, where it then turns south. The corridor travels east again on private land just north of

4 Heinz Road. It continues east past Dryland Road, and turns south along property lines to the

5 Molalla Gate Station. A site certificate condition states that NWN shall use this preferred

6 corridor. An alternate corridor, along Heinz, Zimmerman and Dryland Roads, was proposed but

- 7 will not be used.
- 8

9 IV. Site Certificate Conditions

Based upon the review of the record, excluding any evidence not properly or timely made a part of the record and including the Application for Site Certificate, the Proposed Order, the Hearing Officer's Recommended Order and findings contained therein, parties' exceptions and responses to exceptions to the Recommended Order and oral argument of the parties, the Council adopts the OOE Proposed Order, attached to the Council's final order as Attachment C, as specifically modified by the Council's final order, and approves a site certificate for the SMPE, subject to compliance with the following conditions of approval:

17 18

A. MANDATORY CONDITIONS FROM OAR CHAPTER 345, DIVISION 27

- NWN shall submit to the Office two copies of a legal description of the site to be appended to the Site Certificate prior to beginning operation. For the purposes of this site certificate, the term "legal description" means a legal description of the permanent maintenance easements recorded by NWN, and an accurate map or set of maps that clearly and specifically the boundaries of the maintenance easements. The map must be in no smaller scale than 1 inch to 500 feet. In the event of a conflict between the recorded easements and the map, the recorded easements will control.
- 26

27 2) The pipeline shall be designed, constructed, operated and retired substantially as described in
28 the Final Order Approving Site Certificate; in compliance with the requirements of ORS
29 Chapter 469, applicable Council rules, and applicable state and local laws, rules and
30 ordinances in effect at the time the Site Certificate is issued; and in compliance with all
31 applicable permit requirements of other state agencies.

- 3) Construction shall commence not later than 18 months after issuance of the site certificate or
 the final resolution of appeals and shall be completed not later than three years following the
 commencement of construction. In no event shall construction commence after July 1, 2005.
- 36
- 4) No construction, including clearing of a right of way, except for the initial survey, may
 commence on any part of the facility until the certificate holder has adequate control, or has
 the statutory authority to gain control, of the lands on which clearing or construction will
 occur.
- 41
- 42 5) NWN shall prevent any condition over which NWN has control from developing on the site
 43 that would preclude restoration of the site to a useful condition.
 44

6) NWN shall restore vegetation to the extent practicable and shall landscape portions of the
area disturbed by construction in a manner compatible with its surroundings and/or proposed
future use. Upon completion of construction, NWN shall dispose of all temporary structures
not required for future use and all refuse and flammable materials or combustible material
resulting from the clearing of land or from construction of the facility, as well as timber and
brush that is not used for habitat mitigation in accordance with conditions related to the
Council's Fish and Wildlife Habitat standard.

9 7) The construction easement shall be limited to 80 feet, except where a narrower or wider 10 construction corridor is required by conditions related to individual Council standards. NWN may deviate from this maximum construction easement width if such deviations are 11 12 authorized by the OOE. To obtain authorization from OOE for a deviation in easement 13 width, NWN must provide OOE with the following information: 1) the location of the 14 requested deviation; 2) the reason(s) for the deviation and any documentation necessary to 15 demonstrate such reasons; 3) the proposed easement width; and 4) measures that NWN will 16 implement to mitigate additional impacts, if any, on resources protected by Council 17 standards.

- In determining whether to approve the requested deviation, OOE shall provide a landowner
 with the opportunity to comment on the requested easement and on mitigation and minimization
 measures. OOE shall approve the requested deviation if it determines:
- i. A landowner has granted a wider easement to accommodate topsoil removal and OOE
 concurs that the wider easement is necessary to accommodate additional topsoil removal;
- ii. A deviation in easement width is necessary to comply with other site certificate conditions;
- 25 iii. A deviation in easement width is required to meet federal pipeline safety standards or
 26 OPUC or OSHA safety standards;
- 27 iv. A deviation in easement width is necessary to accommodate:
- a) Laydown and workspace areas for HDD, slick bore, prefabrication and pipe
 forming areas;
 b) Staging areas for wetland, stream and road crossings and hydrostatic testing
- 31 withdrawal and discharge areas;32 c) Temporary construction parking and pipe a
 - c) Temporary construction parking and pipe and construction material storage; or
 - d) Topsoil and subsoil storage areas for side slope or excess trench depth; or
 - e) Access to the pipeline construction easements [amendment 1]
- v. A deviation in easement width is necessary to avoid irrigation infrastructure, existing
 utilities, or other structures; and
- vi. NWN will implement mitigation measures as consistent with state law and this site
 certificate to mitigate or minimize any additional impacts to resources protected by Council
 Standards.
- 40

33

34

- 8) After construction, the site, as that term is defined in ORS 469.300 and OAR 345-01-0010,
 shall be the 40 foot wide permanent easement between the Bacona Blowdown Station and the
 Molalla Gate Station
- 44

- 9) Before any transfer of ownership of the facility or ownership of the site certificate holder,
 NWN shall inform the Office of Energy of the proposed new owners. The requirements of
 OAR 345-027-0100 apply to any transfer of ownership that requires a transfer of the site
 certificate
- 5

6 10) If the Council finds that the certificate holder has permanently ceased construction or 7 operation of the facility without retiring the substantially as described in Section IV.A.6 of 8 the Proposed Order (Attachment C of the Final Order), the Council may direct the Office to 9 prepare a proposed a final retirement plan for the Council's approval. Upon the Council's 10 approval of the final retirement plan, the Council may draw on the bond or letter of credit described in OAR 345-027-0020(8) to restore the site to a useful, non-hazardous condition 11 12 according to the final retirement plan, in addition to any penalties the Council may impose 13 under OAR Chapter 345, Division 29. If the amount of the bond or letter of credit is 14 insufficient to pay the actual cost of retirement, the certificate holder shall pay any additional 15 cost necessary to restore the site to a useful, non-hazardous condition. After completion of 16 site restoration, the Council shall issue an order to terminate the site certificate if the Council 17 finds that the facility has been retired according to the approved final retirement plan.

18 19

26

B. SITE SPECIFIC CONDITIONS UNDER OAR 345-027-0023

- NWN shall notify OOE, the State Building Codes Division and the Department of Geology and Mineral Industries promptly if site investigations or trenching reveal that subsurface conditions differ significantly from those described in the Application for Site Certificate.
 The Council may, at such time, require the certificate holder to propose additional mitigating actions in consultation with the Department of Geology and Mineral Industries and the Building Codes Division.
- 2) NWN shall notify OOE, the State Building Codes Division and the Department of Geology
 and Mineral Industries promptly if shear zones, artesian aquifers, deformations or clastic
 dikes are found at or in the vicinity of the site.
- 3) NWN shall submit to OOE copies of all incident reports involving the certified pipeline
 required under 49 CFR §192.709.

34 C. MONITORING CONDITIONS UNDER OAR 345-027-0028

- NWN shall establish, in consultation with affected state agencies and local governments,
 monitoring programs as required by the Site Certificate for impact on resources protected by
 the standards of OAR Chapter 345, Divisions 22 and 24 and to ensure compliance with the
 Site Certificate. The programs shall be subject to the review and approval of the Council.
- 39
- A0 2) NWN shall establish monitoring programs as required by permitting agencies and local
 governments, as required by the Site Certificate.
- 42
- 43 3) If NWN becomes aware of a significant environmental change or impact attributable to the
 44 facility, NWN shall submit to OOE as soon as possible a written report identifying the issue
 45 and assessing the impact on the facility and any affected Site Certificate conditions.

3

D. CONDITIONS UNDER **OAR 345-027-0020(10)**

- 1) NWN shall locate the SMPE within the road right-of-way along Davis, Milne, Leisy and
 Pleasant Valley Roads. The maintenance/operation easements for these portions of the site
 shall be within the existing road rights-of-way. The width and location of the construction
 easement for these portions of the site shall be governed by General Land Use Condition 5
 (requiring that the easement be no more than 80 feet in width, beginning at the centerline of
 the road right-of-way).
- 10
- On the Flint property, along Scholls Ferry Road, NWN shall locate the pipeline so as to avoid any disruption to the 100 year old chestnut tree that is being registered as a Heritage Tree.
- 3) NWN shall not use the Alternate Corridor Segment (along Sherwood Road, Stark Road,
 LeBeau, Eastview, and Kruger Road) as shown on panels 24 through 26 of Exhibit K-2 of the
 Application. The other proposed alignments for the Corridor in this segment of the facility
 are not affected by this condition and are available for use, subject to compliance with all
 other applicable conditions.
- 4) All temporary access roads will take the form of a traveled path, except where a court has
 ordered NWN to use another location and that location is permitted by the site certificate.
 NWN shall not apply gravel to any of the farm roads unless the road is already graveled prior
 to their use of it. [amendment 1]
- 5) Temporary access roads outside the 200-foot corridor will be at most 30 feet wide. This
 width was selected to accommodate the simultaneous passage of construction equipment
 (e.g., an 11-foot track hoe) and a 10-foot-wide farm tractor with implements. [amendment 1]
- 6) Once construction and restoration are completed, the Clean Water Services easement will
 only be used by inspectors as a footpath except where there is an existing road. [amendment 1]
- Along the PGE power line right of way, NWN will minimize surface impact by restricting
 right-of-way access to vehicles such as side booms and tractor-mounted winch units. NWN
 will not cut any of the coniferous trees outside of the power transmission right-of-way.
 [amendment 1]
- 8) There will be no clearing, grading, or ground disturbance on the workspaces and access
 routes other than the impact of driving vehicles and storing equipment and material except to
 remove vegetation for fire control. At the Chicken Creek bore laydown area in PGE's rightof-way, brush may be cut back to facilitate side-boom access, but no grading will take place.
 Following construction, the shrubs will be allowed to grow back. This condition is not
 intended to preclude post-construction site restoration activities. [amendment 1]
- 43
 44 9) NWN shall use existing farm roads on the 11 properties (Shirazi, Wetter, Davis, Leach, Parks 45 and Rec, Sweningson, Downey, Klupenger, Anderson, Lais and DeMartini) [amendment 1].
 46
 - 1st Amended Site Certificate NWN South Mist Pipeline Extension 8/28/2003 p.10

1 10) If workspace is needed to accommodate hard surface replacement, an HDD bore, or to enable 2 special construction techniques due to unusual site specific constraints, use of the workspace 3 is contingent on NWN performing the hard surface replacement, bore or other special 4 technique [amendment 1]. 5 6 E. **CONDITIONS RELATED TO EFSC STANDARDS** 7 *Organizational Expertise Standard:* 8 1) NWN shall contractually all contractors and subcontractors involved in the construction and 9 operation of the Project to comply with all applicable laws and regulations and with the terms 10 and conditions of the site certificate. Such contractual provision shall not operate to relieve the certificate holder of responsibility under the site certificate. 11 12 13 2) NWN shall obtain all necessary state and local permits or approvals required for the 14 construction, operation and retirement of the Project. 15 16 Structural Standard: 17 1) NWN shall assess seismically induced damage from slope movement following any 18 earthquake that generates peak ground accelerations in excess of 0.1g along the corridor. 19 20 2) NWN shall design and construct the pipeline substantially in accordance with the 21 recommendations of Appendix H-1 of the Application, Section 6.1: "Hazard Mitigation." 22 23 3) During construction of the pipeline, NWN shall provide that construction is observed by a 24 qualified geo-professional to ensure that the recommendations contained in Appendix H-1 of 25 the Application are implemented properly and that any unforeseen field conditions are 26 reported to NWN. If changes are encountered in the field, NWN shall ensure that the 27 pipeline design is modified to provide for safe installation and operation of the pipeline. 28 29 4) In areas of critical geotechnical importance, trenching will not proceed without confirmation 30 that OOE and DOGAMI have been notified at least one week in advance. This notice is 31 required to afford OOE and DOGAMI the opportunity to send qualified monitoring 32 personnel, which monitoring shall be performed at NWN expense. If NWN provides timely 33 notice, the failure of OOE or DOGAMI to send qualified personnel shall not prevent NWN 34 from performing the specified work. The critical areas are defined as the corridor north of 35 the point where Dairy Creek Road terminates, and the corridor between Brookman and 36 Tooze Roads. 37 38 5) On properties to which NWN has been denied access prior to issue of this site certificate, a 39 registered geologist or geotechnical engineer shall be present during trenching along the ridge north of where Dairy Creek Road terminates, and also on private property between 40 41 Brookman Road and the intersection with Ladd Hill Road, and shall provide to OOE a 42 written record of observations prior to pipeline operation. 43 6) NWN shall follow a schedule of right-of-way monitoring for landslide hazard, based on the 44 45 following criteria:

- immediately after 4 or more inches of rain within 48 hours
- immediately after 6 or more inches of rain within 7 days
- immediately after a rain on snow event that might have a similar effect as either of the above precipitation events.
- Rainfall shall be measured using METARS and RAWS, including Miller Station, as described by URS.
- 7) In addition to strain gauges installed on the pipeline, NWN shall install vertical and
 horizontal inclinometers in appropriate locations to monitor for ground movement in the
 vicinity of the Sherman Mill slide. The installation shall be prior to or concurrent with
 pipeline construction. NWN shall monitor these instruments and report findings to OOE
 yearly after installation. If the instruments indicate ground movement that is different from
 what was predicted in the ASC, NWN shall promptly report to the Council and describe any
 corrective actions necessary to alleviate danger to the pipeline.
- 18 Soil Protection Standard
- NWN shall use erosion prevention techniques and sediment control measures as described in the Erosion Prevention and Sediment Control Manual (December 2000) jointly developed by the Clean Water Agency, Washington County, Clackamas County, and the city of West Linn, or its successor. Use of these measures shall not be limited to Washington County.
- 2) OOE will hire an independent, qualified agricultural inspector to facilitate, verify, document
 and enforce the implementation of the AIMP. This agricultural inspector will work with
 NWN, who will continue to have primary responsibility to implement the measures described
 in the AIMP, in accordance with its terms. NWN will reimburse OOE for the expense of the
 independent agricultural inspector.
- 29

1 2

3

4

5

6 7

8 9

- 3) NWN shall implement the Agricultural Impact Mitigation Plan (AIMP) (October 2001) and all steps contained therein, except that the AIMP shall be modified (1) to require segregation of topsoil to the "A" horizon, as opposed to the 12 inches described in the AIMP, and (2) by the inclusion of an alternate method of topsoil segregation described in Addendum 1 to the AIMP. As a supplement to the AIMP, NWN shall implement the Post Construction Crop Monitoring Plan (PCCMP) (November 2002) and all steps contained therein. The AIMP, including revisions adopted by the Council, is included as Attachment D to the Final Order.
- 4) NWN shall design and construct the pipeline substantially in accordance with the
 representations made in Exhibit I of the Application for Site Certificate, March 2001.
 Mitigation steps that are described in Exhibit I and are not listed in the AIMP are nonetheless
 considered binding commitments by NWN and shall apply.
- 43 5) Site specific mitigation measures shall be tailored to the soil type, as listed in Tables I-2, I-3
 44 and I-4 of the ASC.
- 45

- NWN shall certify that all NWN and contract supervisory personnel with construction
 responsibility are trained in the specific mitigation requirements described in Exhibit I, the
 Agricultural Impact Mitigation Plan, and the Council's final order. Plans, subject matter, and
 the schedule for this training shall be made available to OOE and ODA prior to start of
 construction.
- 6 7 Land Use Standard
- 8 General Land Use Conditions
- 9 1) <u>Definition of "Easement."</u> For purposes of the conditions contained in this order and site certificate, the term "easement" means both the area within an existing public road or highway right-of-way within which the construction, operation and/or maintenance of the facility is authorized by a county or state permit or other similar governmental authorization, and any adjoining easement area outside of the right-of-way.
- 14
- 15 2) Permanent Easement: Arterials and Collectors in an EFU Zone. Where the corridor includes 16 existing public road or highway right-of-way (whether or not that right-of-way is improved) 17 within an EFU district, and the road or highway is classified by the county or by the state as 18 an arterial or collector road, the maintenance/operation easement for that portion of the 19 facility shall be located so that the edge of the easement begins at the centerline of the right 20 of way. In addition, the width of the maintenance/operation easement for this portion of the facility may extend beyond the edge of existing public road or highway right-of-way by up to 21 22 20 feet.
- 23
- 24 3) Construction Easement: Arterials and Collectors in an EFU Zone. Where the corridor 25 includes existing public road or highway right-of-way (whether or not that right-of-way is 26 improved) within an EFU district, and the road or highway is classified by the county or by the state as an arterial or collector road, the construction easement for that portion of the 27 28 facility shall be located so that the edge of the easement begins at the centerline of the right 29 of way. In addition, the width of the construction easement for this portion of the facility 30 may extend beyond the edge of existing public road or highway right-of-way by up to 50 31 feet. 32
- 4) <u>Permanent Easement: Local Roads</u> in an EFU Zone. Where the corridor includes existing public road or highway right-of-way (whether or not that right-of-way is improved) within an EFU district, and the road or highway is classified by the county or by the state as a local road, the maintenance/operation easement for that portion of the facility shall be located so that the edge of the easement begins at the centerline of the right of way. In addition, the width of the maintenance/operation easement for this portion of the facility is limited to no more than 40 feet, measured from the centerline of the road right-of-way.
- 40

5) Construction Easement: Local Roads in an EFU Zone. Where the corridor includes existing
public road or highway right-of-way (whether or not that right-of-way is improved) within an
EFU district, and the road or highway is classified by the county or by the state as a local
road, the construction easement for that portion of the facility shall be located so that the
edge of the easement begins at the centerline of the right of way. In addition, the width of

^{1&}lt;sup>st</sup> Amended Site Certificate NWN South Mist Pipeline Extension 8/28/2003 p.13

the construction easement for this portion of the facility is limited to no more than 80 feet,
 measured from the centerline of the road right-of-way.

3

13

4 6) General Width Restrictions (All Zones). Unless otherwise allowed by these conditions, the 5 permanent easements for the facility are limited to no more than 40 feet in width, and the 6 temporary/construction easements are limited to no more than 80 feet in width. See also. 7 Mandatory Conditions 7 and 8. In the event of any conflict between this condition, 8 conditions 2-5 above, or mandatory conditions 7 or 8, the following priority shall control: (a) 9 Mandatory Condition 7 shall take first priority in the event of any conflict involving a 10 temporary/construction easement; (b) General Land Use Conditions 2-5 shall take next priority; and (c) the general widths of 40 and 80 feet specified in this condition and in 11 12 mandatory conditions 7 and 8 shall control to the extent that (a) and/or (b) do not.

- 7) <u>Conflict with Existing Utility Lines.</u> Notwithstanding conditions 2, 4 and 6, above, where
 there are existing utility lines in that portion of the public road or highway right-of-way
 where the facility would otherwise be located, the maintenance/operation easements for the
 facility may extend outside of the existing road or highway right-of-way by up to 20 feet,
 regardless of the classification of the road and regardless of the resulting overall width of the
 easement.
- 8) <u>Conflict with Safety Regulations.</u> Notwithstanding conditions 2, 4 and 6, above, the
 maintenance/operation easements for the facility may extend further outside of existing road
 or highway right-of-way (than otherwise allowed by conditions 1-7, above) where necessary
 to comply with safety regulations of Oregon Occupational Safety and Health Administration
 or the Oregon Public Utilities Commission.
- 9) <u>Split Zone Corridor.</u> Where the corridor includes lands on both sides of a public road, and those lands are zoned EFU only on one side of the road, NWN shall locate the facility on the side of the road that is not zoned EFU except where NWN demonstrates that it would be necessary to remove or displace a building to stay on the non-EFU side. This condition may be relaxed if using the non-EFU side would unavoidably result in the pipeline being less than 40 feet from a building used for human occupancy.
- 33

34 10) Avoidance of Category 1 or Category 2 Habitat. If the construction or permanent easements 35 in or adjacent to road right-of-way would affect Category 1 or Category 2 habitat as described in section IV.7 of the Proposed Order (Attachment C of the Council's final order), 36 37 the construction or permanent easement may be sited on land in the EFU zone that is not 38 within the existing road right-of-way, to the extent necessary to avoid Category 1 or 2 habitat. In such cases the easement shall be located as close to the road right-of-way as 39 40 possible. This permission shall not apply if the habitat will be avoided through HDD or other 41 boring techniques. EFU land that is not in the public road right-of-way shall not be used to 42 avoid habitat of category 3 or lower.

43

- 11) Where the corridor for the facility includes the right-of-way of the existing South Mist
 Feeder line, the permanent easement for the facility shall follow the existing SMF line and
 the width of the right-of-way for the two pipelines shall not exceed 40 feet.
- 4

5 12) Easements allowed under Amendment #1. (a) Notwithstanding conditions 2 and 6, the permanent maintenance easements on the Nordstrom and Schmidt Limited Partnership 6 7 properties (NWN Application for Amendment 1 Exhibit 4 panel 40) may be 60 feet in total 8 width including 30 feet of private easement, where the easement includes the drip lines of an 9 ash tree (Nordstrom property) and an oak tree (Schmidt property) and a permanent access 10 easement is allowed access the Clean Water Services property on panel 14. (b) Notwithstanding conditions 3,5 and 6: (1) if a landowner requests topsoil storage on the 11 12 landowner's property in a location outside the 80-foot easement width, NW Natural may 13 acquire and utilize a temporary easement covering such other location. The selected location 14 may not alter the contour or drainage in any flood hazard zone and may not affect any 15 wetland as that term is defined in the Oregon State Land Division's wetland delineation 16 criteria. All topsoil so stored shall be returned to its original location in or along the pipeline 17 trench.; and (2) the temporary access and construction laydown easements described and 18 shown in Exhibits 3, 4 and 5 to Application for Amendment 1 to the site certificate are 19 authorized. [amendment 1] 20 21 Wash. Co. Floodplain and Drainage Hazard Regulations (WCC § 421), Erosion Control 22 Regulations (WCC § 426), and Grading and Drainage Regulations (WCC § 410): 23 24 1) NWN shall obtain from the Washington County Operations Division, and its equivalent in 25 Clackamas and Marion counties, all required utility permits to allow construction of the 26 pipeline within the County road right-of-way. A copy of the permit shall be submitted to the 27 Land Use planner for that county. 28 29 2) NWN shall provide the Washington County Land Development Division Project Planner, 30 and the equivalent in Clackamas and Marion counties, with a copy of any permits from the Oregon Division of State Lands and/or the U.S. Army Corps of Engineers for work that will 31 32 be done in flood plain areas within those counties. 33 34 3) Prior to construction, NWN shall provide Washington County with the detailed grading plan 35 and obtain a grading permit from Washington County pursuant to WCC § 410. 36 4) NWN shall obtain equivalent utility and grading and drainage permits in Clackamas and 37 38 Marion Counties as applicable. 39 40 5) Prior to construction, NWN shall provide the Washington County Land Use Department with 41 the floodplain delineations meeting the requirements of WCC 421-1.2 A, B, and C. 42 43 6) Prior to construction, NWN shall submit detailed topographic information meeting the 44 requirements of WC 421-3, prepared by civil engineer registered in Oregon. 45

1 7) NWN shall implement the mitigation measures in the "Flood Hazard Impact Mitigation Plan" 2 submitted as Appendix K-10 of the ASC. 3 4 8) NWN shall provide a statement by a registered civil engineer affirming that the pipeline 5 confirms with the standards of WCC § 421-10. 6 7 9) NWN shall perform any maintenance on the maintenance easement outside public right of 8 way by means of hand implements (under WCC 421-14 lawn mowers are considered hand 9 implements). 10 10) Excess soils generated by trench excavation and backfill shall be hauled off of the pipeline 11 12 alignment and disposed of in an approved fill site area. Surface conditions shall be restored 13 to pre-construction slopes and grades and disturbed areas shall be revegetated. 14 15 11) If the pipeline crosses a stream or drainage hazard area, it shall be installed six feet below the 16 bottom of the natural channel. The channel shall be restored to its original conditions. 17 18 12) NWN shall allow no above ground structures that will catch debris or impede floodwater 19 flow. Protective fencing required around above ground facilities shall be designed not to 20 impeded floodwater flow. 21 22 13) The existing grades and dimensions of the floodway shall not be changed. Trench 23 excavations that have disturbed vegetation shall be revegetated. 24 25 14) NWN shall not dump fill material in a flood area without a permit from Washington County. 26 27 15) NWN shall equalize cut and fill and shall certify at the completion of construction of the 28 pipeline that no net fill has occurred in flood hazard areas, except for post-construction 29 "crowning" to allow for soil settlement. 30 31 16) NWN shall observe Washington County's preference for enhancement of riparian habitats 32 through planting or other such improvements. WCC Section 421-4.6B recommends the 33 planting of "at least 5 plants per 100 feet of bank area." 34 35 17) NWN shall implement the Erosion and Sediment Control Plan submitted as ASC Exhibit K-11. Note – the Washington County 1991 Manual is replaced by the CWA Erosion 36 37 Prevention and Sediment Control Manual dated 12/2000 38 39 18) Prior to construction, NWN shall provide OOE with documentation of Washington County 40 review of the final Erosion Control Plan. 41 42 19) Other conditions requested by affected local governments: 43

1	20) For any section of the pipe placed under the road, NWN shall restore the road to pre-
2	construction condition or better, and to a standard designed for normal traffic loading for a 20
3	year life.
4 5	21) NWN shall consult with the appropriate County's operations department regarding load
6	capacity for any bridges utilized during construction.
7	capacity for any oneges utilized during construction.
8	22) NWN shall coordinate any road closures through the affected County.
9	
10	23) NWN shall not deposit spoils from the Tualatin Valley highway bore within the M-2 district
11	in Hillsboro.
12	
13	24) Construction hours for the project are 7:00 AM until 7:00 PM daily expect for Sundays. If
14	work is proposed after these hours or on Sunday, NWN must obtain a variance from
15	Washington County noise standards.
16	
17	25) NWN shall contact the Oregon Heritage Tree program during planning and construction to
18	protect the tree resource located on highway 219 south of Hillsboro.
19	
20	Agricultural Mitigation Conditions under ORS 215.275(5)
21 22	1) Crops prohibited over the pipeline shall be limited to mature fruit and nut trees, and ball and
23	burlap nursery crops and other crops that require any mechanical digging or hand digging
24	deeper than 3 feet. Additionally, Christmas trees that are more than 10 years old, fence posts
25	and other support posts, and other large trees shall be prohibited. Such crops and posts shall
26	not be allowed within 5 feet of the pipe centerline, for a total width of 10 feet. Farmers may
27	install fencing or cross the pipeline above or below the pipe for water service and drainage
28	with prior notification to and written approval by NWN, which approval shall not be
29	unreasonably withheld. Permanent surface structures and permanent reforestation activities
30	are prohibited over the entire 40-foot permanent easement area.
31	
32	2) NWN shall not preclude use of propane blasters for gopher control on private property near
33 24	the easement. The company shall analyze and negotiate the use of such equipment in close
34 35	proximity to the pipeline.
35 36	Site Specific Land Use Conditions
30 37	Site speeme Land Ose Conditions
38	1) In the corridor along Brookman Road, NWN shall locate the pipeline either within road right
39	of way or in exception lands to the north of the road, unless
40	a) NWN submits evidence to the Council that it has attempted to obtain the necessary
41	wetlands permits from DSL and the US Army Corps of Engineers and cannot obtain
42	one; or
43	b) NWN obtains concurrence from OOE that the category 3 habitat cannot feasibly be
44	mitigated consistent with the ODFW Habitat Mitigation Goals as required by OAR
45	345-022-0060.

- 2 2) Along Dryland, Zimmerman and Heinz Roads, the SMPE shall be located within the3 Preferred Corridor.
- 4 5 6

22

27

1

Special Conditions for Temporary Laydown Area

Prior to the temporary, construction-related use of any laydown area shown on Appendix K-2
 of the ASC, as supplemented in July 2001, that is outside the 200-foot pipeline corridor (the
 temporary laydown areas), NWN shall provide the Office of Energy with a map, aerial
 photograph or other depiction of the proposed temporary laydown area, together with a
 description of the temporary laydown area, including the zoning, physical conditions,
 existing uses, and any fieldwork studies performed at the temporary laydown area.

- 14 2) Use of the temporary laydown areas shall conclude within one month of the date construction
 15 is complete. Mitigation for impacts to habitat and farm land shall be completed as soon as
 16 reasonably possible after the temporary use is concluded.
 17
- 3) The temporary laydown area shall not (1) be located within an area identified as Category 1
 or 2 habitat; or (2) contain threatened or endangered species identified in Exhibit Q. It is
 expressly understood that the approval is only for temporary uses and no permanent uses will
 be allowed in these areas.
- 4) NWN shall restore, as nearly as possible, to its former condition any agricultural land and
 associated improvements that are damaged or otherwise disturbed by the siting, maintenance,
 repair or reconstruction of the facility. Mitigation conditions applicable under the Council's
 Soils standard, OAR 345-022-0022, shall apply to any temporary laydown area.
- S) Conditions (1) through (4) above shall apply to the temporary easements described in
 Exhibits 3,4, and 5 of Application for Amendment 1. [amendment 1]
- 3031 Protected Areas Standard
- During construction of the pipeline Willamette River crossing, NWN shall protect riparian areas on both sides of the river by locating all bore holes for directional drilling at least 200 feet from the river's edge on the north side of the river, and 400 feet from the edge on the south side of the river.
- 36

37 Retirement and Financial Assurance Standard

- Prior to beginning construction, the certificate holder shall submit to the State of Oregon
 through the Council a bond or letter of credit in the amount of \$700,000 (in 2001 dollars)
 naming the State of Oregon, acting by and through the Council, as beneficiary or payee.
- a) The calculation of 2001 dollars shall be made using the U.S. Gross Domestic Product
 Implicit Price Deflator, as published by the U. S. Department of Commerce, Bureau of
 Economic Analysis, or any successor agency (the "Index"). The amount of the bond or
 letter of credit account shall increase annually by the percentage increase in the Index and
 shall be pro-rated within the year to the date of retirement. If, at any time, the Index is no

1 2		longer published, the Council shall select a comparable calculation of 2001 dollars. The form of the bond or letter of credit and identity of the issuer shall be subject to approval
3 4 5 6		by the Council.b) The bond or letter of credit shall not be subject to revocation or reduction prior to the certificate holder's satisfaction of Condition (2) below.
7 8 9 10 11 12	2)	Upon completion of construction, NWN may reduce the amount of the bond or letter of credit to \$86,000 (in 2001 dollars) naming the State of Oregon, acting by and through the Council, as beneficiary or payee (the "Retirement Fund"). The calculation of 2001 dollars shall be made using the Index. The form of the Retirement Fund and identity of the issuer of the bond or letter of credit shall be subject to approval by the Council. The Retirement Fund shall not be subject to revocation or reduction prior to retirement of the energy facility.
13 14 15 16	3)	The certificate holder shall describe the status of the Retirement Fund in the annual report submitted to the Council, pursuant to OAR 345-026-0080.
17 18 19 20	4)	If the project is halted prior to completion, NWN shall restore any right of way that has been disturbed. NWN shall be responsible for backfilling of any open ditch, revegetation and restoration costs and any damages to rights of way as specified in easements.
20 21 22 23 24 25 26 27 28 29 30 31 32 33	5)	 Prior to termination of the Site Certificate, NWN shall retire the site sufficiently to restore it to a useful condition. Site restoration shall include, but not be limited to, steps to: (a) Remove any hazardous material stored in buildings or located in process equipment and dispose of them following applicable state hazardous materials statutes and rules, (b) Remove above ground portions of all pipelines, and cut and cap the remaining portion in five mile increments and at each end. NWN shall purge the pipeline to ensure that all natural gas is removed. (c) If necessary, revegetate the area, including pipeline right of ways, to prevent erosion and encourage habitat development, (b) Inspect all pipelines and remove any hazardous materials found, and dispose of hazardous materials generated from cleaning the pipelines in accordance with applicable state hazardous materials statutes and rules.
 33 34 35 36 37 38 39 40 41 42 43 44 45 	6)	If the Council finds that NWN has permanently ceased construction or operation of the SMPE without retiring the SMPE according to a final retirement plan approved by the Council as described in OAR 345-027-0110, the Council shall notify NWN and request that NWN submit a proposed final retirement plan to the Office within a reasonable amount of time, not to exceed 90 days. If NWN does not submit a proposed final retirement plan by the specified date, the Council may direct the Office to prepare a proposed final retirement plan for the Council's approval. Upon the Council's approval of the final retirement plan, the Council may draw on the bond or letter of credit described in condition (1) of this section to restore the site to a useful, non-hazardous condition according to the final retirement plan, in additional to any penalties the Council may impose under OAR Chapter 345 Division 29. If the amount of the bond or letter of credit is insufficient to pay the actual cost of retirement, the certificate holder shall pay any additional cost necessary to restore the site to a useful,

- non-hazardous condition. After completion of site restoration, the Council shall issue an
 order to terminate the site certificate if the Council finds that the SMPE has been retired
 according to the approved retirement plan.
- 4

5 Fish and Wildlife Habitat Standard

- 6 <u>General</u>
- NWN shall take appropriate and reasonable measures to first avoid, then reduce, then restore,
 and then compensate for impacts to fish and wildlife habitat that result from construction and
 operation of the proposed project consistent with that habitat category.
- 10

13

- NWN shall reimburse the Office of Energy for costs associated with on-site construction
 inspection monitoring by either OOE or ODFW.
- 14 3) NWN shall construct the pipeline within the construction corridor along the preferred 15 alignment (the "preferred alignment construction corridor") that was the basis for 16 Supplemental Table P-4 (May 15, 2002), Supplemental Table P-5 (March 5, 2002) and the memo from Meehan, OOE, to Hayward, NWN, dated May 22, 2002, and the Hayward reply 17 to Meehan dated June 12, 2002. NWN may deviate from this construction corridor if there is 18 19 a conflict with other conditions of the site certificate, requirements of other state, local or 20 federal agencies, public health and safety, or if new information is discovered during 21 construction that was not known prior to issuance of the site certificate. 22
- 23 4) Where NWN must deviate from the preferred alignment construction corridor within the 200-24 foot Preferred Corridor or an Alternative Corridor Segment, NWN shall obtain permission 25 from OOE for the following deviations: 1) any stream crossing that will not be bored as shown in Supplemental Table P-4 (May 15, 2002); 2) any deviation that would result in 26 27 impact to a wetland with a higher status code than shown in the April 9, 2002 PHS table; 3) 28 any deviation that would result in impact to Category 3 upland habitat subtypes (as described 29 in Table P-1, Exhibit P) as shown in Supplemental Table P-5 (March 5, 2002). NWN shall 30 not begin construction in a deviation until it has notified OOE and the OOE has approved the requested deviation. 31 32
- 33 5) To obtain permission from the OOE for a deviation from the preferred alignment 34 construction corridor, NWN must provide OOE the following information prior to disturbing 35 the deviation area: 1) the location of the requested deviation; 2) the habitat categories and habitat subtypes of the original preferred alignment construction corridor referenced to 36 37 Supplemental Table P-4 (May 15, 2002), Supplemental Table P-5 (March 5, 2002) and the 38 PHS April 9, 2002 table; 2) the habitat categories and habitat subtypes within the requested 39 deviation referenced to the tables listed above; 3) the number of trees greater than 6-inch dbh 40 that would be removed; 4) the reason for the deviation; and 5) any measures that NWN proposes to use to limit impact to fish and wildlife habitat in the deviation. If the deviation is 41 42 due to unanticipated conditions during excavation, NWN shall notify OOE using the field 43 method described in the following paragraph. 44
- 45 The field method includes the following steps:

1		
1		(1) Identification of a machine with construction in a neuticular second at the
2		(1) Identification of a problem with construction in a particular segment of the
3		original preferred alignment;
4		(2) Identification of an alternative segment;
5		(3) Verbal notification of the Office of Energy and, as appropriate, other
6		agencies;
7		(4) Technical review of the alternative segment to ensure that construction in the
8		alternative segment, taking mitigation into account, would not result in
9		significant adverse impacts to resources protected by Council standards or
10		other permitting criteria;
11		(5) Review of zoning to ensure compliance with local land use laws;
12		(6) Provision of information from steps (4) and (5) to OOE;
13		(7) OOE site inspection, with involvement of other agency personnel, as
14		appropriate; and
15		(8) OOE concurrence, generally verbal, with construction in the alternative
16		segment.
17		
18	6)	The decision criteria for OOE approval of a deviation requested by NWN shall include: 1)
19		whether the deviation would result in a smaller area of impact; 2) whether the deviation
20		would result in impact to the same, a lower or a higher category habitat; and 3) whether
21		NWN provided appropriate documentation to OOE within the necessary time frame.
22		
23	7)	NWN shall plan, construct, operate, restore, maintain and monitor and the project site
24		consistent with the measures identified in its September 2001 Wetland Mitigation Plan,
25		Section 2.5 "Construction Techniques" pages 2-4 to 2-11; Section 4.0 "Conceptual
26		Mitigation Approach" pages 4-1 to 4-2; Section 5.0 "Proposed Conceptual Mitigation" pages
27		5-1 to 5-3; Section 7.0 "Monitoring" page 7-1; and Section 8.0 "Maintenance and
28		Contingency Plan" page 8-1.
29		
30	8)	NWN shall plan, construct, operate, restore, maintain and monitor the project consistent with
31		the measures identified in its September 2001 Habitat Mitigation Plan, Section 2.2
32		"Mitigation Goals" page 2-4; Section 2.5 "Construction Techniques" page 2-5; Section 4.0
33		"Proposed Conceptual Mitigation by Category" pages 4-1 to 4-3; Section 5.0 "Performance
34		Goals" page 5-1; Section 6.0 "Monitoring" page 6-1; and Section 7.0 "Maintenance Plan"
35		page 7-1.
36		
37	9)	NWN shall plan, construct, operate, restore, maintain and monitor the project consistent with
38		the measure identified in Exhibit P of its March 2001 application for site certificate as
39		supplemented by the June 2001 supplemental Exhibit P.
40		
41	10) NWN shall construct the project so as to avoid disturbance to all Category 1 habitat and all
42		Category 2 permanent ponds.
43	_	
44	11) NWN shall provide a net-benefit to Category 2 habitats that are disturbed by construction.
45		This may include, but is not limited to, placing large woody debris, clean sand, gravel and
	1 st	
	1.,	Amended Site Certificate NWN South Mist Pipeline Extension 8/28/2003 p.21

1 rocks within the stream channel at or near the crossing location of Category 2 streams, 2 enhancing habitat quality by planting trees and other woody vegetation or by other measures 3 that provide a net benefit that is acceptable to the Office of Energy in consultation with the 4 Oregon Department of Fish and Wildlife. 5 6 12) NWN shall use Best Management Practices (BMPs) to confine construction-related 7 disturbance to the construction corridor 8 9 13) NWN shall not disturb wetland areas, riparian areas, or waterways until it has obtained all 10 required section 401 and section 404 permits and approvals, including any required authorization relating to a federally-listed threatened or endangered species. If the conditions 11 12 in the amended site certificate conflict with conditions imposed by the DEQ in its section 401 13 certification or the U.S. Army Corps in its section 404 permit, NWN shall consult with OOE and ODFW to resolve the conflict before beginning construction 14 15 16 Pre-construction 17 14) NWN shall incorporate the conditions of the site certificate into its construction documents. 18 19 15) NWN shall provide a copy of its construction documents to the Office before beginning 20 ground-disturbing activity (such as clearing or grading the construction corridor). These shall include five complete sets of detailed maps of the construction corridor that are cross 21 22 referenced or indexed to habitat category maps provided to OOE. 23 24 16) NWN shall mark the construction corridor to indicate areas where the corridor will be 25 restricted to avoid impact to wetlands, riparian areas, streams and other sensitive, important 26 or significant areas before any ground-disturbing activity (including clearing of vegetation). 27 OOE shall be notified when marking is completed and OOE inspectors shall be afforded the 28 opportunity to inspect the marked construction corridor prior to any ground-disturbing 29 activity. 30 31 17) NWN shall document pre-construction conditions at each Category 2 and 3 site within the 32 construction corridor prior to any ground disturbing activity. Documentation shall include an 33 Impact Inventory, including a cross reference to habitat and construction maps, description of 34 the habitat category and habitat unit to be impacted, the number of trees and sizes to be 35 removed, percent native shrub coverage, percent reed canary grass and noxious weed 36 coverage, the acreage of the impacts and photographs of all stream crossings prior to clearing. The Impact Inventory will form the basis of the mitigation and will be included in 37 38 the Detailed Mitigation Plan. The Impact Inventory shall be prepared by a qualified 39 biologist. 40 41 18) NWN shall give the Office at least 7 days notice before beginning ground-disturbing activity. 42 43 19) NWN shall designate a qualified Environmental Inspector to work on all phases of the 44 project, including pre-construction documentation, pipeline construction, restoration, post 45 construction monitoring and preparation of the Detailed Mitigation Plan. The Environmental 1st Amended Site Certificate NWN South Mist Pipeline Extension 8/28/2003 p.22

- Inspector shall have the authority to stop construction activity temporarily to resolve
 environmental issues.
- 20) NWN shall, before beginning ground-disturbing activity, identify to the Office the key
 personnel responsible for construction and environmental protection, including but not
 limited to NWN environmental inspectors and the pipeline construction company's
 environmental inspectors.
- 9 21) NWN shall, before beginning ground-disturbing activity, conduct training of key employees
 and contractor personnel. Training shall cover applicable environmental regulations,
 including site certificate conditions that relate to fish and wildlife habitat, and NWN
 procedures for limiting impact to fish and wildlife habitat. NWN shall provide the Office
 advance notice of the time and place of training sessions and shall allow Office
 representatives to attend training sessions.
- 1516 Construction
- 22) NWN shall use straw and straw bales of oats, wheat, barley and red fescue that are certified
 to be free of noxious (as that term is defined in ODA regulation) and nuisance weed
 contamination for both temporary and permanent erosion control in all category 1, 2 and 3
- habitats, including uplands (Exhibit I, pages I-42, 43, 49, AIMP 18, 19)
- 22 23) NWN shall use topsoil protection measures on all Category 2 and 3 habitats, including 23 upland habitats shown in Table P-1 (March 2001 Application), except permanent ponds (PP2 24 and PP3). Topsoil and subsoil shall be removed and stored separately and backfilled in the 25 reverse order (Conceptual Mitigation Plan, Part 1, Section 2 and CMP, Part 2, Section 2.5). 26 If excavated topsoil contains plants proposed for salvage and re-planting, it shall be replaced within 24-hours. If the topsoil needs to be stored for more than 1 day, it will be covered with 27 28 geotextile fabric and moistened to prevent drying and to ensure the viability of the plant 29 species present (CMP, Part 1, Section 5.1).
- 30
- 24) NWN shall, as necessary, use soil compaction mitigation measures on all Category 2 and 3
 habitats, including uplands. Backfilled soils shall resemble pre-construction soil profiles and
 compacted soil surfaces shall be hand raked or scarified by appropriate equipment prior to
 seeding.
- 25) NWN shall use, if necessary, imported soil that is free of noxious weeds and reed
 canarygrass in Category 2 and 3 habitats, including uplands. NWN shall, prior to
 construction, submit to the Oregon Office of Energy the procedures it will use to ensure that
 imported soils are free of noxious weeds and reed canarygrass.
- 40
- 26) NWN shall reduce and control increased sediment and turbidity by: 1) locating crossings to
 avoid unstable stream banks and the need to remove large trees; 2) dewatering the
 construction reach during construction (by using a dam-and-flume or hose-and-pump to pass
 water around the construction area); 3) routing water pumped from trenchlines to temporary
 surface water detention facilities prior to discharge; 4) using erosion and sediment controls
 - 1st Amended Site Certificate NWN South Mist Pipeline Extension 8/28/2003 p.23

1 during and after construction; 5) monitoring turbidity during construction; 6) stabilizing 2 stream banks and stream beds after construction; and 7) any other measures that may be 3 appropriate. 4 5 27) NWN shall prevent stream bank instability after construction by: 1) locating crossings to 6 avoid unstable stream banks and the need to remove large trees; 2) stabilizing affected stream 7 banks and 3) using Best Management Practices (BMPs) to control slope erosion after 8 construction. 9 10 28) NWN shall prevent stream bed erosion after construction by restoring stream beds to their original condition (substrate and gradient), using appropriate geotextile fabrics or other 11 12 measures, and adding large rocks and or gravel if needed. 13 14 29) NWN shall prevent loss of spawning substrate by restoring stream beds to their original 15 conditions, including replacing spawning gravels, and using appropriate measures to control 16 or prevent the movement of soil and silt into streams. 17 18 30) NWN shall reduce the direct impacts to wetland habitats by: 1) confining construction 19 activities to a 40-foot wide construction corridor and minimizing heavy equipment use within 20 wetlands to the extent practicable; 2) constructing in wetlands when they are dry, to the 21 extent practicable; 3) using construction mats when appropriate; 4) removing topsoil 22 (including plant roots) from the trench separately from subsoil, stockpiling topsoil and 23 subsoil separately and placing the topsoil (including plant roots) on top of the subsoil when 24 backfilling the trench; 5) installing water barriers along the pipeline trench and restoring 25 impermeable soils to prevent draining wetlands; 6) using Best Management Practices 26 (BMPs) to control erosion and turbidity and to prevent movement of loose soil beyond the 27 construction corridor. 28 29 31) Where wetlands and streams must be crossed, the pipeline will be routed through the least 30 sensitive portions of the wetland or stream if it is feasible. The scrub-shrub and forested 31 portions of wetlands and riparian areas shall be avoided to the greatest extent possible. 32 33 32) Construction staging areas shall be located in upland and clearly marked with signs and 34 temporary fencing. 35 36 33) Equipment refueling shall occur a minimum of 100 feet from any wetland or stream channel 37 and within a designated area. The refueling station should be equipped with appropriate 38 hazardous spill containment/clean up materials. 39 40 34) Construction through streams with flowing water and adjacent wetlands will occur during the 41 designated ODFW-approved "in-water work times". 42 43 35) NWN shall complete each stream crossing within a 24-hour period, if practicable. If the 44 crossings require more than 24 hours to complete, appropriate methods to allow upstream

- and downstream fish passage for all life stages shall be implemented using methods approved
 by ODFW.
 3
- 36) NWN shall provide a qualified biologist on-site to prevent stranding fish and large aquatic
 invertebrates in the diversion reach during construction across Category 2 and Category 3
 streams. The qualified biologist must be authorized by NWN to have stop activity authority
 if necessary to prevent stranding fish and large aquatic invertebrates.
- 8

- 37) All flow diversions shall be removed and the hydrology of the site restored immediately after
 completion of construction. The stream channel morphology shall be restored to preconstruction conditions including riffle-pool morphology and stream channel substrate. In
 streams with gravel bottoms, appropriate sized gravel from local sources will be used to
 replace any stream gravels that are lost as a result of construction. Streambanks will be
 stabilized and revegetated as soon as practical after construction is completed.
- 38) NWN shall locate stream crossings to avoid removal of large (>6" dbh) trees where
 practicable and reduce the construction corridor from 80 feet in width to 40 feet within
 riparian and wetland habitats.
- 39) NWN shall provide new woody debris in Category 2 habitats where appropriate and as
 necessary to provide a net benefit in habitat quantity or quality as determined by a qualified
 fisheries biologist. In-stream woody debris dimension, structure design and placement shall
 conform to criteria outlined in A Guide to Placing large Wood in Streams, May 1995
 (Oregon Department of Forestry and Oregon Department of Fish and Wildlife), as
 determined by a qualified fisheries biologist.
- 26
- 40) In wetlands and riparian areas, vegetation that must be removed will be cut at ground level,
 leaving the root system intact. Pulling tree stumps and associated grading activities will be
 limited to those tree stumps that would directly interfere with trenching, pipe installation and
 backfill.
- 31
- 41) Clay trench plugs will be used to prevent diversion of subsurface water from wetlands.
 Trench plugs will be installed at each end of wetland crossings to prevent diversion of
 subsurface water from wetlands and avoid changes to wetland hydrology. An environmental
 monitor will inspect the pipeline trench to check for impermeable soil layers that may be
 penetrated during trenching. If impermeable layers are found in the trench, they will be
 avoided where this is possible, or repaired with clay plugs after the pipe is in place. Clay
 barriers should be installed on each side of any wetland crossing site.
- 39
- 40 42) Matting will be used where this is necessary to support construction equipment in wetlands.
 41 Heavy construction equipment may work without construction mats in wetlands that are
 42 farmed, grazed or dry enough to support the equipment. In wetlands that are not dry enough
 43 to support the equipment, all construction activities will be carried out from the matting.
 44 Where matting is necessary, equipment will not be allowed in the wetland off the mats, at

any time. The mats will be cleaned and inspected prior to placing in the wetland and mats
 with foreign material will not be used.

4 43) Any trees felled within category 2 and 3 habitats shall remain within the habitat site as
5 woody debris. Trees felled within the riparian area shall be used on site for instream habitat
6 structures. If possible the trees should be pushed over to maintain the root ball with the tree
7 trunk.

44) NWN shall replant appropriate species and numbers of trees or shrubs as indicated by the
Impact Inventory in all Category 2 and Category 3 habitats in which NWN removes trees or
shrubs. Shrubs or trees less than 6-inch dbh shall be replaced at a 1-to 1 ratio. Trees equal to
or greater than 6-inch dbh shall be replacement ratio as follows:

13

Size of Tree to be removed	Number of trees to be
(inches dbh)	planted (24-36" height)
6 to 12	4
13-18	6
19-24	8
25-30	10
	12
Over 30	

14

17

22

45) NWN may salvage and restore native plants removed intact from the pipeline trenching area.

- 46) NWN shall, at an appropriate location, thoroughly clean each unit of construction equipment
 with high-pressure washing before the initial move of that unit to the construction site. NWN
 shall, at an appropriate site, clean all construction mats that have been previously used before
 moving them to the construction site or placing them in a wetland.
- 47) NWN shall, at appropriate locations, thoroughly clean each unit of construction equipment
 before working in category 2 or 3 wetlands.
- 48) NWN shall restore the construction corridor in category 2 and 3 habitats by replanting and
 seeding with an approved seed mix to re-establish vegetation. NWN shall provide OOE the
 proposed ODFW-approved seed mix for review and approval prior to ground disturbing
 activity. Substitutions to the approved seed mixes must be approved by OOE.
- 30
- 49) The following actions must be performed immediately after backfilling the trench in trenched areas: (1) installation of erosion control measures; (2) seeding and mulching of exposed soils;
 (3) returning all stream beds and banks to pre-construction grade; (4) restoration of salvaged plant materials and; (5) placement of woody debris.
- 50) NWN must plant trees and shrubs, as indicated by the Impact Inventory and the Detailed
 Mitigation Plan approved by OOE, within 1 year of construction.

1
2 51) NWN shall prepare and submit to OOE for review an Impact Inventory protocol prior to
3 ground disturbing activity. The protocol shall include a standardized data sheet and
4 inventory format with all information stated in Condition 17, as well as cross references to
5 habitat and construction maps. Copies of the field-completed impact inventory forms shall
6 be available for review by OOE inspectors at the job site.

8 52) In the event of a release of drilling mud as a result of boring operations during pipeline 9 construction. NWN shall stop the boring operation until a siltation fence is placed around the 10 release point. NWN shall insure that the release point is fully encircled with siltation fencing and that the fencing effectively contains the released mud. The drilling mud will be allowed 11 12 to vent into the enclosure. NWN shall pump drilling mud from the enclosed area as needed 13 until the boring operation is completed. If the enclosure becomes nearly full, NWN shall 14 remove the drilling mud via a vacuum truck or pump depending on accessibility to the site. 15 NWN shall leave the siltation fencing in place during the boring, back reaming, and pipe-16 pulling procedures, and until the vent has sealed. NWN shall not remove the enclosure until 17 all evidence of the release has ceased.

19 <u>Post-Construction</u>

18

20

25

26

31

32

33

34

- 53) NWN shall prepare and submit to OOE a Detailed Mitigation Plan (DMP) within 60 days
 following the "used and useful" declaration to the OPUC.
- 24 54) In the DMP, NWN shall:
 - (a) include the Impact Inventory for all segments of the pipeline;
 - (b) describe mitigation measures undertaken during the construction phase;
- (c) propose specific additional mitigation measures that will achieve the fish and wildlife
 habitat mitigation goals and standards of OAR 635-415-0025 and prevent harm to the
 federally listed Upper Willamette River steelhead trout and Upper Willamette River
 Chinook salmon; including species, sizes, and quantities of proposed plantings;
 - (d) identify contingency measures, and remedial measures to ensure success criteria are met; and
 - (e) provide a realistic schedule for implementation of the DMP.
- 55) The Office, in consultation with other agencies, shall review the Draft DMP and provide
 NWN with its comments, including changes to the DMP, if necessary within 30 days of
 receipt of the DMP.
- 56) Within 30 days following the receipt of OOE comments, NWN shall prepare and submit to
 OOE a Final DMP that incorporates agency comments. The Final DMP shall provide the
 basis for the monitoring report.

42

57) NWN shall monitor the results of implementing the Final DMP and shall provide annual
 reports to the Office and other agencies for a minimum of three years. The monitoring
 reports shall include the Impact Inventory and provide documentation about

- 1 restoration/enhancement methods, survival of salvaged and planted plants, assessment of 2 streambank stability, net benefit in category 2 habitats, photographs from established pre-3 construction points, including all stream crossings, discussion of success criteria and 4 remedial actions. The reports shall be prepared by a qualified biologist and submitted to the 5 Office and ODFW by December 1. 6 7 58) Success Criteria shall include meeting the ODFW fish and wildlife mitigation goal for each 8 habitat category. In addition, restored areas shall, after 3 years, have: (1) the same number of 9 native trees and shrubs as calculated for replacement in the Impact Inventory and according 10 to the required replacement ratios (this may include native plant volunteers); (2) less than 20 percent coverage of reed canary grass and noxious weeds (as defined by Oregon Department 11 12 of Agriculture and local counties) in habitat units having pre-construction coverage of these 13 plants less than 20 percent and as documented in the impact inventory. 14 15 59) NWN shall take remedial actions if monitoring shows that implementation of the Final DMP 16 is not successful and monitoring shall continue until the success criteria is met. 17 18 **Operation and Maintenance** 19 20 60) NWN shall allow native vegetation, including trees, within the Maintenance Easement, 21 except in a ten-foot-wide zone over pipeline, in all Category 2, Category 3 and Category 4 22 habitats. 23 24 61) NWN shall control vegetation within Maintenance Easement by mechanical means wherever 25 practicable. NWN shall not use chemical spray within 100 feet of water bodies, including 26 wetlands. 27 28 62) NWN shall notify OOE prior to any scheduled repair activity that involves excavation, tree 29 removal, or in-water work. The notification shall include site location, proposed activity, and 30 a description of vegetation to be affected, if any. The notification shall also describe proposed measures to restore the repair site and limit impacts to fish and wildlife habitat, if 31 32 applicable. For emergency repairs necessary to alleviate stress on the pipe or investigate 33 potential damage discovered during inspections required by OPUC or U.S. DOT regulations 34 or this site certificate. NWN may provide the notification as soon as practical following the 35 repair. 36 37 Threatened and Endangered Species 38 1) NWN shall schedule construction within one mile of documented or newly discovered bald 39 eagle nest sites to avoid the critical breeding and rearing period (January 1 to August 31) for 40 this species. 41 42 *Historic, Cultural and Archaeological Resources* 43 1) Before beginning construction of the pipeline, NWN shall certify that all NWN and contract
 - supervisory personnel with construction responsibility are trained in the identification of

cultural resources. NWN shall make plans, subject matter and the schedule for this training
 available to OOE before commencement of the training program.

- 4 2) During construction of the pipeline, in the event any additional "archaeological sites" or 5 "archaeological objects" are identified, NWN shall cease all ground-disturbing activities in 6 the area until a qualified archeologist can evaluate the significance of the find. If the 7 archeologist determines that the materials are significant, NWN shall make recommendations 8 to the Council for mitigation in consultation with SHPO, the Office, and other appropriate 9 parties. Mitigation measures shall include avoidance or data recovery. NWN shall not 10 restart work in the affected area until it has demonstrated to the Office that it has complied with the archeological permit requirements administered by SHPO as set forth in OAR 11 Chapter 736, Division 51 (on public land) or has obtained the landowner's written 12 13 permission to proceed (on private land.)
- 14

15 3) During construction of the pipeline, NWN shall route the pipeline as described in its 16 application for site certificate and its responses to requests for additional information. 17 Specifically, NWN shall route the pipeline as follows, unless NWN, in consultation with a 18 qualified archaeologist, identifies another location which has less impact to these sites: in the 19 vicinity of site S-1, within the existing 16-inch SMF pipeline corridor on the western 20 boundary of the site; in the vicinity of site 35WN33, within the existing pipeline corridor on the west and south edges of the site; in the vicinity of site 35WN35, within the existing 21 22 pipeline corridor, offset from the 16-inch SMF pipeline by 10 feet; in the vicinity of site ORWN1/35WN34, west of the existing pipeline corridor and by means of boring under the 23 24 area; in the vicinity of site S-2, east of the eastern boundary of the site; and in the vicinity of 25 site S-5, in fill and previously disturbed materials under the road within the Barlow Road right-of-way. NWN shall not disturb archaeological sites S-3 and S-4. 26

- 27
 4) During construction of the pipeline, NWN shall avoid any disturbance within archaeological sites S-1, S-2, S-3, S-4, 35WN33 and ORWN1/35WN34. If such avoidance result in adverse impact to jurisdictional wetlands or habitat described in Exhibit P of the ASC, causes the use of additional land in the EFU zone outside public right of way, creates a conflict with other Council standards, or creates a condition adverse to human health and safety, NWN shall obtain approval from OOE, in consultation with SHPO, before causing any disturbance within any of these archaeological sites.
- 35
- 5) During construction of the pipeline, NWN shall retain a qualified archaeologist to monitor
 construction activity in the vicinity of archaeological sites S-1, S-2, S-3, S-4, S-5, 35WN33,
 35WN35, and ORWN1/35WN34 and all grading and excavation activities in the vicinity of
 isolated finds I-1 through I-13 to ensure that archaeological resources in these locations are
 not disturbed.
- 41

6) Before beginning construction, NWN shall conduct an archaeological survey of the
temporary laydown areas and shall submit a report of the survey to the Office of Energy. If
archaeological objects or archaeological sites are discovered in the temporary laydown areas,
NWN may not begin construction of that portion of the pipeline until NWN has submitted to

- the Office a mitigation plan consistent with the other conditions of this site certificate. In
 preparing the mitigation plan, NWN shall consult with SHPO, the Office, and other
 appropriate parties.
- 4

- 5 7) On properties to which NWN has been denied access prior to issue of the site certificate,
 6 NWN shall engage a qualified archeological inspector to look for and analyze artifacts, and
 7 shall comply with state law regarding these resources, if found.
 - Public Services Standard
- NWN shall obtain all required permits from the Oregon Department of Transportation for
 construction in public road right-of-way and shall conform to the Standard Specifications for
 Highway Construction, Oregon Department of Transportation, Section 00220 –
 Accommodation for Public Traffic. Ambulances, fire trucks and police and, in the Dairy
 Creek Valley area, private vehicles providing emergency transportation services, shall be
 afforded immediate passage. NWN will assure that a company representative is present on
 Dairy Creek Road during periods of complete closure Dairy Creek Road.
- 18
 2) NWN shall perform any road work under permit provisions provided by the affected county for work within the right-of-way along county roads. NWN shall develop and implement traffic control planning measures as part of the county permitting process. NWN will have overall responsibility for assuring that all contractors on the Project comply with these permit conditions. NWN shall ensure contractor compliance through construction inspection programs and construction management personnel.
- 3) NWN will provide a detailed traffic control plan for each phase of work, showing signs and cones, certification and use of flaggers, and proposed methods of lane closures. NWN will
 be responsible for safely accommodating public traffic lanes within the construction area.
 NWN shall submit these plans to the ODOT District manager prior to construction along state roads or to the county road department prior to construction along county roads.
- A) NWN shall provide the county road department in each affected county with final
 construction drawings prior to start of construction in that county. Project construction shall
 be coordinated with the county's future paving and culvert replacement programs.
- 35 36

31

25

- 36 5) NWN shall coordinate with school districts along the construction corridor to manage any
 37 potential school bus delays during project construction in months when school is in session.
 38
- 39 *Waste Minimization Standard*
- 1) NWN shall transport construction waste materials to an appropriate recycling facility or to an approved sanitary landfill for nonrecyclable goods. NWN shall collect scrap steel and welding rod for transportation to a recycling facility. Geotextile and straw bales shall be transported to an approved landfill.
- 44
- 45 2) Water used for pressure testing shall be disposed of in a manner consistent with a WPCF

- permit issued by DEQ.
- 3 3) NWN shall minimize the use of water by recycling water for the hydrostatic testing and 4 directional drilling process. Bentonite used the drilling process shall be recycled to the extent 5 practical.
- 6 7 8

18

19

20

21 22

23

24

30

31

32

33 34

35

F.

1

2

CONDITIONS RELATED TO PUBLIC SAFETY, OAR CHAPTER 345, DIV. 24

9 Under ORS 469.401(2), EFSC must impose conditions in the site certificate for the protection of 10 public health and safety. Throughout the final order are conditions related to other decisional criteria that are ultimately intended to protect public health and safety. The following conditions 11 12 protect public health and safety specifically with regard to EFSC standards for surface facilities 13 related to underground natural gas storage and natural gas pipelines.

- 15 1) NWN shall maintain a program to monitor the pipelines to ensure protection of public health 16 and safety, including but not be limited to: 17
 - a) pressure sensing devices positioned on the pipelines at Miller Station to relay information to both Miller Station and the Portland gas control centers.
 - b) high and low pressure alarms monitored on a 24 hour basis to detect and locate areas where pressure variations may indicate abnormal conditions, and
 - c) emergency response personnel on duty 24 hours a day, at Miller Station or in Portland, trained to respond to situations that require immediate attention.
- 25 2) The following specifications are deemed commitments by NWN:
- a) NWN shall specify pipe that meets the requirements for Class 3 locations as defined at 49 26 27 CFR 192.5 (March 15, 1999). NWN shall specify .375 inch wall thickness and minimum 28 52,000 lb. tensile strength in all sections of the pipeline. 29
 - b) NWN shall perform 100% X-ray testing of all welds on the 24 inch pipeline.
 - c) NWN shall maintain at least 24 inches of clearance between the pipeline and the existing 16 inch line. Minimum separation requirements at 49 CFR 192 shall apply otherwise. [amendment 1]
 - d) NWN shall maintain a minimum of 48 inches of pipe cover in all locations, and 60 inches in timberland or cultivated land.
 - e) NWN shall hydrostatically test the pipeline at a minimum of 1080 psig in all sections.
- 36 f) NWN shall use at least a 12 mil thick fusion bonded epoxy (FBE) coating on the pipeline, 37 except that pipe used for road crossings shall have a 25 mil FBE coating.
- 38
- 39 3) Program Development Requirements: Prior to commencement of operations on the 24-inch 40 pipeline, NWN shall develop and obtain OOE approval for the following programs:
- 41 a) Training of personnel responsible for patrolling the pipeline, with emphasis on early 42 recognition of conditions indicating increased landslide hazard.
- 43 b) Accelerated pipeline surveillance program with provisions for increased surveillance in 44 extreme weather years. The program shall include recommendations by a geotechnical 45 engineer for locations that warrant accelerated surveillance in excess of the periodic 46 patrolling requirements for the pipeline in general.
 - 1st Amended Site Certificate NWN South Mist Pipeline Extension 8/28/2003 p.31

1 2 3		c)	Training of personnel responsible for drainage control, with emphasis on identifying areas where pipeline installation could increase the drainage hazard and on implementing effective solutions.
4 5 6 7 8 9 10			Continuing investigation of internal inspection devices (IID's) or "smart pigs," or other appropriate technologies with the capability to detect internal flaws, corrosion, and other pipeline defects, and development of criteria for determining the utilization of IID's, or any other appropriate technologies for detecting flaws, corrosion and other indications that the likelihood of pipeline failure may have increased. Such criteria shall, at a minimum, be consistent with federal and OPUC regulations. Development of criteria to identify the level at which NWN will excavate pipe sections
10 11 12		0)	for stress relief, based on strain gauge readings.
13 14 15 16 17 18 19	4)	rep OC eve	WN shall design and construct the pipeline substantially in accordance with the presentations in ASC Appendix B-1, ASC Exhibit BB and the NWN July 2001 response to DE's May 2001 Request for Additional Information (questions on exhibit BB). In the ent of any conflict between these commitments and other requirements, 49 CFR Part 192 all prevail.
20 21	G.		PERMITTING REQUIREMENTS OF AGENCIES OTHER THAN EFSC
22 23 24			ouncil finds that the NWN Application complies with the requirements for the following s, subject to conditions recommended in consultation with the affected agencies:
24 25 26 27	1)		moval/Fill permits from the Division of State Lands, subject to the conditions listed in tion IV.D.1 of the Proposed Order (Attachment C of the final order).
28 29 30	2)		nited Water Licenses from the Water Resources Department, subject to the conditions red in section IV.D.2 of the Proposed Order (Attachment C of the final order).
31 32 33 34 35	3)	Qu	ater Pollution Control Facilities (WPCF) permits from Department of Environmental bality, subject to the conditions listed in section IV.D.3 of the Proposed Order (Attachment of the final order).
36 37	SE	VER	ABILITY AND CONSTRUCTION.
38 39 40 41 42 43 44	law obl the cor	v, th igat par ntair	provision of this Site Certificate is declared by a court to be illegal or in conflict with any is validity of the remaining terms and conditions shall not be affected, and the rights and tions of the parties shall be construed and enforced as if the Site Certificate did not contain ticular provision held to be invalid. In the event of a conflict between the provisions ned in the Site Certificate and the Council's Order, the provisions contained in this Site cate shall control.
45			

1	GOVERNING LAW AND FORUM	
2	1) This site certificate shall be governed by the laws	s of the State of Oregon.
3		(1)111 1 (1) ¹
4 5	 Any litigation or arbitration arising out of this agree forum in Oregon. 	reement shall be conducted in an appropriate
6	forum in oregon.	
7		
8		
9	IN WITNESS WHEREOF, this Site Certificate has	, e
10	acting by and through its Energy Facility Siting Coun	ncil, and Northwest Natural.
11		
12 13	ENERGY FACILITY SITING COUNCIL	
13		
15	By: D	Date: August, 2003
16	Dr. Roslyn Elms-Sutherland	<u> </u>
17	Chair	
18		
19 20		
20	NORTHWEST NATURAL	
21 22		
22	By:	Date: August , 2003
24		2 a.c. 11 agust, 2005

2) Any litigation or arbitration arising out of this agreement shall be conducted in an appropriate forum in Oregon.

1 2 3

4	
5	
6	IN WITNESS WHEREOF, this Site Certificate has been executed by the State of Oregon,
7	acting by and through its Energy Facility Siting Council, and Northwest Natural.
8	
9	ENERGY FACILITY SITING COUNCIL
10	
11	
12	By: Rentering Date: August, 2003
13	Dr. Roslyn Elms-Sutherland
14	Chair
15	
16	
17	NORTHWEST NATURAL
18	
19	Et 1 to
20	By: Date: August 28, 2003
21	