MATERIAL SAFETY DATA	SHEET
EQUILON MSDS: 02261ET	01/04/99
COLD CLIMATE POWER STEERING FLUI	ID 14315
TELEPHONE NUMBER:	
24 HOUR EMERGENCY ASSISTANCE	GENERAL MSDS ASSISTANCE
EQUIVA SERVICES: 877-276-7283	877-276-7285
CHEMTREC: 800-424-9300	
NAME AND ADDRESS:	
EQUILON ENTERPRISES LLC	
PRODUCT STEWARDSHIP	
P.O. BOX 674414	
HOUSTON, TX 77267-4414	
LEGEND:	
N.D NOT DETERMINED N.A NOT A	PPLICABLE N.T- NOT TESTED
< - LESS THAN > - GREATER THA	AN

1.NAME

MATERIAL IDENTITY Product Code and Name: 02261 COLD CLIMATE POWER STEERING FLUID 14315 Chemical Name and/or Family or Description: Power Steering Fluids

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

THE CRITERIA FOR LISTING COMPONENTS IN THE COMPOSITION SECTION IS AS FOLLOWS: CARCINOGENS ARE LISTED WHEN PRESENT AT 0.1 % OR GREATER; COMPONENTS WHICH ARE OTHERWISE HAZARDOUS ACCORDING TO OSHA ARE LISTED WHEN PRESENT AT 1.0 % OR GREATER; NON-HAZARDOUS COMPONENTS ARE LISTED AT 3.0 % OR GREATER. THIS IS NOT INTENDED TO BE A COMPLETE COMPOSITIONAL DISCLOSURE. REFER TO SECTION 14 FOR APPLICABLE STATES' RIGHT TO KNOW AND OTHER REGULATORY INFORMATION. Product and/or Component(s) Carcinogenic According to: OSHA IARC NTP OTHER NONE

\_ \_ \_ \_ \_

Composition: (Sequence Number and Chemical Name) Seq. Chemical Name CAS Number Range in %
01 # Hydrotreated light paraffinic petroleum 64742-55-8 35.00-49.99 distillate
02 Synthetic hydrocarbon base oil 68649-12-7 20.00-34.99
03 Di(2-ethylhexyl) azelate 103-24-2 10.00-19.99
04 # Solvent-refined heavy paraffinic petroleum 64741-88-4 1.00-2.99 distillates
05 # Solvent-refined light naphthenic petroleum 64741-97-5 1.00-2.99 distillate
06 # Solvent-dewaxed heavy paraffinic petroleum 64742-65-0 1.00-2.99 distillates
07 * Methacrylic acid, copolymer of "butyl", 68516-84-7 1.00-2.99 "lauryl" and "stearyl" esters
PRODUCT IS NON-HAZARDOUS ACCORDING TO OSHA (1910.1200).
* COMPONENT IS HAZARDOUS ACCORDING TO OSHA.
# COMPONENT, BY DEFINITION, IS CONSIDERED HAZARDOUS ACCORDING
TO OSHA
BECAUSE IT CARRIES THE PERMISSIBLE EXPOSURE LIMIT (PEL) FOR
MINERAL OIL
MIST.
Exposure Limits referenced by Sequence Number in the Composition Section
Seq. Limit

_		
01	5	mg/m3 TWA-OSHA (MINERAL OIL MIST)
01	5	mg/m3 TWA-ACGIH (MINERAL OIL MIST)
01	10	mg/m3 STEL ACGIH (MINERAL OIL MIST)
04	5	mg/m3 TWA-OSHA (MINERAL OIL MIST)
04	5	mg/m3 TWA-ACGIH (MINERAL OIL MIST)
04	10	mg/m3 STEL ACGIH (MINERAL OIL MIST)
05	5	mg/m3 TWA-OSHA (MINERAL OIL MIST)
05	5	mg/m3 TWA-ACGIH (MINERAL OIL MIST)
05	10	mg/m3 STEL ACGIH (MINERAL OIL MIST)
06	5	mg/m3 TWA-OSHA (MINERAL OIL MIST)
06	5	mg/m3 TWA-ACGIH (MINERAL OIL MIST)

065mg/m3 TWA-ACGIH (MINERAL OIL MIST)0610mg/m3 STEL ACGIH (MINERAL OIL MIST)

## **3. HAZARD IDENTIFICATION**

**EMERGENCY OVERVIEW** 

Appearance: Pale yellow liquid Odor: Not determined

#### WARNING STATEMENT

#### NONE CONSIDERED NECESSARY HMIS NFPA

Health: 1 Reactivity: 0 Health: 1 Reactivity: 0 Flammability: 1 Special : - Flammability: 1 Special : -POTENTIAL HEALTH EFFECTS

EYE SKIN INHALATION INGESTION Primary Route of Exposure: X X X

## EFFECTS OF OVEREXPOSURE

Acute:

Eyes:

May cause minimal irritation, experienced as temporary discomfort. Skin:

Brief contact may cause slight irritation. Prolonged contact, as with clothing wetted with material, may cause more severe irritation and discomfort, seen as local redness and swelling.

Other than the potential skin irritation effects noted above, acute (short term) adverse effects are not expected from brief skin contact; see other effects, below, and Section 11 for information regarding potential long term effects.

Inhalation:

Vapors or mist, in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness. Ingestion:

If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.

Sensitization Properties:

Unknown.

Chronic:

No adverse effects have been documented in humans as a result of chronic exposure. Section 11 may contain applicable animal data.

Medical Conditions Aggravated by Exposure:

Because of its irritating properties, repeated skin contact may aggravate an existing dermatitis (skin condition).

Other Remarks:

None

#### 4. FIRST AID MEASURES

Eyes:

Flush eyes with plenty of water for several minutes. Get medical attention if eye irritation persists. Skin: Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists. Ingestion: If more than several mouthfuls of this material are swallowed, give two glasses of water (16 oz.). Get medical attention. Inhalation: If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or respiratory irritation persists. Other Instructions: Remove and dry-clean or launder clothing soaked or soiled with this material before reuse. Dry cleaning of contaminated clothing may be more effective than normal laundering. Inform individuals responsible for cleaning of potential hazards associated with handling contaminated clothing.

## 5. FIRE-FIGHTING MEASURES

Ignition Temperature - AIT (degrees F):
Not determined.
Flash Point (degrees F):
410 (COC)
Flammable Limits (%):
Lower: Not determined.
Upper: Not determined.
Recommended Fire Extinguishing Agents And Special Procedures:
Use water spray, dry chemical, foam, or carbon dioxide to extinguish
flames. Use water spray to cool fire-exposed containers. Water or
foam may cause frothing.
Unusual or Explosive Hazards:
None
Extinguishing Media Which Must Not Be Used:
Not determined.
Special Protective Equipment for Firefighters:
Wear full protective clothing and positive pressure breathing apparatus.

# 6. ACCIDENTAL RELEASE MEASURES (Transportation Spills: CHEMTREC (800)424-9300)

Procedures in Case of Accidental Release, Breakage or Leakage: Ventilate area. Avoid breathing vapor. Wear appropriate personal protective equipment, including appropriate respiratory protection. Contain spill if possible. Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways. Avoid contact with skin, eyes or clothing.

## 7. HANDLING AND STORAGE

Precautions to be Taken in Handling: Minimum feasible handling temperatures should be maintained. Storage: Periods of exposure to high temperatures should be minimized. Water contamination should be avoided.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Equipment (Type)

Eye/Face Protection:

Safety glasses, chemical type goggles, or face shield recommended to prevent eye contact.

Skin Protection:

Workers should wash exposed skin several times daily with soap and water. Soiled work clothing should be laundered or dry-cleaned.

Respiratory Protection:

Airborne concentrations should be kept to lowest levels possible. If vapor, mist or dust is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown.

Ventilation:

Adequate to meet component occupational exposure limits (see Section 2).

Exposure Limit for Total Product:

None established for product; refer to Section 2 for component

exposure limits.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pale yellow liquid Odor: Not determined Boiling Point (degrees F): Not determined. Melting/Freezing point (degrees F): Not applicable. Specific Gravity (water=1): .86 pH of undiluted product: Not applicable. Vapor Pressure: Not determined. Viscosity: 28.6 cSt at 40.0 C VOC Content: Not determined. Vapor Density (air=1): Not determined. Solubility in Water (%): Not determined. Other: None

## 10. STABILITY AND REACTIVITY

This Material Reacts Violently With: (If Others is checked below, see comments for details) Air Water Heat Strong Oxidizers Others None of These X Comments: None Products Evolved When Subjected to Heat or Combustion: Toxic levels of carbon monoxide, carbon dioxide, irritating aldehydes and

ketones.

Hazardous Polymerizations: DO NOT OCCUR

#### 11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION(ANIMAL TOXICITY DATA) Median Lethal Dose Oral<sup>.</sup> LD50 Believed to be > 5.00 g/kg (rat) practically non-toxic Inhalation: Not determined. Dermal: LD50 Believed to be > 2.00 g/kg (rabbit) practically non-toxic Irritation Index, Estimation of Irritation (Species) Skin<sup>.</sup> (Draize) Believed to be > .50 - 3.00 / 8.0 (rabbit) slightly irritating Eyes: (Draize) Believed to be < 15.00 / 110 (rabbit) no appreciable effect Sensitization: Not determined. Other: None

## 12. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous. Remarks None

## 13. TRANSPORT INFORMATION

Transportation DOT: Proper Shipping Name: Not regulated IMDG:

Proper Shipping Name: Not evaluated ICAO: Proper Shipping Name: Not evaluated TDG: Proper Shipping Name: Not evaluated

## 14. REGULATORY INFORMATION

Federal Regulations: SARA Title III: Section 302/304 Extremely Hazardous Substances Seq. Chemical Name CAS Number Range in %

None

Section 302/304 Extremely Hazardous Substances (CONT) Seq. TPQ RQ

None

Section 311 Hazardous Categorization: Acute Chronic Fire Pressure Reactive N/A Х

Section 313 Toxic Chemical Chemical Name CAS Number Concentration

None

CERCLA 102(a)/DOT Hazardous Substances: (+ indicates DOT Hazardous Substance) Seq. Chemical Name CAS Number Range in %

#### None

CERCLA/DOT Hazardous Substances (Sequence Numbers and RQ's): Seq. RQ

## None

**TSCA Inventory Status:** 

This product, or its components, are listed on or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory. Other:

None. State Regulations: California Proposition 65: The following detectable components of this product are substances, or belong to classes of substances, known to the State of California to cause cancer and/or reproductive toxicity. Chemical Name CAS Number

None International Regulations: WHMIS Classification: Not controlled Canada Inventory Status: Not determined. EINECS Inventory Status: Not determined. Australia Inventory Status: Not determined. Japan Inventory Status: Not determined.

## 15. ENVIRONMENTAL INFORMATION

Aquatic Toxicity: Not determined. Mobility: Not determined. Persistence and Biodegradability: Not determined. Potential to Bioaccumulate: Not determined. Remarks: None

#### **16. OTHER INFORMATION**

None

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT DATA. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD

COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE

INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH

RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED

HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY,

PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY

COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH

RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE

APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH

MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT

DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN

AS A RESULT OF THAT DATA, IS THE PROPERTY OF EQUIVA SERVICES, LLC AND IS NOT TO

BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF

EQUIVA SERVICES, LLC.

Date: 1999-01-04 New X Revised, Supersedes: 1998-12-11

Inquiries regarding MSDS should be directed to: Equiva Services LLC Manager Product Stewardship P.O. Box 674414 Houston, TX 77267-4414

17. PRODUCT LABEL

Label Date: 1999-01-04

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER

PRODUCT SAFETY ACT OR OTHER RELATED REGULATORY REQUIREMENTS. 02261 COLD CLIMATE POWER STEERING FLUID 14315 WARNING STATEMENT

## NONE CONSIDERED NECESSARY PRECAUTIONARY MEASURES

-Avoid prolonged breathing of vapor, mist, or gas.

-Workers should wash exposed skin several times daily with soap and water.

FIRST AID

Eye Contact:

Flush eyes with plenty of water for several minutes. Get medical attention if eye irritation persists.

Skin Contact:

Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists.

Ingestion:

If more than several mouthfuls of this material are swallowed, give two glasses of water (16 oz.). Get medical attention.

Inhalation:

If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or respiratory

irritation persists.

Note to Physician:

None

#### FIRE

In case of fire, use water spray, dry chemical, foam or carbon dioxide. Water may cause frothing. Use water spray to cool fire-exposed containers. Chemical Name CAS Number Range in %

#	Hydrotreated light paraffinic petroleum distillate	64742-55-8 35.00-49.99
	Synthetic hydrocarbon base oil	68649-12-7 20.00-34.99
	Di(2-ethylhexyl) azelate	103-24-2 10.00-19.99
#	Solvent-refined heavy paraffinic petrole	um 64741-88-4 1.00-2.99
	distillates	

# Solvent-refined light naphthenic petroleum 64741-97-5 1.00-2.99 distillate						
<ul> <li># Solvent-dewaxed heavy paraffinic petroleum 64742-65-0 1.00-2.99 distillates</li> </ul>						
<ul> <li>Methacrylic acid, copolymer of "butyl", 68516-84-7 1.00-2.99</li> <li>"lauryl" and "stearyl" esters</li> </ul>						
PRODUCT IS NON-HAZARDOUS ACCORDING TO OSHA (1910.1200).						
* COMPONENT IS HAZARDOUS ACCORDING TO OSHA. # COMPONENT, BY DEFINITION, IS CONSIDERED HAZARDOUS ACCORDING						
TO OSHA	J					
BECAUSE IT CARRIES THE PERMISSIBLE EXPOSURE LIMIT (PEL) FOR						
MINERAL OIL						
MIST. Pennsylvania Special Hazardous Substance(s) CAS Number Range in %						
Tennsylvania Special Hazardous Substance(s) CAS Number – Kange III /0						
None						
HMIS NFPA						
Health: 1 Reactivity: 0 Health: 1 Reactivity: 0						
Flammability: 1 Special : - Flammability: 1 Special : -						
Transportation DOT:						
Proper Shipping Name:						
Not regulated						
CAUTION: Misuse of empty containers can be hazardous. Empty containers can						
be hazardous if used to store toxic, flammable, or reactive						
materials. Cutting or welding of empty containers might cause						
fire, explosion or toxic fumes from residues. Do not pressurize						
or expose to open flame or heat. Keep container closed and drum						
bungs in place.						
Name and Address:						
Equilon Enterprises LLC						
P.O. Box 674414						
Houston ,TX 77267-4414						
TRANSPORTATION EMERGENCY: (877)276-7283						
CHEMTREC: (800)424-9300						
HEALTH EMERGENCY: (877)276-7283						
}						