

CPI RAD VISION™ Product Definition Form / Compatibility Statement

This Product Definition Form must be completed for your order to be processed. Please contact CPI Customer Support at 905 877 0161 ext. 249 if you require assistance in completing this form.

Customer Name:

CPI RAD VISION™ Model #:

X-ray Generator Option

What x-ray generator will be connected to CPI RAD VISION™ ?

☐ CMP 200 DR, new generator order

Please complete Product Definition Form MF-1149

☐ Indico 100, new generator order

Please complete Product Definition Form MF-0546

☐ CMP 200 DR, existing generator installation

Generator Serial Number :

☐ Indico 100, existing generator installation

Generator Serial Number :

☐ Non- clinical evaluation or other use

Please specify :

☐ Other x-ray generator

Generator Model :

Interface signal type:

☐ 5 VDC

☐ 12 VDC

☐ 24 VDC

☐ 110 VAC

☐ 220 VAC

Digital Detector Option

What digital detector(s) will be connected to CPI RAD VISION™ ?

☐ Varian 4343R

Please complete **Section A**

☐ Varian 4336R

Please complete **Section B**

☐ Toshiba 4343R

Please complete **Section C**

☐ Wireless - 1

Please complete **Section D**

CPI RAD VISION™ Product Definition Form / Compatibility Statement

General

Software Options

- ☐ Image Stitching ☐ Grid Suppression ☐ Advanced WYSIWYG Printing (consult factory)

Language (User Interface)

- ☐ English ☐ French ☐ Spanish ☐ German ☐ Other (consult factory)

Display

- ☐ 1680 x 1050 standard monitor
☐ 1680 x 1050 touch screen monitor
☐ 1600 x 1200 medical grade monitor (not touch screen)
☐ 1680 x 1050 standard monitor **and** 1600 x 1200 medical grade monitor (not touch screen)
☐ 1680 x 1050 touch screen monitor **and** 1600 x 1200 medical grade monitor (not touch screen)

Documentation

Manuals are provided in electronic format on CD. Both the Operator Manual and Installation Manual are available in English only.

- ☐ Operator manual, printed hardcopy ☐ Installation manual, printed hardcopy

Power

- ☐ 120 VAC, North America ☐ 240 VAC, UK ☐ 240 VAC, EU ☐ 240 VAC, Asia

Power Cord Style

- ☐ North America ☐ UK ☐ EU ☐ Asia

Regulatory

The CPI RAD VISION™ system is FDA, UL/CSA, and CE compliant. Please specify any additional regulatory requirements:

CPI RAD VISION™ Product Definition Form / Compatibility Statement

Section A: Varian 4343R

CPI will supply the following items for your detector, even if you do not order the detector from us:

CPI will supply a Gigabit Ethernet cable for each detector that you order from us. If you source your detectors independently you may still order this cable from us at an extra charge

CPI RAD VISION™ is designed to use Varian detectors that have a single acquisition mode with an integration time of 1100 ms. If you order your detectors directly from Varian, please ensure that they conform to this configuration

CPI RAD VISION™ is designed to use Varian detectors that have the L04 version of receptor setup files. If you order your detectors directly from Varian, please ensure that they conform to this configuration.

Varian 4343R: First Detector

Power cord length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Scintillator type?	<input type="checkbox"/> CSI	<input type="checkbox"/> GADOX
CPI supplies detector?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Gig-E cable length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Extended warranty?	<input type="checkbox"/> Not required	<input type="checkbox"/> Required. Number of years: _____

Varian 4343R: Second Detector

Power cord length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Scintillator type?	<input type="checkbox"/> CSI	<input type="checkbox"/> GADOX
CPI supplies detector?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Gig-E cable length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Extended warranty?	<input type="checkbox"/> Not required	<input type="checkbox"/> Required. Number of years: _____

CPI RAD VISION™ Product Definition Form / Compatibility Statement

Section B: Varian 4336R

CPI will supply the following items for your detector, even if you do not order the detector from us:

CPI will supply a Gigabit Ethernet cable for each detector that you order from us. If you source your detectors independently you may still order this cable from us at an extra charge

The *tether cable* is separate from the Gigabit Ethernet cable, and will only be supplied if you order the detector from us. (The tether cable connects the detector to its I/O box. The tether cable, detector, and I/O box are always supplied together.

CPI RAD VISION™ is designed to use Varian detectors that have a single acquisition mode with an integration time of 1100 ms. If you order your detectors directly from Varian, please ensure that they conform to this configuration

CPI RAD VISION™ is designed to use Varian detectors that have the L04 version of receptor setup files. If you order your detectors directly from Varian, please ensure that they conform to this configuration.

Varian 4336R : First Detector

Power cord length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Scintillator type?	<input type="checkbox"/> CSI	<input type="checkbox"/> GADOX
CPI supplies detector?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Gig-E cable length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Tether cable length?	<input type="checkbox"/> 4.5 m (14') (standard)	<input type="checkbox"/> 7 m (23') (extra charge)
Enclosure with handle?	<input type="checkbox"/> Not required	<input type="checkbox"/> Varian (consult factory) <input type="checkbox"/> Reina Imaging (consult factory)
Extended warranty?	<input type="checkbox"/> Not required	<input type="checkbox"/> Required. Number of years: _____
No-fault insurance?	<input type="checkbox"/> Not required	<input type="checkbox"/> Required.

Varian 4336R: Second Detector

Power cord length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Scintillator type?	<input type="checkbox"/> CSI	<input type="checkbox"/> GADOX
CPI supplies detector?	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Gig-E cable length?	<input type="checkbox"/> 15 m (49') (standard)	<input type="checkbox"/> 25 m (82') (extra charge)
Tether cable length?	<input type="checkbox"/> 4.5 m (14') (standard)	<input type="checkbox"/> 7 m (23') (extra charge)
Enclosure with handle?	<input type="checkbox"/> Not required	<input type="checkbox"/> Varian (consult factory) <input type="checkbox"/> Reina Imaging (consult factory)
Extended warranty?	<input type="checkbox"/> Not required	<input type="checkbox"/> Required. Number of years: _____
No-fault insurance?	<input type="checkbox"/> Not required	<input type="checkbox"/> Required.

Section C: Toshiba 4343R

CPI will supply the following items for your detector, even if you do not order the detector from us:

CPI will supply a Gigabit Ethernet cable for each detector that you order from us. If you source your detectors independently you may still order this cable from us at an extra charge. If you choose to source this cable independently, be aware that the Toshiba 4343R detector requires a cross-over type Gigabit Ethernet cable.

CPI RAD VISION™ is designed to support a single Toshiba 4343R detector.

Toshiba 4343R : First Detector

Power cord length? ☐ 15 m (49') (standard) ☐ 25 m (82') (extra charge)

Scintillator type? ☐ CSI

CPI supplies detector? ☐ Yes ☐ No

Gig-E cable length? ☐ 15 m (49') (standard) ☐ 25 m (82') (extra charge)

Extended warranty? ☐ Not required ☐ Required. Number of years: _____

Section D: Wireless - 1

CPI will supply the following items for your detector, even if you do not order the detector from us:

CPI will not supply accessories such as additional batteries, the optional tether, or the Wireless Access Point (WAP) if you do not order the detector from us.

Please use the following information to make a decision about your requirement for additional batteries: The WIRELESS-1 detector includes 1 battery charger and 2 batteries. A battery charger can recharge 3 batteries at once. It takes approximately 3 hours to fully charge a battery. A fully charged battery can be used for approximately 90 acquisitions over the course of 3 hours.

Wireless-1 : First Detector

Scintillator type? ☐ GADOX

CPI supplies detector? ☐ Yes ☐ No

Only complete the following section if you are ordering the detector from CPI

Optional tether? ☐ Yes ☐ No

Tether power cord length? ☐ 15 m (49') (standard) ☐ 25 m (82') (extra charge)

Additional batteries? ☐ Not required ☐ Required. Enter quantity: _____

WAP Gig-E cable length? ☐ 15 m (49') (standard) ☐ 25 m (82') (extra charge)

WAP regulatory domain?

☐ FCC (USA, Canada) (A)

☐ China (C)

☐ Japan2 (P)

☐ Middle East (I)

☐ Singapore (S)

☐ Taiwan (T)

☐ Non-FCC (N)

☐ ETSI (Europe) (E)

☐ Korea (K)

The corresponding Cisco suffix is shown in brackets beside each domain name. For further assistance please consult the Cisco Wireless LAN Compliance Status document, for base model AIR-AP1252AG.

http://www.cisco.com/en/US/prod/collateral/wireless/ps5679/ps5861/product_data_sheet0900aecd80537b6a.pdf

Wireless-1 : Second Detector

Scintillator type? ☐ GADOX

CPI supplies detector? ☐ Yes ☐ No

Only complete the following section if you are ordering the detector from CPI

Optional tether? ☐ Yes ☐ No

Tether power cord length? ☐ 15 m (49') (standard) ☐ 25 m (82') (extra charge)

Additional batteries? ☐ Not required ☐ Required. Enter quantity: _____

WAP Gig-E cable length? ☐ 15 m (49') (standard) ☐ 25 m (82') (extra charge)

CPI RAD VISION™ Product Definition Form / Compatibility Statement

Software Updates

When you purchase the software update package for CPI RAD VISION™ you will receive all product software updates for one year. If you decline this package you will not receive software updates.

Purchase software update package? ☐ Yes ☐ No

After-Sales Support

Site support or training is mandatory for your first installation of this product.

Service support packages are available. Please consult factory for more details.

Please select all that are required.

- ☐ Customer Site Support and Applications Education. *(consult factory)*
- ☐ Training at CPI facility and Applications Education. *(consult factory)*
- ☐ Extended warranties; up to 5 years. *(consult factory)*

Shipping

U.S. destinations must provide a valid customer or ultimate consignee tax ID, IRS or SS number to satisfy U.S. Custom Border Protection.

Please select a shipping option

- ☐ FCA factory, prepaid & charge. (CPI Canada will be responsible for customs clearance.)
- ☐ FCA factory, collect. (Customer must provide account # and customs broker information.)

Account # : _____ Customer broker : _____

Do you require shipping insurance with your order? ☐ Yes ☐ No

CPI RAD VISION™ Product Definition Form / Compatibility Statement

Integration to Third-Party Software

The CPI RAD VISION™ workstation is designed to integrate seamlessly with third-party software for PACS or MWL, so long as that software is designed to DICOM 3.0 and IHE standards. Please be aware of the following integration information

Please acknowledge the integration information provided above

☐ I have read and understood the integration information provided above.

Announcements

Please indicate whether or not CPI may make the following public announcement based on your purchase of this product.

“CPI has placed another CPI RAD VISION™ digital radiographic system with <CustomerName>.”

☐ Yes. CPI may make the public announcement stated above.

☐ No. CPI may not make a public announcement based on this purchase.