

Lightline® Recessed Wall-Wash Direct T5/T5HO

Type:

Project:


SPECIFICATIONS

Recessed

LWR9

LAMPING OPTIONS


□ LWR9 - 1 2'




2'



□ LWR9 - 1 4'



4'



SPECIFICATIONS

Construction

Housing is formed, pre-finished steel. Four-stage, iron-phosphate pretreatment ensures superior paint adhesion and rust resistance. Painted parts are finished with low-gloss baked enamel.

Electrical

Specify 120V, 277V, or 347V. For special circuits, consult factory. UL and C-UL listed (non-IC).

Luminaire Size

Nominal 2 1/2" aperture. 2' and 4' lengths available.

Reflectors

Specular asymmetric reflector system. Black perforated metal diffuser with round holes.

CATALOG NUMBER

Examples: LWR9 G 1 54T5HO HOL U4 120 GEB10 L/LP C200 — LWR9 G 1 14T5 HOL U2 277 GEB10 LP835 C201

Luminaire	Ceiling Type	# of Lamps in Cross Section	Lamp Type	Shielding	Luminaire Row Length	Voltage	Ballast Type
LWR9	G Lay in grid	1	24T5HO 2' 24W T5HO 54T5HO 4' 54W T5HO 14T5 2' 14W T5 28T5 4' 28W T5	HOL Black metal diffuser with round holes	U2 2' U4 4'	120 277 347	GEB10 <10% THD Electronic ADEZ ^{1,2} Advance Mark 10 dim DMHL3D ^{1,3} Lutron Hi-Lume dim ADZT ^{1,3} Advance Mark 7 0-10V dim OSDIM ^{1,2} Osram 0-10V dim <i>Reference Ballast Wizard on website or consult factory for other options.</i>

Emergency Type	Lamp Color	Finish	Options
EL ^{1,3} Emergency battery pack	L/LP No lamp LP830 3000K 80+ CRI LP835 3500K 80+ CRI LP841 4100K 80+ CRI Available with 28T5 only: LP830P 3000K 80+ CRI Premier LP835P 3500K 80+ CRI Premier LP841P 4100K 80+ CRI Premier <i>Reference Lamp Chart on website or consult factory for other options.</i>	C200 White (low gloss) C201 Black (low gloss)	CP Chicago plenum FLNGW Flange kit (dry wall only) white FLNGB Flange kit (dry wall only) black GLR Fusing (fast blow) GMF Fusing (slow blow) NYC New York City code

Notes:

- 1 Not available in 347V
- 2 Only available with 54T5HO
- 3 Only available with 28T5 and 54T5HO

2246 5th Street, Berkeley, CA 94710 • Tel: 510.845.2760 • Fax: 510.845.2776 • Email: techsupport@peerlesslighting.com • PeerlessLighting.com

Lightline® Recessed Wall-Wash

Direct T5/T5HO


Type:

Project:

Recessed

LWR9

PHOTOMETRICS Actual performance may differ as a result of end-user environment and application.




1-LAMP 24W T5HO

59.2% efficiency

1303 delivered lumens

0.0% up / 100.0% down



1-LAMP 54W T5HO

62.8% efficiency

3138 delivered lumens

0.0% up / 100.0% down