|--|



Shower System 5501 Specification Submittal







Feature Highlights

- Symmons Shower System with lever handle
- Symmons Temptrol[®] pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless escutcheon
- Showerhead #552SH three mode, 4 inch diameter
- Showerhead mounting bracket and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)
 Optional lower flow rate restrictor available
- Polished chrome finish

Noc	del Numbers
	5501 Shower System with Symmons Temptrol® mixing valve p/n 4000-BODY
	5501-TRM Trim only, mixing valve ordered separately
	4000-BODY Symmons Temptrol [®] mixing valve without trim
	4000-X-BODY Symmons Temptrol [®] mixing valve without trim. Valve includes integral service stops to allow water shut-off for service
	sh Options / Modifications nd appropriate -suffix to model number
	-STN Satin Nickel

- Polished Chrome (standard finish)

-SBZ Seasoned Bronze

Options / Modifications

ΑD	pend	appropriate	-suffix to	model	number

1 1	11 1	2
	-IPS	1/2 inch female IPS connections on Symmons Temptrol® mixing valve
	-X	Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n 4000-X-BODY (option only applies when ordering model 5501)
	-CHKS	Check Stops: Temptrol® mixing valve includes integral check stops (Requires integral service stops, suffix -X. Used in installations where a positive shut-off

	, , ,
-REV	Reverse core: Temptrol® mixing valve
	with reverse core. (Requires integral service
	stops, suffix -X. Used in back-to-back system
	installations. HOT on the right, COLD on the left
	9

device is used downstream of mixing valve.)

-L/HD	Showerhead not included. (Includes			
	showerhead arm and flange only)			

-2.0	2.0 gpm (7.6 L/min) flow rate restrictor
 _	

	-1 5	1.5 gpm	(5 7	I /min	flow rate	restricto
	-1.5	1.5 gpm	(0.7	L/1111111)	mow rate	resurcio

Standards / Certifications

ASME A112.18.1-2005 / CSA B125.1-05 Americans with Disabilities Act (ADA) compliant

Warranty

- Limited Lifetime to the original end purchaser in consumer installations
- 5 years for commercial installations

