



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

CUTTER MIXER CAPACITY CHART



PRODUCT	ACCESSORIES	METHOD	(Approximate) TIME	HCM-450 MIN.-MAX.	
KITCHEN CAPACITIES					
Bread or Cake Crumbs	Cut/Mix Attachment, Mixing Baffle	RUN	2 Min.	3-8 lbs.	
Chopped Cheese (approx. 30°F)		JOG-RUN	20-30 Sec.	15-20 lbs.	
Cheese Spreads	Cut/Mix Attachment, Mixing Baffle with Scraper	RUN	3-4 Min.	20-40 lbs.	
Chopped Potatoes		RUN-JOG	15-30 Sec.	16-35 lbs.	
Whipped Potatoes (Instant)		RUN	1 Min.	16-35 qts.	
Potato Salad		RUN-JOG	15-30 Sec.	25-40 lbs.	
Salad Dressings		RUN	1 Min.	16-32 qts.	
Mayonnaise		RUN	3 Min.	16-32 qts.	
Cole Slaw		RUN	15-20 Sec.	20-35 lbs.	
Crushed Ice		RUN	30 Sec.	20-35 lbs.	
Vegetable Chunks		Cut/Mix Attachment with Strainer Basket	RUN	15-30 Sec.	10-20 lbs.
Tossed Salad			JOG	2-3 Jogs	6-8-10 hds.
MEAT CAPACITIES					
Chopped Sausage	Cut/Mix Attachment, Mixing Baffle with Scraper	RUN	1-2 Min.	20-30 lbs.	
Hamburger (1st Cut)		RUN	1-2 Min.	20-40 lbs.	
Liver Paste		RUN-JOG	2-3 Min.	20-40 lbs.	
Meat Emulsions (ground $\frac{3}{32}$ ")		RUN	2-3 Min.	20-40 lbs.	
Meat Loaf (blend)		RUN-JOG	1-1½ Min.	20-30 lbs.	
Meat Salad (Ham, Chicken, Fish & Egg)		RUN-JOG	1-1½ Min.	20-40 lbs.	
BAKERY CAPACITIES					
Bread Dough	Knead/Mix Attachment	RUN	1½-2½ Min.	18-36 lbs.	
Pizza Thin Crust (37-45%)*		RUN	1½-3 Min.	18-39 lbs.	
Pizza Medium Crust (50-55%)*		RUN	1½-2½ Min.	18-36 lbs.	
Pizza Thick Crust (60-65%)*		RUN	1½-2½ Min.	18-32 lbs.	
Cake Batter	Cut/Mix Attachment, Mixing Baffle with Scraper	RUN	2½-4 Min.	25-60 lbs.	
Cookie Dough		RUN	2-3 Min.	16-32 lbs.	
Fruit Fillings		RUN	60-90 Sec.	25-65 lbs.	
Icings/Frostings		RUN	2-3 Min.	25-65 lbs.	
Pie Dough		JOG	30 Sec.	15-30 lbs.	
Sweet Dough		RUN	2-3 Min.	18-36 lbs.	

* Moisture absorption. Example: 50%—12 lbs. Flour & 6 lbs. Water = 18 lbs. Dough
Consult Use and Care Manual (Form F-8218) for complete processing information.

CUTTER MIXER CAPACITY CHART

CUTTER MIXER CAPACITY CHART



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

The Hobart HCM lets you cut, mix and blend in seconds with complete control from start to finish . . .


FEATURES

- See-through cover – made of high impact plastic, strong yet lightweight. A built-in scraper, located on the mixing baffle, helps keep the cover clear. Electric interlocks prevent operation when cover is open or bowl tilted.

- Streamlined, functional controls – magnetically operated start and stop selectors are completely sealed and washable.

- Easily removable attachment shafts – the lock knob lets you remove them without tools. A Cut/Mix Attachment and a Knead/Mix Attachment are provided to handle all of your needs.

STANDARD UNIT FEATURES



MODEL	CAPACITY	MOTOR	ELECTRICAL	STANDARD EQUIPMENT	OPTIONAL ACCESSORIES	NET. WT./ SHIP. WT.
HCM-450	45 Qts.	5 H.P.	200-60-3 230/460-60-3 with Solid state motor Protection as standard	5 Minute Timer Cut/Mix Attachment Knead/Mix Attachment Strainer Basket, Mixing Baffle & Cover Scraper, Basic Unit	Casters Set of 2	260/340

As continued product improvement is a policy of Hobart, specifications are subject to change without notice.