



**Motion Control Engineering**  
Voice: 916 463 9200  
Fax: 916 463 9201

## Hydraulic Elevator Data Forms

Page 1 of 6

Doc #: JER032 2/13  
www.mceinc.com

### LOGISTICS DATA

In order to better serve you and meet your schedule, this form must be completed and signed. Timely delivery and trouble-free installation begin with these data forms. Accurate, complete information is essential. Non-response to a question will be defined as meaning that the item does not apply.

|  |                 |
|--|-----------------|
| Date:  | Number of cars: |
| Job Name (please do not abbreviate):   |                 |
| Job Location (city and state):   |                 |
| Contract Date:   |                 |
| Project Type: <input type="checkbox"/> New construction <input type="checkbox"/> Modernization   |                 |
| <input type="checkbox"/> Job has Specifications<br><input type="checkbox"/> Specifications being sent to MCE<br>Please send a copy of job specifications to MCE. |                 |
| Customer Job #:  | PO#:            |

### Delivery Schedule

| Control | Delivery Date |
|---------|---------------|
| Car     |               |
| Car     |               |
| Car     |               |
| Car     |               |
| Group   |               |

### Shipping Information

|   |       |          |
|---|-------|----------|
| Contact:  |       |          |
| Phone:  |       | Fax:     |
| Company name and address:   |       |          |
|   |       |          |
| City  | State | Zip Code |
| Notice required: <input type="checkbox"/> 24 hours <input type="checkbox"/> 48 hours Other: |       |          |
| <input type="checkbox"/> Check if lift gate truck needed                                    |       |          |

### Contractor Information ☐ Check if same as above

|                           |       |          |
|---------------------------|-------|----------|
| Contact:                  |       |          |
| Phone:                    |       | Fax:     |
| Email:                    |       |          |
| Company name and address: |       |          |
|                           |       |          |
| City                      | State | Zip Code |

### Consultant (leave blank if none)

|               |      |
|---------------|------|
| Contact:      |      |
| Phone:        | Fax: |
| Email:        |      |
| Company name: |      |

### Elevator Safety Code Compliance

Accurate information is essential.

|   |  |
|---|--|
| <b>North American Compliance:</b> <input type="checkbox"/> U.S. <input type="checkbox"/> Canada   |  |
| ASME A17.1/B44 Edition: <input type="checkbox"/> 2010 <input type="checkbox"/> 2007 <input type="checkbox"/> 2004 <input type="checkbox"/> 2000   |  |
| Addenda/Supplements: <input type="checkbox"/> 2008(a) <input type="checkbox"/> 2005(a) <input type="checkbox"/> 2002(a)<br><input type="checkbox"/> 2009(b) <input type="checkbox"/> 2005(S) <input type="checkbox"/> 2003(b) |  |
| <input type="checkbox"/> ASME A17.1-1996/98   |  |
| <input type="checkbox"/> ASME A17.1- Specify edition & addenda.   |  |

### International compliance

|  |
|--|
| <input type="checkbox"/> Australia AS 1735 |
| <input type="checkbox"/> EN 81             |
| <input type="checkbox"/> Other (Specify):  |

### Additional state or local code compliance

|   |   |
|---|---|
| <input type="checkbox"/> California medical facility OSHPD Seismic Certification<br>(additional charge for certified cabinet) |   |
| <input type="checkbox"/> Chicago  |   |
| <input type="checkbox"/> Denver   | <input type="checkbox"/> Pressurized hoistway |
| <input type="checkbox"/> GSA  |   |
| <input type="checkbox"/> Houston – Existing Door Reopen Button, Fire Phase I  |   |
| <input type="checkbox"/> Michigan   | <input type="checkbox"/> Nebraska             |
| <input type="checkbox"/> New York City  | <input type="checkbox"/> Other:               |
| <input type="checkbox"/> Additional Compliance Requirements? Explain:   |   |

Per state tax laws, it is critical that MCE receive exemption or resale certificates prior to the material being shipped and billed. If the job is a tax exempt job, send the exemption certificate with this form. If you are a resale customer and have a resale certificate, please make sure that the MCE accounting department has a copy on file.

### Form Completed By

|               |      |
|---------------|------|
| Name/Title:   |      |
| Phone:        | Fax: |
| Cell:         |      |
| Email:        |      |
| Company name: |      |
| Signature:    |      |



**Motion Control Engineering**  
Voice: 916 463 9200  
Fax: 916 463 9201

## Hydraulic Elevator Data Forms

Page 2 of 6

Doc #: JER032 2/13  
www.mceinc.com

### ENGINEERING DATA

#### Enclosures

Machine room NEMA rating: ☐ 1(std) ☐ 12 ☐ 4 ☐ 4X  
☐ Air conditioned enclosure (recommended for all but NEMA 1)  
☐ Hinged enclosure (additional charge)  
☐ GFCI outlet and light required in enclosure (added charge)  
☐ Machine room space limitations?  
Indicate maximum space available for enclosure. Otherwise, MCE will select the enclosure based on job requirements. (Consider also limitations of entry halls and doors.)  
\_\_\_\_\_ H x \_\_\_\_\_ W x \_\_\_\_\_ D

#### Type of Operation

##### ☐ Simplex

Parking Floor: \_\_\_\_\_ Floor Label: \_\_\_\_\_

If no parking floor, car stays at last call answered.

☐ Selective collective  
(intermediate floors have two call buttons in hall)

☐ SAPB Single Automatic Pushbutton  
(intermediate floors have one call button in hall)

☐ SBC Single Button Collective  
(intermediate floors have one call button in hall)

☐ Duplex or Group  
(provide hoistway and machine room drawings)

☐ Duplex Selective Collective

☐ Group Operation  
Number of hall call risers per floor:  
First Parking Floor: \_\_\_\_\_ Floor Label: \_\_\_\_\_  
Second Parking Floor: \_\_\_\_\_ Floor Label: \_\_\_\_\_  
Third Parking Floor: \_\_\_\_\_ Floor Label: \_\_\_\_\_

First free car will park at **First Parking** floor.  
Second free car will park at **Second Parking** floor, etc.  
If no parking floors, cars stay at last call answered floor.

☐ Swing Car Operation Car(s): \_\_\_\_\_  
Please describe in special instructions on next page.

☐ Cross Cancellation Panel (existing must be relay logic)  
Existing hall P/B schematics are required.

☐ Cross Registration  
Existing hall P/B schematics are required.

#### Fire Service Operation

##### ☐ Fire Service Phase I

##### ☐ Fire Service Phase II

Main Landing #: \_\_\_\_\_ Floor Label: \_\_\_\_\_  
Doors will open: ☐ Front ☐ Rear

Alternate Landing #: \_\_\_\_\_ Floor Label: \_\_\_\_\_  
Doors will open: ☐ Front ☐ Rear

☐ Additional Fire Phase I main return switch:  
Switch location: Landing #: \_\_\_\_\_ Floor Label: \_\_\_\_\_

☐ "Master Fire Service" switch (Chicago only)

☐ Shunt trip delay by MCE – permitted only in certain regions or on Federal jobs. Provide operating details: \_\_\_\_\_

#### Monitoring

☐ mView complete in machine room  
☐ mView interface only to allow future connection  
☐ iMonitor / iReport, machine room or remote  
☐ iMon/Report interface only to allow future connection  
☐ IDS Liftnet interface

#### Operating Features

☐ Attendant Service  
☐ Annunciator Panel in car

##### ☐ Car-to-Lobby Lobby/Floor switch

Location: ☐ Car ☐ Hall ☐ Remote Panel

Park with doors: ☐ Open  
☐ Closed (not recommended if in-car switch)

Return Landing#: \_\_\_\_\_ Floor Label: \_\_\_\_\_

##### ☐ Flood Operation ☐ Yes ☐ No

Lowest landing that the car can go in an event of a flood:  
Landing: \_\_\_\_\_ Floor Label: \_\_\_\_\_

##### ☐ Earthquake Service

☐ Emergency Power Generator: (not battery lowering)  
Generator voltage same as line voltage? ☐ Yes ☐ No  
Does same generator power other cars? ☐ Yes ☐ No  
Number of cars to run at a time: ☐ 1 ☐ 2 ☐ 3 ☐:

Emer pwr contacts during normal pwr: ☐ Open ☐ Closed

☐ Power pre-transfer contact – 10 sec minimum

☐ Manual Select Switch  
Number of positions: \_\_\_\_\_ Labels: \_\_\_\_\_

☐ Hoistway Access Operation (select switch style below)  
Standard design is top and bottom landings/front doors. If front doors are not available, rear doors will be used. If different configuration required, provide special instructions.

☐ In-Car Inspection switch (select switch style below)  
☐ Using top/bottom car calls or up/down buttons.

##### Select In-Car Access & Inspection Switch Style

Only for ASME A17.1-2000/CSA B44-00 or later

☐ 2-Position (indicate) ☐ 3-Position

| ACCESS          |  | INSPECTION          |  | OR |  | NORMAL                  |  |
|-----------------|--|---------------------|--|----|--|-------------------------|--|
| NORMAL          |  | NORMAL              |  |    |  | ACCESS                  |  |
| Requires Access |  | Requires Inspection |  |    |  | Requires Access & Inspt |  |

##### ☐ Hospital Service (Code Blue):

Landing #s: \_\_\_\_\_ Floor labels: \_\_\_\_\_

##### ☐ Emergency Medical Technician Service (EMT)

Landing #: \_\_\_\_\_ Floor label: \_\_\_\_\_

##### ☐ Independent Service

☐ Pre-test switch in Controller

##### ☐ Fan / Light Timer Option

Turns off in-car fan and light after period of inactivity.

##### ☐ Security

☐ Call enable  
☐ Car: ☐ Key ☐ Card Reader – dry contact  
☐ Hall: ☐ Key ☐ Card Reader – dry contact  
☐ Car Call Card Reader Override Switch

☐ Car call code security: (enter security code using car call buttons)  
☐ MCE Basic with: ☐ mView ☐ Key on/off switch  
☐ MCE ACE (requires mView)

##### ☐ Bypass Security: (Fire service bypass is standard)

☐ Independent Service ☐ Attendant Service  
☐ Other Specify: \_\_\_\_\_

☐ Other security: Complete special instructions on next page.



**Motion Control Engineering**  
Voice: 916 463 9200  
Fax: 916 463 9201

## Hydraulic Elevator Data Forms

Page 3 of 6

Doc #: JER032 2/13  
www.mceinc.com

### HYDRAULIC DATA

**Foldable/Collapsible Cartop Rail Required:** ☐ Yes ☐ No

**Line Voltage** (actual measured line voltage) Choose closest selection below.

☐ 600 ☐ 575 ☐ 480 ☐ 460 ☐ 440 ☐ 415  
☐ 380 ☐ 240 ☐ 230 ☐ 220 ☐ 208 ☐ 200  
☐ 115 ☐ Other:

☐ AC 3 Phase (standard) ☐ AC 2 Phase ☐ AC Single Phase  
☐ AC 3 phase (grounded leg delta configuration)\*

\* ATL motor starting only, unless isolation transformer used.

☐ 60 Hz (standard in U.S.) ☐ 50 Hz

Available Fault Current from AC Feed (kA): \_\_\_\_\_  
Standard controller SCCR (Short Circuit Current Rating) is typically 5-10kA. If available fault current exceeds 10kA and cannot be reduced, please notify MCE for a quote.

**Motor Starting** (All MCE starters include Reverse Phase Sensor)

☐ Solid State ☐ 3/9 Lead Motor  
☐ 6/12 Lead Motor (standard)

☐ WYE-DELTA

☐ ATL (Across the Line)

☐ Customer supplied starter  
(Interface charges apply. Indicate type of starter above.)  
Brand: \_\_\_\_\_ Model: \_\_\_\_\_

☐ Remote

☐ In MCE controller

☐ MCE to install (customer shipping to MCE)

☐ Customer to install (provide location/dimension sketch)

Additional charges will apply if coil voltage other than 120VAC.

#### Features

☐ Load Weighing  
(Discrete oil pressure switches for load weighing)

☐ Viscosity Control

☐ Low Oil Switch

☐ Oil Tank Temperature Shutdown Switch

☐ Resynchronous circuit for telescopic or dual pistons

☐ Roped Hydro

☐ Governor Set (electrical schematic required)

☐ Governor Set/Reset

Coil Voltage:

☐ Pressure Switch Interface  
(required when top of cylinder is above top of storage tank)

☐ Life Jacket Interface

☐ Battery Powered Lowering

☐ By MCE

☐ Other: \_\_\_\_\_ (electrical schematic required)

#### Sketch or Special Instructions

### Hydraulic Data

#### Pump Motor(s)

☐ New by MCE (Complete pump unit data form)

☐ New ☐ Existing

HP: \_\_\_\_\_ Motor brand: \_\_\_\_\_

Full load amps (MCE will estimate if blank): \_\_\_\_\_

Starts per hour: ☐ 80 (std) ☐ 120 (requires larger starter)

Multiple Motors (complete only for 2 or more motors)

Number of motors: ☐ 2 ☐ 3 ☐ 4

Number of disconnects: ☐ 1 ☐ 2 ☐ 3 ☐ 4

Starting: ☐ Sequential (recommended) ☐ Simultaneous

☐ Single motor operation if abnormal conditions

#### Valve(s)

Brand ☐ Maxton ☐ Blain ☐ EECO

☐ TKE/Dover ☐ Bucher (Beringer)

☐ Other (specify): \_\_\_\_\_

Model: \_\_\_\_\_

Number of valves: ☐ 1 (standard) ☐ 2 ☐ 3 ☐ 4

Coils per valve: ☐ 1 ☐ 2 ☐ 3 ☐ 4 (standard) ☐ 5

Voltage: ☐ 120VAC (standard)

☐ Other (additional charge): V= \_\_\_\_\_



**Motion Control Engineering**  
Voice: 916 463 9200  
Fax: 916 463 9201

## Hydraulic Elevator Data Forms

Page 4 of 6

Doc #: JER032 2/13  
www.mceinc.com

### DOOR DATA

#### Car Door/Gate

- ☐ Automatic passenger style doors
- ☐ Powered freight style doors
- ☐ Manual doors
- ☐ Other:

#### Hoistway Doors

- ☐ Automatic passenger style doors
- ☐ Powered freight style doors
- ☐ Manual doors (complete below)
- ☐ Other: \_\_\_\_\_ (complete below)

##### Interlocks:

- Closed contact ☐ Yes ☐ No  
Locked contact ☐ Yes ☐ No

##### Door locking cam

- ☐ Retiring (not driven by automatic passenger style car gate)  
Voltage: ☐ 3-Ph AC ☐ 1-Ph AC ☐ DC  
Fuse: ☐ 2A ☐ 3A ☐ Other:
- ☐ Fixed cam
- ☐ Bar lock (manually operated)
- ☐ Driven by automatic passenger style car gate

#### Door Features

- ☐ Infrared detector unit/photo eye
    - ☐ Cut-out switch in COP
    - ☐ Anti-Nuisance
  - ☐ Mechanical safety edge
  - ☐ Heavy doors at landings (list landings): \_\_\_\_\_
  - ☐ Dual door operators on same side for wide opening
  - ☐ Cartop door open/close buttons (non solid state door operators)
  - ☐ Door Hold Operation (non-fire operation)
    - ☐ Switch ☐ Button (max hold = 120 seconds)
  - ☐ Nudging
    - ☐ Reduced torque with buzzer
    - ☐ Buzzer only
    - ☐ Ignore photo eye after \_\_\_\_\_ seconds
- If safety edge or door open button activated, doors should:
- ☐ Stop ☐ Re-open ☐ Other: \_\_\_\_\_

#### Sketch or Special Instructions

#### Automatic Passenger Style Doors

##### MCE

- ☐ SmarTraq Complete (Complete SmarTraq data forms)
- ☐ SmarTraq Upgrade  
(Upgrades existing operator to closed loop. Mark existing model below.)

##### GAL

- ☐ MOVFR I
- ☐ MOVFR II
- Voltage: ☐ 220VAC ☐ 110VAC (220 is default if no selection made)

- |                                       |  |
|---------------------------------------|--|
| <input type="checkbox"/> MOMVC/MOHVC  | <input type="checkbox"/> MOM/MOH   |
| <input type="checkbox"/> MOD (230V)   | <input type="checkbox"/> MOSVCL  |
| <input type="checkbox"/> MOD (115V)   | <input type="checkbox"/> MOPM-P/MOPM-PL                                  |
| <input type="checkbox"/> MODHA        | <input type="checkbox"/> MOCT/MOCTA/MODCT/MOMCT/MOHCT                    |
| <input type="checkbox"/> MODVC/MODHVC | Motor Voltage: <input type="checkbox"/> 220 <input type="checkbox"/> 110 |
| <input type="checkbox"/> MOA          | Logic Voltage: <input type="checkbox"/> 220 <input type="checkbox"/> 110 |

##### MAC/Kone

- ☐ PM-SSC/104 Board ☐ MAC (old style)
- ☐ AMD/Kone

##### TKE/Dover

- ☐ HD03M
- ☐ HDLM ☐ HD68/70/73/91
- ☐ HD98/85 (Requires SmarTraq upgrade kit)

##### Otis

- |   |  |
|---|--|
| <input type="checkbox"/> 6970A – Resistance | <input type="checkbox"/> 6970A – Reactance |
| <input type="checkbox"/> 7300               | <input type="checkbox"/> A7770A            |
| <input type="checkbox"/> 7782AA             | <input type="checkbox"/> OVL               |
| <input type="checkbox"/> iMotion 1 & 2      | <input type="checkbox"/> AT400             |

##### ECI

- ☐ 895/1000 ☐ 2000

##### Other

- ☐ IPC Encore (closed loop) ☐ Mitsubishi LV1/4K
- ☐ Delco (closed loop) ☐ Schindler QKS 14 & 15
- ☐ Atlantic/Vertisys Model:
- ☐ Other (wiring diagram required):

#### Powered Freight Style Doors

##### Door Controller Model

- |         |                                   |                                   |
|---------|-----------------------------------|-----------------------------------|
| Peelle  | <input type="checkbox"/> New      | Model:                            |
|         | <input type="checkbox"/> Existing | (electrical schematic required)   |
| Courion | <input type="checkbox"/> New      | Model:                            |
|         | <input type="checkbox"/> Existing | (electrical schematic required)   |
| EMS     | <input type="checkbox"/> New      | <input type="checkbox"/> Existing |
|         | (electrical schematic required)   |                                   |
| Other   | <input type="checkbox"/> New      | <input type="checkbox"/> Existing |
| Model:  | (electrical schematic required)   |                                   |

##### Door Operation (freight only)

- |                       |  |   |
|-----------------------|--|---|
| Opening:              | <input type="checkbox"/> Automatic         | <input type="checkbox"/> Momentary pressure |
| Closing:              | <input type="checkbox"/> Automatic         | <input type="checkbox"/> Momentary pressure |
|                       | <input type="checkbox"/> Constant pressure |   |
| Fire Phase I Closing: | <input type="checkbox"/> Automatic         | <input type="checkbox"/> Momentary pressure |
|                       | <input type="checkbox"/> Constant pressure |   |





**Motion Control Engineering**  
Voice: 916 463 9200  
Fax: 916 463 9201

## Hydraulic Elevator Data Forms

Page 6 of 6

Doc #: JER032 2/13  
www.mceinc.com

### HOISTWAY DATA

| Floor Label*  | Landing # | Floor Height | Car  |                          | Car                      |                          | Car                      |                          | Car                      |                          |
|---|-----------|--------------|--|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
|   |           |              | F  | R                        | F                        | R                        | F                        | R                        | F                        | R                        |
|   |           |              | <b>Check front and rear floor openings below</b> |                          |                          |                          |                          |                          |                          |                          |
|   | 16        | overhead     | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 15        | 15-16        | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 14        | 14-15        | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 13        | 13-14        | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 12        | 12-13        | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 11        | 11-12        | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 10        | 10-11        | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 9         | 9-10         | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 8         | 8-9          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 7         | 7-8          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 6         | 6-7          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 5         | 5-6          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 4         | 4-5          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 3         | 3-4          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 2         | 2-3          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   | 1         | 1-2          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|   |           | Pit          | <input type="checkbox"/>                         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Capacity: <input type="checkbox"/> lbs <input type="checkbox"/> kg    |           |              |  |                          |                          |                          |                          |                          |                          |                          |
| Up Speed: <input type="checkbox"/> fpm <input type="checkbox"/> m/s   |           |              |  |                          |                          |                          |                          |                          |                          |                          |
| Down Speed: <input type="checkbox"/> fpm <input type="checkbox"/> m/s |           |              |  |                          |                          |                          |                          |                          |                          |                          |
| Total Travel: <input type="checkbox"/> ft <input type="checkbox"/> m  |           |              |  |                          |                          |                          |                          |                          |                          |                          |

\* Floor Label note: If using CE or E-Motive driver board, floor label should not be more characters than the number of digital PI display characters (BBB)

**Hoistway NEMA Rating:** ☐ 1 (standard) ☐ 12 ☐ 4 ☐ 4X

☐ **EECO Hoistway Limit Switches and Brackets by MCE**

☐ **MCE Landing System:**

☐ Tape (LS-QUTE) Hoistway NEMA 1 only

☐ Vane (LS-STAN)

Rail (lbs): ☐ 8 – 12 ☐ 15 – 18.5 ☐ 22.5 – 30

☐ **Customer Supplied Landing System**