
NS-23

Fresnel Lens with Metal Trim

TRIM DIMENSIONS



Trim OD: 5" Height: 1-5/8"

FEATURES

<u>Trim</u>

High grade fresnel lens attached to metal trim.

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage and Compact Fluorescent housings. See individual specification sheets for more information.

Lamp

Line Voltage

50W R20/PAR20 Max. (NS-401QAT; NSIC-401QAT; NSR-404QAT)

Compact Fluorescent

13W Quad/Triple (NS-406Q; NS-406EL; NSR-408Q; NSR-408EL)

Labels and Listings

cULus Listed for Wet Location when used with compatible housing.


BNORALIGHTING.

Type Project


Catalog No.

Lamp/Wattage


HOUSING DIMENSIONS




NSIC-401QAT




NSR-404QAT



NS-406Q / NS-406EL



NSR-408Q / NSR-408EL



Compatible Housings

	LINE VOLTAGE			
Fresnel Lens with Metal Trim	Item Number	Installation Type	Lamp	Dimensions
NS-23B: Fresnel Lens with Black Metal Trim	NS-401QAT	Non-IC Air-Tight New Const.	50W R/PAR20	W: 5-5/8" L: 8-1/2" H: 5-5/8"
NS-23BZ: Fresnel Lens with Bronze Metal Trim	NSIC-401QAT	IC Air-Tight New Construction	50W R/PAR20	W: 5-1/4" L: 8-1/2" H: 6-3/8"
	■NSR-404QAT	Non-IC Air-Tight Remodel	50W R/PAR20	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NS-23C: Fresnel Lens with Chrome Metal Trim	COMPACT FLUORESCENT			
NS-23CO: Fresnel Lens with Copper Metal Trim	NS-406Q	Non-IC New Constr., Magnetic	13W Quad	W: 6-1/4" L: 10" H: 5-1/2"
NS-23G: Fresnel Lens with Gold Metal Trim	NS-406EL	Non-IC New Constr., Electronic	13W Quad/Triple	W: 6-1/4" L: 9" H: 5-1/2"
NS-23N: Fresnel Lens with Natural Metal Trim	NSR-408Q	Non-IC Remodel, Magnetic	13W Quad	W: 4-3/4" L: 11-7/8" H: 5-1/2"
NS-23W: Fresnel Lens with White Metal Trim	NSR-408EL	Non-IC Remodel, Electronic	13W Quad/Triple	W: 4-3/4" L: 11-7/8" H: 5-1/2"

0

0 0

10" (Magnetic)