

Identity (As Used on Label and List): <b>COPALITE® SOLVENT/THINNER</b>	Manufacturer's Product: <b>4000-03</b>	Revised MSDS: October 17, 2006
---	---	--------------------------------

### SECTION I - PRODUCT IDENTIFICATION AND USE

Manufacturer's Name: <b>COOLEY &amp; COOLEY, LTD.</b>	Information Telephone Number: <b>281-897-0009</b>
Address (Number, Street, City, State Zip Code, and Country): <b>8550 WESTLAND WEST BLVD. HOUSTON, TX 77041 U.S.A.</b>	Emergency Telephone Number: <b>1-800-535-5053 (USA) (INFOTRAC) 1-352-323-3500 (International) (FOR CHEMICAL EMERGENCY ONLY)</b>

### SECTION II

Hazardous Components (Specific Chemical Identity: Common Name(s):	CAS #	OSHA PEL	ACGIH TLV	WHMIS	%
<b>BLENDED INGREDIENTS:</b>					
ETHYL ETHER ANYDROUS	60-29-7	400PPM	500PPM	Class B	
CHLOROFORM	67-66-3	50PPM	50PPM	Class D/Div.1	
<b>FLAMMABLE LIQUIDS N.O.S. , CLASS #3, Packing Group II, UN #1993 Health: 2-Hazardous</b>					
<b>Specific Hazard: Blank, Fire: 4-Store below 73° F Reactivity: 1-Unstable if heated</b>					

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: <b>34° ± 4°C</b>	Specific Gravity (H20-1): <b>1-1.474 - 1.478</b>
Vapor Pressure (mm Hg.): <b>760MM</b>	Melting Point: <b>N/A LIQUID FORM</b>
Vapor Density (Air=1): <b>25% 1.471</b>	Evaporation Rate: <b>(BUTYL ACETATE=1) 2.2</b>
Solubility in Water: <b>INSOLUBLE</b>	Appearance and Odor: <b>CLEAR COLOR; SWEET ODOR</b>

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method used): <b>75°F ± 5°F ASTM TAG OPEN CUP</b>	Flammable Limits:	LEL <b>65°F</b>	UEL <b>75°F</b>
Extinguishing Media: <b>FIRE EXTINGUISHER A, B &amp; C CLASSIFICATION</b>			
Special Fire Fighting Procedures: <b>PUT ON GAS MASK. AIM THE FIRE EXTINGUISHER AT THE BASE OF THE FLAME.</b>			
Unusual Fire and Explosion Hazards: <b>ETHER IS VOLATILE. CO2 AND CO ARE GASES PRODUCED DURING A HIGH HEAT FIRE. GAS MASK AND FIRE EXTINGUISHER ARE NECESSARY TO PUT OUT FIRE.</b>			

### SECTION V - REACTIVITY DATA

Stability:	Unstable:	Conditions to Avoid: <b>AVOID EXCESSIVE EXPOSURE TO HIGH HEAT/FLAMES.</b>
	<b>ABOVE 75°F</b>	
	Stable: <b>65°F</b>	
Incompatibility (Materials to Avoid): <b>WATER</b>		
Hazardous Decomposition or Byproducts: <b>CHLOROFORM</b>		
Hazardous Polymerization:	May Occur:	Conditions to Avoid: <b>MELTS SOFT PLASTIC MATERIAL. WILL NOT MELT OR SOFTEN HARDER GRADE PLASTICS.</b>
	<b>X</b>	
	Will Not Occur: <b>X</b>	

**SECTION VI - HEALTH HAZARD DATA**

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	X	X	X
Health Hazards (Acute & Chronic):			
INHALATION: ACUTE DIFFICULTY IN BREATHING, CHRONIC LUNG DISEASE PERSONS SHOULD LIMIT EXPOSURE.			
SKIN: ACUTE - CLEAN AREA WITH ISOPROPYL ALCOHOL; CHRONIC - UNKNOWN.			
INGESTION: INDUCE VOMITING WITH IPECAC SYRUP ACCORDING TO DIRECTIONS.			
Carcinogenicity :	NTP?	IARC Monographs?	OSHA Regulated?
N/A	N/A	N/A	YES
CHLOROFORM IS A KNOWN CARCINOGEN TO LABORATORY RATS IN EXTREME CASES.			
Signs and Symptoms of Exposure:			
DIFFICULTY IN BREATHING, TIGHTNESS IN CHEST DUE TO CONSTRICTION OF BRONCHIOLES.			
Medical Conditions Generally Aggravated by Exposure:			
DISEASES OF THE LUNGS, EMPHYSEMA, ASTHMA, TUBERCULOSIS, PNEUMONIA, PLEURASIS.			
Emergency and First Aid Procedures:			
VENTILATE AREA. MOVE PERSON(S) TO FRESH AIR. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES, OR USE EYEWASH, AND CALL AN OPHTHALMOLOGIST.			

**SECTION VII- PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps To Be Taken In Case Material is Released or Spilled:	
SPILLS: VENTILATE AREA, EXIT ALL PERSONS UNTIL AROMA DISSIPATES. CLEAN AREA UP WITH ISOPROPYL ALCOHOL.	
RELEASE OF FUMES: REMOVE ALL PERSONS, VENTILATE AREA UNTIL AROMA DISSIPATES.	
Waste Disposal Method:	
DISPOSE AS HAZARDOUS MATERIAL, BY INCINERATION ACCORDING TO OSHA REGULATIONS.	
Precautions To Be Taken In Handling and Storing:	
DUE TO EVAPORATION, KEEP BOTTLE TIGHTLY CAPPED WHEN NOT IN USE. STORE IN A COOL, DRY PLACE.	
Other Precautions:	
THIS PRODUCT IS FOR PROFESSIONAL USE ONLY AS STATED IN THE DIRECTIONS. IT IS THE RESPONSIBILITY OF THE DENTIST TO TRAIN HIS AUXILIARY PERSONNEL IN THE SAFE USE, STORAGE AND FIRST AID PROCEDURES.	

**SECTION VIII-CONTROL MEASURES**

Respiratory Protection (Specify Type):		
RESPIRATOR OR MASK USED FOR PROTECTION AGAINST ORGANIC VAPORS.		
Ventilation :	Local Exhaust:	Special:
	OPEN WINDOWS, EXHAUST FANS	EXIT AREA
	Mechanical (General):	Other:
	VENT HOODS (INDUSTRIAL TYPE)	
Protective Gloves :	Eye Protection:	
LATEX	SAFETY GLASSES/GOGGLES	
Other Protective Clothing or Equipment:		
LAB COAT		
Work/Hygienic Practices:		
MAINTAIN ASEPSIS. DO NOT PLACE CONTAMINATED INSTRUMENTS INTO BOTTLE OF SOLVENT.		