REO INTERIOR WALL


AIW10363



ADA

Reo can be mounted to any wall surface and comply with ADA requirements while providing supplemental side illumination. Five optional color gels add a splash of color, serving as a guide or visual path. The ability to complement any style comes standard.

JOB NAME TYPE



Dimensions

W	Н	D	MC	
13.0 in	28.0 in	3.7 in	14.0 in	
330 mm	711 mm	94 mm	356 mm	

Weight

Hanging weight: 25.0 lb (11.4 kg).

Features

- Integral Class II power supply included, eliminating the need for remote mounting, simplifying installation.
- Formed metal construction provides durable protection for internal components and is recyclable.
- Embossed stainless steel-linear and crosshatch face plate option adds a unique, metal accent and texture to a space.
- Durable wood laminate faceplate option adds a warm, natural texture to a space.
- Fixture adds a splash of color to a space with theatrical color gels. Standard colors are available with other colors available upon request. Contact factory to customize a color gel that coordinates with your application.
- Standard thermoset polyester powder coat paint provides durable protection in a palette of color options. Custom colors available upon request.
- Compliant with Americans with Disabilities Act (ADA) requirements.

Technical Notes

Electrical

- Fluorescent versions have integral electronic ballasts utilizing the latest energy-saving technology, providing prolonged lamp life and maintaining consistent color.
- Advent uses strict quality guidelines in LED selection to ensure the white LED's we use meet or exceed ANSI Binning Standards (ANSI C78.733).
- Thermally protected ballast limits operating temperature.
- Class "A" sound rated ballast for use in low ambient noise applications.
- Meets NEC 410.73 double-ended, fluorescent lamp ballast disconnect requirements.
- ETL listed to UL standards (US and Canada) for use in damp locations. Not recommended for exterior applications.

Lamping/lamp

- L70 life= 50,000+ hours.
- · Fluorescent lamps are 3500K unless specified.

Lamps included, with the exception of T8, T5 and incandescent.

Mounting

- Mounts to standard 4" octagonal junction box.
- Additional mounting structure and hardware required (by others).

Additional Documents

Color Chart (http://www.specAdvent.com/pdfs/advent_color_chart.pdf)

MODEL NUMBER	LIGHT SOURCE	FINISH	VOLTAGE	LAMP OPTIONS	OPTIONS	COLOR ACCENTS

Not all options are available in all configurations, consult factory for details.

Light Source		Photometry
L21.5W	White 21.5W 3.2W/6" LED Light Engine Delivered Lumens: 880	28IN REC WS LED LOW
L43.0W	White 43.0W 6.4W/6" LED Light Engine Delivered Lumens: 1,760	28IN REC WS LED HIGH
2F14	2F14WT5/Mini Bipin	
2F14DM	2F14WT5/Mini Bipin Dimming	
2F17	2F17WT8/Med Bipin	
2F24	2F24WT5HO/Mini Bipin	
2F24DM	2F24WT5HO/Mini Bipin Dimming	

120V	120 Volt
120-277V	Universal Voltage
277V	277 Volt
mp Options	
DML ²	0-10V Dimming
3000K	3000K Cct
3500K	3500K Cct
4000K	4000K Cct
EMR	Emergency Ballast Remote

Options	
ES1	Embossed Stainless Steel-linear Pattern
ES2	Embossed Stainless Steel-cross Hatch Pattern
WF1	Cherry Laminate
WF2	Maple Laminate
Color Accent	S
CG00	White Color Gel
CG01	Red Color Gel
CG02	Orange Color Gel
CG03	Green Color Gel
CG04	Blue Color Gel

Brass Bronze

Painted Finishes

PT01	SuperWhite	PT07	Light Taupe	PT13	Warm Gray	PT19	Blue	PT29	Red Brass	PT42	Sky Blue	PT48
PT02	White	PT08	Medium Taupe	PT14	Light Gray	PT20	Dark Green	PT31	Medium Bronze	PT43	Teal	PT49
PT03	Morning Light	PT09	Medium Gray	PT15	Sage	PT21	Pearl White	PT32	Dark Bronze	PT44	Green	
PT04	Warm White	PT10	Dark Gray	PT16	Spruce	PT22	Platinum	PT33	Dark Blue	PT45	Purple	
PT05	Putty	PT11	Black	PT17	Red	PT27	Deep Copper	PT40	Yellow	PT46	Aluminum	
PT06	Warm Beige	PT12	Dark Chocolate	PT18	Deep Red	PT28	Dark Stainless	PT41	Orange	PT47	Deep Red Brass	

Metal and Plated Finishes

BAL Brushed Aluminum	
----------------------	--

T5 & T8 Fluorescent Linear Lamp(s) Not Included
DML with LED light engine only.