	Customer Number:				
	P.O. Number:		Ship Via:		
	P.O. Date:		Ship Date:		
SOLD TO			SHIP TO		Same as SOLD TO
Name:			Na	ıme:	
Address 1:		=	Addres		
Address 2:		=	Addres		
City:			c	City:	
State:			Sta	ate:	
Postal Code:			Postal Co	ode:	
Country:			Coun	ntry:	
Additional Instructions:					
	IP-2 2 channel mic/line input card OP-2e 2 channel mic/line output card	AEC-2HD 2 channel mice card with acoust cancellation TI-2 2 line POTS in	non-CobraNet //line input ustic echo nterface card f 6 total telephony cards (in any combination of ut Cards at per chassis) of Units	PA-2 2 channel power amplification card VolP-2 2 line VolP card	
100-240V~ 50/60Hz	Serial Control Port Serial Control Port Serial Control Port	Installation Instructions: Telephone Interf This device must be installed by qualified, traine Connections to the telephone network must be #26 AWG sold copper wire for continued safety.	face TI-2 and ia. FLEX	BIAMP SYSTEMS MODEL TH-2 US-6RIMBROGRAUDIATI2 IC-3184A-AUDIATH-2 X	BIAMP SYSTEMS designed and assemble in the USA workshild argusters X

