

ISCOM2110A-MA Managed L2 Ethernet Switch

Datasheet

ISCOM2100 series is a fully managed Ethernet Switch product line, provides cost-effective L2 aggregation with carrier grade reliability. Its wire-speed store and forward capabilities, and powerful network management features are ideal for deployments in MDUs, residential, office buildings, and campus environment.

ISCOM2110A-MA is designed to provide eight FE downlinks and two GigE uplinks for redundant protection; supports metro access standards, basic 802.3ah OAM discovery, and 802.1ag CFM, and SLA for Carrier Ethernet services.

Feature

Basic Feature

Forwarding Mode	Store-and-forward mode Buffer size:128KB
Packet Forwarding	MTU:1,632byte DLF forward control
Bandwidth Profile	Max rate limit:1,000,000Kbps Based on Ingress and/or Egress - per port Increments: 64Kbps (64K-1M), 1Mbps (1-100M), 10Mbps (100-1000M) Rate limit based on ethertype / Queue
Storm Control	Broadcast storm control Multicast storm control Unicast DLF storm control Control mode: Global, bps
Link Aggregation	Up to 5 groups Up to 8 ports in each group Support load balance based on CRC hash value of MAC address
Mirroring	N:1 port mirroring Separate mirrorings for egress & ingress ports Mirroring per VLAN Allow separate mirroring configurations for ingress & egress ports
MAC Address Table	IEEE 802.1Q 8K MAC address Add/remove MAC address View MAC address statistic Search MAC address Aging time:15-3825s MAC table threshold per port MAC table limit:1-255
Multicast	1K multicast addresses Static multicast group IGMP Snooping (V1,V2,V3) Multicast filtering & unknown multicast discard MVR
STP	STP, RSTP & MSTP 64 instances
Flow Control	IEEE 802.3x in full duplex mode Back pressure in half duplex mode Port-based configurations
VLAN	IEEE 802.1Q VLAN 4K active VLANs Port PVID Overwrite
QinQ	Port QinQ
L2TP	BPDU



**ISCOM2110A-MA
Managed L2 Access
Ethernet Switch**

Specification

Performance	Switching fabric 5.6 Gbps
Capacity	32MB SDRAM 4MB flash 128KB Switch buffer 1K IGMP groups
Max Transmission Unit	1,632 Bytes
Management port	1 console (RJ45)
Serial port configuration	9,600bps/8bit/none parity/1 stop bit/none flow control
Port specification	10BASE-T (RJ45, Cat3/Cat4/Cat5 UTP) 100BASE-T (RJ45, Cat5 UTP) 1000BASE-LX/BX/FX (LC/SC fiber connector, single/multi mode)
Ports	8 (10/100BASE-T) 2 (1000 BASE-X SFP)
Indicators	Power supply (flashing) System (flashing) 10/100BASE-T: FDX, 100M & LNK/ACT indicators. 1000BASE-X SFP: LNK/ACT indicator
Dimension	43.6(H)*260(W)*130(D)mm
Weight	≤1.2Kg
Power supply	AC: 90~264V, 47~63Hz DC: 36~72V
Power consumption	≤6.5W (full load)
Working ambience	Temp: 0 ~ 50 centigrade RH: 10~90% non-condensing
Safety compliance	N/A (In process of applying)

	DOT1X LACP Specified VLAN to receive specific multicast
Digital Diagnostic	SFP digital diagnostic
Port Loopback Detection	Individual port will be shutdown if loopback is detected
Port Backup	Support
Ethernet Ring	RAISECOM Ethernet ring: ≤ 50 ms recovery time Max 8 ethernet rings, max 124 devices in each ring
Management Feature	
System Management	CLI ARP 16 L3 interfaces, Super VLAN, max 4K VLANs Telnet Console SSHV2 RMON Group 1,2,3 & 9 SNMP Bridge MIB (RFC1493) RAISECOM NMS Web management System log Hierarchical alarms Link alarm per port Keepalive report Fault pass through Module information management
Cluster Management	RAISECOM Neighbor Discovery Protocol (RNDP) RAISECOM Topology Discovery Protocol (RTDP) RAISECOM Cluster Management Protocol (RCMP) RAISECOM Cluster Program
Auto Configuration	Support
Software Upgrade	Xmodem/FTP upgrade in BOOTROM FTP/TFTP (system & configuration files)
Scheduling	System task scheduling
Time Management	Timezone Time modification DST System time synchronization by SNTP Client NTP
DHCP	DHCP Snooping DHCP Client DHCP Option82
OAM	802.3ah OAM (Discovery, Link Performance, Remote loopback, Fault detection and Performance Stats per OAM standards) OAM Master Extended OAM (Configure on remote switches)
CFM	802.1ag, Y.1731 protocol, Support 256 MEP,256 MA
SLA	Layer-2/Layer-3 SLA (frame delay, jitter & loss)
Error Tolerance	& System error report
Redundancy	Fast recovery during serious error
Filter	Switch access IP packet filter

Storage
ambience

Temp: -25~70 centigrade

Compliance

MIB Management	802-1x-2004-MIB DISMAN-PING-MIB DOT3-OAM-MIB IEEE8021-CFM-MIB81 RFC1213 RFC1493 RFC1757 RFC1907 RFC2233 RFC2571 RFC2572 RFC2573N RFC2573P RFC2573T RFC2574 RFC2575 RFC2665 RFC2674P RFC4363Q TRACEROUTE RAISECOM-ACL-MIB RAISECOM-COMMON-MANAGEMENT-MIB RAISECOMDOT1XMIB RAISECOM-EXTEND-OAM-UPGRADE-MIB RAISECOM-EXTOAM-MIB RAISECOM-KEEPALIVE-MIB RAISECOM-OAM-MIB RAISECOM-OPTICAL-MONITOR-MIB RAISECOM-PPPOEAGENT-MIB RAISECOM-QOS-MIB RAISECOM-RCMP-MIB RAISECOM-RELAY-MIB RAISECOM-REMOTE-MANAGEMENT-LOCAL-MIB RAISECOM-REMOTE-MANAGEMENT-REMOTE-MIB RAISECOM-RNDP-MIB RAISECOM-RTDP-MIB RAISECOM-SCHEDULE-MIB
----------------	--

QoS	CoS to queue mapping DSCP to queue mapping Port priority override Port TRUST mode TRUST port priority TRUST CoS priority TRUST DSCP priority Global queue scheduling 4 queues per port SP WRR WRR weight range:1-125 SP+WRR
Safety Feature	User classification & password protection RADIUS TACAS+ Binding of MAC address & port Port protection PPPoE Agent DOT1X
Routing Protocol	Static routing & default gateway
Maintenance	Debug information output PING (Packet Internet Groper) Telnet Client Trace route Port statistic Port dynamic statistic
Password Recovery	Support
MEF 9&14	Support

Ordering Information

Part number	Description
ISCOM2110A-MA-AC	Manageable layer-2 Ethernet switch, 8*10/100BASE-T+2*1000BASE-X SFP, AC power supply
ISCOM2110A-MA-DC	Manageable layer-2 Ethernet switch, 8*10/100BASE-T+2*1000BASE-X SFP, DC power supply

Standards

RAISECOM-SYSLOG-SERVICE-MIB
 SWITCH-SYSTEM-MIB
 RAISECOM-UPGRADE-MIB
 RAISECOM-USER-MIB
 RC802-1X-MIB
 RCCFM
 RCDOT1AG
 RCQINQ
 RCSLA
 RMONMIB
 SWITCH-AUTOCONFIG-MIB
 SWITCH-DHCPCLIENT-MIB
 SWITCH-DHCPOPTION-MIB
 SWITCH-DHCPSNOOPING-MIB
 SWITCH-ERING-MIB
 SWITCH-IFEXTEND-MIB
 SWITCH-L3FILTER-MIB
 SWITCH-LINKSTATETRACK-MIB
 SWITCH-MACCONFIG-MIB
 SWITCH-MSTP-MIB
 SWITCH-MVR-MIB
 SWITCH-NTP-MIB
 SWITCH-PORTBACKUP-MIB
 SWITCH-PORTMIRROR-MIB
 SWITCH-PORTSTATISTIC-MIB
 SWITCH-RATELIMIT-MIB
 SWITCH-RSTP-MIB
 SWITCH-SNMP-MIB
 SWITCH-SYSTEM-MIB
 SWITCH-TRUNK-MIB
 SWITCH-VLANCFG-MIB
 IEEE 802.1Q VLAN
 IEEE 802.3ad Link Aggregation
 IEEE 802.1ad QinQ
 IEEE 802.1D Spanning Tree Protocol
 IEEE 802.1w RSTP
 IEEE 802.1s MSTP
 IEEE 802.1x Security
 IEEE 802.1p CoS Prioritization
 IEEE 802.3x Flow Control
 IEEE 802.3ah OAM
 IEEE 802.1ag Connectivity Fault Management
 ITU Y.1731 Services OAM
 Static Routing
 IGMP v1, v2, v3 Multicast
 RMON I and II standards
 SNMPv1,SNMPv2c and SNMPv3
 MEF9 MEF14