



Ceiling Opening: 3-3/4" (95mm)

Complete fixture consists of the Trim and Frame-in Kit. Select each separately.

| Reflector Trim |               | Frame-in Kit  |                   | Lamp                   |
|----------------|---------------|---------------|-------------------|------------------------|
| <b>344DSTX</b> | Brushed steel | Remodeler     | <b>3401MREX</b>   | 37W MR16 IR            |
| <b>344DWHX</b> | White paint   | Non-IC        | <b>302MREX</b>    | 50W MR16 / 37W MR16 IR |
|                |               | IC / AirSeal® | <b>302MRAICEX</b> | 37W MR16 IR            |

## Features

- Housing:** 25 ga steel. Black painted finish.
- Residence Mounting Clips:** Factory-installed; zinc plated spring steel; free-hand installation.
- Flange:** Die-cast aluminum 0.060" (1.5mm) thick.
- Lampholder Assembly Support:** Die-cast aluminum, Black painted finish.
- Mounting Clips (2):** 24ga. stainless steel. Provides easy snap-in / snap-out action.
- Lamp guard:** 2" (51mm) dia. borosilicate glass.
- Baffle:** Die-cast aluminum with stepped conical surface for low brightness. Black painted finish.

**Note:** For complete Frame-in Kit specifications, refer to the 300X series Frame-in Kit specification sheets.

## Accessories

2" (51mm) dia. Specialized Filters and Louvers.

- AF2SY** Symmetric: Prismatic Spread Lens (55°).
- AF2AS** Asymmetric: Beam Elongator (5° x 55°).
- AF2LF** Light Frost: Softens light beam.
- 7550FD** Frosted Lens: Softens and enlarges beam.
- AF2PF** Perimeter Frost.
- AF2UV** UV Filters: Blocks UV radiation.
- AF2IR** Infrared Filter: Block infrareds.
- AL2HC** Hex Cell Louver: matte black. Use only with shielded MR16 flat lens lamps.
- 300XTC** Thick ceiling housing kit.

## Labels

**CSA, UL** Suitable for damp locations.

## Job Information

**Type:**

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**