



## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

## EVATION CERTIFICAT

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FiRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

BUILDING OWNER'S				on 40.	340 N 1	<del></del>	
ZJo( ) / /	17 F	reldsp	ממיחים	ADDRESS -	Lake	Inc 1	noles
ROPEPTY LOCATIO	N (Łot and BI	ock numbers an	d address if	available)	Lake	COS 77.	93591
"Manager of the second	• •			TR	28486.	- 16 M	B 764-64
certify that the information	nation on this	certificate repr	esents my be	est efforts to interp	ret the data availal		
ECTION I ELIGIBII		ICATION (Com	pleted by Lo	cal Community Pe		gistered Profess	ional Engineer.
OMMUNITY NO PANEL	NO SUFFIX	Archit	ect, or Surve	DATE OF CONSTR.			
	7 × 1	11-15-85	A		BASE FLOOD ELEV	h) 38/17	☐ New/Emergency ☐ Pre-FIRM Reg.
065043 30	OB	L.A. CO. DPW	) [4]	1987	NA	j	Post-FIRM Reg.
州 of <u>101.6</u>	The certifier  7 ft, NGVD	may rely on cor	nmunity reco struct the bu	ords. The lowest fl uilding at this elevi	compliance with the confidence with the confidence that the confidence the confidence the confidence the confidence the confidence the confidence that the confidence	ement) will be a	t an elevation
□ □ ordinance	based on elev	ation data and	visual inspec	in compliance wit tion or other reason the community.	h the community's onable means.	flood plain mar	nagement
ES NO The mobile	home locate	d at the address	described a	above has been tie	d down (anchored)	in compliance	with the
MOBILE HOME N			<del></del>	<del></del>	n the NFIP Specific	خانت بوسونت نسبت	
MODILE HOME N	IARE	MODEL	TH.	OF MANUFACTU	RE SERIA	L NO. DI	MENSIONS X
Community Permit O	Micial or Book	storest Professio	ani Facina	a Assistant on Co.			
_	S HUN					AVR U	<b>7</b>
,	,				70 001	2 4	
ITLE Flood Co	ontrol C	=119 / CITY	<b></b>		STATE	<u>a</u>	ZIP 9353
IGNATURE LA	mis	Skint	of RC	= 36624 DATE	PHONE &	305-945	-6417
ECTION II ELEVA	TION CERTIF	ICATION (Cert	ified by a Lo				
	•	Arch	itect, or Sun	rêyor.)	9 A	e is a region, shakiliyan	
IRM ZONE A1-A30:	I certify that	the building at					1 4 A P
	at an elevat	ion of-	feet, NG	VD (mean sea leve	el) and the average		
	at an elevation	ion of-	feet, NG	VD (mean sea leve			
IRM ZONES V, V1-1	/30: I certify	that the building	feet, NGVD at the prop	VD (mean sea leve	el) and the average	grade at the b	wilding site is at
IRM ZONES A, A99, A	/30: I certify at an el is at an	that the building evation of	fest, NGVD  g at the propfeet,feet	vD (mean sea leve erty location descr NGVD (mean sea it, NGVD.	ibed above has the level), and the average the property location	bottom of the lograge grade at t	west floor beam he building site
IRM ZONES A, A99, a cor elevation of 101	/30: I certify at an el is at an AH and EMER(	that the building evation of elevation of GENCY PROGRAGOVD. The elevation of the server	feet, NGVD  g at the propfeet,fee  AM: I certify tion of the higher-	erty location descr NGVD (mean sea it, NGVD. that the building at	ibed above has the level), and the avo	bottom of the lograge grade at to 1.3	west floor beam he building site
IRM ZONES A, A99, And Andrewston of 101	/30: I certify at an el is at an AH and EMER.	that the building evation of elevation of GENCY PROGRAGOVD. The elevation of the control of the	feet, NGVD  g at the propfeet,fee  AM: I certify ion of the higherty location	erty location descr NGVD (mean sea of, NGVD. that the building at thest adjacent grade	ibed above has the level), and the aventhe property location next to the building	bottom of the lograge grade at to 1.3	west floor beam. he building site has the lowest feet, NGVD.
IRM ZONES A, A99, oor elevation of 101 IRM ZONE AO: 1 ceret, NGVD. The elevation	An elevation  /30: I certify at an elevation of the high	that the building evation of elevation of elevation of elevation of the service o	at the property locations next to the l	erty location descr NGVD (mean sea et, NGVD. that the building at sheet adjecent grade described above has	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD,	bottom of the lograge grade at the bottom of the lograge grade at the lograge grade at the lograge grade above is 101.3	west floor beam he building site has the lowest feet, NGVD.
IRM ZONES A, A99, a cor elevation of 101 IRM ZONE AO: 1 ceret, NGVD. The elevation of 101 Certify to the best covalls substantially impact of the hydrodynamic to	AH and EMERICATION of the high control of the	that the building evation of elevation of elevation of elevation of the elevation of the elevation of the passage of the passage of the flooding, will of fl	at the property location and belief, water and belief, water degree	erty location described (mean sea level)  NGVD (mean sea level)  that the building at the sea level described above has building is  tion by a Registers that the building structural componies caused by the feat floodproofing	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD.  If the professional Engineers having the callood depths, pressione achieved with here	bottom of the lobrage grade at the building is pability of resistency elections, in the building is pability of resistency elections, in the building is pability of resistency electrons.	west floor beam he building site a has the lowest feet, NGVD.  cct) watertight, with sting hydrostatic mpact and uplift
IRM ZONES A, A99, to oor elevation of 101 IRM ZONE AO: 1 ceret, NGVD. The elevation of 101 ECTION III FLOOI certify to the best of the certify in the best of the certify in the desired with the certify in the certification of 101 IRM ZONES A, A99, the certification of 101	an elevation  /30: I certify at an el is at an el is at an el elect, Note that the building of the high open meable to ads and effect in the event (Human into cur unless elevations)	that the building evation of elevation of elevation of elevation of elevation of the elevation of the passage o	at the property location of the high location locat	erty location descring location descring location descring that the building at the described above has building is that the building structural componies caused by the find floodproofing will enter the building the flood to preven	ibed above has the level), and the average the level, and the average the property location next to the building the lowest floor elegant, NGVD.  If the professional Engineers having the callood depths, pressure achieved with he ling when floods up it entry of water (e.	bottom of the lobrage grade at the business of the base floor, botting meta	west floor beam he building site has the lowest feet, NGVD.  cct) watertight, with sting hydrostatic mpact and uplift on? od level oc-
IRM ZONES A, A99, to oor elevation of 101 IRM ZONE AO: 1 ceret, NGVD. The elevation of 101 ECTION III FLOOI certify to the best of the certify in the best of the certify in the desired with the certify in the certification of 101 IRM ZONES A, A99, the certification of 101	an elevation  /30: I certify at an el is at an el is at an el elect, Note that the building of the high open meable to add and effect in the event (Human into corrections and electrons are electrons	that the building evation of elevation of elevation of elevation of elevation of the elevation of the passage o	at the property location and belief, water and that would be that water water to the standard water and that water and the standard and the st	erty location described (mean sea level)  NGVD (mean sea level)  that the building at the stadjacent grade described above has building is  tion by a Registers that the building structural compones caused by the foodproofing will enter the building the flood to prevent.	ibed above has the level), and the average the level, and the average the property location next to the building the lowest floor elegant, NGVD.  If the professional Engineers having the callood depths, pressure achieved with he ling when floods up it entry of water (e.	bottom of the lobrage grade at the building is pability of resisters yelocities, in the base floot to	west floor beam he building site has the lowest feet, NGVD.  cct) watertight, with sting hydrostatic mpact and uplift on? od level oc-
IRM ZONES A, A99, poor elevation of 101	an elevation  /30: I certify at an el is el is el is el is at an el is e	that the building evation of elevation of elevation of elevation of elevation of the elevation of the passage o	at the property location of the highest to the learn to the learn that would be that water and the water and	erty location descring location descring location descring that the building at the state of the	ibed above has the level), and the average the level), and the average the property location next to the building the lowest floor elegates, NGVD. It designed so that ents having the callood depths, pressure achieved with his given floods up at entry of water (e.e.	bottom of the to brage grade at the business of the base floor, bolting metals the actual lower the business of the base floor, business of the business of th	west floor beam he building site a has the lowest feet, NGVD.  act) watertight, with sting hydrostatic mpact and uplift on? od level oc-
IRM ZONES A, A99, a poor elevation of 101	an elevation  /30: I certify at an elevation is at an elevation of the high open open open open open open open open	that the building evation of elevation of elevation of elevation of elevation of elevation of the elevation of elevation of elevation of elevation of the passage of the elevation means measures are tally indows). Iding be occupited, the floodpromplete both the	at the property location of the highest to the learn to the learn that would be that water and the water and	erty location described (mean sea level)  It was the building at the sea level)  It was the building at the sea level described above has building is the sea level described above has building is that the building structural compone caused by the sea level level level to prevent the sea level level to prevent level.	ibed above has the level), and the average the level), and the average the property location next to the building the lowest floor elegates, NGVD. It designed so that ents having the callood depths, pressure achieved with his given floods up at entry of water (e.e.	bottom of the lobrage grade at the barage grad	west floor beam he building site is at he building site is has the lowest feet, NGVD.  Oct)  watertight, with sting hydrostatic impact and uplift on? od level oc- il shields over
IRM ZONES A, A99, coor elevation of 101 IRM ZONE AO: I certet, NGVD. The elevation of 101 IRM ZONE AO: I certify to the best coralis substantially immoderate associated with YES INO IRM ZONES A, A1-A	an elevation  /30: I certify at an elevation  AH and EMERG	that the building evation of elevation of elevation of elevation of elevation of the elevation of the elevation of elevation of the elevation of the passage	at the property location, and belief, water and that would be that water to the state of the sta	erty location described (mean sea level)  It was the building at the sea level)  It was the building at the sea level described above has building is the sea level described above has building is that the building structural compone caused by the sea level level level to prevent the sea level level to prevent level.	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD, and Professional Englis designed so that ents having the callood depths, pressure achieved with hing when floods up at entry of water (e.e.	bottom of the lobrage grade at the barage grad	west floor beam he building site has the lowest feet, NGVD.  cct) watertight, with sting hydrostatic mpact and uplift on? od level oc- il shields over
IRM ZONES A, A99, a coor elevation of 101	an elevation  /30: I certify at an elevation  AH and EMERG	that the building evation of elevation of elevation of elevation of elevation of the elevation of the passage o	at the property location is next to the latest and belief, water and that would be that water to the latest and belief, and belief, water and that would be that water and selevation are levation as a residuoling cannot be levation as a residuoling cannot belief.	erty location descring location descring (mean sea level)  that the building at the stade above has building is  tion by a Registered that the building structural compones caused by the food floodproofing will enter the building lenter	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD.  Id Professional Englis designed so that ents having the callood depths, pressure achieved with he ing when floods up it entry of water (elegant flood purposes and ertificates.  Floodproofed Eleval (Check One)	bottom of the loberage grade at the barage grade at the barage grade at the loberage grade at the loberage grade at the loberage grade at the barage grade at the barage grade at the barage grade at the barage grade g	west floor beam he building site has the lowest feet, NGVD.  cct) watertight, with sting hydrostatic mpact and uplift on? od level oc- il shields over
YES D NO D I the answer to both completed and certification in the complete of the complete of the certification certification certification certification in the certification certification in the certification certification in the certification in the certification certification in the certification i	an elevation  /30: I certify at an elevation  AH and EMERG	that the building evation of elevation of elevation of elevation of elevation of the elevation of the passage o	at the property location is next to the latest and belief, water and that would be that water to the latest and belief, and belief, water and that would be that water and selevation are levation as a residuoling cannot be levation as a residuoling cannot belief.	erty location descr NGVD (mean sea et, NGVD.  that the building at phest adjecent grade described above has building is tion by a Registers that the building structural compon be caused by the f e of floodproofing will enter the build the flood to preven estructural componies caused by the f e of floodproofing of the credited for a Certified CTIONS II AND III	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD.  Id Professional Englis designed so that ents having the callood depths, pressure achieved with he ing when floods up it entry of water (elegant flood purposes and ertificates.  Floodproofed Eleval (Check One)	bottom of the to brage grade at the brage grade gra	west floor beam he building site is at hes the lowest feet, NGVD.  Oct)  watertight, with sting hydrostatic mpact and uplift on?  od level octished over the sting hydrostatic mpact and uplift on?  of the sting hydrostatic mpact and uplift on?  of level octished over the sting hydrostatic mpact and uplift on?  of level octished over the sting hydrostatic mpact and uplift on?  of Affix Seal)
IRM ZONES A, A99, coor elevation of 101 IRM ZONE AO: I ceret, NGVD. The elevation of 201 IRM ZONE AO: I ceret, NGVD. The elevation of the substantially in the hydrodynamic to corces associated with YES   NO   YES   NO   If the answer to both completed and certification of the complete and certification of the cer	an elevation  /30: I certify at an elevation  AH and EMERICAT feet, Note of the high  DPROOFING  If my knowled the base flood in the event (Human into the build doors and will the build questions is yed instead. Co.  N IS FOR AS	that the building evation of elevation of elevation of elevation of elevation of the elevation of the passage o	at the property location and belief, water and that would be that water to the prior to get as a residuoling cannot be elevation as a COMPANY ADDRESS	erty location descring location descring location descring that the building at the stade above has building is that the building structural compone caused by the food floodproofing will enter the building lenter the building location to prevent location of the credited for and floodproofing of the credited for an and floodproofing of the credited for an analysis of the credited floodproofing of	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD.  Id Professional Englis designed so that ents having the callood depths, pressure achieved with his ing when floods up it entry of water (easing purposes and ertificates.  Floodproofed Eleval (Check One)	bottom of the lobrage grade at the bottom of the lobrage grade at the described above is 101.3 vertion of the building is pability of resisters velocities, in the building is pability of resisters velocities, in the base floor grade bottom is the actual lower the actual lower the actual lower the actual lower the base floor grade bottom is the actual lower the	west floor beam he building site has the lowest feet, NGVD.  The building site has the lowest feet, NGVD.  The building site has the lowest feet, NGVD.  The building hydrostatic mpact and uplift on?  The building hydrostatic mpact and uplift on the building hydrostatic mpact and u
IRM ZONES A, A99, coor elevation of 101 IRM ZONE AO: I ceret, NGVD. The elevation of 201 IRM ZONE AO: I ceret, NGVD. The elevation of the best of the corresponding to the process associated with the completed and certification of the answer to both completed and certification certi	an elevation  /30: I certify at an elevation  AH and EMERICAT feet, Note that the busion of the high  DPROOFING  If my knowled the base flood in the event (Human interested of the base flood in the busidoors and will the busing questions is yellow and instead. Co.  N IS FOR AS	that the building evation of elevation of elevation of elevation of elevation of the elevation of the elevation of the passage	at the property location and belief, water and that would be that water to the prior to the prio	erty location described (May Described above has building at that the building at that the building structural componies caused by the first flood to prevent the flood to prevent the flood proving the flood to prevent the flood	ibed above has the level), and the average the property location next to the building the lowest floor elegants feet, NGVD, and Professional Englis designed so that ents having the callood depths, pressure achieved with hing when floods up at entry of water (e  Floodproofed Eleval (Check One)	bottom of the to brage grade at the brage grade at the brage grade at the property of the building is pability of resisures velocities, in the building is publify of resisures velocities, in the building is publify of resisures velocities, in the brage to the base floor to the base floor bottom is the actual lower than its publication is actually	west floor beam he building site has the lowest feet, NGVD.  act) watertight, with sting hydrostatic mpact and uplift on? od level ocal shields over test floor must be feet, (NGVD).
IRM ZONES A, A99, coor elevation of 101 IRM ZONE AO: I ceret, NGVD. The elevation of 201 IRM ZONE AO: I ceret, NGVD. The elevation of the best of the corresponding to the process associated with YES ID NO ID I the answer to both completed and certification of the complete and certification of the cer	an elevation  /30: I certify at an elevation  /30: I certify at an elevation  AH and EMERICATION  feet, Notify that the build of the high  DPROOFING  of my knowled to add and effect the base floor in the event (Human into the current elevations is yellow in the build questions in th	that the building evation of elevation of elevation of elevation of elevation of the elevation of the elevation of the passage	at the property location and belief, water and that would be that water to the last water and selevation are residuoling cannot selevation and belief, water and selevation are selevation and selevation are selevation and belief.  BOTH SECOMPANY COMPANY COMPANY ST.	erty location described (May Described above has building at that the building at that the building structural componies caused by the first flood to prevent the flood to prevent the flood proving the flood to prevent the flood	ibed above has the level), and the average the property location next to the building the lowest floor elegant, NGVD.  Id Professional Englis designed so that ents having the callood depths, pressure achieved with his ing when floods up it entry of water (easing purposes and ertificates.  Floodproofed Eleval (Check One)	bottom of the lobrage grade at the bearing grade at the bearing described above is 101.3 vertion of the building is pability of resisters velocities, in the base floor grade at the building meters velocities are selection in the base floor grade at the actual lower the actual	west floor beam he building site has the lowest feet, NGVD.  The building site has the lowest feet, NGVD.  The building site has the lowest feet, NGVD.  The building hydrostatic mpact and uplift on?  The building hydrostatic mpact and uplift on the building hydrostatic mpact and u