

# Inventory Control Form

## Small Fragment DCP and LC-DCP (Stainless Steel)



Patient Information:

SYNTHES (USA) To Order: (800) 523-0322  
 SYNTHES (Canada) Ltd. To Order: (800) 668-1119

Date: \_\_\_\_\_  
 Hospital: \_\_\_\_\_  
 Surgeon: \_\_\_\_\_  
 Procedure: \_\_\_\_\_

### Screws

#### 3.5 mm Cortex Screws



	LENGTH		LENGTH	
	204.010	10 mm	204.045	45 mm
	204.012	12 mm	204.050	50 mm
	204.014	14 mm	204.055	55 mm
	204.016	16 mm	204.060	60 mm
	204.018	18 mm	204.065	65 mm
	204.020	20 mm	204.070	70 mm
	204.022	22 mm	204.075	75 mm
	204.024	24 mm	204.080	80 mm
	204.026	26 mm	204.085	85 mm
	204.028	28 mm	204.090	90 mm
	204.030	30 mm	204.095	95 mm
	204.032	32 mm	204.100	100 mm
	204.034	34 mm	204.105	105 mm
	204.036	36 mm	204.110	110 mm
	204.038	38 mm	204.115	115 mm
	204.040	40 mm	204.120	120 mm

#### 3.5 mm Pelvic Cortex Screws, self-tapping



	LENGTH		LENGTH	
	204.640	40 mm	204.700	100 mm
	204.645	45 mm	204.705	105 mm
	204.650	50 mm	204.710	110 mm
	204.655	55 mm	204.715	115 mm
	204.660	60 mm	204.720	120 mm
	204.665	65 mm	204.725	125 mm
	204.670	70 mm	204.730	130 mm
	204.675	75 mm	204.735	135 mm
	204.680	80 mm	204.740	140 mm
	204.685	85 mm	204.745	145 mm
	204.690	90 mm	204.750	150 mm
	204.695	95 mm		

#### 3.5 mm Shaft Screws



	LENGTH		LENGTH	
	204.216	16 mm	204.232	32 mm
	204.218	18 mm	204.234	34 mm
	204.220	20 mm	204.236	36 mm
	204.222	22 mm	204.238	38 mm
	204.224	24 mm	204.240	40 mm
	204.226	26 mm	204.245	45 mm
	204.228	28 mm	204.250	50 mm
	204.230	30 mm		

#### 3.5 mm Cortex Screws, self-tapping



	LENGTH		LENGTH	
	204.810	10 mm	204.844	44 mm
	204.812	12 mm	204.845	45 mm
	204.814	14 mm	204.846	46 mm
	204.816	16 mm	204.848	48 mm
	204.818	18 mm	204.850	50 mm
	204.820	20 mm	204.855	55 mm
	204.822	22 mm	204.860	60 mm
	204.824	24 mm	204.865	65 mm
	204.826	26 mm	204.870	70 mm
	204.828	28 mm	204.875	75 mm
	204.830	30 mm	204.880	80 mm
	204.832	32 mm	204.885	85 mm
	204.834	34 mm	204.890	90 mm
	204.836	36 mm	204.895	95 mm
	204.838	38 mm	204.900	100 mm
	204.840	40 mm	204.905	105 mm
	204.842	42 mm	204.910	110 mm

# Inventory Control Form

## Screws (cont'd)

### 4.0 mm Cancellous Bone Screws, fully threaded



	LENGTH		LENGTH
	206.010		206.040
	206.012		206.045
	206.014		206.050
	206.016		206.055
	206.018		206.060
	206.020		206.065
	206.022		206.070
	206.024		206.075
	206.026		206.080
	206.028		206.085
	206.030		206.090
	206.032		206.095
	206.035		206.100
	206.036		100 mm

### 4.0 mm Cancellous Bone Screws, partially threaded



	LENGTH		LENGTH
	207.010		207.045
	207.012		207.050
	207.014		207.055
	207.016		207.060
	207.018		207.065
	207.020		207.070
	207.022		207.075
	207.024		207.080
	207.026		207.085
	207.028		207.090
	207.030		207.095
	207.035		207.100
	207.040		100 mm

### 4.0 mm Cancellous Bone Screws, 5 mm head, partially threaded



	LENGTH		LENGTH
	207.916		207.936
	207.918		207.938
	207.920		207.940
	207.922		207.942
	207.924		207.944
	207.926		207.946
	207.928		207.948
	207.930		207.950
	207.932		207.952
	207.934		

## Plates

### 3.5 mm DCP Plates



	HOLES		HOLES
	248.02		248.10
	248.03		248.12
	248.04		248.14
	248.05		248.16
	248.06		248.18
	248.07		248.20
	248.08		248.22
	248.09		

### 3.5 mm LC-DCP Plates



	HOLES		HOLES
	223.52		223.60
	223.53		223.61
	223.54		223.62
	223.55		223.64
	223.56		223.65
	223.57		223.66
	223.58		223.68
	223.59		223.70

### Cloverleaf Plates, thin blade



	HOLES		HOLES
	241.83		241.87
	241.84		241.88
	241.85		241.89
	241.86		

### One-Third Tubular Plates with collar



	HOLES		HOLES
	241.32		241.37
	241.33		241.38
	241.34		241.39
	241.35		241.40
	241.36		241.42

### 3.5 mm Curved Reconstruction Plates



	HOLES		HOLES
	245.30		245.34
	245.31		245.35
	245.32		245.36
	245.33		

**Plates (cont'd)**

**3.5 mm Reconstruction Plates**



	HOLES		HOLES	
<input type="checkbox"/>	245.14	4	245.02	12
<input type="checkbox"/>	245.15	5	245.03	13
<input type="checkbox"/>	245.16	6	245.04	14
<input type="checkbox"/>	245.17	7	245.05	15
<input type="checkbox"/>	245.18	8	245.06	16
<input type="checkbox"/>	245.19	9	245.08	18
<input type="checkbox"/>	245.00	10	245.10	20
<input type="checkbox"/>	245.01	11	245.12	22

**3.5 mm T-Plates, oblique angle**



	HOLES HEAD	HOLES SHAFT	
<input type="checkbox"/>	241.23	3	3
<input type="checkbox"/>	241.24	3	4
<input type="checkbox"/>	241.25	3	5

**Calcaneal Plates**



	LENGTH		LENGTH	
<input type="checkbox"/>	241.61	60 mm	241.65	Y-Plate, 87 mm
<input type="checkbox"/>	241.62	70 mm		

**Implants**

**Washers**

<input type="checkbox"/>	219.931	Spiked Washer, 8.0 mm/3.2 mm
<input type="checkbox"/>	219.941	Spiked Washer, 13.5 mm/4.0 mm
<input type="checkbox"/>	219.98	Washer, 7.0 mm, for small screws



**3.5 mm Clavicle Hook Plates**



	HOLES	HOOK DEPTH	
<input type="checkbox"/>	241.062	6	15 mm right
<input type="checkbox"/>	241.063	6	15 mm left
<input type="checkbox"/>	241.064	6	18 mm right
<input type="checkbox"/>	241.065	6	18 mm left
<input type="checkbox"/>	241.066	8	15 mm right
<input type="checkbox"/>	241.067	8	15 mm left
<input type="checkbox"/>	241.068	8	18 mm right
<input type="checkbox"/>	241.069	8	18 mm left

**Kirschner Wires**

**Trocar point (Pkgs. of 10)**

	DIAMETER	LENGTH
<input type="checkbox"/>	292.12	1.25 mm 150 mm
<input type="checkbox"/>	292.13	1.25 mm 285 mm
<input type="checkbox"/>	292.16	1.6 mm 150 mm
<input type="checkbox"/>	292.18	1.6 mm 285 mm
<input type="checkbox"/>	292.20	2.0 mm 150 mm
<input type="checkbox"/>	292.21	2.0 mm 285 mm

**Trocar point, with thread (Pkgs. of 10)**

	DIAMETER	LENGTH	THREAD LENGTH
<input type="checkbox"/>	292.71	1.6 mm 150 mm	5 mm
<input type="checkbox"/>	292.73	1.6 mm 150 mm	15 mm

**Trocar points on both ends (Pkgs. of 10)**

	DIAMETER	LENGTH
<input type="checkbox"/>	292.56	1.6 mm 150 mm
<input type="checkbox"/>	292.58	2.0 mm 150 mm





**3.5 mm T-Plates, right angle**



	HOLES HEAD	HOLES SHAFT	
<input type="checkbox"/>	241.13	3	3
<input type="checkbox"/>	241.14	4	4
<input type="checkbox"/>	241.15	3	5
<input type="checkbox"/>	241.16	4	6
<input type="checkbox"/>	241.17	4	7
<input type="checkbox"/>	241.18	4	8
<input type="checkbox"/>	241.189	4	9

## Instruments


### Drill Bits – Quick Coupling

		DIAMETER	LENGTH
	310.23	2.5 mm	180 mm, gold
	310.25	2.5 mm	110 mm, gold
	310.35	3.5 mm	110 mm
	310.37	3.5 mm	195 mm

### Drill Bits – Jacobs Chuck

		DIAMETER	LENGTH
	310.24	2.5 mm	95 mm, gold
	310.36	3.5 mm	95 mm
	310.38	3.5 mm	180 mm

### Taps

	311.32	For 3.5 mm Cortex Screws, 110 mm
	311.33	For 3.5 mm Cortex Screws, 180 mm
	311.34	For 4.0 mm Cancellous Bone Screws, 110 mm