

Tailgate/Toolbox Safety Training Safety Services Company-Safety Meeting Division, PO Box 6408 Yuma, AZ 85366-6408 Toll Free (866) 204-4786

	De la	(P)	
	A Vo		
6	F. 18	M	3
<u>.</u>	14	111	

Company Name:		Job Site Location:	
Date:	Start Time: Finish Tir	me: Foreman/Supervisor:	
Introduction: Hand truck safety guidelines for move only use the two Make sure the ways push a hand Make sure the low of the make sure the low of the make sure the low of the make sure the result of the make sure the result of the make sure the sure that sure t	Start Time: Finish Tir Topic 544: He is, dollies, and carts are carriers ing light and heavy loads with he wheel hand truck for light load eight is evenly distributed on all and truck, cart, or dolly, do not had is evenly distributed on four before moving loads. Only used der section, vertical bar, and crowheels and tires when any sign har swivel castered support is local three in heavy-duty nylon belts. Do not deterioration. Always use a ratical or hydraulic lifting mechanic crawlers for climbing and descent load, review the task to deter handle the load alone? Is the ite	re: Foreman/Supervisor:	carts asport material a short distance. Following are truck for heavy loads. seeled hand trucks. e railings. y loads. dolly. seen stitching, are frayed, or show any signs of d to prevent load from slipping or shifting. I - not your back! and is secured with nylon belts. heavy the load is, and where it's going. Ask eavy? Will it block my vision?
whenever the slo When loading/u All elevated ram Means for slow workers. Never s When a worker horn, bell, or oth The underside of provided with ot Do not use a ra paneling from flo Personal Protective Equ Large heavy ma Wear protective rolling objects, of Special types or where conditions Wear a back bel Conclusion: Hand trucks	of adequate width for their integrated per per require guardrails/railing. Infoading from trucks, use a sperps require guardrails/railing. Ing material being moved down at and in front of a load while design moving material down a ramper warning device which is autofall material handling ramps, of the adequate means of protecting mp unless it has toeboards. We core, to intermediate, or top rail, ipment terial, that has sharp or rough exported that has sharp or rough exposured to be sexist that makes their use neces that makes their use neces that the sharp or rough exposured to be a sexist that makes their use neces that makes their use neces that makes are designed to be a dollies, and carts are invaluable to the state of the sharp of the	orn ramps must be provided whenever scending a ramp. does not have a clear view of a loomatic in operation must be provide or landings, must be fenced off and any workers from falling material. There material is piled to a height must be provided. dges, should be handled with leather as where there is a danger of foot in where feet are exposed to heavy may at guards, such as non-skid soles, and issuary for the safety of workers.	ver excessive speed might create a hazard to ower landing on which workers are located, a ed, maintained, and in good working order. marked with appropriate warning signs unless that a toeboard does not provide protection, er gloves. Injuries due to falling or aterials. d steel toes are required
Specific Work-Site Hazards Personnel Safety Violations:	and Safety Suggestions:		
Employee Signatures	and regulatio	ons, and that I have not suffered, experienced	agreement to comply with, all company safety policies d, or sustained any recent job-related injury or illness.)
Foreman/Supervisor's Sign			