

- (1) BASE: HEATTREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) A BRA SIVE: A LUM INUM O XIDE SILIC O N C A RBIDE G RA NULES IN A UV PRO TEC TED, 2 PART EPO XY, LO C KED INTO EXTRUDED C HANNELS
- 3. BASE FINISH: MILL
- 4. PO URED CONCRETE STAIRS: NO SING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONC RETE FILLED STEEL PAN STAIRS: NO SING SHAIL BE FULL LENG TH OF STEPS, LESS 1/8" C LEARANC E
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURG UNDY, BLUE, BUFF. LUMINESC ENT

- 7. LENG TH: 12'0" MAXIMUM
- 8. C O UNTER SUNK HO LES PRE-DRILLED FO R A # 10 FA STENER SPA C ED 3" FRO M ENDS AND A PPRO XIM A TELY 12" TO  $\,$  15" O . C .
- 9. UL 1994 LISTED: C O M BINED W ID TH O F PHO TO LUM INESC ENT MA TERIA L SHA LL NO T BE LESS THAN 1"

QTY	COLOR
	QTY

	PROJEC	CT:					
ARCHITECT:							
CO	NTRAC	TOR:					
	QTY:						
PART#:			STRB-L11D				
Right to site.  9300 73rd Avenue North Brooklyn Park, MN 55428			TITLE:	V505, Stair Tread, Bar Ribbed Abrasive ng Nose, Drilled For E	<b>)</b> ,		
	NAME	DATE	SIZE	DWG. NO.			REV
DRAWN	ВМН	3/11/11	Α		STRB-L11D		Α
RELEASED	PE	3/11/11	WE	IGHT: 4.7 LB		SHEET 1	OF 1

PRO PRIETARY AND C ONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SO LE PRO PERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHO LE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1