

Theatre Black *f*

PERFORMANCE SERIES FIBERGLASS CEILINGS

CertainTeed
SAINT-GOBAIN

Specification Sheet

Features & Benefits:

- Specifically developed to meet acoustical requirements for theatre applications.
- Rich matte black color enhances theatre aesthetics.
- Creates a unique atmosphere from the typical white tile application.
- Humidity and sag resistant.

See reverse for additional product specifications.

Applications:

- Theatres
- School Auditoriums
- Salons
- Galleries
- Restaurants

Attributes:


ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	R-VALUE	NRC	CAC†	AC	LR	RECYCLED CONTENT %
SAFETONE® CLASS A								
1912-THB-5	24 x 24 x 5/8	Trim	2.7	0.75	20	180	—	33-39
1910-THB-5	24 x 48 x 5/8	Trim	2.7	0.75	20	180	—	33-39
1942-THB-5	24 x 24 x 1	Trim	4.3	0.90	25	190	—	33-39
1940-THB-5	24 x 48 x 1	Trim	4.3	0.90	25	190	—	33-39

ASTM E 1264 Classification: Type XII, Form 2, Pattern E

† With optional Foil Backing.



Edge Details:



TRIM EDGE
(Square) 15/16" Grid



Product Specification Details

Acoustical Ceilings

09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XII
2. Form 2
3. Pattern E
4. Fiberglass lay-in panel with black mat finish.
5. Size [5/8"] [1"] thick x [24"x 24"] [24"x 48"]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) [0.75] [0.90]
8. Articulation Class (AC) [180] [190]
9. Ceiling Attenuation Class (CAC) [20] [25]
10. Recycled Content 33-39
11. Color Black
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Theatre Black f

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

www.cerainteed.com <http://blog.cerainteed.com>

© 05/10 CertainTeed Corporation
Code No. CTC-4748

