

## Specification Sheet

### Features & Benefits:

- Vinyl-faced fiberglass panel.
- Ideally suited for environments where economical installation and low maintenance are primary considerations.
- Exceptional sound absorption.
- Handsomely embossed vinyl facings are soil/odor resistant and washable, providing an easily maintained surface.

See reverse for additional product specifications.

### Applications:

- Offices
- Retail
- Healthcare
- Open Plan Areas
- Warehouses

### Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	R-VALUE	NRC PERF.*	NRC UNPERF.	CAC	AC	LR	RECYCLED CONTENT %
<b>SAFETONE® CLASS A</b>									
<b>White Vintage</b>									
<b>1532-VIN-1</b>	24 x 24 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	0.79	<b>41-42</b>
<b>1530-VIN-1</b>	24 x 48 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	0.79	<b>41-42</b>
<b>White Astra</b>									
<b>1532-AST-1</b>	24 x 24 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	0.78	<b>41-42</b>
<b>1530-AST-1</b>	24 x 48 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	0.78	<b>41-42</b>
<b>White Stipple</b>									
<b>1532-STP-1</b>	24 x 24 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	0.73	<b>41-42</b>
<b>1530-STP-1</b>	24 x 48 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	0.73	<b>41-42</b>
<b>Black Astra</b>									
<b>1532-AST-5</b>	24 x 24 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	—	<b>41-42</b>
<b>1530-AST-5</b>	24 x 48 x 5/8	Trim	2.7	<b>0.70</b>	<b>0.65</b>	—	180	—	<b>41-42</b>

ASTM E 1264 Classification: Type XII, Form 1, Pattern C E (perforated), E (unperforated)

**\*Ordering Procedure:** To order perforation, add P to code.

Example: 1532-VINP-1

### Finishes:

LR=Light Reflectance




**WHITE ASTRA**  
AST-1 (LR=0.78)



**WHITE STIPPLE**  
STP-1 (LR=0.73)




**BLACK ASTRA**  
AST-5 (LR=0.03)



**WHITE VINTAGE**  
VIN-1 (LR=0.79)

### Edge Details:



**TRIM EDGE**  
(Square) 15/16" Grid



# Product Specification Details

## Acoustical Ceilings

### 09 51 00

#### PART 2: PRODUCTS

##### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

##### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XII
2. Form 1
3. Pattern [C E] [E]
4. Medium density fiberglass core with embossed vinyl fiberglass or mat finishes [White Astra] [Black Astra] [White Stipple] [White Vintage]
5. Size 5/8" thickness x [24" x 24"] [24" x 48"]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) [0.70 perforated] [0.65 unperforated]
8. Articulation Class (AC) 180
9. Ceiling Attenuation Class (CAC) NA
10. Light Reflectance Coefficient (LR) [0.73] [0.78] [0.79]
11. Recycled Content 41-42
12. Color [White] [Black]
13. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
14. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
15. Product Name Versatone™

---

Distributed by:

---

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

---

#### ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE  
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777

[www.cerainteed.com](http://www.cerainteed.com) <http://blog.cerainteed.com>

© 05/10 CertainTeed Corporation  
Code No. CTC-3995

