

Aluminum Sulfate, Solution

Safety Data Sheet

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name: Aluminum sulfate, solution

Manufacturer Information

USALCO, LLC 2601 Cannery Avenue Baltimore, MD 21226

Emergency # 1-800-282-5322

Synonyms

ALUM

Chemical Family

inorganic, salt

Product Use

water treatment coagulant, flocculent, alumina source for catalyst, pH control in papermaking/water treatment

Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Color: colorless to amber, colorless to green

Physical Form: liquid Odor: odorless

Health Hazards: respiratory tract irritation, skin irritation, eye irritation

POTENTIAL HEALTH EFFECTS

Inhalation

Short Term: irritation, cough, sore throat

Long Term: irritation, difficulty breathing, wheezing, lung damage

Skin

Short Term: irritation (possibly severe), allergic reactions **Long Term:** irritation (possibly severe), allergic reactions

Eye

Short Term: irritation (possibly severe) **Long Term:** irritation (possibly severe)

Ingestion

Short Term: digestive disorders **Long Term:** no information is available

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component	Percent	Symbol(s)	Risk Phrase(s)
7732-18-5	Water	>50		
	231-791-2			
10043-01-3	Aluminum sulfate	<50	Xi	R:36-37-38
	233-135-0			

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Aluminium compounds.

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

Skin

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.



Safety Data Sheet

Ingestion

If a large amount is swallowed, get medical attention.

Section 5 - FIRE FIGHTING MEASURES

See Section 9 for Flammability Properties

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Flammable Properties

Negligible fire hazard.

Extinguishing Media

Use extinguishing agents appropriate for surrounding fire.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

Thermal Decomposition Products

Combustion: oxides of sulfur Sensitivity to Mechanical Impact

Not sensitive

Sensitivity to Static Discharge

Not sensitive

Section 6 - ACCIDENTAL RELEASE MEASURES

Occupational spill/release

Stop leak if possible without personal risk. **Small spills**: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Keep unnecessary people away, isolate hazard area and deny entry. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).

Section 7 - HANDLING AND STORAGE

Handling Procedures

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage Procedures

Store and handle in accordance with all current regulations and standards. Store with acids. See original container for storage recommendations. Keep separated from incompatible substances.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

ACGIH and EU have not developed exposure limits for any of this product's components.

Ventilation

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

Wear appropriate chemical resistant clothing.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Page 2 of 6 Issue Date: 09/20/2011 Revision: 1.0310 Print Date: 7/3/2013



Not applicable

SDS ID: 00231225

Safety Data Sheet

Consider warning properties before use.

Any air-purifying full-facepiece respirator equipped with an N95, R95, or P95 filter. The following filters may also be used: N99, R99, P99, N100, R100 or P100.

Any powered, air-purifying respirator with a tight-fitting facepiece and a high-efficiency particulate filter.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator or self-contained breathing apparatus (SCBA) with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Odor Threshold:

Characteristics: colorless to clear amber or Odor: Negligible odor

clear light green liquid

2.0 – 2.4 @ 20°C

1 water=1

Boiling Point: 109° C/228° F

Melting Point: -13° C/9° F

Flash Point: Not applicable

%VOC 0.0 **Density:** 11.1 lbs/gal 15.5 °C **Vapor Density (air = 1):** Not applicable **Specific Gravity (water = 1):** 1.32 - 1.34 @ 15.5 °C

Vapor Pressure: Not applicable Water Solubility: Complete

Viscosity: 25 cps @ 20°C/68° F

Section 10 - STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and pressure.

:Ha

Evaporation Rate:

Conditions to Avoid

Protect from freezing. Keep separated from incompatible substances.

Materials to Avoid

Alkalis, metals

Alkalis (bases): Violent reaction.

Metals: May be corrosive in the presence of moisture.

Thermal Decomposition Products

Combustion: Thermal oxidative decomposition of Aluminum Sulfate occurs at temperatures greater than 1400°F and can produce sulfur oxides.

Possibility of Hazardous Reactions

Will not polymerize.

Section 11 - TOXICOLOGICAL INFORMATION

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Aluminum sulfate (10043-01-3)

Oral LD50 Rat 1930 mg/kg

Water (7732-18-5)

Oral LD50 Rat >90 mL/kg

RTECS Acute Toxicity (selected)

The components of this material have been reviewed, and RTECS publishes the following endpoints:

Aluminum sulfate (10043-01-3)

Oral: 6207 mg/kg Oral Mouse LD50

Water (7732-18-5)

Oral: >90 mL/kg Oral Rat LD50

Page 3 of 6 Issue Date: 09/20/2011 Revision: 1.0310 Print Date: 7/3/2013

Aluminum Sulfate, Solution



SDS ID: 00231225

Safety Data Sheet

Acute Toxicity Level

Aluminum sulfate (10043-01-3)

Slightly Toxic: ingestion

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, or DFG.

RTECS Irritation

The components of this material have been reviewed, and RTECS publishes the following endpoints:

Aluminum sulfate (10043-01-3)

10 mg/24 hour Eyes Rabbit severe

Local Effects

Aluminum sulfate (10043-01-3)

Irritant: inhalation, skin, eye

RTECS Mutagenic

The components of this material have been reviewed, and RTECS publishes the following endpoints:

Aluminum sulfate (10043-01-3)

20 mg/L human; 20 mg/L human; 20 mg/L human; 762 mg/kg/7 day(s) continuous rat; 762 mg/kg/7 day(s) continuous rat

RTECS Reproductive Effects

The components of this material have been reviewed, and RTECS publishes the following endpoints:

Aluminum sulfate (10043-01-3)

800 mg/kg Intraperitoneal Mouse TDLo (pregnant 10-13 day(s)); 27371 ug/kg Subcutaneous Mouse TDLo (male 30 day(s)); 27371 ug/kg Intratesticular Rat TDLo (male 1 day(s))

HEALTH EFFECTS

Inhalation - Acute Exposure

Aluminum sulfate: Inhalation may cause irritation of mucous membranes with sore throat and cough due to sulfuric acid which is formed by the hydrolysis of the salt upon contact with moisture.

Inhalation - Chronic Exposure

Aluminum sulfate: Repeated or prolonged exposure may cause bronchial irritation, leading to nocturnal wheezing, and breathlessness. Prolonged inhalation of dusts containing high concentrations of aluminum have produced emphysema, non-nodular pulmonary fibrosis and fatalities.

Skin Contact - Acute Exposure

Aluminum sulfate: Aluminum sulfate hydrolyzes readily with moisture to form some sulfuric acid which may produce irritation, dermatosis and eczema. Excessive formation of sulfuric acid may produce possible burns. Aluminum sulfate may rarely cause skin sensitization.

Skin Contact - Chronic Exposure

Aluminum sulfate: Repeated or prolonged contact with some soluble salts of aluminum results in acid irritation from hydrolysis. A congestive, anesthetic condition of the fingers (acroanesthesia) may occur from prolonged contact. Repeated exposure may result in sensitization.

Eye Contact - Acute Exposure

Aluminum sulfate: May cause irritation, redness, and corneal burns due to the reaction of the compound with moisture to form sulfuric acid.

Eye Contact - Chronic Exposure

Aluminum sulfate: Repeated or prolonged contact with irritants may cause conjunctivitis or effects similar to those for acute exposure.

Ingestion - Acute Exposure

Aluminum sulfate: Ingestion of a large dose was lethal in mice. Aluminum salts, particularly concentrated solutions (20%), may produce gingival necrosis and fatal hemorrhagic gastroenteritis, in coordination, colonic contractions, evidence of nephritis and death.

Ingestion - Chronic Exposure

Aluminum sulfate: No data available.

Page 4 of 6 Issue Date: 09/20/2011 Revision: 1.0310 Print Date: 7/3/2013



Safety Data Sheet

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity Aluminum sulfate (10043-01-3)

Fish: 96 Hr LC50 Carassius auratus: 100 mg/L; 96 Hr LC50 Gambusia affinis: 37

mg/L [static]

Invertebrate: 15 Min EC50 Daphnia magna: 136 mg/L

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D002 (Corrosive) if the pH is <2.

May be D002 under §261.22(a)(2) due to the rate of corrosion of steel.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information, TDG Information, ADR Information, RID Information, IATA Information, ICAO Information, IMDG Information

Shipping Name: UN3264, Corrosive, liquid, acidic, inorganic, n.o.s., (Aluminum sulfate), 8, III, RQ

Required Label(s): 8

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Aluminum sulfate (10043-01-3)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes; Chronic Health: No; Fire: No; Pressure: No; Reactive: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Aluminum sulfate	10043-01-3	Yes	Yes	No	Yes	Yes

Not regulated under California Proposition 65

Germany Water Classification

Aluminum sulfate (10043-01-3)

ID Number 486, hazard class 1 - low hazard to waters (footnote 8)

EU Marking and Labeling

Symbols

Xi Irritant

Risk Phrases

R36/37/38 Irritating to eyes, respiratory system and skin.

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Aluminum sulfate	10043-01-3	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Water	7732-18-5	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes

Page 5 of 6 Issue Date: 09/20/2011 Revision: 1.0310 Print Date: 7/3/2013



Safety Data Sheet

Section 16 - OTHER INFORMATION

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR -Controlled Products Regulations: DFG - Deutsche Forschungsgemeinschaft: DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID -European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US -**United States**

Full text of R phrases in Section 3

R36 Irritating to eyes.

R37 Irritating to respiratory system.

R38 Irritating to skin.

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. **Disclaimer:** Supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. THIS MSDS IS TO BE UTILIZED SOLEY AS A REFERENCE DOCUMENT AND IT IS NOT TO BE USED TO SATISFY THE DISTRIBUTION REQUIREMENTS OF OSHA'S HAZARD COMMUNICATION STANDARD (HCS) NOR CANADA'S CONTROLLED PRODUCT REGULATION (CPR). Read the Material Safety Data Sheet before handling product.

"RTECS®" is a United States trademark owned and licensed under authority of the U.S. Government, by and through Accelrys, Inc. Portions ©Copyright 2011, U.S. Government. All rights reserved.

End of Sheet 00231225

Page 6 of 6 Issue Date: 09/20/2011 Revision: 1.0310 Print Date: 7/3/2013