

PVFW-LED

Construction:

- Steel housing and chassis
- Diffuser is white smooth acrylic or optional frosted glass

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup – hardware included
- ADA compliant
- UL and CUL listed DAMP location
- LED Components
 - OSRAM Distributed Array
 - CRI > 80
 - 9w -1000 Lumens
 - Dimming (10% or 1%)
 - Osram Power Supply
 - 5-Year Warranty on LED Components



Type:	
Job Name:	



PVFW-8

Height - 8 ¼"
Width - 16 ½"
Depth - 4"



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: PVFW-8-LED-U-9W-3-W1-WFG

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
PVFW-8-LED		U 120 - 277	9w LED / 1000lm (111 lm per watt)	2 3000K 3 3500K 4 4000K	T6 Pewter W2 Gloss White Z3 Text Bronze Optional Finishes (see Price List) W1 Yolk W3 Text White B1 Satin Black B2 Text Black Z1 Satin Bronze T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige P9 Brushed Nickel M16 Antique Brass	WSA White Smooth Acrylic Optional Lens Material (see Price List) WFG White Frosted Glass	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) DIM1 LED dimming driver (0 - 10v) Dimming to 1% (See Price List)



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

