

Construction:

- Steel chassis
- Diffuser is injection molded white smooth acrylic

Lamps:

- Lamps **NOT INCLUDED**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Dimming ballast may be limited with some lamps
- Battery backup available in the 36" and 48" only
- Consult Factory on lumen level available with specific lamps
- UL and CUL listed DAMP location

Type:

Job Name:



WALL

CEILING

PENDANT

OUTDOOR

VLCV-24

Height - 6"
Depth - 4 1/2"
Length - 27"

VLCV-36

Height - 6"
Depth - 4 1/2"
Length - 39"

VLCV-48

Height - 6"
Depth - 4 1/2"
Length - 51"



ORDERING INFORMATION

Example: VLCV-36-A-2F25-NL-W2-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
VLCV-24		A 120v NPF (Elec) U 277v HPF (Elec) UPS - Program Start	1F17 (1) 17w T8 NL 2F17 (2) 17w T8 NL 1F24 (1) 24w T5HO NL 2F24 (2) 24w T5HO NL		W2 Gloss White	WSA White Smooth Acrylic	(Dimming option - See Notes) DIM10 - Mark 10 Dimming Ballast DIM7 - Mark 7 Dimming Ballast 01 120v 02 277v
VLCV-36			1F25 (1) 25w T8 NL 2F25 (2) 25w T8 NL 1F39 (1) 39w T5HO NL 2F39 (2) 39w T5HO NL				BB option - See Notes /36 & 48 only BB - Battery Backup 01 120v 02 277v
VLCV-48			1F32 (1) 32w T8 NL 2F32 (2) 32w T8 NL 1F54 (1) 54w T5HO NL 2F54 (2) 54w T5HO NL				05 500 Lumen (nominal) 07 700 Lumen (nominal) 14 1400 Lumen (nominal)

