in accordance with Regulation (EC) 1907/2006



Trade name Revised on Date printed : Probau Siloxane Scratch Plaster 2 and 3 mm 12 April 2013 12 April 2013

Version (Revision) : 13.0.0 (12.0.1)

### 1. Identification of the substance or preparation and the company

- 1.1 **Product identifier** Probau Siloxane Scratch Plaster 2 and 3 mm
- 1.2 Relevant identified uses of the substance or preparation and uses Coatings and paints, hardeners, filler compounds and thinners
- 1.3 Details of the supplier of the safety data sheet

   Manufacturer/ Supplier
   BAHAG AG

   Street address or P.O. box
   Gutenbergstrasse 21

   Nat. I D/ Postcode/ Town
   D 68167 Mannheim

   Telephone
   0049(0)800/1016370
- 1.4 Emergency telephone number GGIZ Erfurt emergency telephone number 0049 361 730730

#### 2. Hazards identification

2.1 Classification of the substance or material Directive 67/ 548/ EEC and 1999/ 45/ EC

Regulation (EC) No. 1272/2008 (GHS)

- 2.2 Label elements
- 2.3 Other hazards
  - None.

3. Composition/ information on constituents

#### 3.2 Mixtures

#### Chemical characteristics

Water-dilutable siloxane-acrylate copolymer emulsion with inorganic pigments, fillers and additives **Hazardous constituents** 

#### 4. First aid measures

#### 4.1 Description of first aid measures

#### **General information**

If symptoms occur, or in case of doubt, get medical advice/attention.

#### Following inhalation

Introduce fresh air. If the product causes respiratory irritation: Consult a doctor.

#### Following skin contact

Remove soiled items of clothing immediately. Wash the skin with water and soap and rinse. Do not use solvents or thinners!

#### Following eye contact

Remove contact lenses; hold eyelids open. Rinse with plenty of water (for 10 to 15 minutes). Consult a doctor.

#### Following ingestion

Consult a doctor immediately. Keep the victim calm and still. Do not induce vomiting.

in accordance with Regulation (EC) 1907/2006



Trade nameProbau Siloxane Scratch Plaster 2 and 3 mmRevised on12 April 2013VersionDate printed :12 April 2013

Version (Revision) :

13.0.0 (12.0.1)

# 4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed None.

#### 5. Firefighting measures

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam (alcohol resistant), carbon dioxide, powder, spray mist (water).

# Extinguishing media that are unsuitable due to safety reasons Water jet.

#### 5.2 Special hazards arising from the substance or mixture In the event of a fire, poisonous gases can develop. Do not inhale combustion gases.

#### 5.3 Advice for firefighters

Use breathing apparatus if necessary.

#### 5.4 Additional information Do not allow the extinguishing water to enter the sewer system.

#### 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Observe the protection regulations (see Sections 7 and 8). No further special measures are required.

#### 6.2 Environmental precautions

Do not allow the product to enter the sewer system. If rivers, lakes or sewers are polluted, inform the relevant authorities in accordance with the local regulations.

#### 6.3 Methods and material for containment and cleaning up:

Limit the spread of leaked material using an incombustible absorbent material (such as sand, soil, diatomaceous earth or vermiculite) and collect in the appropriate designated containers for disposal in accordance with the local regulations. Later, collect in waste packaging and do not seal (evolution of CO2). Preferably use plenty of water or a cleaning agent for cleaning. If possible, avoid the use of solvents.

## 6.4 Reference to other sections None.

#### 7. Handling and storage

#### 7.1 Precautions for safe handling

#### Information on safe handling

Provide adequate ventilation during and after use. If used correctly, no special protective measures are required.

#### Measures to prevent fire and explosion

The material itself is non-flammable.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep containers tightly closed. Do not use pressure to empty the container. It is not a pressure vessel! No smoking. Access by unauthorised persons is forbidden. Opened containers must be carefully closed and kept upright during storage to prevent any leakage.

#### Storing with other substances

Keep away from strongly acidic and alkaline materials and oxidising agents.

#### Further information on storage conditions

Always store in containers that have the same properties as the original packaging. Observe the instructions on the label.

Page : 2 / 5

#### in accordance with Regulation (EC) 1907/2006



Trade name	Probau Siloxane Scratch Plaster 2 and 3 mm		
Revised on	12 April 2013	Version (Revision):	13.0.0 (12.0.1)
Date printed :	12 April 2013		

Protect from heat and direct sunlight. Protect from frost. Storage class: 12 Storage class in accordance with TRGS 510 (Technical Rules for 12

Hazardous Substances) :

#### 7.3 Specific end use(s)

None.

#### 8. Exposure controls/ personal protection

#### 8.1 Control parameters

 Information on the occupational exposure limit according to TRGS 900 (D) (Technical Rules for Hazardous Substances)

 Specification:
 Calculated RCP occupational exposure limit (D)

 Value:
 Not relevant

#### 8.2 Environmental exposure controls

#### Personal protective equipment

#### **Respiratory protection**

Respiratory protection is necessary if the workplace is insufficiently ventilated during spray application.

#### Hand protection

Skin protection/barrier cream

#### Eye protection

If there is a danger of splashing: Wear safety goggles

#### Body protection

Light protective clothing.

#### Additional instructions regarding the design of technical systems

The product contains no relevant quantities of substances with workplace-related limit values that require monitoring.

#### 9. Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

#### General information

General information					
Form:	Paste-like.				
Colour:	White.				
Odour:	Weak, characteristic.				
Safety data					
I nitial boiling point and b range:	oiling (1013 hPa)	>=	100	°C	
Flash point:			Not applicable		
Vapour pressure:	(50 °C)	<	1000	hPa	
Density:	( 20 °C)	Approx.	1.91	g/cm <sup>3</sup>	
Solvent separation test	(20 °C)		Not applicable		
Flow time:	(20 °C)	>	90	S	DIN 4 mm cup
Maximum VOC content (E	C):		1.3	wt%	
VOC value:			36.7	g/I	
Other information					

None.

9.2

#### 10. Stability and reactivity

in accordance with Regulation (EC) 1907/2006



Trade name	Probau Siloxane Scratch Plaster 2 and 3 mm		
Revised on	12 April 2013	Version (Revision):	13.0.0 (12.0.1)
Date printed :	12 April 2013		

10.1	Reactivity
	There is no available data for the product.
10.2	Chemical stability
	There is no available data for the product.
10.3	Possibility of hazardous reactions
	There is no available data for the product.
10.4	Conditions to avoid
	Stable when used in accordance with the recommended regulations on storage and handling (see Section 7).
10.5	Incompatible materials
	No special regulations need to be observed.
10.6	Hazardous decomposition products
	There is no available data for the product

There is no available data for the product.

#### 11. Toxicological information

11.1 11.1 Information on toxicological effects There is no available data for the product.

#### 11.3 Further information regarding toxicology

According to our current knowledge, there have been no instances of harm being caused during proper use of the product.

#### 12. Ecological information

#### 12.1 Toxicity

There is no available data for the product.

- 12.2 Persistence and degradability There is no available data for the product.
- 12.3 Bioaccumulative potential There is no available data for the product.
- 12.4 Mobility in soil There is no available data for the product.

#### 12.5 Results of PBT and vPvB assessment

There is no available data for the product.

#### 12.6 Other adverse effects

There is no available data for the product.

#### 12.7 Additional information

Do not allow the product to enter water bodies or the sewer system.

#### 13. Disposal considerations

Contaminated packaging must be emptied of all residues. After appropriate cleaning, the packaging can be sent for recycling. Packaging that has not been cleaned must be disposed of in the same way as the substance itself. Do not allow the product to enter water bodies or the sewer system. Dried paint residues can be disposed of with the household waste. Do not dispose of liquid paint residues with the household waste.

#### 13.1 Waste treatment methods

#### Waste code numbers

Waste code number 55508: Waste code numbers 08 01 19 (aqueous suspensions containing paint or varnish containing organic solvents or other dangerous substances)

#### 14. Transport information

#### 14.1 UN number

#### in accordance with Regulation (EC) 1907/2006



Trade name	Probau Siloxane Scratch Plaster 2 and 3 mm		
Revised on	12 April 2013	Version (Revision):	13.0.0 (12.0.1)
Date printed :	12 April 2013		

The product is not classified as a hazardous material with regard to national/international road, rail, maritime and air transport.

#### 14.2 UN proper shipping name

The product is not classified as a hazardous material with regard to national/international road, rail, maritime and air transport.

#### 14.3 Transport hazard class(es)

The product is not classified as a hazardous material with regard to national/international road, rail, maritime and air transport. 14.4 Packing group

The product is not classified as a hazardous material with regard to national/international road, rail, maritime and air transport. 14.5 Environmental hazards

The product is not classified as a hazardous material with regard to national/international road, rail, maritime and air transport.

#### 14.6 Special precautions for user

None.

#### 15. Regulatory information

#### Safety, health and environmental regulations/ legislation specific for the substance or 15.1 mixture

#### National regulations

Technical instructions regarding air (Technische Anleitung zur Reinhaltung der Luft)

Percentage by weight (Point 5.2.5. I): < 5 %

Water hazard class (Wassergefährdungsklasse)

Class: 1 Classified in accordance with the German Regulation on the Classification of Substances Hazardous to Water (VwVwS).

#### 15.2 Chemical safety assessment

There is no available data for the product.

#### 16. Other information

#### Other advice

The information provided in this safety data sheet complies with national and EU legislation. We have no knowledge of or control over the working conditions of the user, however. Unless written approval is given, the product must never be used for any other purpose than that described in Section 1. The user is responsible for complying with all of the relevant legal provisions. The information in this document is based on our knowledge at the time of writing. It does not represent a guarantee of product properties, however, and does not establish a contractual relationship.

#### Safety-related changes

02.2 GHS - Supplementary hazard characteristics · 07.2 Storing with other substances · 08.1 Information on limit values · 14. Land transport ADR/RID and GGVS/GGVE 14. Maritime transport IMDG/GGVSee 14. Air transport ICAO-TI and IATA-DGR 15. Regulation regarding flammable liquids · 15. Technical instructions regarding air (Technische Anleitung zur Reinhaltung der Luft) · 15. Water hazard class (Wassergefährdungsklasse)

The information in this document is based on our knowledge at the time of writing. It does not represent a guarantee of product properties, however, and does not establish a contractual relationship.