



# MATERIAL SAFETY DATA SHEET

**Metallic Resources, Inc.**

## A. GENERAL INFORMATION

TRADE NAME (COMMON NAME OR SYNONYM) Sn/63 HASL Electrolytic Grade Solder		PRODUCT CODE#	
CHEMICAL NAME Tin-Lead Alloy			
FORMULA Sn-Pb		MOLECULAR WEIGHT Not Applicable	
ADDRESS (No., STREET, CITY, STATE AND ZIP CODE) 2116 Enterprise Parkway Twinsburg, Ohio 44087			
CONTACT Metallic Resources, Inc. or contact any emergency room within 15 minutes of your location.		PHONE NUMBER (330) 425-3155	ISSUED DATE: 11/25/85 REVISED DATE: 1/4/95

## B. HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT	C.A.S. #	WT. %	PERMISSIBLE AIR CONCENTRATION
Tin	7440-31-5	63	2.0 mg/cu.m.
*Lead	7439-92-1	37	.05 mg/cu.m.
*Regulated as a toxic substance under section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.			<input checked="" type="checkbox"/> OSHA <input type="checkbox"/> ACGIH <input type="checkbox"/> OTHER

## C. FIRST AID MEASURES

INHALATION: Remove from exposure; place individual under care of physician.

INGESTION: See a physician immediately.

D. HAZARDOUS INFORMATION		
HEALTH		
INHALATION	Lead intoxication may result from chronic high lead exposures with symptoms of anemia, insomnia, weakness, constipation, and gastrointestinal disorders. Stannosis - a benign pneumoconiosis may result from excessive tin exposure.	
INGESTION	Ingestion of lead may cause lead intoxication with accompanying symptoms of nausea and abdominal pain. Tin is relatively non-toxic but may cause fever, nausea, stomach cramps or diarrhea.	
SKIN	Possible mechanical irritation of skin.	
EYES	Mechanical irritation.	
MEDICAL CONDITIONS POSSIBLY AGGRAVATED	Diseases of the blood and blood-forming organs, kidneys, nervous and possibly reproductive systems. Should be determined by physician.	
UNUSUAL CHRONIC TOXICITY	Damage to liver, kidneys, nervous system and blood forming activity. Potential injury to developing fetus and possible effects on reproduction. Should be determined by physician.	
<b>FIRE AND EXPLOSION</b>		
FLASH POINT	°C	AUTO IGNITION °C
Not Applicable		TEMPERATURE
<input type="checkbox"/> OPEN CUP <input type="checkbox"/> CLOSED CUP		Not Applicable
		FLAMMABLE LIMITS IN AIR (% BY VOL.)
		Not Applicable
UNUSUAL FIRE AND EXPLOSION HAZARDS	Not Applicable	
<b>E. PRECAUTIONS/PROCEDURES</b>		
FIRE EXTINGUISHING AGENTS RECOMMENDED	No specific agents recommended.	
FIRE EXTINGUISHING AGENTS TO AVOID	No specific agents.	
SPECIAL FIRE FIGHTING PRECAUTIONS	Use NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing if involved in fire.	
ENGINEERING CONTROLS	Local exhaust ventilation is required for melting, grinding, screening, soldering, or other operations where excessive exposures may occur.	
NORMAL HANDLING	Use of approved respirators is required for applications where adequate ventilation cannot be provided. When melted, the temperature should be kept as low as possible	
STORAGE	No Special Requirements.	
SPILL OR LEAK	A clean-up procedure which minimizes exposure is required. Vacuuming is preferred. Place all material in closed containers. Do not use compressed air for cleaning. Use approved respiratory protection if possibility of dust/fume exposure exists.	
SPECIAL: PRECAUTIONS/PROCEDURES/LABEL INSTRUCTIONS	Signs and labels in work areas and for contaminated containers or equipment may be required under OSHA regulations.	
PERSONAL HYGIENE	Practice good housekeeping and personal hygiene procedures. No tobacco or food in work area. Wash thoroughly before eating or smoking. Avoid ingestion or inhalation. Take a shower and change clothes at end of shift. Do not wear contaminated clothing home. Do not use compressed air for blowing dust off clothes.	

**F. PERSONAL PROTECTIVE EQUIPMENT****RESPIRATORY PROTECTION**

NIOSH/MSHA approved respirator for toxic dust and/or fume.

**EYES AND FACE**

Safety glasses recommended for grinding or other operations generating flying materials.

**HANDS, ARMS, AND BODY**

Gloves recommended for grinding or other operations with significant skin contact.

**OTHER CLOTHING AND EQUIPMENT**

Protective clothing is required if lead exposures exceed the OSHA PEL or significant contact occurs. Remove all work clothing before leaving plant premises.

**G. PHYSICAL DATA****MATERIAL IS (AT NORMAL CONDITIONS):**

Liquid  Solid  Gas  
 \_\_\_\_\_

**APPEARANCE AND ODOR**

Silver-gray metal, odorless  
 Various shapes and sizes

**BOILING POINT**

Melting Point 361° - 370°

**SPECIFIC GRAVITY**

(H<sub>2</sub>O = 1)

8.42

**VAPOR DENSITY**

(AIR = 1)

Not Applicable

**SOLUBILITY IN WATER**

(% by Weight) Insoluble

**pH**

Not Applicable

**VAPOR PRESSURE**

(mm Hg at 20°C)  (PSIG)   
 Not Applicable

**EVAPORATION RATE**

(Butyl Acetate = 1)  (Ether = 1)   
 Not Applicable

**% VOLATILES BY VOLUME**

(At 20°C)

Not Applicable

**H. REACTIVITY DATA****STABILITY**

UNSTABLE  STABLE

**CONDITIONS TO AVOID**

Not Applicable

**INCOMPATIBILITY (MATERIAL TO AVOID)**

Halogen gases, oxidizers or acids may react violently or explode. Contact with hydrogen peroxide may cause a violent reaction.

**HAZARDOUS DECOMPOSITION PRODUCTS**

At temperatures above the melting point, metal oxide fumes may be evolved.

**HAZARDOUS POLYMERIZATION**

MAY OCCUR  WILL NOT OCCUR

**CONDITIONS TO AVOID**

Not Applicable

**I. ENVIRONMENTAL**

EPA HAZARDOUS SUBSTANCE?   IF SO, REPORTABLE QUANTITY: \_\_\_\_\_  
 Yes No

40 CFR  
 116-117

**WASTE DISPOSAL METHODS (DISPOSER MUST COMPLY WITH FEDERAL, STATE AND LOCAL DISPOSAL OR DISCHARGE LAWS)**

If hazardous under 40 CFR 261, Subparts B and C, material must be treated or disposed in a facility meeting the requirements of 40 CFR 264 or 265. If non-hazardous, material should be disposed in a facility meeting the requirements of 40 CFR 257. This material may have value on a recycled basis.

**RCRA STATUS OF UNUSED MATERIAL:**

If discarded in unaltered form material should be considered a hazardous waste due to listing in 40 CFR 216.11 (3), Appendix VIII. Under specific circumstances, application can be made to the EPA Administrator to have a particular waste designated non-hazardous.

40 CFR  
 261

## J. REFERENCES

### PERMISSIBLE CONCENTRATION REFERENCES

OSHA regulations 29 CFR 1910.1000 and 1910.1025

### HAZARD INFORMATION REFERENCES

"Documentation of the Threshold Limit Values," 4th Ed., ACGIH Patty's Industrial Hygiene and Toxicology, Vol. 2A, 3rd Rev. Ed., 1981 NFPA "Fire Protection Guide on Hazardous Materials." 6th Ed., 1975 "Registry of Toxic Effects of Chemical Substances," NIOSH, 1980 Hamilton A. and Hardy, H. "Industrial Toxicology" 3rd Ed., 1974.

### GENERAL

"Handbook of Chemistry and Physics, 57th Ed., "1976-77, Weast, R.C. Editor, CRC Inc.

## K. ADDITIONAL INFORMATION

One should remember that when handling this material when molten, any malaise, such as headache, nausea, vomiting or vertigo can be related to the flux used in conjunction with the alloy.

Due to the unpredictable responses of an individual to fumes and vapors it is advisable not to allow pregnant women in a soldering area.

THIS MATERIAL SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. IT PROVIDES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN.