

	TECHNICAL BULLETIN	SOLENOID REPLACEMENT CHART
---	---------------------------	---------------------------------------

REPLACEMENT SOLENOID CHART			
Old/Obsolete Solenoid			Replace with
Normally Closed		Rated to 250 PSI	
Viking P/N	ASCO Catalog No.		Viking P/N
10199	HV274060-001	24 VDC	11601
10738	HV274060-003	24 VDC Explosion Proof	11602
10850	HV274060-002	110 VAC/50 HZ/120 VAC/60 HZ	11593
10853	HV274060-004	110 VAC/50 HZ/120 VAC/60 HZ Explosion Proof	11594
Normally Closed		Rated to 175 PSI	
Viking P/N	ASCO Catalog No.		Viking P/N
01412A	T8210A107	24 VDC	11601
07830	HV2648572	24 VDC Explosion Proof	11592
07832	HV2648571	24 VDC	11591
07833	HV2648571	110 VAC/50 HZ/120 VAC/60 HZ	11593
07834	HV2648572	110 VAC/50 HZ/120 VAC/60 HZ Explosion Proof	11594
R8801415A	T8210A107	120 VDC	--
R8901413A	T8210A107	120 VAC	11593
Normally Open		Rated to 175 PSI	
Viking P/N	ASCO Catalog No.		Viking P/N
04895A	WPHTX8223-A3ENO	24 VDC	--
07829	HV2648582	24 VDC Explosion Proof	11596
07831	HV2648581	24 VDC	11595

**THIS PAGE
INTENTIONALLY
LEFT BLANK**